



wxErlang

Copyright © 2009-2017 Ericsson AB. All Rights Reserved.
wxErlang 0.98.5
21 2017

Copyright © 2009-2017 Ericsson AB. All Rights Reserved.

The contents of this file are subject to the Erlang Public License, Version 1.1, (the "License"); you may not use this file except in compliance with the License. You should have received a copy of the Erlang Public License along with this software. If not, it can be retrieved online at <http://www.erlang.org/>. Software distributed under the License is distributed on an "AS IS" basis, WITHOUT WARRANTY OF ANY KIND, either express or implied. See the License for the specific language governing rights and limitations under the License. Ericsson AB. All Rights Reserved..

21 2017

1 User's Guide

The *wxErlang* application is an api for writing graphical user interfaces with wxWidgets.

1.1 wx the erlang binding of wxWidgets

The *wx* application is an erlang binding of *wxWidgets*. This document describes the erlang mapping to wxWidgets and it's implementation. It is not a complete users guide to wxWidgets. If you need that, you will have to read the wxWidgets documentation instead. *wx* tries to keep a one-to-one mapping with the original api so that the original documentation and examples shall be as easy as possible to use.

wxErlang examples and test suite can be found in the erlang src release. They can also provide some help on how to use the api.

This is currently a very brief introduction to *wx*. The application is still under development, which means the interface may change, and the test suite currently have a poor coverage ratio.

1.1.1 Contents

- *Introduction*
- *Multiple processes and memory handling*
- *Event Handling*
- *Acknowledgments*

1.1.2 Introduction

The original *wxWidgets* is an object-oriented (C++) api and that is reflected in the erlang mapping. In most cases each class in wxWidgets is represented as a module in erlang. This gives the *wx* application a huge interface, spread over several modules, and it all starts with the *wx* module. The *wx* module contains functions to create and destroy the gui, i.e. *wx:new/0*, *wx:destroy/0*, and some other useful functions.

Objects or object references in *wx* should be seen as erlang processes rather than erlang terms. When you operate on them they can change state, e.g. they are not functional objects as erlang terms are. Each object has a type or rather a class, which is manipulated with the corresponding module or by sub-classes of that object. Type checking is done so that a module only operates on it's objects or inherited classes.

An object is created with *new* and destroyed with *destroy*. Most functions in the classes are named the same as their C++ counterpart, except that for convenience, in erlang they start with a lowercase letter and the first argument is the object reference. Optional arguments are last and expressed as tagged tuples in any order.

For example the *wxWindow* C++ class is implemented in the *wxWindow* erlang module and the member *wxWindow::CenterOnParent* is thus *wxWindow:centerOnParent*. The following C++ code:

```
wxWindow MyWin = new wxWindo();
MyWin.CenterOnParent(wxVERTICAL);
...
delete MyWin;
```

would in erlang look like:

1.1 wx the erlang binding of wxWidgets

```
MyWin = wxWindow:new(),
wxWindow:centerOnParent(MyWin, [{dir,?wxVERTICAL}]),
...
wxWindow:destroy(MyWin),
```

When you are reading wxWidgets documentation or the examples, you will notice that some of the most basic classes are missing in *wx*, they are directly mapped to corresponding erlang terms:

wxPoint is represented by {Xcoord,Ycoord}
wxSize is represented by {Width,Height}
wxRect is represented by {Xcoord,Ycoord,Width,Height}
wxColour is represented by {Red,Green,Blue[,Alpha]}
wxPoint is represented by {Xcoord,Ycoord}
wxString is represented by *unicode:charlist()*
wxGBPosition is represented by {Row,Column}
wxGBSpan is represented by {RowSpan,ColumnSPAN}
wxGridCellCoords is represented by {Row,Column}

In the places where the erlang api differs from the original one it should be obvious from the erlang documentation which representation has been used. E.g. the C++ arrays and/or lists are sometimes represented as erlang lists and sometimes as tuples.

Colours are represented with {Red,Green,Blue[,Alpha]}, the Alpha value is optional when used as an argument to functions, but it will always be returned from *wx* functions.

Defines, enumerations and global variables exists in *wx.hrl* as defines. Most of these defines are constants but not all. Some are platform dependent and therefore the global variables must be instantiated during runtime. These will be acquired from the driver with a call, so not all defines can be used in matching statements. Class local enumerations will be prefixed with the class name and a underscore as in *ClassName_Enum*.

Additionally some global functions, i.e. non-class functions, exist in the *wx_misc* module.

wxErlang is implemented as a (threaded) driver and a rather direct interface to the C++ api, with the drawback that if the erlang programmer does an error, it might crash the emulator.

Since the driver is threaded it requires a *smp* enabled emulator, that provides a thread safe interface to the driver.

1.1.3 Multiple processes and memory handling

The intention is that each erlang application calls *wx:new()* once to setup it's gui which creates an environment and a memory mapping. To be able to use *wx* from several processes in your application, you must share the environment. You can get the active environment with *wx:get_env/0* and set it in the new processes with *wx:set_env/1*. Two processes or applications which have both called *wx:new()* will not be able use each others objects.

```
wx:new(),
MyWin = wxFrame:new(wx:null(), 42, "Example", []),
Env = wx:get_env(),
spawn(fun() ->
    wx:set_env(Env),
    %% Here you can do wx calls from your helper process.
    ...
end),
...
```

When *wx:destroy/0* is invoked or when all processes in the application have died, the memory is deleted and all windows created by that application are closed.

The *wx* application never cleans or garbage collects memory as long as the user application is alive. Most of the objects are deleted when a window is closed, or at least all the objects which have a parent argument that is non null. By using `wxCLASS:destroy/1` when possible you can avoid an increasing memory usage. This is especially important when *wxWidgets* assumes or recommends that you (or rather the C++ programmer) have allocated the object on the stack since that will never be done in the erlang binding. For example `wxDC` class or its sub-classes or `wxSizerFlags`.

Currently the dialogs show modal function freezes *wxWidgets* until the dialog is closed. That is intended but in erlang where you can have several gui applications running at the same time it causes trouble. This will hopefully be fixed in future *wxWidgets* releases.

1.1.4 Event Handling

Event handling in *wx* differs most the from the original api. You must specify every event you want to handle in *wxWidgets*, that is the same in the erlang binding but can you choose to receive the events as messages or handle them with callback funs.

Otherwise the event subscription is handled as *wxWidgets* dynamic event-handler connection. You subscribe to events of a certain type from objects with an *ID* or within a range of *ID*:s. The callback fun is optional, if not supplied the event will be sent to the process that called `connect/2`. Thus, a handler is a callback fun or a process which will receive an event message.

Events are handled in order from bottom to top, in the widgets hierarchy, by the last subscribed handler first. Depending on if `wxEvent:skip()` is called the event will be handled by the other handler(s) afterwards. Most of the events have default event handler(s) installed.

Message events looks like `#wx{id=integer(), obj=wx:wxObject(), userData=term(), event=Rec }`. The *id* is the identifier of the object that received the event. The *obj* field contains the object that you used `connect` on. The *userData* field contains a user supplied term, this is an option to `connect`. And the *event* field contains a record with event type dependent information. The first element in the event record is always the type you subscribed to. For example if you subscribed to `key_up` events you will receive the `#wx{event=Event}` where *Event* will be a `wxKey` event record where `Event#wxKey.type = key_up`.

In *wxWidgets* the developer have to call `wxEvent:skip()` if he wants the event to be processed by other handlers. You can do the same in *wx* if you use callbacks. If you want the event as messages you just don't supply a callback and you can set the `skip` option in `connect` call to true or false, the default it is false. True means that you get the message but let the subsequent handlers also handle the event. If you want to change this behavior dynamically you must use callbacks and call `wxEvent:skip()`.

Callback event handling is done by using the optional callback *fun/2* when attaching the handler. The `fun(#wx{},wxObject())` must take two arguments where the first is the same as with message events described above and the second is an object reference to the actual event object. With the event object you can call `wxEvent:skip()` and access all the data. When using callbacks you must call `wxEvent:skip()` by yourself if you want any of the events to be forwarded to the following handlers. The actual event objects are deleted after the *fun* returns.

The callbacks are always invoked by another process and have exclusive usage of the gui when invoked. This means that a callback fun can not use the process dictionary and should not make calls to other processes. Calls to another process inside a callback fun may cause a deadlock if the other process is waiting on completion of his call to the gui.

1.1.5 Acknowledgments

Mats-Ola Persson wrote the initial *wxWidgets* binding as part of his master thesis. The current version is a total re-write but many ideas have been reused. The reason for the re-write was mostly due to the limited requirements he had been given by us.

Also thanks to the *wxWidgets* team that develops and supports it so we have something to use.

2 Reference Manual

The *wxErlang* application is an api for writing graphical user interfaces with wxWidgets.

WX

Erlang module

A port of **wxWidgets**.

This is the base api of **wxWidgets**. This module contains functions for starting and stopping the wx-server, as well as other utility functions.

wxWidgets is object oriented, and not functional. Thus, in wxErlang a module represents a class, and the object created by this class has an own type, wxCLASS(). This module represents the base class, and all other wxMODULE's are sub-classes of this class.

Objects of a class are created with wxCLASS:new(...) and destroyed with wxCLASS:destroy(). Member functions are called with wxCLASS:member(Object, ...) instead of as in C++ Object.member(...).

Sub class modules inherit (non static) functions from their parents. The inherited functions are not documented in the sub-classes.

This erlang port of wxWidgets tries to be a one-to-one mapping with the original wxWidgets library. Some things are different though, as the optional arguments use property lists and can be in any order. The main difference is the event handling which is different from the original library. See *wxEvtHandler*.

The following classes are implemented directly as erlang types:

wxPoint={x,y}, wxSize={w,h}, wxRect={x,y,w,h}, wxColour={r,g,b [a]}, wxString=*unicode:charlist()*,
wxGBPosition={r,c}, wxGBSpan={rs,cs}, wxGridCellCoords={r,c}.

wxWidgets uses a process specific environment, which is created by *wx:new/0*. To be able to use the environment from other processes, call *get_env/0* to retrieve the environment and *set_env/1* to assign the environment in the other process.

Global (classless) functions are located in the wx_misc module.

DATA TYPES

`colour()`

A 3 or 4 tuple: {R,G,B,A} or as argument {R,G,B} is also accepted where each colour channel is a integer between 0-255.

`datetime()`

{{Year,Month,Day}, {Hour,Minute,Second}} in local timezone.

`mouseState()`

See #wxMouseEvent{} defined in wx.hrl

`wxObject()`

Opaque object

`wx_env()`

Wx process environment

`wx_mem()`

Wx memory area

Exports

new() -> wxObject()

Starts a wx server.

new(Options::[Option]) -> wxObject()

Starts a wx server. Option may be {debug, Level}, see debug/1.

destroy() -> ok

Stops a wx server.

get_env() -> wx_env()

Gets this process's current wx environment. Can be sent to other processes to allow them use this process wx environment.

See also: set_env/1.

set_env(Wx_env::wx_env()) -> ok

Sets the process wx environment, allows this process to use another process wx environment.

null() -> wxObject()

Returns the null object

is_null(Wx_ref::wxObject()) -> boolean()

Returns true if object is null, false otherwise

getObjectType(Wx_ref::wxObject()) -> atom()

Returns the object type

typeCast(Old::wxObject(), NewType::atom()) -> wxObject()

Casts the object to class NewType. It is needed when using functions like wxWindow:findWindow/2, which returns a generic wxObject type.

batch(Fun::function()) -> term()

Batches all wx commands used in the fun. Improves performance of the command processing by grabbing the wxWidgets thread so that no event processing will be done before the complete batch of commands is invoked.

See also: foldl/3, foldr/3, foreach/2, map/2.

foreach(Fun::function(), List::list()) -> ok

Behaves like *lists:foreach/2* but batches wx commands. See *batch/1*.

map(Fun::function(), List::list()) -> list()

Behaves like *lists:map/2* but batches wx commands. See *batch/1*.

foldl(Fun::function(), Acc::term(), List::list()) -> term()

Behaves like *lists:foldl/3* but batches wx commands. See *batch/1*.

foldr(Fun::function(), Acc::term(), List::list()) -> term()

Behaves like *lists:foldr/3* but batches wx commands. See *batch/1*.

create_memory(Size::integer()) -> wx_memory()

Creates a memory area (of Size in bytes) which can be used by an external library (i.e. opengl). It is up to the client to keep a reference to this object so it does not get garbage collected by erlang while still in use by the external library.

This is far from erlang's intentional usage and can crash the erlang emulator. Use it carefully.

get_memory_bin(Wx_mem::wx_memory()) -> binary()

Returns the memory area as a binary.

retain_memory(Wx_mem::wx_memory()) -> ok

Saves the memory from deletion until *release_memory/1* is called. If *release_memory/1* is not called the memory will not be garbage collected.

release_memory(Wx_mem) -> term()

debug(Level::term()) -> ok

Types:

Level = none | verbose | trace | driver | [Level]

Sets debug level. If debug level is verbose or trace each call is printed on console. If Level is driver each allocated object and deletion is printed on the console.

demo() -> ok

Starts a wxErlang demo if examples directory exists and is compiled

wx_object

Erlang module

wx_object - Generic wx object behaviour

This is a behaviour module that can be used for "sub classing" wx objects. It works like a regular `gen_server` module and creates a server per object.

NOTE: Currently no form of inheritance is implemented.

The user module should export:

`init(Args)` should return

`{wxObject, State}` | `{wxObject, State, Timeout}` | `ignore` | `{stop, Reason}`

`handle_call(Msg, {From, Tag}, State)` should return

`{reply, Reply, State}` | `{reply, Reply, State, Timeout}` | `{noreply, State}` | `{noreply, State, Timeout}` | `{stop, Reason, Reply, State}`

Asynchronous window event handling:

`handle_event(#wx{ }, State)` should return

`{noreply, State}` | `{noreply, State, Timeout}` | `{stop, Reason, State}`

Info is message e.g. `{'EXIT', P, R}, {nodedown, N}, ...`

`handle_info(Info, State)` should return , ...

`{noreply, State}` | `{noreply, State, Timeout}` | `{stop, Reason, State}`

When `stop` is returned in one of the functions above with `Reason = normal` | `shutdown` | `Term`, `terminate(State)` is called. It lets the user module clean up, it is always called when server terminates or when `wxObject()` in the driver is deleted. If the Parent process terminates the `Module:terminate/2` function is called.

`terminate(Reason, State)`

Example:

```
-module(myDialog).
-export([new/2, show/1, destroy/1]). %% API
-export([init/1, handle_call/3, handle_event/2,
        handle_info/2, code_change/3, terminate/2]).
        new/2, showModal/1, destroy/1]). %% Callbacks

%% Client API
new(Parent, Msg) ->
    wx_object:start(?MODULE, [Parent, Id], []).

show(Dialog) ->
    wx_object:call(Dialog, show_modal).

destroy(Dialog) ->
    wx_object:call(Dialog, destroy).

%% Server Implementation ala gen_server
init([Parent, Str]) ->
    Dialog = wxDialog:new(Parent, 42, "Testing", []),
    ...
    wxDialog:connect(Dialog, command_button_clicked),
    {Dialog, MyState}.

handle_call(show, _From, State) ->
    wxDialog:show(State#state.win),
    {reply, ok, State};
```

```
...
handle_event(#wx{}, State) ->
    io:format("Users clicked button~n",[]),
    {noreply, State};
...
```

Exports

start(Mod, Args, Options) -> wxWindow() (see module wxWindow)

Types:

Mod = atom()
Args = term()
Options = [{timeout, Timeout} | {debug, [Flag]}]
Flag = trace | log | {logfile, File} | statistics | debug

Starts a generic wx_object server and invokes Mod:init(Args) in the new process.

start(Name, Mod, Args, Options) -> wxWindow() (see module wxWindow)

Types:

Name = {local, atom()}
Mod = atom()
Args = term()
Options = [{timeout, Timeout} | {debug, [Flag]}]
Flag = trace | log | {logfile, File} | statistics | debug

Starts a generic wx_object server and invokes Mod:init(Args) in the new process.

start_link(Mod, Args, Options) -> wxWindow() (see module wxWindow)

Types:

Mod = atom()
Args = term()
Options = [{timeout, Timeout} | {debug, [Flag]}]
Flag = trace | log | {logfile, File} | statistics | debug

Starts a generic wx_object server and invokes Mod:init(Args) in the new process.

start_link(Name, Mod, Args, Options) -> wxWindow() (see module wxWindow)

Types:

Name = {local, atom()}
Mod = atom()
Args = term()
Options = [{timeout, Timeout} | {debug, [Flag]}]
Flag = trace | log | {logfile, File} | statistics | debug

Starts a generic wx_object server and invokes Mod:init(Args) in the new process.

wx_object

```
call(Ref::wxObject() | atom() | pid(), Request::term()) -> term()
```

Make a call to a wx_object server. The call waits until it gets a result. Invokes handle_call(Request, From, State) in the server

```
call(Ref::wxObject() | atom() | pid(), Request::term(), Timeout::integer()) -> term()
```

Make a call to a wx_object server with a timeout. Invokes handle_call(Request, From, State) in server

```
cast(Ref::wxObject() | atom() | pid(), Request::term()) -> ok
```

Make a cast to a wx_object server. Invokes handle_cast(Request, State) in the server

```
get_pid(Ref::wxObject()) -> pid()
```

Get the pid of the object handle.

```
reply(From::tuple(), Reply::term()) -> pid()
```

Get the pid of the object handle.

wxAcceleratorEntry

Erlang module

See external documentation: **wxAcceleratorEntry**.

DATA TYPES

`wxAcceleratorEntry()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new()` -> `wxAcceleratorEntry()`

Equivalent to `new([])`.

`new(X::term() | wxAcceleratorEntry()) -> wxAcceleratorEntry()`

See **external documentation**.

Alternatives:

`new([Option]) -> wxAcceleratorEntry()`

`Option = {flags, integer()} | {keyCode, integer()} | {cmd, integer()} | {item, wxMenuItem:wxMenuItem()}`

`new(Entry::wxAcceleratorEntry()) -> wxAcceleratorEntry()`

`getCommand(This::wxAcceleratorEntry()) -> integer()`

See **external documentation**.

`getFlags(This::wxAcceleratorEntry()) -> integer()`

See **external documentation**.

`getKeyCode(This::wxAcceleratorEntry()) -> integer()`

See **external documentation**.

`set(This::wxAcceleratorEntry(), Flags::integer(), KeyCode::integer(), Cmd::integer()) -> ok`

Equivalent to `set(This, Flags, KeyCode, Cmd, [])`.

`set(This::wxAcceleratorEntry(), Flags::integer(), KeyCode::integer(), Cmd::integer(), Options::[Option]) -> ok`

Types:

`Option = {item, wxMenuItem()} (see module wxMenuItem)`

See **external documentation**.

wxAcceleratorEntry

`destroy(This::wxAcceleratorEntry()) -> ok`

Destroys this object, do not use object again

wxAcceleratorTable

Erlang module

See external documentation: **wxAcceleratorTable**.

DATA TYPES

`wxAcceleratorTable()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxAcceleratorTable()`

See external documentation.

`new(N::integer(), Entries::[wxAcceleratorEntry() (see module wxAcceleratorEntry)]) -> wxAcceleratorTable()`

See external documentation.

`ok(This::wxAcceleratorTable()) -> bool()`

See external documentation.

`destroy(This::wxAcceleratorTable()) -> ok`

Destroys this object, do not use object again

wxArtProvider

Erlang module

See external documentation: **wxArtProvider**.

DATA TYPES

`wxArtProvider()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparsion stored on disc or distributed for use on other nodes.

Exports

`getBitmap(Id::string()) -> wxBitmap()` (see module `wxBitmap`)

Equivalent to `getBitmap(Id, [])`.

`getBitmap(Id::string(), Options::[Option]) -> wxBitmap()` (see module `wxBitmap`)

Types:

Option = {client, string()} | {size, {W::integer(), H::integer()}}

See external documentation.

`getIcon(Id::string()) -> wxIcon()` (see module `wxIcon`)

Equivalent to `getIcon(Id, [])`.

`getIcon(Id::string(), Options::[Option]) -> wxIcon()` (see module `wxIcon`)

Types:

Option = {client, string()} | {size, {W::integer(), H::integer()}}

See external documentation.

wxAuiDockArt

Erlang module

See external documentation: **wxAuiDockArt**.

DATA TYPES

`wxAuiDockArt()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

wxAuiManager

Erlang module

See external documentation: **wxAuiManager**.

This class is derived (and can use functions) from:
wxEvtHandler

DATA TYPES

`wxAuiManager()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxAuiManager()`

Equivalent to `new([])`.

`new(Options::[Option]) -> wxAuiManager()`

Types:

Option = {managed_wnd, wxWindow() (see module wxWindow)} | {flags, integer()}

See external documentation.

`addPane(This::wxAuiManager(), Window::wxWindow() (see module wxWindow)) -> bool()`

Equivalent to `addPane(This, Window, [])`.

`addPane(This::wxAuiManager(), Window::wxWindow() (see module wxWindow), X::term()) -> bool()`

See external documentation.

Alternatives:

`addPane(This::wxAuiManager(), Window::wxWindow:wxWindow(), [Option]) -> bool()`
Option = {direction, integer()} | {caption, string()}

`addPane(This::wxAuiManager(), Window::wxWindow:wxWindow(), Pane_info::wxAuiPaneInfo:wxAuiPaneInfo()) -> bool()`

`addPane(This::wxAuiManager(), Window::wxWindow() (see module wxWindow), Pane_info::wxAuiPaneInfo() (see module wxAuiPaneInfo), Drop_pos:: {X::integer(), Y::integer()}) -> bool()`

See external documentation.

`detachPane(This::wxAuiManager(), Window::wxWindow() (see module wxWindow)) -> bool()`

See external documentation.

`getAllPanels(This::wxAuiManager()) -> wxAuiPaneInfoArray()` (see module `wxAuiPaneInfoArray`)

See external documentation.

`getArtProvider(This::wxAuiManager()) -> wxAuiDockArt()` (see module `wxAuiDockArt`)

See external documentation.

`getDockSizeConstraint(This::wxAuiManager()) -> {Width_pct::float(), Height_pct::float()}`

See external documentation.

`getFlags(This::wxAuiManager()) -> integer()`

See external documentation.

`getManagedWindow(This::wxAuiManager()) -> wxWindow()` (see module `wxWindow`)

See external documentation.

`getManager(Window::wxWindow())` (see module `wxWindow`) -> `wxAuiManager()`

See external documentation.

`getPane(This::wxAuiManager(), X::string() | term()) -> wxAuiPaneInfo()` (see module `wxAuiPaneInfo`)

See external documentation.

Alternatives:

`getPane(This::wxAuiManager(), Name::string()) -> wxAuiPaneInfo:wxAuiPaneInfo()`

`getPane(This::wxAuiManager(), Window::wxWindow:wxWindow()) -> wxAuiPaneInfo:wxAuiPaneInfo()`

`hideHint(This::wxAuiManager()) -> ok`

See external documentation.

`insertPane(This::wxAuiManager(), Window::wxWindow() (see module wxWindow), Insert_location::wxAuiPaneInfo() (see module wxAuiPaneInfo)) -> bool()`

Equivalent to `insertPane(This, Window, Insert_location, [])`.

`insertPane(This::wxAuiManager(), Window::wxWindow() (see module wxWindow), Insert_location::wxAuiPaneInfo() (see module wxAuiPaneInfo), Options::[Option]) -> bool()`

Types:

`Option = {insert_level, integer()}`

See external documentation.

`loadPaneInfo(This::wxAuiManager(), Pane_part::string(), Pane::wxAuiPaneInfo()
(see module wxAuiPaneInfo)) -> ok`

See external documentation.

`loadPerspective(This::wxAuiManager(), Perspective::string()) -> bool()`

Equivalent to `loadPerspective(This, Perspective, [])`.

`loadPerspective(This::wxAuiManager(), Perspective::string(), Options::
[Option]) -> bool()`

Types:

`Option = {update, bool()}`

See external documentation.

`savePaneInfo(This::wxAuiManager(), Pane::wxAuiPaneInfo() (see module
wxAuiPaneInfo)) -> string()`

See external documentation.

`savePerspective(This::wxAuiManager()) -> string()`

See external documentation.

`setArtProvider(This::wxAuiManager(), Art_provider::wxAuiDockArt() (see module
wxAuiDockArt)) -> ok`

See external documentation.

`setDockSizeConstraint(This::wxAuiManager(), Width_pct::float(),
Height_pct::float()) -> ok`

See external documentation.

`setFlags(This::wxAuiManager(), Flags::integer()) -> ok`

See external documentation.

`setManagedWindow(This::wxAuiManager(), Managed_wnd::wxWindow() (see module
wxWindow)) -> ok`

See external documentation.

`showHint(This::wxAuiManager(), Rect::{X::integer(), Y::integer(),
W::integer(), H::integer()}) -> ok`

See external documentation.

`unInit(This::wxAuiManager()) -> ok`

See external documentation.

`update(This::wxAuiManager()) -> ok`

See external documentation.

destroy(This::wxAuiManager()) -> ok

Destroys this object, do not use object again

wxAuiManagerEvent

Erlang module

See external documentation: **wxAuiManagerEvent**.

Use *wxEvtHandler:connect/3* with EventType:

lui_pane_button, lui_pane_close, lui_pane_maximize, lui_pane_restore, lui_render, lui_find_manager

See also the message variant *#wxAuiManager{}* event record type.

This class is derived (and can use functions) from:

wxEvt

DATA TYPES

wxAuiManagerEvent()

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

setManager(This::wxAuiManagerEvent(), Mgr::wxAuiManager()) (see module **wxAuiManager**) -> ok

See external documentation.

getManager(This::wxAuiManagerEvent()) -> wxAuiManager() (see module **wxAuiManager**)

See external documentation.

setPane(This::wxAuiManagerEvent(), P::wxAuiPaneInfo()) (see module **wxAuiPaneInfo**) -> ok

See external documentation.

getPane(This::wxAuiManagerEvent()) -> wxAuiPaneInfo() (see module **wxAuiPaneInfo**)

See external documentation.

setButton(This::wxAuiManagerEvent(), B::integer()) -> ok

See external documentation.

getButton(This::wxAuiManagerEvent()) -> integer()

See external documentation.

setDC(This::wxAuiManagerEvent(), Pdc::wxDC()) (see module **wxDC**) -> ok

See external documentation.

`getDC(This::wxAuiManagerEvent()) -> wxDC()` (see module `wxDC`)

See external documentation.

`veto(This::wxAuiManagerEvent()) -> ok`

Equivalent to `veto(This, [])`.

`veto(This::wxAuiManagerEvent(), Options::[Option]) -> ok`

Types:

Option = {veto, bool()}

See external documentation.

`getVeto(This::wxAuiManagerEvent()) -> bool()`

See external documentation.

`setCanVeto(This::wxAuiManagerEvent(), Can_veto::bool()) -> ok`

See external documentation.

`canVeto(This::wxAuiManagerEvent()) -> bool()`

See external documentation.

wxAuiNotebook

Erlang module

See external documentation: **wxAuiNotebook**.

This class is derived (and can use functions) from:

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxAuiNotebook()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxAuiNotebook()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow)) -> wxAuiNotebook()`

Equivalent to `new(Parent, [])`.

`new(Parent::wxWindow() (see module wxWindow), Options::[Option]) -> wxAuiNotebook()`

Types:

Option = {id, integer()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`addPage(This::wxAuiNotebook(), Page::wxWindow() (see module wxWindow), Caption::string()) -> bool()`

Equivalent to `addPage(This, Page, Caption, [])`.

`addPage(This::wxAuiNotebook(), Page::wxWindow() (see module wxWindow), Caption::string(), Options::[Option]) -> bool()`

Types:

Option = {select, bool()} | {bitmap, wxBitmap() (see module wxBitmap)}

See external documentation.

`create(This::wxAuiNotebook(), Parent::wxWindow() (see module wxWindow)) -> bool()`

Equivalent to `create(This, Parent, [])`.

`create(This::wxAuiNotebook(), Parent::wxWindow() (see module wxWindow),
Options::[Option]) -> bool()`

Types:

`Option = {id, integer()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style,
integer()}`

See external documentation.

`deletePage(This::wxAuiNotebook(), Page::integer()) -> bool()`

See external documentation.

`getArtProvider(This::wxAuiNotebook()) -> wxAuiTabArt() (see module
wxAuiTabArt)`

See external documentation.

`getPage(This::wxAuiNotebook(), Page_idx::integer()) -> wxWindow() (see module
wxWindow)`

See external documentation.

`getPageBitmap(This::wxAuiNotebook(), Page_idx::integer()) -> wxBitmap() (see
module wxBitmap)`

See external documentation.

`getPageCount(This::wxAuiNotebook()) -> integer()`

See external documentation.

`getPageIndex(This::wxAuiNotebook(), Page_wnd::wxWindow() (see module
wxWindow)) -> integer()`

See external documentation.

`getPageText(This::wxAuiNotebook(), Page_idx::integer()) -> string()`

See external documentation.

`getSelection(This::wxAuiNotebook()) -> integer()`

See external documentation.

`insertPage(This::wxAuiNotebook(), Page_idx::integer(), Page::wxWindow() (see
module wxWindow), Caption::string()) -> bool()`

Equivalent to `insertPage(This, Page_idx, Page, Caption, [])`.

`insertPage(This::wxAuiNotebook(), Page_idx::integer(), Page::wxWindow() (see
module wxWindow), Caption::string(), Options::[Option]) -> bool()`

Types:

`Option = {select, bool()} | {bitmap, wxBitmap() (see module wxBitmap)}`

See external documentation.

`removePage(This::wxAuiNotebook(), Page::integer()) -> bool()`

See external documentation.

`setArtProvider(This::wxAuiNotebook(), Art::wxAuiTabArt() (see module wxAuiTabArt)) -> ok`

See external documentation.

`setFont(This::wxAuiNotebook(), Font::wxFont() (see module wxFont)) -> bool()`

See external documentation.

`setPageBitmap(This::wxAuiNotebook(), Page::integer(), Bitmap::wxBitmap() (see module wxBitmap)) -> bool()`

See external documentation.

`setPageText(This::wxAuiNotebook(), Page::integer(), Text::string()) -> bool()`

See external documentation.

`setSelection(This::wxAuiNotebook(), New_page::integer()) -> integer()`

See external documentation.

`setTabCtrlHeight(This::wxAuiNotebook(), Height::integer()) -> ok`

See external documentation.

`setUniformBitmapSize(This::wxAuiNotebook(), Size::{W::integer(), H::integer()}) -> ok`

See external documentation.

`destroy(This::wxAuiNotebook()) -> ok`

Destroys this object, do not use object again

wxAuiNotebookEvent

Erlang module

See external documentation: **wxAuiNotebookEvent**.

Use *wxEvtHandler::connect/3* with EventType:

<i>command_auiNotebook_page_close,</i>	<i>command_auiNotebook_page_changed,</i>
<i>command_auiNotebook_page_changing,</i>	<i>command_auiNotebook_button,</i>
<i>command_auiNotebook_end_drag,</i>	<i>command_auiNotebook_begin_drag,</i>
<i>command_auiNotebook_drag_motion,</i>	<i>command_auiNotebook_allow_dnd,</i>
<i>command_auiNotebook_tab_middle_down,</i>	<i>command_auiNotebook_tab_middle_up,</i>
<i>command_auiNotebook_tab_right_down,</i>	<i>command_auiNotebook_tab_right_up,</i>
<i>command_auiNotebook_page_closed,</i>	<i>command_auiNotebook_drag_done,</i>
	<i>command_auiNotebook_bg_dclick</i>

See also the message variant *#wxAuiNotebook{}* event record type.

This class is derived (and can use functions) from:

wxNotifyEvent

wxCommandEvent

wxEvt

DATA TYPES

wxAuiNotebookEvent()

An object reference, The representation is internal and can be changed without notice. It can't be used for comparsion stored on disc or distributed for use on other nodes.

Exports

setSelection(This::wxAuiNotebookEvent(), S::integer()) -> ok

See external documentation.

getSelection(This::wxAuiNotebookEvent()) -> integer()

See external documentation.

setOldSelection(This::wxAuiNotebookEvent(), S::integer()) -> ok

See external documentation.

getOldSelection(This::wxAuiNotebookEvent()) -> integer()

See external documentation.

setDragSource(This::wxAuiNotebookEvent(), S::wxAuiNotebook()) (see module wxAuiNotebook) -> ok

See external documentation.

getDragSource(This::wxAuiNotebookEvent()) -> wxAuiNotebook() (see module wxAuiNotebook)

See external documentation.

wxAuiPaneInfo

Erlang module

See external documentation: **wxAuiPaneInfo**.

DATA TYPES

`wxAuiPaneInfo()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxAuiPaneInfo()`

See external documentation.

`new(C::wxAuiPaneInfo()) -> wxAuiPaneInfo()`

See external documentation.

`bestSize(This::wxAuiPaneInfo(), Size::{W::integer(), H::integer()}) -> wxAuiPaneInfo()`

See external documentation.

`bestSize(This::wxAuiPaneInfo(), X::integer(), Y::integer()) -> wxAuiPaneInfo()`

See external documentation.

`bottom(This::wxAuiPaneInfo()) -> wxAuiPaneInfo()`

See external documentation.

`bottomDockable(This::wxAuiPaneInfo()) -> wxAuiPaneInfo()`

Equivalent to `bottomDockable(This, [])`.

`bottomDockable(This::wxAuiPaneInfo(), Options::[Option]) -> wxAuiPaneInfo()`

Types:

Option = {b, bool()}

See external documentation.

`caption(This::wxAuiPaneInfo(), C::string()) -> wxAuiPaneInfo()`

See external documentation.

`captionVisible(This::wxAuiPaneInfo()) -> wxAuiPaneInfo()`

Equivalent to `captionVisible(This, [])`.

captionVisible(This::wxAuiPaneInfo(), Options::[Option]) -> wxAuiPaneInfo()

Types:

Option = {visible, bool()}

See external documentation.

centre(This::wxAuiPaneInfo()) -> wxAuiPaneInfo()

See external documentation.

centrePane(This::wxAuiPaneInfo()) -> wxAuiPaneInfo()

See external documentation.

closeButton(This::wxAuiPaneInfo()) -> wxAuiPaneInfo()

Equivalent to *closeButton(This, [])*.

closeButton(This::wxAuiPaneInfo(), Options::[Option]) -> wxAuiPaneInfo()

Types:

Option = {visible, bool()}

See external documentation.

defaultPane(This::wxAuiPaneInfo()) -> wxAuiPaneInfo()

See external documentation.

destroyOnClose(This::wxAuiPaneInfo()) -> wxAuiPaneInfo()

Equivalent to *destroyOnClose(This, [])*.

destroyOnClose(This::wxAuiPaneInfo(), Options::[Option]) -> wxAuiPaneInfo()

Types:

Option = {b, bool()}

See external documentation.

direction(This::wxAuiPaneInfo(), Direction::integer()) -> wxAuiPaneInfo()

See external documentation.

dock(This::wxAuiPaneInfo()) -> wxAuiPaneInfo()

See external documentation.

dockable(This::wxAuiPaneInfo()) -> wxAuiPaneInfo()

Equivalent to *dockable(This, [])*.

dockable(This::wxAuiPaneInfo(), Options::[Option]) -> wxAuiPaneInfo()

Types:

Option = {b, bool()}

See external documentation.

`fixed(This::wxAuiPaneInfo()) -> wxAuiPaneInfo()`

See external documentation.

`float(This::wxAuiPaneInfo()) -> wxAuiPaneInfo()`

See external documentation.

`floatable(This::wxAuiPaneInfo()) -> wxAuiPaneInfo()`

Equivalent to `floatable(This, [])`.

`floatable(This::wxAuiPaneInfo(), Options::[Option]) -> wxAuiPaneInfo()`

Types:

Option = {b, bool()}

See external documentation.

`floatingPosition(This::wxAuiPaneInfo(), Pos::{X::integer(), Y::integer()}) -> wxAuiPaneInfo()`

See external documentation.

`floatingPosition(This::wxAuiPaneInfo(), X::integer(), Y::integer()) -> wxAuiPaneInfo()`

See external documentation.

`floatingSize(This::wxAuiPaneInfo(), Size::{W::integer(), H::integer()}) -> wxAuiPaneInfo()`

See external documentation.

`floatingSize(This::wxAuiPaneInfo(), X::integer(), Y::integer()) -> wxAuiPaneInfo()`

See external documentation.

`gripper(This::wxAuiPaneInfo()) -> wxAuiPaneInfo()`

Equivalent to `gripper(This, [])`.

`gripper(This::wxAuiPaneInfo(), Options::[Option]) -> wxAuiPaneInfo()`

Types:

Option = {visible, bool()}

See external documentation.

`gripperTop(This::wxAuiPaneInfo()) -> wxAuiPaneInfo()`

Equivalent to `gripperTop(This, [])`.

gripperTop(This::wxAuiPaneInfo(), Options::[Option]) -> wxAuiPaneInfo()

Types:

Option = {attop, bool()}

See external documentation.

hasBorder(This::wxAuiPaneInfo()) -> bool()

See external documentation.

hasCaption(This::wxAuiPaneInfo()) -> bool()

See external documentation.

hasCloseButton(This::wxAuiPaneInfo()) -> bool()

See external documentation.

hasFlag(This::wxAuiPaneInfo(), Flag::integer()) -> bool()

See external documentation.

hasGripper(This::wxAuiPaneInfo()) -> bool()

See external documentation.

hasGripperTop(This::wxAuiPaneInfo()) -> bool()

See external documentation.

hasMaximizeButton(This::wxAuiPaneInfo()) -> bool()

See external documentation.

hasMinimizeButton(This::wxAuiPaneInfo()) -> bool()

See external documentation.

hasPinButton(This::wxAuiPaneInfo()) -> bool()

See external documentation.

hide(This::wxAuiPaneInfo()) -> wxAuiPaneInfo()

See external documentation.

isBottomDockable(This::wxAuiPaneInfo()) -> bool()

See external documentation.

isDocked(This::wxAuiPaneInfo()) -> bool()

See external documentation.

`isFixed(This::wxAuiPaneInfo()) -> bool()`

See external documentation.

`isFloatable(This::wxAuiPaneInfo()) -> bool()`

See external documentation.

`isFloating(This::wxAuiPaneInfo()) -> bool()`

See external documentation.

`isLeftDockable(This::wxAuiPaneInfo()) -> bool()`

See external documentation.

`isMovable(This::wxAuiPaneInfo()) -> bool()`

See external documentation.

`isOk(This::wxAuiPaneInfo()) -> bool()`

See external documentation.

`isResizable(This::wxAuiPaneInfo()) -> bool()`

See external documentation.

`isRightDockable(This::wxAuiPaneInfo()) -> bool()`

See external documentation.

`isShown(This::wxAuiPaneInfo()) -> bool()`

See external documentation.

`isToolbar(This::wxAuiPaneInfo()) -> bool()`

See external documentation.

`isTopDockable(This::wxAuiPaneInfo()) -> bool()`

See external documentation.

`layer(This::wxAuiPaneInfo(), Layer::integer()) -> wxAuiPaneInfo()`

See external documentation.

`left(This::wxAuiPaneInfo()) -> wxAuiPaneInfo()`

See external documentation.

`leftDockable(This::wxAuiPaneInfo()) -> wxAuiPaneInfo()`

Equivalent to `leftDockable(This, [])`.

`leftDockable(This::wxAuiPaneInfo(), Options::[Option]) -> wxAuiPaneInfo()`

Types:

`Option = {b, bool()}`

See external documentation.

`maxSize(This::wxAuiPaneInfo(), Size::{W::integer(), H::integer()}) -> wxAuiPaneInfo()`

See external documentation.

`maxSize(This::wxAuiPaneInfo(), X::integer(), Y::integer()) -> wxAuiPaneInfo()`

See external documentation.

`maximizeButton(This::wxAuiPaneInfo()) -> wxAuiPaneInfo()`

Equivalent to `maximizeButton(This, [])`.

`maximizeButton(This::wxAuiPaneInfo(), Options::[Option]) -> wxAuiPaneInfo()`

Types:

`Option = {visible, bool()}`

See external documentation.

`minSize(This::wxAuiPaneInfo(), Size::{W::integer(), H::integer()}) -> wxAuiPaneInfo()`

See external documentation.

`minSize(This::wxAuiPaneInfo(), X::integer(), Y::integer()) -> wxAuiPaneInfo()`

See external documentation.

`minimizeButton(This::wxAuiPaneInfo()) -> wxAuiPaneInfo()`

Equivalent to `minimizeButton(This, [])`.

`minimizeButton(This::wxAuiPaneInfo(), Options::[Option]) -> wxAuiPaneInfo()`

Types:

`Option = {visible, bool()}`

See external documentation.

`movable(This::wxAuiPaneInfo()) -> wxAuiPaneInfo()`

Equivalent to `movable(This, [])`.

`movable(This::wxAuiPaneInfo(), Options::[Option]) -> wxAuiPaneInfo()`

Types:

`Option = {b, bool()}`

See external documentation.

`name(This::wxAuiPaneInfo(), N::string()) -> wxAuiPaneInfo()`

See [external documentation](#).

`paneBorder(This::wxAuiPaneInfo()) -> wxAuiPaneInfo()`

Equivalent to `paneBorder(This, [])`.

`paneBorder(This::wxAuiPaneInfo(), Options::[Option]) -> wxAuiPaneInfo()`

Types:

Option = {visible, bool()}

See [external documentation](#).

`pinButton(This::wxAuiPaneInfo()) -> wxAuiPaneInfo()`

Equivalent to `pinButton(This, [])`.

`pinButton(This::wxAuiPaneInfo(), Options::[Option]) -> wxAuiPaneInfo()`

Types:

Option = {visible, bool()}

See [external documentation](#).

`position(This::wxAuiPaneInfo(), Pos::integer()) -> wxAuiPaneInfo()`

See [external documentation](#).

`resizable(This::wxAuiPaneInfo()) -> wxAuiPaneInfo()`

Equivalent to `resizable(This, [])`.

`resizable(This::wxAuiPaneInfo(), Options::[Option]) -> wxAuiPaneInfo()`

Types:

Option = {resizable, bool()}

See [external documentation](#).

`right(This::wxAuiPaneInfo()) -> wxAuiPaneInfo()`

See [external documentation](#).

`rightDockable(This::wxAuiPaneInfo()) -> wxAuiPaneInfo()`

Equivalent to `rightDockable(This, [])`.

`rightDockable(This::wxAuiPaneInfo(), Options::[Option]) -> wxAuiPaneInfo()`

Types:

Option = {b, bool()}

See [external documentation](#).

row(This::wxAuiPaneInfo(), Row::integer()) -> wxAuiPaneInfo()

See external documentation.

safeSet(This::wxAuiPaneInfo(), Source::wxAuiPaneInfo()) -> ok

See external documentation.

setFlag(This::wxAuiPaneInfo(), Flag::integer(), Option_state::bool()) -> wxAuiPaneInfo()

See external documentation.

show(This::wxAuiPaneInfo()) -> wxAuiPaneInfo()

Equivalent to *show(This, [])*.

show(This::wxAuiPaneInfo(), Options::[Option]) -> wxAuiPaneInfo()

Types:

Option = {show, bool()}

See external documentation.

toolbarPane(This::wxAuiPaneInfo()) -> wxAuiPaneInfo()

See external documentation.

top(This::wxAuiPaneInfo()) -> wxAuiPaneInfo()

See external documentation.

topDockable(This::wxAuiPaneInfo()) -> wxAuiPaneInfo()

Equivalent to *topDockable(This, [])*.

topDockable(This::wxAuiPaneInfo(), Options::[Option]) -> wxAuiPaneInfo()

Types:

Option = {b, bool()}

See external documentation.

window(This::wxAuiPaneInfo(), W::wxWindow() (see module wxWindow)) -> wxAuiPaneInfo()

See external documentation.

destroy(This::wxAuiPaneInfo()) -> ok

Destroys this object, do not use object again

wxAuiTabArt

Erlang module

See external documentation: **wxAuiTabArt**.

DATA TYPES

`wxAuiTabArt()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparsion stored on disc or distributed for use on other nodes.

wxBitmapButton

Erlang module

See external documentation: **wxBitmapButton**.

This class is derived (and can use functions) from:

wxButton

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxBitmapButton()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxBitmapButton()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(),
Bitmap::wxBitmap() (see module wxBitmap)) -> wxBitmapButton()`

Equivalent to `new(Parent, Id, Bitmap, [])`.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(),
Bitmap::wxBitmap() (see module wxBitmap), Options::[Option]) ->
wxBitmapButton()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()} |
{validator, wx() (see module wx)}

See external documentation.

`create(This::wxBitmapButton(), Parent::wxWindow() (see module wxWindow),
Id::integer(), Bitmap::wxBitmap() (see module wxBitmap)) -> bool()`

Equivalent to `create(This, Parent, Id, Bitmap, [])`.

`create(This::wxBitmapButton(), Parent::wxWindow() (see module wxWindow),
Id::integer(), Bitmap::wxBitmap() (see module wxBitmap), Options::[Option]) -
> bool()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()} |
{validator, wx() (see module wx)}

See external documentation.

`getBitmapDisabled(This::wxBitmapButton()) -> wxBitmap()` (see module `wxBitmap`)

See external documentation.

`getBitmapFocus(This::wxBitmapButton()) -> wxBitmap()` (see module `wxBitmap`)

See external documentation.

`getBitmapLabel(This::wxBitmapButton()) -> wxBitmap()` (see module `wxBitmap`)

See external documentation.

`getBitmapSelected(This::wxBitmapButton()) -> wxBitmap()` (see module `wxBitmap`)

See external documentation.

`setBitmapDisabled(This::wxBitmapButton(), Disabled::wxBitmap()` (see module `wxBitmap`)) `-> ok`

See external documentation.

`setBitmapFocus(This::wxBitmapButton(), Focus::wxBitmap()` (see module `wxBitmap`)) `-> ok`

See external documentation.

`setBitmapLabel(This::wxBitmapButton(), Bitmap::wxBitmap()` (see module `wxBitmap`)) `-> ok`

See external documentation.

`setBitmapSelected(This::wxBitmapButton(), Sel::wxBitmap()` (see module `wxBitmap`)) `-> ok`

See external documentation.

`destroy(This::wxBitmapButton()) -> ok`

Destroys this object, do not use object again

wxBitmapDataObject

Erlang module

See external documentation: **wxBitmapDataObject**.

This class is derived (and can use functions) from:
wxDataObject

DATA TYPES

`wxBitmapDataObject()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxBitmapDataObject()`

Equivalent to `new([])`.

`new(X::term()) -> wxBitmapDataObject()`

See external documentation.

Alternatives:

`new([Option]) -> wxBitmapDataObject()`

Option = {bitmap, wxBitmap:wxBitmap()}

`new(Bitmap::wxBitmap:wxBitmap()) -> wxBitmapDataObject()`

`getBitmap(This::wxBitmapDataObject()) -> wxBitmap()` (see module `wxBitmap`)

See external documentation.

`setBitmap(This::wxBitmapDataObject(), Bitmap::wxBitmap())` (see module `wxBitmap`) `-> ok`

See external documentation.

`destroy(This::wxBitmapDataObject()) -> ok`

Destroys this object, do not use object again

wxBitmap

Erlang module

See external documentation: **wxBitmap**.

DATA TYPES

`wxBitmap()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new()` -> `wxBitmap()`

See external documentation.

`new(X::string() | term()) -> wxBitmap()`

See external documentation.

Alternatives:

`new(Filename::string()) -> new(Filename, [])`

`new(Image::wxImage:wxImage()) -> new(Image, [])`

`new(X::integer() | string() | term(), X::integer() | term()) -> wxBitmap()`

See external documentation.

Alternatives:

`new(Width::integer(), Height::integer()) -> new(Width,Height, [])`

`new(Filename::string(), [Option]) -> wxBitmap()`

Option = {type, WxBitmapType}

WxBitmapType = integer()

WxBitmapType is one of ?wxBITMAP_TYPE_INVALID | ?wxBITMAP_TYPE_BMP | ?wxBITMAP_TYPE_BMP_RESOURCE | ?wxBITMAP_TYPE_RESOURCE | ?wxBITMAP_TYPE_ICO | ?wxBITMAP_TYPE_ICO_RESOURCE | ?wxBITMAP_TYPE_CUR | ?wxBITMAP_TYPE_CUR_RESOURCE | ?wxBITMAP_TYPE_XBM | ?wxBITMAP_TYPE_XBM_DATA | ?wxBITMAP_TYPE_XPM | ?wxBITMAP_TYPE_XPM_DATA | ?wxBITMAP_TYPE_TIF | ?wxBITMAP_TYPE_TIF_RESOURCE | ?wxBITMAP_TYPE_GIF | ?wxBITMAP_TYPE_GIF_RESOURCE | ?wxBITMAP_TYPE_PNG | ?wxBITMAP_TYPE_PNG_RESOURCE | ?wxBITMAP_TYPE_JPEG | ?wxBITMAP_TYPE_JPEG_RESOURCE | ?wxBITMAP_TYPE_PNM | ?wxBITMAP_TYPE_PNM_RESOURCE | ?wxBITMAP_TYPE_PCX | ?wxBITMAP_TYPE_PCX_RESOURCE | ?wxBITMAP_TYPE_PICT | ?wxBITMAP_TYPE_PICT_RESOURCE | ?wxBITMAP_TYPE_ICON | ?wxBITMAP_TYPE_ICON_RESOURCE | ?wxBITMAP_TYPE_ANI | ?wxBITMAP_TYPE_IFF | ?wxBITMAP_TYPE_TGA | ?wxBITMAP_TYPE_MACCURSOR | ?wxBITMAP_TYPE_MACCURSOR_RESOURCE | ?wxBITMAP_TYPE_ANY

`new(Image::wxImage:wxImage(), [Option]) -> wxBitmap()`

Option = {depth, integer()}


```
new(X::binary() | integer(), X::integer(), X::integer() | term()) ->
wxBitmap()
```

See external documentation.

Alternatives:

```
new(Bits::binary(), Width::integer(), Height::integer()) ->
new(Bits,Width,Height, [])
```

```
new(Width::integer(), Height::integer(), [Option]) -> wxBitmap()
Option = {depth, integer()}
```

```
new(Bits::binary(), Width::integer(), Height::integer(), Options::[Option]) -
> wxBitmap()
```

Types:

Option = {depth, integer()}

See external documentation.

```
convertToImage(This::wxBitmap()) -> wxImage() (see module wxImage)
```

See external documentation.

```
copyFromIcon(This::wxBitmap(), Icon::wxIcon() (see module wxIcon)) -> bool()
```

See external documentation.

```
create(This::wxBitmap(), Width::integer(), Height::integer()) -> bool()
```

Equivalent to *create(This, Width, Height, [])*.

```
create(This::wxBitmap(), Width::integer(), Height::integer(), Options::
[Option]) -> bool()
```

Types:

Option = {depth, integer()}

See external documentation.

```
getDepth(This::wxBitmap()) -> integer()
```

See external documentation.

```
getHeight(This::wxBitmap()) -> integer()
```

See external documentation.

```
getPalette(This::wxBitmap()) -> wxPalette() (see module wxPalette)
```

See external documentation.

```
getMask(This::wxBitmap()) -> wxMask() (see module wxMask)
```

See external documentation.

getWidth(This::wxBitmap()) -> integer()

See [external documentation](#).

getSubBitmap(This::wxBitmap(), Rect::{X::integer(), Y::integer(), W::integer(), H::integer()}) -> wxBitmap()

See [external documentation](#).

loadFile(This::wxBitmap(), Name::string()) -> bool()

Equivalent to *loadFile(This, Name, [])*.

loadFile(This::wxBitmap(), Name::string(), Options::[Option]) -> bool()

Types:

Option = {type, WxBitmapType}

WxBitmapType = integer()

See [external documentation](#).

WxBitmapType is one of ?wxBITMAP_TYPE_INVALID | ?wxBITMAP_TYPE_BMP | ?wxBITMAP_TYPE_BMP_RESOURCE | ?wxBITMAP_TYPE_RESOURCE | ?wxBITMAP_TYPE_ICO | ?wxBITMAP_TYPE_ICO_RESOURCE | ?wxBITMAP_TYPE_CUR | ?wxBITMAP_TYPE_CUR_RESOURCE | ?wxBITMAP_TYPE_XBM | ?wxBITMAP_TYPE_XBM_DATA | ?wxBITMAP_TYPE_XPM | ?wxBITMAP_TYPE_XPM_DATA | ?wxBITMAP_TYPE_TIF | ?wxBITMAP_TYPE_TIF_RESOURCE | ?wxBITMAP_TYPE_GIF | ?wxBITMAP_TYPE_GIF_RESOURCE | ?wxBITMAP_TYPE_PNG | ?wxBITMAP_TYPE_PNG_RESOURCE | ?wxBITMAP_TYPE_JPEG | ?wxBITMAP_TYPE_JPEG_RESOURCE | ?wxBITMAP_TYPE_PNM | ?wxBITMAP_TYPE_PNM_RESOURCE | ?wxBITMAP_TYPE_PCX | ?wxBITMAP_TYPE_PCX_RESOURCE | ?wxBITMAP_TYPE_PICT | ?wxBITMAP_TYPE_PICT_RESOURCE | ?wxBITMAP_TYPE_ICON | ?wxBITMAP_TYPE_ICON_RESOURCE | ?wxBITMAP_TYPE_ANI | ?wxBITMAP_TYPE_IFF | ?wxBITMAP_TYPE_TGA | ?wxBITMAP_TYPE_MACCursors | ?wxBITMAP_TYPE_MACCursors_RESOURCE | ?wxBITMAP_TYPE_ANY

ok(This::wxBitmap()) -> bool()

See [external documentation](#).

saveFile(This::wxBitmap(), Name::string(), Type::WxBitmapType) -> bool()

Equivalent to *saveFile(This, Name, Type, [])*.

saveFile(This::wxBitmap(), Name::string(), Type::WxBitmapType, Options::[Option]) -> bool()

Types:

Option = {palette, wxPalette() (see module wxPalette)}

WxBitmapType = integer()

See [external documentation](#).

WxBitmapType is one of ?wxBITMAP_TYPE_INVALID | ?wxBITMAP_TYPE_BMP | ?wxBITMAP_TYPE_BMP_RESOURCE | ?wxBITMAP_TYPE_RESOURCE | ?wxBITMAP_TYPE_ICO | ?wxBITMAP_TYPE_ICO_RESOURCE | ?wxBITMAP_TYPE_CUR | ?wxBITMAP_TYPE_CUR_RESOURCE | ?wxBITMAP_TYPE_XBM | ?wxBITMAP_TYPE_XBM_DATA | ?wxBITMAP_TYPE_XPM | ?wxBITMAP_TYPE_XPM_DATA | ?wxBITMAP_TYPE_TIF | ?wxBITMAP_TYPE_TIF_RESOURCE | ?wxBITMAP_TYPE_GIF | ?wxBITMAP_TYPE_GIF_RESOURCE | ?wxBITMAP_TYPE_PNG | ?

wxBITMAP_TYPE_PNG_RESOURCE | ?wxBITMAP_TYPE_JPEG | ?wxBITMAP_TYPE_JPEG_RESOURCE
| ?wxBITMAP_TYPE_PNM | ?wxBITMAP_TYPE_PNM_RESOURCE | ?wxBITMAP_TYPE_PCX | ?
wxBITMAP_TYPE_PCX_RESOURCE | ?wxBITMAP_TYPE_PICT | ?wxBITMAP_TYPE_PICT_RESOURCE
| ?wxBITMAP_TYPE_ICON | ?wxBITMAP_TYPE_ICON_RESOURCE | ?wxBITMAP_TYPE_ANI
| ?wxBITMAP_TYPE_IFF | ?wxBITMAP_TYPE_TGA | ?wxBITMAP_TYPE_MACCURSOR | ?
wxBITMAP_TYPE_MACCURSOR_RESOURCE | ?wxBITMAP_TYPE_ANY

setDepth(This::wxBitmap(), Depth::integer()) -> ok

See external documentation.

setHeight(This::wxBitmap(), Height::integer()) -> ok

See external documentation.

setMask(This::wxBitmap(), Mask::wxMask() (see module wxMask)) -> ok

See external documentation.

**setPalette(This::wxBitmap(), Palette::wxPalette() (see module wxPalette)) ->
ok**

See external documentation.

setWidth(This::wxBitmap(), Width::integer()) -> ok

See external documentation.

destroy(This::wxBitmap()) -> ok

Destroys this object, do not use object again

wxBoundingBox

Erlang module

See external documentation: **wxBoundingBox**.

This class is derived (and can use functions) from:
wxBoundingBox

DATA TYPES

`wxBoundingBox()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new(Orient::integer()) -> wxBoundingBox()`

See external documentation.

`getOrientation(This::wxBoundingBox()) -> integer()`

See external documentation.

`destroy(This::wxBoundingBox()) -> ok`

Destroys this object, do not use object again

wxBrush

Erlang module

See external documentation: **wxBrush**.

DATA TYPES

`wxBrush()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxBrush()`

See external documentation.

`new(X::term()) -> wxBrush()`

See external documentation.

Alternatives:

`new(Colour::wx:colour()) -> new(Colour, [])`

`new(StippleBitmap::wxBitmap:wxBitmap()) -> wxBrush()`

`new(Colour::colour() (see module wx), Options::[Option]) -> wxBrush()`

Types:

Option = {style, integer()}

See external documentation.

`getColour(This::wxBrush()) -> colour() (see module wx)`

See external documentation.

`getStipple(This::wxBrush()) -> wxBitmap() (see module wxBitmap)`

See external documentation.

`getStyle(This::wxBrush()) -> integer()`

See external documentation.

`isHatch(This::wxBrush()) -> bool()`

See external documentation.

`isOk(This::wxBrush()) -> bool()`

See external documentation.

`setColour(This::wxBrush(), Col::colour() (see module wx)) -> ok`

See external documentation.

`setColour(This::wxBrush(), R::integer(), G::integer(), B::integer()) -> ok`

See external documentation.

`setStipple(This::wxBrush(), Stipple::wxBitmap() (see module wxBitmap)) -> ok`

See external documentation.

`setStyle(This::wxBrush(), Style::integer()) -> ok`

See external documentation.

`destroy(This::wxBrush()) -> ok`

Destroys this object, do not use object again

wxBufferedDC

Erlang module

See external documentation: **wxBufferedDC**.

This class is derived (and can use functions) from:

wxMemoryDC

wxDC

DATA TYPES

`wxBufferedDC()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new()` -> `wxBufferedDC()`

See external documentation.

`new(Dc::wxDC() (see module wxDC)) -> wxBufferedDC()`

Equivalent to `new(Dc, [])`.

`new(Dc::wxDC() (see module wxDC), X::term()) -> wxBufferedDC()`

See external documentation.

Alternatives:

`new(Dc::wxDC:wxDC(), Area::{W::integer(),H::integer()}) -> new(Dc,Area, [])`

`new(Dc::wxDC:wxDC(), [Option]) -> wxBufferedDC()`

Option = {buffer, wxBitmap:wxBitmap()} | {style, integer()}

`new(Dc::wxDC() (see module wxDC), Area::{W::integer(), H::integer()}, Options::[Option]) -> wxBufferedDC()`

Types:

Option = {style, integer()}

See external documentation.

`init(This::wxBufferedDC(), Dc::wxDC() (see module wxDC)) -> ok`

Equivalent to `init(This, Dc, [])`.

`init(This::wxBufferedDC(), Dc::wxDC() (see module wxDC), X::term()) -> ok`

See external documentation.

Alternatives:

`init(This::wxBufferedDC(), Dc::wxDC:wxDC(), Area::{W::integer(),H::integer()}) -> init(This,Dc,Area, [])`

wxBufferedDC

```
init(This::wxBufferedDC(), Dc::wxDC:wxDC(), [Option]) -> ok  
Option = {buffer, wxBitmap:wxBitmap()} | {style, integer()}
```

```
init(This::wxBufferedDC(), Dc::wxDC() (see module wxDC), Area::{W::integer(),  
H::integer()}, Options::[Option]) -> ok
```

Types:

Option = {style, integer()}

See **external documentation**.

```
destroy(This::wxBufferedDC()) -> ok
```

Destroys this object, do not use object again

wxBufferedPaintDC

Erlang module

See external documentation: **wxBufferedPaintDC**.

This class is derived (and can use functions) from:

wxBufferedDC

wxMemoryDC

wxDC

DATA TYPES

`wxBufferedPaintDC()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new(Window::wxWindow() (see module wxWindow)) -> wxBufferedPaintDC()`

Equivalent to `new(Window, [])`.

`new(Window::wxWindow() (see module wxWindow), X::term()) -> wxBufferedPaintDC()`

See external documentation.

Alternatives:

`new(Window::wxWindow:wxWindow(), Buffer::wxBitmap:wxBitmap()) -> new(Window, Buffer, [])`

`new(Window::wxWindow:wxWindow(), [Option]) -> wxBufferedPaintDC()`

Option = {style, integer()}

`new(Window::wxWindow() (see module wxWindow), Buffer::wxBitmap() (see module wxBitmap), Options::[Option]) -> wxBufferedPaintDC()`

Types:

Option = {style, integer()}

See external documentation.

`destroy(This::wxBufferedPaintDC()) -> ok`

Destroys this object, do not use object again

wxButton

Erlang module

See external documentation: **wxButton**.

This class is derived (and can use functions) from:

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxButton()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxButton()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Id::integer()) -> wxButton()`

Equivalent to `new(Parent, Id, [])`.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Options::[Option]) -> wxButton()`

Types:

Option = {label, string()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()} | {validator, wx() (see module wx)}

See external documentation.

`create(This::wxButton(), Parent::wxWindow() (see module wxWindow), Id::integer()) -> bool()`

Equivalent to `create(This, Parent, Id, [])`.

`create(This::wxButton(), Parent::wxWindow() (see module wxWindow), Id::integer(), Options::[Option]) -> bool()`

Types:

Option = {label, string()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()} | {validator, wx() (see module wx)}

See external documentation.

`getDefaultSize() -> {W::integer(), H::integer()}`

See external documentation.

setDefault(This::wxButton()) -> ok

See external documentation.

setLabel(This::wxButton(), Label::string()) -> ok

See external documentation.

destroy(This::wxButton()) -> ok

Destroys this object, do not use object again

wxCalendarCtrl

Erlang module

See external documentation: **wxCalendarCtrl**.

This class is derived (and can use functions) from:

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxCalendarCtrl()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxCalendarCtrl()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Id::integer()) -> wxCalendarCtrl()`

Equivalent to `new(Parent, Id, [])`.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Options::[Option]) -> wxCalendarCtrl()`

Types:

Option = {date, datetime() (see module wx)} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`create(This::wxCalendarCtrl(), Parent::wxWindow() (see module wxWindow), Id::integer()) -> bool()`

Equivalent to `create(This, Parent, Id, [])`.

`create(This::wxCalendarCtrl(), Parent::wxWindow() (see module wxWindow), Id::integer(), Options::[Option]) -> bool()`

Types:

Option = {date, datetime() (see module wx)} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`setDate(This::wxCalendarCtrl(), Date::datetime() (see module wx)) -> bool()`

See external documentation.

`getDate(This::wxCalendarCtrl()) -> datetime()` (see module `wx`)

See external documentation.

`enableYearChange(This::wxCalendarCtrl()) -> ok`

Equivalent to `enableYearChange(This, [])`.

`enableYearChange(This::wxCalendarCtrl(), Options::[Option]) -> ok`

Types:

Option = {enable, bool()}

See external documentation.

`enableMonthChange(This::wxCalendarCtrl()) -> ok`

Equivalent to `enableMonthChange(This, [])`.

`enableMonthChange(This::wxCalendarCtrl(), Options::[Option]) -> ok`

Types:

Option = {enable, bool()}

See external documentation.

`enableHolidayDisplay(This::wxCalendarCtrl()) -> ok`

Equivalent to `enableHolidayDisplay(This, [])`.

`enableHolidayDisplay(This::wxCalendarCtrl(), Options::[Option]) -> ok`

Types:

Option = {display, bool()}

See external documentation.

`setHeaderColours(This::wxCalendarCtrl(), ColFg::colour() (see module wx), ColBg::colour() (see module wx)) -> ok`

See external documentation.

`getHeaderColourFg(This::wxCalendarCtrl()) -> colour() (see module wx)`

See external documentation.

`getHeaderColourBg(This::wxCalendarCtrl()) -> colour() (see module wx)`

See external documentation.

`setHighlightColours(This::wxCalendarCtrl(), ColFg::colour() (see module wx), ColBg::colour() (see module wx)) -> ok`

See external documentation.

`getHighlightColourFg(This::wxCalendarCtrl()) -> colour() (see module wx)`

See external documentation.

getHighlightColourBg(This::wxCalendarCtrl()) -> colour() (see module wx)

See external documentation.

setHolidayColours(This::wxCalendarCtrl(), ColFg::colour() (see module wx), ColBg::colour() (see module wx)) -> ok

See external documentation.

getHolidayColourFg(This::wxCalendarCtrl()) -> colour() (see module wx)

See external documentation.

getHolidayColourBg(This::wxCalendarCtrl()) -> colour() (see module wx)

See external documentation.

getAttr(This::wxCalendarCtrl(), Day::integer()) -> wxCalendarDateAttr() (see module wxCalendarDateAttr)

See external documentation.

setAttr(This::wxCalendarCtrl(), Day::integer(), Attr::wxCalendarDateAttr() (see module wxCalendarDateAttr)) -> ok

See external documentation.

setHoliday(This::wxCalendarCtrl(), Day::integer()) -> ok

See external documentation.

resetAttr(This::wxCalendarCtrl(), Day::integer()) -> ok

See external documentation.

hitTest(This::wxCalendarCtrl(), Pos::{X::integer(), Y::integer()}) -> {WxCalendarHitTestResult, Date::datetime() (see module wx), Wd::WeekDay}

Types:

WxCalendarHitTestResult = integer()

WeekDay = integer()

See external documentation.

WxCalendarHitTestResult is one of ?wxCAL_HITTEST_NOWHERE | ?wxCAL_HITTEST_HEADER | ?wxCAL_HITTEST_DAY | ?wxCAL_HITTEST_INCMONTH | ?wxCAL_HITTEST_DECMONTH | ?wxCAL_HITTEST_SURROUNDING_WEEK

WeekDay is one of ?wxDateTime_Sun | ?wxDateTime_Mon | ?wxDateTime_Tue | ?wxDateTime_Wed | ?wxDateTime_Thu | ?wxDateTime_Fri | ?wxDateTime_Sat | ?wxDateTime_Inv_WeekDay

destroy(This::wxCalendarCtrl()) -> ok

Destroys this object, do not use object again

wxCalendarDateAttr

Erlang module

See external documentation: [wxCalendarDateAttr](#).

DATA TYPES

`wxCalendarDateAttr()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxCalendarDateAttr()`

See external documentation.

`new(X::WxCalendarDateBorder | term()) -> wxCalendarDateAttr()`

See external documentation.

Alternatives:

`new(Border::WxCalendarDateBorder) -> new(Border, [])`

`new(ColText::wx:colour()) -> new(ColText, [])`

`new(X::WxCalendarDateBorder | term(), Options::[Option]) -> wxCalendarDateAttr()`

See external documentation.

Alternatives:

`new(Border::WxCalendarDateBorder, [Option]) -> wxCalendarDateAttr()`

Option = {colBorder, wx:colour()}

WxCalendarDateBorder = integer()

WxCalendarDateBorder is one of ?wxCAL_BORDER_NONE | ?wxCAL_BORDER_SQUARE | ?wxCAL_BORDER_ROUND

`new(ColText::wx:colour(), [Option]) -> wxCalendarDateAttr()`

Option = {colBack, wx:colour()} | {colBorder, wx:colour()} | {font, wxFont:wxFont()} | {border, WxCalendarDateBorder}

WxCalendarDateBorder = integer()

WxCalendarDateBorder is one of ?wxCAL_BORDER_NONE | ?wxCAL_BORDER_SQUARE | ?wxCAL_BORDER_ROUND

`setTextColour(This::wxCalendarDateAttr(), ColText::colour() (see module wx)) -> ok`

See external documentation.

`setBackgroundColour(This::wxCalendarDateAttr(), ColBack::colour() (see module wx)) -> ok`

See external documentation.

`setBorderColour(This::wxCalendarDateAttr(), Col::colour() (see module wx)) -> ok`

See external documentation.

`setFont(This::wxCalendarDateAttr(), Font::wxFont() (see module wxFont)) -> ok`

See external documentation.

`setBorder(This::wxCalendarDateAttr(), Border::WxCalendarDateBorder) -> ok`

Types:

`WxCalendarDateBorder = integer()`

See external documentation.

WxCalendarDateBorder is one of ?wxCAL_BORDER_NONE | ?wxCAL_BORDER_SQUARE | ?wxCAL_BORDER_ROUND

`setHoliday(This::wxCalendarDateAttr(), Holiday::bool()) -> ok`

See external documentation.

`hasTextColour(This::wxCalendarDateAttr()) -> bool()`

See external documentation.

`hasBackgroundColour(This::wxCalendarDateAttr()) -> bool()`

See external documentation.

`hasBorderColour(This::wxCalendarDateAttr()) -> bool()`

See external documentation.

`hasFont(This::wxCalendarDateAttr()) -> bool()`

See external documentation.

`hasBorder(This::wxCalendarDateAttr()) -> bool()`

See external documentation.

`isHoliday(This::wxCalendarDateAttr()) -> bool()`

See external documentation.

`getTextColour(This::wxCalendarDateAttr()) -> colour() (see module wx)`

See external documentation.

`getBackgroundColour(This::wxCalendarDateAttr()) -> colour() (see module wx)`

See external documentation.

`getBorderColour(This::wxCalendarDateAttr()) -> colour() (see module wx)`

See external documentation.

getFont(This::wxCalendarDateAttr()) -> wxFont() (see module wxFont)

See external documentation.

getBorder(This::wxCalendarDateAttr()) -> WxCalendarDateBorder

Types:

WxCalendarDateBorder = integer()

See external documentation.

WxCalendarDateBorder is one of ?wxCAL_BORDER_NONE | ?wxCAL_BORDER_SQUARE | ?wxCAL_BORDER_ROUND

destroy(This::wxCalendarDateAttr()) -> ok

Destroys this object, do not use object again

wxCalendarEvent

Erlang module

See external documentation: **wxCalendarEvent**.

Use *wxEvtHandler:connect/3* with EventType:

calendar_sel_changed, *calendar_day_changed*, *calendar_month_changed*, *calendar_year_changed*,
calendar_doubleclicked, *calendar_weekday_clicked*

See also the message variant *#wxCalendar{}* event record type.

This class is derived (and can use functions) from:

wxDateEvent

wxCommandEvent

wxEvent

DATA TYPES

wxCalendarEvent()

An object reference, The representation is internal and can be changed without notice. It can't be used for comparsion stored on disc or distributed for use on other nodes.

Exports

getWeekDay(This::wxCalendarEvent()) -> WeekDay

Types:

WeekDay = integer()

See **external documentation**.

WeekDay is one of ?wxDateTime_Sun | ?wxDateTime_Mon | ?wxDateTime_Tue | ?wxDateTime_Wed | ?wxDateTime_Thu | ?wxDateTime_Fri | ?wxDateTime_Sat | ?wxDateTime_Inv_WeekDay

wxCaret

Erlang module

See external documentation: **wxCaret**.

DATA TYPES

`wxCaret()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new(Window::wxWindow() (see module wxWindow), Size::{W::integer(), H::integer()}) -> wxCaret()`

See external documentation.

`new(Window::wxWindow() (see module wxWindow), Width::integer(), Height::integer()) -> wxCaret()`

See external documentation.

`create(This::wxCaret(), Window::wxWindow() (see module wxWindow), Size::{W::integer(), H::integer()}) -> bool()`

See external documentation.

`create(This::wxCaret(), Window::wxWindow() (see module wxWindow), Width::integer(), Height::integer()) -> bool()`

See external documentation.

`getBlinkTime() -> integer()`

See external documentation.

`getPosition(This::wxCaret()) -> {X::integer(), Y::integer()}`

See external documentation.

`getSize(This::wxCaret()) -> {W::integer(), H::integer()}`

See external documentation.

`getWindow(This::wxCaret()) -> wxWindow() (see module wxWindow)`

See external documentation.

`hide(This::wxCaret()) -> ok`

See external documentation.

isOk(This::wxCaret()) -> bool()

See external documentation.

isVisible(This::wxCaret()) -> bool()

See external documentation.

move(This::wxCaret(), Pt::{X::integer(), Y::integer()}) -> ok

See external documentation.

move(This::wxCaret(), X::integer(), Y::integer()) -> ok

See external documentation.

setBlinkTime(Milliseconds::integer()) -> ok

See external documentation.

setSize(This::wxCaret(), Size::{W::integer(), H::integer()}) -> ok

See external documentation.

setSize(This::wxCaret(), Width::integer(), Height::integer()) -> ok

See external documentation.

show(This::wxCaret()) -> ok

Equivalent to *show(This, [])*.

show(This::wxCaret(), Options::[Option]) -> ok

Types:

Option = {show, bool()}

See external documentation.

destroy(This::wxCaret()) -> ok

Destroys this object, do not use object again

wxCheckBox

Erlang module

See external documentation: **wxCheckBox**.

This class is derived (and can use functions) from:

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxCheckBox()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxCheckBox()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Label::string()) -> wxCheckBox()`

Equivalent to `new(Parent, Id, Label, [])`.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Label::string(), Options::[Option]) -> wxCheckBox()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()} | {validator, wx() (see module wx)}

See external documentation.

`create(This::wxCheckBox(), Parent::wxWindow() (see module wxWindow), Id::integer(), Label::string()) -> bool()`

Equivalent to `create(This, Parent, Id, Label, [])`.

`create(This::wxCheckBox(), Parent::wxWindow() (see module wxWindow), Id::integer(), Label::string(), Options::[Option]) -> bool()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()} | {validator, wx() (see module wx)}

See external documentation.

`getValue(This::wxCheckBox()) -> bool()`

See external documentation.

wxCheckBox

get3StateValue(This::wxCheckBox()) -> WxCheckBoxState

Types:

WxCheckBoxState = integer()

See **external documentation**.

WxCheckBoxState is one of ?wxCHK_UNCHECKED | ?wxCHK_CHECKED | ?wxCHK_UNDETERMINED

is3rdStateAllowedForUser(This::wxCheckBox()) -> bool()

See **external documentation**.

is3State(This::wxCheckBox()) -> bool()

See **external documentation**.

isChecked(This::wxCheckBox()) -> bool()

See **external documentation**.

setValue(This::wxCheckBox(), State::bool()) -> ok

See **external documentation**.

set3StateValue(This::wxCheckBox(), State::WxCheckBoxState) -> ok

Types:

WxCheckBoxState = integer()

See **external documentation**.

WxCheckBoxState is one of ?wxCHK_UNCHECKED | ?wxCHK_CHECKED | ?wxCHK_UNDETERMINED

destroy(This::wxCheckBox()) -> ok

Destroys this object, do not use object again

wxCheckListBox

Erlang module

See external documentation: **wxCheckListBox**.

This class is derived (and can use functions) from:

wxListBox

wxControlWithItems

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxCheckListBox()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxCheckListBox()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Id::integer()) -> wxCheckListBox()`

Equivalent to `new(Parent, Id, [])`.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Options::[Option]) -> wxCheckListBox()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {choices, [[string()]]} | {style, integer()} | {validator, wx() (see module wx)}

See external documentation.

`check(This::wxCheckListBox(), Index::integer()) -> ok`

Equivalent to `check(This, Index, [])`.

`check(This::wxCheckListBox(), Index::integer(), Options::[Option]) -> ok`

Types:

Option = {check, bool()}

See external documentation.

`isChecked(This::wxCheckListBox(), Index::integer()) -> bool()`

See external documentation.

wxCheckListBox

`destroy(This::wxCheckListBox()) -> ok`

Destroys this object, do not use object again

wxChildFocusEvent

Erlang module

See external documentation: **wxChildFocusEvent**.

Use *wxEvtHandler:connect/3* with EventType:

child_focus

See also the message variant *#wxChildFocus{}* event record type.

This class is derived (and can use functions) from:

wxCommandEvent

wxEvent

DATA TYPES

`wxChildFocusEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparsion stored on disc or distributed for use on other nodes.

Exports

`getWindow(This::wxChildFocusEvent()) -> wxWindow()` (see module `wxWindow`)

See **external documentation**.

wxChoicebook

Erlang module

See external documentation: **wxChoicebook**.

This class is derived (and can use functions) from:

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxChoicebook()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxChoicebook()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Id::integer()) -> wxChoicebook()`

Equivalent to `new(Parent, Id, [])`.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Options::[Option]) -> wxChoicebook()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`addPage(This::wxChoicebook(), Page::wxWindow() (see module wxWindow), Text::string()) -> bool()`

Equivalent to `addPage(This, Page, Text, [])`.

`addPage(This::wxChoicebook(), Page::wxWindow() (see module wxWindow), Text::string(), Options::[Option]) -> bool()`

Types:

Option = {bSelect, bool()} | {imageId, integer()}

See external documentation.

`advanceSelection(This::wxChoicebook()) -> ok`

Equivalent to `advanceSelection(This, [])`.

`advanceSelection(This::wxChoicebook(), Options::[Option]) -> ok`

Types:

`Option = {forward, bool()}`

See external documentation.

`assignImageList(This::wxChoicebook(), ImageList::wxImageList() (see module wxImageList)) -> ok`

See external documentation.

`create(This::wxChoicebook(), Parent::wxWindow() (see module wxWindow), Id::integer()) -> bool()`

Equivalent to `create(This, Parent, Id, [])`.

`create(This::wxChoicebook(), Parent::wxWindow() (see module wxWindow), Id::integer(), Options::[Option]) -> bool()`

Types:

`Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}`

See external documentation.

`deleteAllPages(This::wxChoicebook()) -> bool()`

See external documentation.

`deletePage(This::wxChoicebook(), N::integer()) -> bool()`

See external documentation.

`removePage(This::wxChoicebook(), N::integer()) -> bool()`

See external documentation.

`getCurrentPage(This::wxChoicebook()) -> wxWindow() (see module wxWindow)`

See external documentation.

`getImageList(This::wxChoicebook()) -> wxImageList() (see module wxImageList)`

See external documentation.

`getPage(This::wxChoicebook(), N::integer()) -> wxWindow() (see module wxWindow)`

See external documentation.

`getPageCount(This::wxChoicebook()) -> integer()`

See external documentation.

`getPageImage(This::wxChoicebook(), N::integer()) -> integer()`

See external documentation.

`getPageText(This::wxChoicebook(), N::integer()) -> string()`

See external documentation.

`getSelection(This::wxChoicebook()) -> integer()`

See external documentation.

`hitTest(This::wxChoicebook(), Pt::{X::integer(), Y::integer()}) -> {integer(), Flags::integer()}`

See external documentation.

`insertPage(This::wxChoicebook(), N::integer(), Page::wxWindow() (see module wxWindow), Text::string()) -> bool()`

Equivalent to `insertPage(This, N, Page, Text, [])`.

`insertPage(This::wxChoicebook(), N::integer(), Page::wxWindow() (see module wxWindow), Text::string(), Options::[Option]) -> bool()`

Types:

`Option = {bSelect, bool()} | {imageId, integer()}`

See external documentation.

`setImageList(This::wxChoicebook(), ImageList::wxImageList() (see module wxImageList)) -> ok`

See external documentation.

`setPageSize(This::wxChoicebook(), Size::{W::integer(), H::integer()}) -> ok`

See external documentation.

`setPageImage(This::wxChoicebook(), N::integer(), ImageId::integer()) -> bool()`

See external documentation.

`setPageText(This::wxChoicebook(), N::integer(), StrText::string()) -> bool()`

See external documentation.

`setSelection(This::wxChoicebook(), N::integer()) -> integer()`

See external documentation.

`changeSelection(This::wxChoicebook(), N::integer()) -> integer()`

See external documentation.

`destroy(This::wxChoicebook()) -> ok`

Destroys this object, do not use object again

wxChoice

Erlang module

See external documentation: **wxChoice**.

This class is derived (and can use functions) from:

wxControlWithItems

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxChoice()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxChoice()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Id::integer()) -> wxChoice()`

Equivalent to `new(Parent, Id, [])`.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Options::[Option]) -> wxChoice()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {choices, [[string()]]} | {style, integer()} | {validator, wx() (see module wx)}

See external documentation.

`create(This::wxChoice(), Parent::wxWindow() (see module wxWindow), Id::integer(), Pos::{X::integer(), Y::integer()}, Size::{W::integer(), H::integer()}, Choices::[[string()]]) -> bool()`

Equivalent to `create(This, Parent, Id, Pos, Size, Choices, [])`.

`create(This::wxChoice(), Parent::wxWindow() (see module wxWindow), Id::integer(), Pos::{X::integer(), Y::integer()}, Size::{W::integer(), H::integer()}, Choices::[[string()]], Options::[Option]) -> bool()`

Types:

Option = {style, integer()} | {validator, wx() (see module wx)}

See external documentation.

delete(This::wxChoice(), N::integer()) -> ok

See **external documentation**.

getColumns(This::wxChoice()) -> integer()

See **external documentation**.

setColumns(This::wxChoice()) -> ok

Equivalent to *setColumns(This, [])*.

setColumns(This::wxChoice(), Options::[Option]) -> ok

Types:

Option = {n, integer()}

See **external documentation**.

destroy(This::wxChoice()) -> ok

Destroys this object, do not use object again

wxClientDC

Erlang module

See external documentation: **wxClientDC**.

This class is derived (and can use functions) from:

wxWindowDC

wxDC

DATA TYPES

`wxClientDC()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new()` -> **`wxClientDC()`**

See external documentation.

`new(Win::wxWindow())` (see module **`wxWindow`**) -> **`wxClientDC()`**

See external documentation.

`destroy(This::wxClientDC())` -> **`ok`**

Destroys this object, do not use object again

wxClipboard

Erlang module

See external documentation: **wxClipboard**.

DATA TYPES

`wxClipboard()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxClipboard()`

See external documentation.

`addData(This::wxClipboard(), Data::wxDataObject() (see module wxDataObject))
-> bool()`

See external documentation.

`clear(This::wxClipboard()) -> ok`

See external documentation.

`close(This::wxClipboard()) -> ok`

See external documentation.

`flush(This::wxClipboard()) -> bool()`

See external documentation.

`getData(This::wxClipboard(), Data::wxDataObject() (see module wxDataObject))
-> bool()`

See external documentation.

`isOpened(This::wxClipboard()) -> bool()`

See external documentation.

`open(This::wxClipboard()) -> bool()`

See external documentation.

`setData(This::wxClipboard(), Data::wxDataObject() (see module wxDataObject))
-> bool()`

See external documentation.

usePrimarySelection(This::wxClipboard()) -> ok

Equivalent to *usePrimarySelection(This, [])*.

usePrimarySelection(This::wxClipboard(), Options::[Option]) -> ok

Types:

Option = {primary, bool()}

See **external documentation**.

isSupported(This::wxClipboard(), Format::integer()) -> bool()

See **external documentation**.

get() -> wxClipboard()

See **external documentation**.

destroy(This::wxClipboard()) -> ok

Destroys this object, do not use object again

wxCloseEvent

Erlang module

See external documentation: **wxCloseEvent**.

Use *wxEvtHandler:connect/3* with EventType:

close_window, end_session, query_end_session

See also the message variant *#wxClose{}* event record type.

This class is derived (and can use functions) from:

wxEvt

DATA TYPES

`wxCloseEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparsion stored on disc or distributed for use on other nodes.

Exports

canVeto(This::wxCloseEvent()) -> bool()

See external documentation.

getLoggingOff(This::wxCloseEvent()) -> bool()

See external documentation.

setCanVeto(This::wxCloseEvent(), CanVeto::bool()) -> ok

See external documentation.

setLoggingOff(This::wxCloseEvent(), LogOff::bool()) -> ok

See external documentation.

veto(This::wxCloseEvent()) -> ok

Equivalent to *veto(This, [])*.

veto(This::wxCloseEvent(), Options::[Option]) -> ok

Types:

Option = {veto, bool()}

See external documentation.

wxColourData

Erlang module

See external documentation: **wxColourData**.

DATA TYPES

`wxColourData()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxColourData()`

See external documentation.

`new(Data::wxColourData()) -> wxColourData()`

See external documentation.

`getChooseFull(This::wxColourData()) -> bool()`

See external documentation.

`getColour(This::wxColourData()) -> colour() (see module wx)`

See external documentation.

`getCustomColour(This::wxColourData(), I::integer()) -> colour() (see module wx)`

See external documentation.

`setChooseFull(This::wxColourData(), Flag::bool()) -> ok`

See external documentation.

`setColour(This::wxColourData(), Colour::colour() (see module wx)) -> ok`

See external documentation.

`setCustomColour(This::wxColourData(), I::integer(), Colour::colour() (see module wx)) -> ok`

See external documentation.

`destroy(This::wxColourData()) -> ok`

Destroys this object, do not use object again

wxColourDialog

Erlang module

See external documentation: **wxColourDialog**.

This class is derived (and can use functions) from:

wxDialog

wxTopLevelWindow

wxWindow

wxEvtHandler

DATA TYPES

`wxColourDialog()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxColourDialog()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow)) -> wxColourDialog()`

Equivalent to `new(Parent, [])`.

`new(Parent::wxWindow() (see module wxWindow), Options::[Option]) -> wxColourDialog()`

Types:

Option = {data, wxColourData() (see module wxColourData)}

See external documentation.

`create(This::wxColourDialog(), Parent::wxWindow() (see module wxWindow)) -> bool()`

Equivalent to `create(This, Parent, [])`.

`create(This::wxColourDialog(), Parent::wxWindow() (see module wxWindow), Options::[Option]) -> bool()`

Types:

Option = {data, wxColourData() (see module wxColourData)}

See external documentation.

`getColourData(This::wxColourDialog()) -> wxColourData() (see module wxColourData)`

See external documentation.

```
destroy(This::wxColourDialog()) -> ok
```

Destroys this object, do not use object again

wxColourPickerCtrl

Erlang module

See external documentation: **wxColourPickerCtrl**.

This class is derived (and can use functions) from:

wxPickerBase

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxColourPickerCtrl()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxColourPickerCtrl()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Id::integer()) -> wxColourPickerCtrl()`

Equivalent to `new(Parent, Id, [])`.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Options::[Option]) -> wxColourPickerCtrl()`

Types:

Option = {col, colour() (see module wx)} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()} | {validator, wx() (see module wx)}

See external documentation.

`create(This::wxColourPickerCtrl(), Parent::wxWindow() (see module wxWindow), Id::integer()) -> bool()`

Equivalent to `create(This, Parent, Id, [])`.

`create(This::wxColourPickerCtrl(), Parent::wxWindow() (see module wxWindow), Id::integer(), Options::[Option]) -> bool()`

Types:

Option = {col, colour() (see module wx)} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()} | {validator, wx() (see module wx)}

See external documentation.

getColour(This::wxColourPickerCtrl()) -> colour() (see module wx)

See external documentation.

setColour(This::wxColourPickerCtrl(), X::string() | term()) -> bool() | ok

See external documentation.

Alternatives:

setColour(This::wxColourPickerCtrl(), Text::string()) -> bool()

setColour(This::wxColourPickerCtrl(), Col::wx:colour()) -> ok

destroy(This::wxColourPickerCtrl()) -> ok

Destroys this object, do not use object again

wxColourPickerEvent

Erlang module

See external documentation: **wxColourPickerEvent**.

Use *wxEvtHandler:connect/3* with EventType:

command_colourpicker_changed

See also the message variant *#wxColourPicker{}* event record type.

This class is derived (and can use functions) from:

wxCommandEvent

wxEvent

DATA TYPES

`wxColourPickerEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`getColour(This::wxColourPickerEvent()) -> colour()` (see module `wx`)

See **external documentation**.

wxComboBox

Erlang module

See external documentation: **wxComboBox**.

This class is derived (and can use functions) from:

wxControlWithItems

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxComboBox()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxComboBox()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Id::integer()) -> wxComboBox()`

Equivalent to `new(Parent, Id, [])`.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Options::[Option]) -> wxComboBox()`

Types:

Option = {value, string()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {choices, [[string()]]} | {style, integer()} | {validator, wx() (see module wx)}

See external documentation.

`create(This::wxComboBox(), Parent::wxWindow() (see module wxWindow), Id::integer(), Value::string(), Pos::{X::integer(), Y::integer()}, Size::{W::integer(), H::integer()}, Choices:[[string()]]) -> bool()`

Equivalent to `create(This, Parent, Id, Value, Pos, Size, Choices, [])`.

`create(This::wxComboBox(), Parent::wxWindow() (see module wxWindow), Id::integer(), Value::string(), Pos::{X::integer(), Y::integer()}, Size::{W::integer(), H::integer()}, Choices:[[string()]], Options:[Option]) -> bool()`

Types:

Option = {style, integer()} | {validator, wx() (see module wx)}

See external documentation.

`canCopy(This::wxComboBox()) -> bool()`

See external documentation.

`canCut(This::wxComboBox()) -> bool()`

See external documentation.

`canPaste(This::wxComboBox()) -> bool()`

See external documentation.

`canRedo(This::wxComboBox()) -> bool()`

See external documentation.

`canUndo(This::wxComboBox()) -> bool()`

See external documentation.

`copy(This::wxComboBox()) -> ok`

See external documentation.

`cut(This::wxComboBox()) -> ok`

See external documentation.

`getInsertionPoint(This::wxComboBox()) -> integer()`

See external documentation.

`getLastPosition(This::wxComboBox()) -> integer()`

See external documentation.

`getValue(This::wxComboBox()) -> string()`

See external documentation.

`paste(This::wxComboBox()) -> ok`

See external documentation.

`redo(This::wxComboBox()) -> ok`

See external documentation.

`replace(This::wxComboBox(), From::integer(), To::integer(), Value::string())
-> ok`

See external documentation.

`remove(This::wxComboBox(), From::integer(), To::integer()) -> ok`

See external documentation.

setInsertionPoint(This::wxComboBox(), Pos::integer()) -> ok

See external documentation.

setInsertionPointEnd(This::wxComboBox()) -> ok

See external documentation.

setSelection(This::wxComboBox(), N::integer()) -> ok

See external documentation.

setSelection(This::wxComboBox(), From::integer(), To::integer()) -> ok

See external documentation.

setValue(This::wxComboBox(), Value::string()) -> ok

See external documentation.

undo(This::wxComboBox()) -> ok

See external documentation.

destroy(This::wxComboBox()) -> ok

Destroys this object, do not use object again

wxCommandEvent

Erlang module

See external documentation: **wxCommandEvent**.

Use *wxEvtHandler:connect/3* with EventType:

command_button_clicked, command_checkbox_clicked, command_choice_selected, command_listbox_selected, command_listbox_doubleclicked, command_text_updated, command_text_enter, command_menu_selected, command_slider_updated, command_radiobox_selected, command_radiobutton_selected, command_scrollbar_updated, command_vlbox_selected, command_combobox_selected, command_tool_rclicked, command_tool_enter, command_checklistbox_toggled, command_togglebutton_clicked, command_left_click, command_left_dclick, command_right_click, command_set_focus, command_kill_focus, command_enter

See also the message variant *#wxCommandEvent* event record type.

This class is derived (and can use functions) from:

wxEvent

DATA TYPES

wxCommandEvent ()

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

getClientData(*This::wxCommandEvent*() -> *term*()

See external documentation.

getExtraLong(*This::wxCommandEvent*() -> *integer*()

See external documentation.

getInt(*This::wxCommandEvent*() -> *integer*()

See external documentation.

getSelection(*This::wxCommandEvent*() -> *integer*()

See external documentation.

getString(*This::wxCommandEvent*() -> *string*()

See external documentation.

isChecked(*This::wxCommandEvent*() -> *bool*()

See external documentation.

isSelection(This::wxCommandEvent()) -> bool()

See external documentation.

setInt(This::wxCommandEvent(), I::integer()) -> ok

See external documentation.

setString(This::wxCommandEvent(), S::string()) -> ok

See external documentation.

wxContextMenuEvent

Erlang module

See external documentation: **wxContextMenuEvent**.

Use *wxEvtHandler:connect/3* with EventType:

context_menu

See also the message variant *#wxContextMenu{}* event record type.

This class is derived (and can use functions) from:

wxCommandEvent

wxEvent

DATA TYPES

wxContextMenuEvent()

An object reference, The representation is internal and can be changed without notice. It can't be used for comparsion stored on disc or distributed for use on other nodes.

Exports

getPosition(This::wxContextMenuEvent()) -> {X::integer(), Y::integer()}

See external documentation.

setPosition(This::wxContextMenuEvent(), Pos::{X::integer(), Y::integer()}) -> ok

See external documentation.

wxControl

Erlang module

See external documentation: **wxControl**.

This class is derived (and can use functions) from:

wxWindow

wxEvtHandler

DATA TYPES

`wxControl()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`getLabel(This::wxControl()) -> string()`

See external documentation.

`setLabel(This::wxControl(), Label::string()) -> ok`

See external documentation.

wxControlWithItems

Erlang module

See external documentation: **wxControlWithItems**.

This class is derived (and can use functions) from:

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxControlWithItems()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`append(This::wxControlWithItems(), Item::string()) -> integer()`

See external documentation.

`append(This::wxControlWithItems(), Item::string(), ClientData::term()) -> integer()`

See external documentation.

`appendStrings(This::wxControlWithItems(), Strings::[[string()]]) -> ok`

See external documentation.

`clear(This::wxControlWithItems()) -> ok`

See external documentation.

`delete(This::wxControlWithItems(), N::integer()) -> ok`

See external documentation.

`findString(This::wxControlWithItems(), S::string()) -> integer()`

Equivalent to `findString(This, S, [])`.

`findString(This::wxControlWithItems(), S::string(), Options::[Option]) -> integer()`

Types:

`Option = {bCase, bool()}`

See external documentation.

`getClientData(This::wxControlWithItems(), N::integer()) -> term()`

See external documentation.


```
setClientData(This::wxControlWithItems(), N::integer(), ClientData::term()) -  
> ok
```

See external documentation.

```
getCount(This::wxControlWithItems()) -> integer()
```

See external documentation.

```
getSelection(This::wxControlWithItems()) -> integer()
```

See external documentation.

```
getString(This::wxControlWithItems(), N::integer()) -> string()
```

See external documentation.

```
getStringSelection(This::wxControlWithItems()) -> string()
```

See external documentation.

```
insert(This::wxControlWithItems(), Item::string(), Pos::integer()) ->  
integer()
```

See external documentation.

```
insert(This::wxControlWithItems(), Item::string(), Pos::integer(),  
ClientData::term()) -> integer()
```

See external documentation.

```
isEmpty(This::wxControlWithItems()) -> bool()
```

See external documentation.

```
select(This::wxControlWithItems(), N::integer()) -> ok
```

See external documentation.

```
setSelection(This::wxControlWithItems(), N::integer()) -> ok
```

See external documentation.

```
setString(This::wxControlWithItems(), N::integer(), S::string()) -> ok
```

See external documentation.

```
setStringSelection(This::wxControlWithItems(), S::string()) -> bool()
```

See external documentation.

wxCursor

Erlang module

See external documentation: **wxCursor**.

This class is derived (and can use functions) from:

wxBitmap

DATA TYPES

`wxCursor()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxCursor()`

See external documentation.

`new(X::integer() | term()) -> wxCursor()`

See external documentation.

Alternatives:

`new(CursorId::integer()) -> wxCursor()`

`new(Image::wxImage:wxImage()) -> wxCursor()`

`new(Bits::binary(), Width::integer(), Height::integer()) -> wxCursor()`

Equivalent to `new(Bits, Width, Height, [])`.

`new(Bits::binary(), Width::integer(), Height::integer(), Options::[Option]) -> wxCursor()`

Types:

Option = {hotSpotX, integer()} | {hotSpotY, integer()}

See external documentation.

`ok(This::wxCursor()) -> bool()`

See external documentation.

`destroy(This::wxCursor()) -> ok`

Destroys this object, do not use object again

wxDataObject

Erlang module

See external documentation: **wxDataObject**.

DATA TYPES

`wxDataObject()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

wxDatEvent

Erlang module

See external documentation: **wxDatEvent**.

Use *wxEvtHandler:connect/3* with EventType:

date_changed

See also the message variant *#wxDat{}* event record type.

This class is derived (and can use functions) from:

wxCommandEvent

wxEvt

DATA TYPES

wxDatEvent()

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

getDate(This::wxDatEvent()) -> datetime() (see module wx)

See external documentation.

wxDatePickerCtrl

Erlang module

See external documentation: **wxDatePickerCtrl**.

This class is derived (and can use functions) from:

wxPickerBase

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxDatePickerCtrl()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxDatePickerCtrl()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Id::integer()) -> wxDatePickerCtrl()`

Equivalent to `new(Parent, Id, [])`.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Options::[Option]) -> wxDatePickerCtrl()`

Types:

Option = {date, datetime() (see module wx)} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()} | {validator, wx() (see module wx)}

See external documentation.

`getRange(This::wxDatePickerCtrl(), Dt1::datetime() (see module wx), Dt2::datetime() (see module wx)) -> bool()`

See external documentation.

`getValue(This::wxDatePickerCtrl()) -> datetime() (see module wx)`

See external documentation.

`setRange(This::wxDatePickerCtrl(), Dt1::datetime() (see module wx), Dt2::datetime() (see module wx)) -> ok`

See external documentation.

wxDaterangepickerCtrl

setValue(This::wxDaterangepickerCtrl(), Date::datetime() (see module wx)) -> ok

See **external documentation**.

destroy(This::wxDaterangepickerCtrl()) -> ok

Destroys this object, do not use object again

wxDC

Erlang module

See external documentation: **wxDC**.

DATA TYPES

`wxDC()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

```
blit(This::wxDC(), DestPt::{X::integer(), Y::integer()}, Sz::{W::integer(),
H::integer()}, Source::wxDC(), SrcPt::{X::integer(), Y::integer()}) -> bool()
```

Equivalent to *blit(This, DestPt, Sz, Source, SrcPt, [])*.

```
blit(This::wxDC(), DestPt::{X::integer(), Y::integer()}, Sz::{W::integer(),
H::integer()}, Source::wxDC(), SrcPt::{X::integer(), Y::integer()}, Options::
[Option]) -> bool()
```

Types:

Option = {rop, integer()} | {useMask, bool()} | {srcPtMask, {X::integer(), Y::integer()}}

See external documentation.

```
calcBoundingBox(This::wxDC(), X::integer(), Y::integer()) -> ok
```

See external documentation.

```
clear(This::wxDC()) -> ok
```

See external documentation.

```
computeScaleAndOrigin(This::wxDC()) -> ok
```

See external documentation.

```
crossHair(This::wxDC(), Pt::{X::integer(), Y::integer()}) -> ok
```

See external documentation.

```
destroyClippingRegion(This::wxDC()) -> ok
```

See external documentation.

```
deviceToLogicalX(This::wxDC(), X::integer()) -> integer()
```

See external documentation.

`deviceToLogicalXRel(This::wxDC(), X::integer()) -> integer()`

See external documentation.

`deviceToLogicalY(This::wxDC(), Y::integer()) -> integer()`

See external documentation.

`deviceToLogicalYRel(This::wxDC(), Y::integer()) -> integer()`

See external documentation.

`drawArc(This::wxDC(), Pt1::{X::integer(), Y::integer()}, Pt2::{X::integer(), Y::integer()}, Centre::{X::integer(), Y::integer()}) -> ok`

See external documentation.

`drawBitmap(This::wxDC(), Bmp::wxBitmap() (see module wxBitmap), Pt::{X::integer(), Y::integer()}) -> ok`

Equivalent to *drawBitmap(This, Bmp, Pt, [])*.

`drawBitmap(This::wxDC(), Bmp::wxBitmap() (see module wxBitmap), Pt::{X::integer(), Y::integer()}, Options::[Option]) -> ok`

Types:

`Option = {useMask, bool()}`

See external documentation.

`drawCheckMark(This::wxDC(), Rect::{X::integer(), Y::integer(), W::integer(), H::integer()}) -> ok`

See external documentation.

`drawCircle(This::wxDC(), Pt::{X::integer(), Y::integer()}, Radius::integer()) -> ok`

See external documentation.

`drawEllipse(This::wxDC(), Rect::{X::integer(), Y::integer(), W::integer(), H::integer()}) -> ok`

See external documentation.

`drawEllipse(This::wxDC(), Pt::{X::integer(), Y::integer()}, Sz::{W::integer(), H::integer()}) -> ok`

See external documentation.

`drawEllipticArc(This::wxDC(), Pt::{X::integer(), Y::integer()}, Sz::{W::integer(), H::integer()}, Sa::float(), Ea::float()) -> ok`

See external documentation.

```
drawIcon(This::wxDC(), Icon::wxIcon() (see module wxIcon), Pt::{X::integer(),
Y::integer()}) -> ok
```

See external documentation.

```
drawLabel(This::wxDC(), Text::string(), Rect::{X::integer(), Y::integer(),
W::integer(), H::integer()}) -> ok
```

Equivalent to *drawLabel(This, Text, Rect, [])*.

```
drawLabel(This::wxDC(), Text::string(), Rect::{X::integer(), Y::integer(),
W::integer(), H::integer()}, Options::[Option]) -> ok
```

Types:

Option = {alignment, integer()} | {indexAccel, integer()}

See external documentation.

```
drawLine(This::wxDC(), Pt1::{X::integer(), Y::integer()}, Pt2::{X::integer(),
Y::integer()}) -> ok
```

See external documentation.

```
drawLines(This::wxDC(), Points::{[X::integer(), Y::integer()]}) -> ok
```

Equivalent to *drawLines(This, Points, [])*.

```
drawLines(This::wxDC(), Points::{[X::integer(), Y::integer()]}, Options::
[Option]) -> ok
```

Types:

Option = {xoffset, integer()} | {yoffset, integer()}

See external documentation.

```
drawPolygon(This::wxDC(), Points::{[X::integer(), Y::integer()]}) -> ok
```

Equivalent to *drawPolygon(This, Points, [])*.

```
drawPolygon(This::wxDC(), Points::{[X::integer(), Y::integer()]}, Options::
[Option]) -> ok
```

Types:

Option = {xoffset, integer()} | {yoffset, integer()} | {fillStyle, integer()}

See external documentation.

```
drawPoint(This::wxDC(), Pt::{X::integer(), Y::integer()}) -> ok
```

See external documentation.

```
drawRectangle(This::wxDC(), Rect::{X::integer(), Y::integer(), W::integer(),
H::integer()}) -> ok
```

See external documentation.

```
drawRectangle(This::wxDC(), Pt::{X::integer(), Y::integer()}, Sz::
{W::integer(), H::integer()}) -> ok
```

See external documentation.

```
drawRotatedText(This::wxDC(), Text::string(), Pt::{X::integer(),
Y::integer()}, Angle::float()) -> ok
```

See external documentation.

```
drawRoundedRectangle(This::wxDC(), R::{X::integer(), Y::integer(),
W::integer(), H::integer()}, Radius::float()) -> ok
```

See external documentation.

```
drawRoundedRectangle(This::wxDC(), Pt::{X::integer(), Y::integer()}, Sz::
{W::integer(), H::integer()}, Radius::float()) -> ok
```

See external documentation.

```
drawText(This::wxDC(), Text::string(), Pt::{X::integer(), Y::integer()}) ->
ok
```

See external documentation.

```
endDoc(This::wxDC()) -> ok
```

See external documentation.

```
endPage(This::wxDC()) -> ok
```

See external documentation.

```
floodFill(This::wxDC(), Pt::{X::integer(), Y::integer()}, Col::colour() (see
module wx)) -> bool()
```

Equivalent to *floodFill(This, Pt, Col, [])*.

```
floodFill(This::wxDC(), Pt::{X::integer(), Y::integer()}, Col::colour() (see
module wx), Options::[Option]) -> bool()
```

Types:

Option = {style, integer()}

See external documentation.

```
getBackground(This::wxDC()) -> wxBrush() (see module wxBrush)
```

See external documentation.

```
getBackgroundMode(This::wxDC()) -> integer()
```

See external documentation.

```
getBrush(This::wxDC()) -> wxBrush() (see module wxBrush)
```

See external documentation.

`getCharHeight(This::wxDC()) -> integer()`

See external documentation.

`getCharWidth(This::wxDC()) -> integer()`

See external documentation.

`getClippingBox(This::wxDC(), Rect::{X::integer(), Y::integer(), W::integer(), H::integer()}) -> ok`

See external documentation.

`getFont(This::wxDC()) -> wxFont() (see module wxFont)`

See external documentation.

`getLayoutDirection(This::wxDC()) -> WxLayoutDirection`

Types:

`WxLayoutDirection = integer()`

See external documentation.

WxLayoutDirection is one of ?wxLayout_Default | ?wxLayout_LeftToRight | ?wxLayout_RightToLeft

`getLogicalFunction(This::wxDC()) -> integer()`

See external documentation.

`getMapMode(This::wxDC()) -> integer()`

See external documentation.

`getMultiLineTextExtent(This::wxDC(), String::string()) -> {W::integer(), H::integer()}`

See external documentation.

`getMultiLineTextExtent(This::wxDC(), String::string(), Options::[Option]) -> {Width::integer(), Height::integer(), HeightLine::integer()}`

Types:

`Option = {font, wxFont() (see module wxFont)}`

See external documentation.

`getPartialTextExtents(This::wxDC(), Text::string(), Widths::[integer()]) -> bool()`

See external documentation.

`getPen(This::wxDC()) -> wxPen() (see module wxPen)`

See external documentation.

`getPixel(This::wxDC(), Pt::{X::integer(), Y::integer()}, Col::colour())` (see module `wx`) -> `bool()`

See external documentation.

`getPPI(This::wxDC())` -> `{W::integer(), H::integer()}`

See external documentation.

`getSize(This::wxDC())` -> `{W::integer(), H::integer()}`

See external documentation.

`getSizeMM(This::wxDC())` -> `{W::integer(), H::integer()}`

See external documentation.

`getTextBackground(This::wxDC())` -> `colour()` (see module `wx`)

See external documentation.

`getTextExtent(This::wxDC(), String::string())` -> `{W::integer(), H::integer()}`

See external documentation.

`getTextExtent(This::wxDC(), String::string(), Options::[Option])` -> `{X::integer(), Y::integer(), Descent::integer(), ExternalLeading::integer()}`

Types:

`Option = {theFont, wxFont() (see module wxFont)}`

See external documentation.

`getTextForeground(This::wxDC())` -> `colour()` (see module `wx`)

See external documentation.

`getUserScale(This::wxDC())` -> `{X::float(), Y::float()}`

See external documentation.

`gradientFillConcentric(This::wxDC(), Rect::{X::integer(), Y::integer(), W::integer(), H::integer()}, InitialColour::colour() (see module wx), DestColour::colour() (see module wx))` -> `ok`

See external documentation.

`gradientFillConcentric(This::wxDC(), Rect::{X::integer(), Y::integer(), W::integer(), H::integer()}, InitialColour::colour() (see module wx), DestColour::colour() (see module wx), CircleCenter::{X::integer(), Y::integer()})` -> `ok`

See external documentation.

```
gradientFillLinear(This::wxDC(), Rect::{X::integer(), Y::integer(),
W::integer(), H::integer()}, InitialColour::colour() (see module wx),
DestColour::colour() (see module wx)) -> ok
```

Equivalent to `gradientFillLinear(This, Rect, InitialColour, DestColour, [])`.

```
gradientFillLinear(This::wxDC(), Rect::{X::integer(), Y::integer(),
W::integer(), H::integer()}, InitialColour::colour() (see module wx),
DestColour::colour() (see module wx), Options::[Option]) -> ok
```

Types:

Option = {nDirection, WxDirection}

WxDirection = integer()

See external documentation.

WxDirection is one of ?wxLEFT | ?wxRIGHT | ?wxUP | ?wxDOWN | ?wxTOP | ?wxBOTTOM | ?wxNORTH | ?wxSOUTH | ?wxWEST | ?wxEAST | ?wxALL

```
logicalToDeviceX(This::wxDC(), X::integer()) -> integer()
```

See external documentation.

```
logicalToDeviceXRel(This::wxDC(), X::integer()) -> integer()
```

See external documentation.

```
logicalToDeviceY(This::wxDC(), Y::integer()) -> integer()
```

See external documentation.

```
logicalToDeviceYRel(This::wxDC(), Y::integer()) -> integer()
```

See external documentation.

```
maxX(This::wxDC()) -> integer()
```

See external documentation.

```
maxY(This::wxDC()) -> integer()
```

See external documentation.

```
minX(This::wxDC()) -> integer()
```

See external documentation.

```
minY(This::wxDC()) -> integer()
```

See external documentation.

```
isOk(This::wxDC()) -> bool()
```

See external documentation.

```
resetBoundingBox(This::wxDC()) -> ok
```

See external documentation.

setAxisOrientation(This::wxDC(), XLeftRight::bool(), YBottomUp::bool()) -> ok

See external documentation.

setBackground(This::wxDC(), Brush::wxBrush() (see module wxBrush)) -> ok

See external documentation.

setBackgroundMode(This::wxDC(), Mode::integer()) -> ok

See external documentation.

setBrush(This::wxDC(), Brush::wxBrush() (see module wxBrush)) -> ok

See external documentation.

setClippingRegion(This::wxDC(), X::term()) -> ok

See external documentation.

Alternatives:

setClippingRegion(This::wxDC(), Region::wxRegion:wxRegion()) -> ok

**setClippingRegion(This::wxDC(),
{X::integer(),Y::integer(),W::integer(),H::integer()}) -> ok** Rect::

**setClippingRegion(This::wxDC(), Pt::{X::integer(), Y::integer()}, Sz::{
W::integer(), H::integer()}) -> ok**

See external documentation.

setDeviceOrigin(This::wxDC(), X::integer(), Y::integer()) -> ok

See external documentation.

setFont(This::wxDC(), Font::wxFont() (see module wxFont)) -> ok

See external documentation.

setLayoutDirection(This::wxDC(), Dir::WxLayoutDirection) -> ok

Types:

WxLayoutDirection = integer()

See external documentation.

WxLayoutDirection is one of ?wxLayout_Default | ?wxLayout_LeftToRight | ?wxLayout_RightToLeft

setLogicalFunction(This::wxDC(), Function::integer()) -> ok

See external documentation.

setMapMode(This::wxDC(), Mode::integer()) -> ok

See external documentation.

setPalette(This::wxDC(), Palette::wxPalette() (see module wxPalette)) -> ok

See external documentation.

setPen(This::wxDC(), Pen::wxPen() (see module wxPen)) -> ok

See external documentation.

setTextBackground(This::wxDC(), Colour::colour() (see module wx)) -> ok

See external documentation.

setTextForeground(This::wxDC(), Colour::colour() (see module wx)) -> ok

See external documentation.

setUserScale(This::wxDC(), X::float(), Y::float()) -> ok

See external documentation.

startDoc(This::wxDC(), Message::string()) -> bool()

See external documentation.

startPage(This::wxDC()) -> ok

See external documentation.

wxDiallog

Erlang module

See external documentation: **wxDiallog**.

This class is derived (and can use functions) from:

wxTopLevelWindow

wxWindow

wxEvtHandler

DATA TYPES

`wxDiallog()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxDiallog()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Title::string()) -> wxDiallog()`

Equivalent to `new(Parent, Id, Title, [])`.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Title::string(), Options::[Option]) -> wxDiallog()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`create(This::wxDiallog(), Parent::wxWindow() (see module wxWindow), Id::integer(), Title::string()) -> bool()`

Equivalent to `create(This, Parent, Id, Title, [])`.

`create(This::wxDiallog(), Parent::wxWindow() (see module wxWindow), Id::integer(), Title::string(), Options::[Option]) -> bool()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`createButtonSizer(This::wxDiallog(), Flags::integer()) -> wxSizer() (see module wxSizer)`

See external documentation.

`createStdDialogButtonSizer(This::wxDialog(), Flags::integer()) -> wxStdDialogButtonSizer()` (see module `wxStdDialogButtonSizer`)

See external documentation.

`endModal(This::wxDialog(), RetCode::integer()) -> ok`

See external documentation.

`getAffirmativeId(This::wxDialog()) -> integer()`

See external documentation.

`getReturnCode(This::wxDialog()) -> integer()`

See external documentation.

`isModal(This::wxDialog()) -> bool()`

See external documentation.

`setAffirmativeId(This::wxDialog(), AffirmativeId::integer()) -> ok`

See external documentation.

`setReturnCode(This::wxDialog(), ReturnCode::integer()) -> ok`

See external documentation.

`show(This::wxDialog()) -> bool()`

Equivalent to `show(This, [])`.

`show(This::wxDialog(), Options::[Option]) -> bool()`

Types:

Option = {show, bool()}

See external documentation.

`showModal(This::wxDialog()) -> integer()`

See external documentation.

`destroy(This::wxDialog()) -> ok`

Destroys this object, do not use object again

wxDirDialog

Erlang module

See external documentation: **wxDirDialog**.

This class is derived (and can use functions) from:

wxDialog

wxTopLevelWindow

wxWindow

wxEvtHandler

DATA TYPES

`wxDirDialog()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new(Parent::wxWindow() (see module wxWindow)) -> wxDirDialog()`

Equivalent to `new(Parent, [])`.

`new(Parent::wxWindow() (see module wxWindow), Options::[Option]) -> wxDirDialog()`

Types:

`Option = {title, string()} | {defaultPath, string()} | {style, integer()} | {pos, {X::integer(), Y::integer()}} | {sz, {W::integer(), H::integer()}}`

See external documentation.

`getPath(This::wxDirDialog()) -> string()`

See external documentation.

`getMessage(This::wxDirDialog()) -> string()`

See external documentation.

`setMessage(This::wxDirDialog(), Message::string()) -> ok`

See external documentation.

`setPath(This::wxDirDialog(), Path::string()) -> ok`

See external documentation.

`destroy(This::wxDirDialog()) -> ok`

Destroys this object, do not use object again

wxDirPickerCtrl

Erlang module

See external documentation: **wxDirPickerCtrl**.

This class is derived (and can use functions) from:

wxPickerBase

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxDirPickerCtrl()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxDirPickerCtrl()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Id::integer()) -> wxDirPickerCtrl()`

Equivalent to `new(Parent, Id, [])`.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Options::[Option]) -> wxDirPickerCtrl()`

Types:

Option = {path, string()} | {message, string()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()} | {validator, wx() (see module wx)}

See external documentation.

`create(This::wxDirPickerCtrl(), Parent::wxWindow() (see module wxWindow), Id::integer()) -> bool()`

Equivalent to `create(This, Parent, Id, [])`.

`create(This::wxDirPickerCtrl(), Parent::wxWindow() (see module wxWindow), Id::integer(), Options::[Option]) -> bool()`

Types:

Option = {path, string()} | {message, string()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()} | {validator, wx() (see module wx)}

See external documentation.

wxDirPickerCtrl

getPath(This::wxDirPickerCtrl()) -> string()

See **external documentation**.

setPath(This::wxDirPickerCtrl(), Str::string()) -> ok

See **external documentation**.

destroy(This::wxDirPickerCtrl()) -> ok

Destroys this object, do not use object again

wxDisplayChangedEvent

Erlang module

See external documentation: **wxDisplayChangedEvent**.

Use *wxEvtHandler:connect/3* with EventType:

display_changed

See also the message variant *#wxDisplayChanged{}* event record type.

This class is derived (and can use functions) from:

wxEvent

DATA TYPES

`wxDisplayChangedEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

wxEraseEvent

Erlang module

See external documentation: **wxEraseEvent**.

Use *wxEvtHandler:connect/3* with EventType:

erase_background

See also the message variant *#wxErase{}* event record type.

This class is derived (and can use functions) from:

wxEvt

DATA TYPES

wxEraseEvent ()

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

getDC(This::wxEraseEvent()) -> wxDC() (see module **wxDC**)

See external documentation.

wxEvent

Erlang module

See external documentation: **wxEvent**.

DATA TYPES

`wxEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`getId(This::wxEvent()) -> integer()`

See external documentation.

`getSkipped(This::wxEvent()) -> bool()`

See external documentation.

`getTimestamp(This::wxEvent()) -> integer()`

See external documentation.

`isCommandEvent(This::wxEvent()) -> bool()`

See external documentation.

`resumePropagation(This::wxEvent(), PropagationLevel::integer()) -> ok`

See external documentation.

`shouldPropagate(This::wxEvent()) -> bool()`

See external documentation.

`skip(This::wxEvent()) -> ok`

Equivalent to `skip(This, [])`.

`skip(This::wxEvent(), Options::[Option]) -> ok`

Types:

`Option = {skip, bool()}`

See external documentation.

`stopPropagation(This::wxEvent()) -> integer()`

See external documentation.

wxEvtHandler

Erlang module

The Event handler.

To get events from wxwidgets objects you subscribe to them by calling `connect/[2-3]`. Events are sent as messages, if no callback was supplied These messages will be `#wx{}` where `EventRecord` is a record that depends on the *event type*. The records are defined in: `wx/include/wx.hrl`.

If a callback was supplied to `connect`, the callback will be invoked (in another process) to handle the event. The callback should be of arity 2. `fun(EventRecord::wx(), EventObject::wxObject())`.

Beware that the callback will be in executed in new process each time.

The original documentation.

DATA TYPES

```
wx() = #wx{id=integer(), obj=wxObject() (see module wx), userData=term(),
event=Rec}
```

Rec is a event record.

```
wxAuiManager() = #wxAuiManager{type=wxEventType(), manager=wxAuiManager()
(see module wxAuiManager), pane=wxAuiPaneInfo() (see module wxAuiPaneInfo),
button=integer(), veto_flag=bool(), canveto_flag=bool(), dc=wxDC() (see
module wxDC)}
```

EventType:

lui_pane_button, lui_pane_close, lui_pane_maximize, lui_pane_restore, lui_render, lui_find_manager

Callback event: *wxAuiManagerEvent*

```
wxAuiNotebook() = #wxAuiNotebook{type=wxEventType(), old_selection=integer(),
selection=integer(), drag_source=wxAuiNotebook() (see module wxAuiNotebook)}
```

EventType:

command_auiNotebook_page_close, command_auiNotebook_page_changed,
command_auiNotebook_page_changing, command_auiNotebook_button, command_auiNotebook_begin_drag,
command_auiNotebook_end_drag, command_auiNotebook_drag_motion, command_auiNotebook_allow_dnd,
command_auiNotebook_tab_middle_down, command_auiNotebook_tab_middle_up,
command_auiNotebook_tab_right_down, command_auiNotebook_tab_right_up,
command_auiNotebook_page_closed, command_auiNotebook_drag_done, command_auiNotebook_bg_dclick

Callback event: *wxAuiNotebookEvent*

```
wxCalendar() = #wxCalendar{type=wxEventType() }
```

EventType:

calendar_sel_changed, calendar_day_changed, calendar_month_changed, calendar_year_changed,
calendar_doubleclicked, calendar_weekday_clicked

Callback event: *wxCalendarEvent*

```
wxChildFocus() = #wxChildFocus{type=wxEventType() }
```

EventType:

child_focus

Callback event: *wxChildFocusEvent*

```
wxClose() = #wxClose{type=wxEventType()}
```

EventType:

close_window, end_session, query_end_session

Callback event: *wxCloseEvent*

```
wxColourPicker() = #wxColourPicker{type=wxEventType(), colour=colour() (see module wx)}
```

EventType:

command_colourpicker_changed

Callback event: *wxColourPickerEvent*

```
wxCommand() = #wxCommand{type=wxEventType(), cmdString=string(),
commandInt=integer(), extraLong=integer()}
```

EventType:

*command_button_clicked, command_checkbox_clicked, command_choice_selected, command_listbox_selected,
command_listbox_doubleclicked, command_text_updated, command_text_enter, command_menu_selected,
command_slider_updated, command_radiobox_selected, command_radiobutton_selected,
command_scrollbar_updated, command_vlbox_selected, command_combobox_selected,
command_tool_rclicked, command_tool_enter, command_checklistbox_toggled,
command_togglebutton_clicked, command_left_click, command_left_dclick, command_right_click,
command_set_focus, command_kill_focus, command_enter*

Callback event: *wxCommandEvent*

```
wxContextMenu() = #wxContextMenu{type=wxEventType()}
```

EventType:

context_menu

Callback event: *wxContextMenuEvent*

```
wxDate() = #wxDate{type=wxEventType(), date=datetime() (see module wx)}
```

EventType:

date_changed

Callback event: *wxDateEvent*

```
wxDisplayChanged() = #wxDisplayChanged{type=wxEventType()}
```

EventType:

display_changed

Callback event: *wxDisplayChangedEvent*

```
wxErase() = #wxErase{type=wxEventType(), dc=wxDC() (see module wxDC)}
```

EventType:

erase_background

Callback event: *wxEraseEvent*

```
wxEventType() = aui_find_manager | aui_pane_button | aui_pane_close |
aui_pane_maximize | aui_pane_restore | aui_render | calendar_day_changed
| calendar_doubleclicked | calendar_month_changed | calendar_sel_changed
| calendar_weekday_clicked | calendar_year_changed | char | char_hook
```

| child_focus | close_window | command_aui notebook_allow_dnd |
command_aui notebook_begin_drag | command_aui notebook_bg_dclick
| command_aui notebook_button | command_aui notebook_drag_done |
command_aui notebook_drag_motion | command_aui notebook_end_drag |
command_aui notebook_page_changed | command_aui notebook_page_changing
| command_aui notebook_page_close | command_aui notebook_page_closed |
command_aui notebook_tab_middle_down | command_aui notebook_tab_middle_up
| command_aui notebook_tab_right_down | command_aui notebook_tab_right_up
| command_button_clicked | command_checkbox_clicked |
command_checklistbox_toggled | command_choice_selected |
command_colourpicker_changed | command_combobox_selected |
command_dirpicker_changed | command_enter | command_filepicker_changed
| command_fontpicker_changed | command_html_link_clicked |
command_kill_focus | command_left_click | command_left_dclick
| command_list_begin_drag | command_list_begin_label_edit
| command_list_begin_rdrag | command_list_cache_hint |
command_list_col_begin_drag | command_list_col_click |
command_list_col_dragging | command_list_col_end_drag |
command_list_col_right_click | command_list_delete_all_items
| command_list_delete_item | command_list_end_label_edit
| command_list_insert_item | command_list_item_activated |
command_list_item_deselected | command_list_item_focused |
command_list_item_middle_click | command_list_item_right_click
| command_list_item_selected | command_list_key_down |
command_listbox_doubleclicked | command_listbox_selected
| command_menu_selected | command_notebook_page_changed |
command_notebook_page_changing | command_radiobox_selected
| command_radiobutton_selected | command_right_click |
command_scrollbar_updated | command_set_focus | command_slider_updated
| command_spinctrl_updated | command_splitter_doubleclicked |
command_splitter_sash_pos_changed | command_splitter_sash_pos_changing
| command_splitter_unsplit | command_text_enter | command_text_updated |
command_togglebutton_clicked | command_tool_enter | command_tool_rclicked
| command_tree_begin_drag | command_tree_begin_label_edit |
command_tree_begin_rdrag | command_tree_delete_item | command_tree_end_drag
| command_tree_end_label_edit | command_tree_get_info |
command_tree_item_activated | command_tree_item_collapsed |
command_tree_item_collapsing | command_tree_item_expanded |
command_tree_item_expanding | command_tree_item_gettooltip
| command_tree_item_menu | command_tree_item_middle_click
| command_tree_item_right_click | command_tree_key_down |
command_tree_sel_changed | command_tree_sel_changing | command_tree_set_info
| command_tree_state_image_click | command_vlbox_selected | context_menu
| create | date_changed | destroy | detailed_help | display_changed |
end_session | enter_window | erase_background | grid_cell_begin_drag
| grid_cell_change | grid_cell_left_click | grid_cell_left_dclick
| grid_cell_right_click | grid_cell_right_dclick | grid_col_size
| grid_editor_created | grid_editor_hidden | grid_editor_shown |
grid_label_left_click | grid_label_left_dclick | grid_label_right_click
| grid_label_right_dclick | grid_range_select | grid_row_size |
grid_select_cell | help | iconize | idle | joy_button_down | joy_button_up
| joy_move | joy_zmove | key_down | key_up | kill_focus | leave_window

```
| left_dclick | left_down | left_up | maximize | menu_close |
menu_highlight | menu_open | middle_dclick | middle_down | middle_up
| motion | mouse_capture_changed | mousewheel | move | navigation_key
| nc_enter_window | nc_leave_window | nc_left_dclick | nc_left_down |
nc_left_up | nc_middle_dclick | nc_middle_down | nc_middle_up | nc_motion
| nc_paint | nc_right_dclick | nc_right_down | nc_right_up | paint |
paint_icon | palette_changed | query_end_session | query_new_palette
| right_dclick | right_down | right_up | sash_dragged | scroll_bottom
| scroll_changed | scroll_linedown | scroll_lineup | scroll_pagedown |
scroll_pageup | scroll_thumbrelease | scroll_thumbtrack | scroll_top |
scrollwin_bottom | scrollwin_linedown | scrollwin_lineup | scrollwin_pagedown
| scrollwin_pageup | scrollwin_thumbrelease | scrollwin_thumbtrack |
scrollwin_top | set_cursor | set_focus | show | size | spin | spin_down
| spin_up | stc_autocomp_selection | stc_calltip_click | stc_change |
stc_charadded | stc_do_drop | stc_doubleclick | stc_drag_over | stc_dwelling
| stc_dwellingstart | stc_hotspot_click | stc_hotspot_dclick | stc_key
| stc_macrorecord | stc_marginclick | stc_modified | stc_needshown |
stc_painted | stc_romodifyattempt | stc_savepointleft | stc_savepointreached
| stc_start_drag | stc_styleneeded | stc_updateui | stc_uridropped |
stc_userlistselection | stc_zoom | sys_colour_changed | update_ui
wxEvtHandler()
```

An object reference

```
wxFileDialogPicker() = #wxFileDialogPicker{type=wxEventType(), path=string()}
```

EventType:

command_filepicker_changed, command_dirpicker_changed

Callback event: *wxFileDialogPickerEvent*

```
wxFocus() = #wxFocus{type=wxEventType()}
```

EventType:

set_focus, kill_focus

Callback event: *wxFocusEvent*

```
wxFontPicker() = #wxFontPicker{type=wxEventType(), font=wxFont() (see module
wxFont)}
```

EventType:

command_fontpicker_changed

Callback event: *wxFontPickerEvent*

```
wxGrid() = #wxGrid{type=wxEventType(), row=integer(), col=integer(),
x=integer(), y=integer(), selecting=bool(), control=bool(), meta=bool(),
shift=bool(), alt=bool()}
```

EventType:

grid_cell_left_click, grid_cell_right_click, grid_cell_left_dclick, grid_cell_right_dclick, grid_label_left_click, grid_label_right_click, grid_label_left_dclick, grid_label_right_dclick, grid_row_size, grid_col_size, grid_range_select, grid_cell_change, grid_select_cell, grid_editor_shown, grid_editor_hidden, grid_editor_created, grid_cell_begin_drag

Callback event: *wxGridEvent*

`wxHelp()` = `#wxHelp{type=wxEventType() }`

EventType:

help, detailed_help

Callback event: *wxHelpEvent*

`wxHtmlLink()` = `#wxHtmlLink{type=wxEventType(), linkInfo=wxHtmlLinkInfo() (see module wx) }`

EventType:

command_html_link_clicked

Callback event: *wxHtmlLinkEvent*

`wxIconize()` = `#wxIconize{type=wxEventType() }`

EventType:

iconize

Callback event: *wxIconizeEvent*

`wxIdle()` = `#wxIdle{type=wxEventType() }`

EventType:

idle

Callback event: *wxIdleEvent*

`wxJoystick()` = `#wxJoystick{type=wxEventType() }`

EventType:

joy_button_down, joy_button_up, joy_move, joy_zmove

Callback event: *wxJoystickEvent*

`wxKey()` = `#wxKey{type=wxEventType(), x=integer(), y=integer(),
keyCode=integer(), controlDown=bool(), shiftDown=bool(), altDown=bool(),
metaDown=bool(), scanCode=bool(), uniChar=integer(), rawCode=integer(),
rawFlags=integer() }`

EventType:

char, char_hook, key_down, key_up

Callback event: *wxKeyEvent*

`wxList()` = `#wxList{type=wxEventType(), code=integer(),
oldItemIndex=integer(), itemIndex=integer(), col=integer(),
pointDrag={X::integer(), Y::integer() } }`

EventType:

<i>command_list_begin_drag,</i>	<i>command_list_begin_rdrag,</i>	<i>command_list_begin_label_edit,</i>	
<i>command_list_end_label_edit,</i>	<i>command_list_delete_item,</i>	<i>command_list_delete_all_items,</i>	
<i>command_list_key_down,</i>	<i>command_list_insert_item,</i>	<i>command_list_col_click,</i>	<i>command_list_col_right_click,</i>
<i>command_list_col_begin_drag,</i>	<i>command_list_col_dragging,</i>	<i>command_list_col_end_drag,</i>	
<i>command_list_item_selected,</i>	<i>command_list_item_deselected,</i>	<i>command_list_item_right_click,</i>	
<i>command_list_item_middle_click,</i>	<i>command_list_item_activated,</i>	<i>command_list_item_focused,</i>	
<i>command_list_cache_hint</i>			

Callback event: *wxListEvent*

```

wxMaximize() = #wxMaximize{type=wxEventType()}
    EventType:
        maximize
    Callback event: wxMaximizeEvent

wxMenu() = #wxMenu{type=wxEventType()}
    EventType:
        menu_open, menu_close, menu_highlight
    Callback event: wxMenuEvent

wxMouse() = #wxMouse{type=wxEventType(), x=integer(), y=integer(),
leftDown=bool(), middleDown=bool(), rightDown=bool(), controlDown=bool(),
shiftDown=bool(), altDown=bool(), metaDown=bool(), wheelRotation=integer(),
wheelDelta=integer(), linesPerAction=integer()}
    EventType:
        left_down, left_up, middle_down, middle_up, right_down, right_up, motion, enter_window, leave_window,
left_dclick, middle_dclick, right_dclick, mousewheel, nc_left_down, nc_left_up, nc_middle_down,
nc_middle_up, nc_right_down, nc_right_up, nc_motion, nc_enter_window, nc_leave_window, nc_left_dclick,
nc_middle_dclick, nc_right_dclick
    Callback event: wxMouseEvent

wxMouseCaptureChanged() = #wxMouseCaptureChanged{type=wxEventType()}
    EventType:
        mouse_capture_changed
    Callback event: wxMouseCaptureChangedEvent

wxMove() = #wxMove{type=wxEventType()}
    EventType:
        move
    Callback event: wxMoveEvent

wxNavigationKey() = #wxNavigationKey{type=wxEventType(), flags=integer(),
focus=wxWindow() (see module wxWindow)}
    EventType:
        navigation_key
    Callback event: wxNavigationKeyEvent

wxNcPaint() = #wxNcPaint{type=wxEventType()}
    EventType:
        nc_paint
    Callback event: wxNcPaintEvent

wxNotebook() = #wxNotebook{type=wxEventType()}
    EventType:
        command_notebook_page_changed, command_notebook_page_changing
    Callback event: wxNotebookEvent

```

```
wxPaint() = #wxPaint{type=wxEventType()}
    EventType:
        paint, paint_icon
    Callback event: wxPaintEvent

wxPaletteChanged() = #wxPaletteChanged{type=wxEventType()}
    EventType:
        palette_changed
    Callback event: wxPaletteChangedEvent

wxQueryNewPalette() = #wxQueryNewPalette{type=wxEventType()}
    EventType:
        query_new_palette
    Callback event: wxQueryNewPaletteEvent

wxSash() = #wxSash{type=wxEventType(), edge=WxSashEdgePosition,
dragRect={X::integer(), Y::integer(), W::integer(), H::integer()},
dragStatus=WxSashDragStatus}
    EventType:
        sash_dragged
    Callback event: wxSashEvent

wxScroll() = #wxScroll{type=wxEventType(), commandInt=integer(),
extraLong=integer()}
    EventType:
        scroll_top, scroll_bottom, scroll_lineup, scroll_linedown, scroll_pageup, scroll_pagedown, scroll_thumbtrack,
        scroll_thumbrelease, scroll_changed
    Callback event: wxScrollEvent

wxScrollWin() = #wxScrollWin{type=wxEventType()}
    EventType:
        scrollwin_top, scrollwin_bottom, scrollwin_lineup, scrollwin_linedown, scrollwin_pageup,
        scrollwin_pagedown, scrollwin_thumbtrack, scrollwin_thumbrelease
    Callback event: wxScrollWinEvent

wxSetCursor() = #wxSetCursor{type=wxEventType()}
    EventType:
        set_cursor
    Callback event: wxSetCursorEvent

wxShow() = #wxShow{type=wxEventType()}
    EventType:
        show
    Callback event: wxShowEvent
```

```
wxSize() = #wxSize{type=wxEventType(), size={W::integer(), H::integer()},
rect={X::integer(), Y::integer(), W::integer(), H::integer()}}
```

EventType:

size

Callback event: *wxSizeEvent*

```
wxSpin() = #wxSpin{type=wxEventType(), commandInt=integer()}
```

EventType:

command_spinctrl_updated, spin_up, spin_down, spin

Callback event: *wxSpinEvent*

```
wxSplitter() = #wxSplitter{type=wxEventType()}
```

EventType:

command_splitter_sash_pos_changed, *command_splitter_sash_pos_changing,*
command_splitter_doubleclicked, command_splitter_unsplit

Callback event: *wxSplitterEvent*

```
wxStyledText() = #wxStyledText{type=wxEventType(), position=integer(),
key=integer(), modifiers=integer(), modificationType=integer(),
text=string(), length=integer(), linesAdded=integer(), line=integer(),
foldLevelNow=integer(), foldLevelPrev=integer(), margin=integer(),
message=integer(), wParam=integer(), lParam=integer(), listType=integer(),
x=integer(), y=integer(), dragText=string(), dragAllowMove=bool(),
dragResult=WxDragResult}
```

EventType:

stc_change, stc_styleneeded, stc_charadded, stc_savepointreached, stc_savepointleft, stc_romodifyattempt,
stc_key, stc_doubleclick, stc_updateui, stc_modified, stc_macrorecord, stc_marginclick, stc_needshown,
stc_painted, stc_userlistselection, stc_uridropped, stc_dwellstart, stc_dwellend, stc_start_drag, stc_drag_over,
stc_do_drop, stc_zoom, stc_hotspot_click, stc_hotspot_dclick, stc_calltip_click, stc_autocomp_selection

Callback event: *wxStyledTextEvent*

```
wxSysColourChanged() = #wxSysColourChanged{type=wxEventType()}
```

EventType:

sys_colour_changed

Callback event: *wxSysColourChangedEvent*

```
wxTree() = #wxTree{type=wxEventType(), item=integer(), itemOld=integer(),
pointDrag={X::integer(), Y::integer()}}
```

EventType:

command_tree_begin_drag, *command_tree_begin_rdrag,* *command_tree_begin_label_edit,*
command_tree_end_label_edit, command_tree_delete_item, command_tree_get_info, command_tree_set_info,
command_tree_item_expanded, *command_tree_item_expanding,* *command_tree_item_collapsed,*
command_tree_item_collapsing, *command_tree_sel_changed,* *command_tree_sel_changing,*
command_tree_key_down, *command_tree_item_activated,* *command_tree_item_right_click,*
command_tree_item_middle_click, *command_tree_end_drag,* *command_tree_state_image_click,*
command_tree_item_gettooltip, command_tree_item_menu

Callback event: *wxTreeEvent*

```
wxUpdateUI() = #wxUpdateUI{type=wxEventType()}
  EventType:
    update_ui
  Callback event: wxUpdateUIEvent

wxWindowCreate() = #wxWindowCreate{type=wxEventType()}
  EventType:
    create
  Callback event: wxWindowCreateEvent

wxWindowDestroy() = #wxWindowDestroy{type=wxEventType()}
  EventType:
    destroy
  Callback event: wxWindowDestroyEvent
```

Exports

```
connect(This::wxEvtHandler(), EventType::wxEventType()) -> ok
```

Equivalent to *connect(This, EventType, [])*

```
connect(This::wxEvtHandler(), EventType::wxEventType(), Options::[Options]) -> ok
```

This function subscribes the to events of EventType, in the range id, lastId. The events will be received as messages if no callback is supplied.

Options: {id, integer()}, The identifier (or first of the identifier range) to be associated with this event handler. Default ?wxID_ANY {lastId, integer()}, The second part of the identifier range. If used 'id' must be set as the starting identifier range. Default ?wxID_ANY {skip, boolean()}, If skip is true further event_handlers will be called. This is not used if the 'callback' option is used. Default false. {callback, function()} Use a callback fun(EventRecord::wx(), EventObject::wxObject()) to process the event. Default not specified i.e. a message will be delivered to the process calling this function. {userData, term()} An erlang term that will be sent with the event. Default: [].

```
disconnect(This::wxEvtHandler()) -> true | false
```

Equivalent to *disconnect(This, null, [])* Can also have an optional callback Fun() as an additional last argument.

```
disconnect(This::wxEvtHandler(), EventType::wxEventType()) -> true | false
```

Equivalent to *disconnect(This, EventType, [])*

```
disconnect(This::wxEvtHandler(), EventType::wxEventType(), Opts) -> true | false
```

See **external documentation** This function unsubscribes the process or callback fun from the event handler. EventType may be the atom 'null' to match any eventtype. Notice that the options skip and userdata is not used to match the eventhandler.

wxFileDataObject

Erlang module

See external documentation: **wxFileDataObject**.

This class is derived (and can use functions) from:
wxDataObject

DATA TYPES

`wxFileDataObject()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxFileDataObject()`

See external documentation.

`addFile(This::wxFileDataObject(), Filename::string()) -> ok`

See external documentation.

`getFilenames(This::wxFileDataObject()) -> [[string()]]`

See external documentation.

`destroy(This::wxFileDataObject()) -> ok`

Destroys this object, do not use object again

wxFileDialog

Erlang module

See external documentation: **wxFileDialog**.

This class is derived (and can use functions) from:

wxDialog

wxTopLevelWindow

wxWindow

wxEvtHandler

DATA TYPES

`wxFileDialog()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new(Parent::wxWindow() (see module wxWindow)) -> wxFileDialog()`

Equivalent to `new(Parent, [])`.

`new(Parent::wxWindow() (see module wxWindow), Options::[Option]) -> wxFileDialog()`

Types:

`Option = {message, string()} | {defaultDir, string()} | {defaultFile, string()} | {wildCard, string()} | {style, integer()} | {pos, {X::integer(), Y::integer()}} | {sz, {W::integer(), H::integer()}}`

See external documentation.

`getDirectory(This::wxFileDialog()) -> string()`

See external documentation.

`getFilename(This::wxFileDialog()) -> string()`

See external documentation.

`getFilenames(This::wxFileDialog()) -> [[string()]]`

See external documentation.

`getFilterIndex(This::wxFileDialog()) -> integer()`

See external documentation.

`getMessage(This::wxFileDialog()) -> string()`

See external documentation.

getPath(This::wxFileDialog()) -> string()

See external documentation.

getPaths(This::wxFileDialog()) -> [[string()]]

See external documentation.

getWildcard(This::wxFileDialog()) -> string()

See external documentation.

setDirectory(This::wxFileDialog(), Dir::string()) -> ok

See external documentation.

setFilename(This::wxFileDialog(), Name::string()) -> ok

See external documentation.

setFilterIndex(This::wxFileDialog(), FilterIndex::integer()) -> ok

See external documentation.

setMessage(This::wxFileDialog(), Message::string()) -> ok

See external documentation.

setPath(This::wxFileDialog(), Path::string()) -> ok

See external documentation.

setWildcard(This::wxFileDialog(), WildCard::string()) -> ok

See external documentation.

destroy(This::wxFileDialog()) -> ok

Destroys this object, do not use object again

wxFileDirPickerEvent

Erlang module

See external documentation: **wxFileDirPickerEvent**.

Use *wxEvtHandler:connect/3* with EventType:

command_filepicker_changed, command_dirpicker_changed

See also the message variant *#wxFileDirPicker{}* event record type.

This class is derived (and can use functions) from:

wxCommandEvent

wxEvent

DATA TYPES

`wxFileDirPickerEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`getPath(This::wxFileDirPickerEvent()) -> string()`

See external documentation.

wxFilePickerCtrl

Erlang module

See external documentation: **wxFilePickerCtrl**.

This class is derived (and can use functions) from:

wxPickerBase

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxFilePickerCtrl()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxFilePickerCtrl()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Id::integer()) -> wxFilePickerCtrl()`

Equivalent to `new(Parent, Id, [])`.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Options::[Option]) -> wxFilePickerCtrl()`

Types:

Option = {path, string()} | {message, string()} | {wildcard, string()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()} | {validator, wx() (see module wx)}

See external documentation.

`create(This::wxFilePickerCtrl(), Parent::wxWindow() (see module wxWindow), Id::integer()) -> bool()`

Equivalent to `create(This, Parent, Id, [])`.

`create(This::wxFilePickerCtrl(), Parent::wxWindow() (see module wxWindow), Id::integer(), Options::[Option]) -> bool()`

Types:

Option = {path, string()} | {message, string()} | {wildcard, string()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()} | {validator, wx() (see module wx)}

See external documentation.

wxFilePickerCtrl

getPath(This::wxFilePickerCtrl()) -> string()

See **external documentation**.

setPath(This::wxFilePickerCtrl(), Str::string()) -> ok

See **external documentation**.

destroy(This::wxFilePickerCtrl()) -> ok

Destroys this object, do not use object again

wxFindReplaceData

Erlang module

See external documentation: **wxFindReplaceData**.

DATA TYPES

`wxFindReplaceData()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxFindReplaceData()`

See external documentation.

`new(Flags::integer()) -> wxFindReplaceData()`

See external documentation.

`getFindString(This::wxFindReplaceData()) -> string()`

See external documentation.

`getReplaceString(This::wxFindReplaceData()) -> string()`

See external documentation.

`getFlags(This::wxFindReplaceData()) -> integer()`

See external documentation.

`setFlags(This::wxFindReplaceData(), Flags::integer()) -> ok`

See external documentation.

`setFindString(This::wxFindReplaceData(), Str::string()) -> ok`

See external documentation.

`setReplaceString(This::wxFindReplaceData(), Str::string()) -> ok`

See external documentation.

`destroy(This::wxFindReplaceData()) -> ok`

Destroys this object, do not use object again

wxFindReplaceDialog

Erlang module

See external documentation: **wxFindReplaceDialog**.

This class is derived (and can use functions) from:

wxDialog

wxTopLevelWindow

wxWindow

wxEvtHandler

DATA TYPES

`wxFindReplaceDialog()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxFindReplaceDialog()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Data::wxFindReplaceData() (see module wxFindReplaceData), Title::string()) -> wxFindReplaceDialog()`

Equivalent to `new(Parent, Data, Title, [])`.

`new(Parent::wxWindow() (see module wxWindow), Data::wxFindReplaceData() (see module wxFindReplaceData), Title::string(), Options::[Option]) -> wxFindReplaceDialog()`

Types:

Option = {style, integer()}

See external documentation.

`create(This::wxFindReplaceDialog(), Parent::wxWindow() (see module wxWindow), Data::wxFindReplaceData() (see module wxFindReplaceData), Title::string()) -> bool()`

Equivalent to `create(This, Parent, Data, Title, [])`.

`create(This::wxFindReplaceDialog(), Parent::wxWindow() (see module wxWindow), Data::wxFindReplaceData() (see module wxFindReplaceData), Title::string(), Options::[Option]) -> bool()`

Types:

Option = {style, integer()}

See external documentation.

getData(This::wxFindReplaceDialog()) -> wxFindReplaceData() (see module **wxFindReplaceData**)

See external documentation.

destroy(This::wxFindReplaceDialog()) -> ok

Destroys this object, do not use object again

wxFlexGridSizer

Erlang module

See external documentation: **wxFlexGridSizer**.

This class is derived (and can use functions) from:

wxGridSizer

wxSizer

DATA TYPES

`wxFlexGridSizer()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new(Cols::integer()) -> wxFlexGridSizer()`

Equivalent to `new(Cols, [])`.

`new(Cols::integer(), Options::[Option]) -> wxFlexGridSizer()`

Types:

Option = {vgap, integer()} | {hgap, integer()}

See external documentation.

`new(Rows::integer(), Cols::integer(), Vgap::integer(), Hgap::integer()) -> wxFlexGridSizer()`

See external documentation.

`addGrowCol(This::wxFlexGridSizer(), Idx::integer()) -> ok`

Equivalent to `addGrowCol(This, Idx, [])`.

`addGrowCol(This::wxFlexGridSizer(), Idx::integer(), Options::[Option]) -> ok`

Types:

Option = {proportion, integer()}

See external documentation.

`addGrowRow(This::wxFlexGridSizer(), Idx::integer()) -> ok`

Equivalent to `addGrowRow(This, Idx, [])`.

`addGrowRow(This::wxFlexGridSizer(), Idx::integer(), Options::[Option]) -> ok`

Types:

Option = {proportion, integer()}

See [external documentation](#).

getFlexibleDirection(This::wxFlexGridSizer()) -> integer()

See [external documentation](#).

getNonFlexibleGrowMode(This::wxFlexGridSizer()) -> WxFlexSizerGrowMode

Types:

WxFlexSizerGrowMode = integer()

See [external documentation](#).

WxFlexSizerGrowMode is one of ?wxFLEX_GROWMODE_NONE | ?wxFLEX_GROWMODE_SPECIFIED | ?wxFLEX_GROWMODE_ALL

removeGrowCol(This::wxFlexGridSizer(), Idx::integer()) -> ok

See [external documentation](#).

removeGrowRow(This::wxFlexGridSizer(), Idx::integer()) -> ok

See [external documentation](#).

setFlexibleDirection(This::wxFlexGridSizer(), Direction::integer()) -> ok

See [external documentation](#).

setNonFlexibleGrowMode(This::wxFlexGridSizer(), Mode::WxFlexSizerGrowMode) -> ok

Types:

WxFlexSizerGrowMode = integer()

See [external documentation](#).

WxFlexSizerGrowMode is one of ?wxFLEX_GROWMODE_NONE | ?wxFLEX_GROWMODE_SPECIFIED | ?wxFLEX_GROWMODE_ALL

destroy(This::wxFlexGridSizer()) -> ok

Destroys this object, do not use object again

wxFocusEvent

Erlang module

See external documentation: **wxFocusEvent**.

Use *wxEvtHandler:connect/3* with EventType:

set_focus, kill_focus

See also the message variant *#wxFocus{}* event record type.

This class is derived (and can use functions) from:

wxEvent

DATA TYPES

`wxFocusEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparsion stored on disc or distributed for use on other nodes.

Exports

`getWindow(This::wxFocusEvent()) -> wxWindow()` (see module `wxWindow`)

See external documentation.

wxFontData

Erlang module

See external documentation: **wxFontData**.

DATA TYPES

`wxFontData()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxFontData()`

See external documentation.

`new(Data::wxFontData()) -> wxFontData()`

See external documentation.

`enableEffects(This::wxFontData(), Flag::bool()) -> ok`

See external documentation.

`getAllowSymbols(This::wxFontData()) -> bool()`

See external documentation.

`getColour(This::wxFontData()) -> colour() (see module wx)`

See external documentation.

`getChosenFont(This::wxFontData()) -> wxFont() (see module wxFont)`

See external documentation.

`getEnableEffects(This::wxFontData()) -> bool()`

See external documentation.

`getInitialFont(This::wxFontData()) -> wxFont() (see module wxFont)`

See external documentation.

`getShowHelp(This::wxFontData()) -> bool()`

See external documentation.

`setAllowSymbols(This::wxFontData(), Flag::bool()) -> ok`

See external documentation.

setChosenFont(This::wxFontData(), Font::wxFont() (see module wxFont)) -> ok

See external documentation.

setColour(This::wxFontData(), Colour::colour() (see module wx)) -> ok

See external documentation.

setInitialFont(This::wxFontData(), Font::wxFont() (see module wxFont)) -> ok

See external documentation.

setRange(This::wxFontData(), MinRange::integer(), MaxRange::integer()) -> ok

See external documentation.

setShowHelp(This::wxFontData(), Flag::bool()) -> ok

See external documentation.

destroy(This::wxFontData()) -> ok

Destroys this object, do not use object again

wxFontDialog

Erlang module

See external documentation: **wxFontDialog**.

This class is derived (and can use functions) from:

wxDialog

wxTopLevelWindow

wxWindow

wxEvtHandler

DATA TYPES

`wxFontDialog()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxFontDialog()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Data::wxFontData() (see module wxFontData)) -> wxFontDialog()`

See external documentation.

`create(This::wxFontDialog(), Parent::wxWindow() (see module wxWindow), Data::wxFontData() (see module wxFontData)) -> bool()`

See external documentation.

`getFontData(This::wxFontDialog()) -> wxFontData() (see module wxFontData)`

See external documentation.

`destroy(This::wxFontDialog()) -> ok`

Destroys this object, do not use object again

wxFont

Erlang module

See external documentation: **wxFont**.

DATA TYPES

`wxFont()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxFont()`

See external documentation.

`new(Fontname::string()) -> wxFont()`

See external documentation.

`new(Size::integer(), Family::WxFontFamily, Style::WxFontStyle, Weight::integer()) -> wxFont()`

Equivalent to `new(Size, Family, Style, Weight, [])`.

`new(Size::integer(), Family::WxFontFamily, Style::WxFontStyle, Weight::integer(), Options::[Option]) -> wxFont()`

Types:

Option = {underlined, bool()} | {face, string()} | {encoding, WxFontEncoding}

WxFontFamily = integer()

WxFontStyle = integer()

WxFontEncoding = integer()

See external documentation.

WxFontFamily is one of ?wxFONTFAMILY_DEFAULT | ?wxFONTFAMILY_DECORATIVE | ?wxFONTFAMILY_ROMAN | ?wxFONTFAMILY_SCRIPT | ?wxFONTFAMILY_SWISS | ?wxFONTFAMILY_MODERN | ?wxFONTFAMILY_TELETYPE | ?wxFONTFAMILY_MAX | ?wxFONTFAMILY_UNKNOWN

WxFontStyle is one of ?wxFONTSTYLE_NORMAL | ?wxFONTSTYLE_ITALIC | ?wxFONTSTYLE_SLANT | ?wxFONTSTYLE_MAX

WxFontEncoding is one of ?wxFONTENCODING_SYSTEM | ?wxFONTENCODING_DEFAULT | ?wxFONTENCODING_ISO8859_1 | ?wxFONTENCODING_ISO8859_2 | ?wxFONTENCODING_ISO8859_3 | ?wxFONTENCODING_ISO8859_4 | ?wxFONTENCODING_ISO8859_5 | ?wxFONTENCODING_ISO8859_6 | ?wxFONTENCODING_ISO8859_7 | ?wxFONTENCODING_ISO8859_8 | ?wxFONTENCODING_ISO8859_9 | ?wxFONTENCODING_ISO8859_10 | ?wxFONTENCODING_ISO8859_11 | ?wxFONTENCODING_ISO8859_12 | ?wxFONTENCODING_ISO8859_13 | ?wxFONTENCODING_ISO8859_14 | ?wxFONTENCODING_ISO8859_15 | ?wxFONTENCODING_ISO8859_MAX | ?wxFONTENCODING_KOI8 | ?wxFONTENCODING_KOI8_U | ?wxFONTENCODING_ALTERNATIVE | ?wxFONTENCODING_BULGARIAN | ?wxFONTENCODING_CP437 | ?wxFONTENCODING_CP850 | ?wxFONTENCODING_CP852 | ?


```

wxFONTENCODING_CP855 | ?wxFONTENCODING_CP866 | ?wxFONTENCODING_CP874 | ?
wxFONTENCODING_CP932 | ?wxFONTENCODING_CP936 | ?wxFONTENCODING_CP949 | ?
wxFONTENCODING_CP950 | ?wxFONTENCODING_CP1250 | ?wxFONTENCODING_CP1251 | ?
wxFONTENCODING_CP1252 | ?wxFONTENCODING_CP1253 | ?wxFONTENCODING_CP1254 | ?
wxFONTENCODING_CP1255 | ?wxFONTENCODING_CP1256 | ?wxFONTENCODING_CP1257 | ?
wxFONTENCODING_CP12_MAX | ?wxFONTENCODING_UTF7 | ?wxFONTENCODING_UTF8 | ?
wxFONTENCODING_EUC_JP | ?wxFONTENCODING_UTF16BE | ?wxFONTENCODING_UTF16LE | ?
wxFONTENCODING_UTF32BE | ?wxFONTENCODING_UTF32LE | ?wxFONTENCODING_MACROMAN
| ?wxFONTENCODING_MACJAPANESE | ?wxFONTENCODING_MACCHINESETRAD | ?
wxFONTENCODING_MACKOREAN | ?wxFONTENCODING_MACARABIC | ?
wxFONTENCODING_MACHEBREW | ?wxFONTENCODING_MACGREEK | ?
wxFONTENCODING_MACCYRILLIC | ?wxFONTENCODING_MACDEVANAGARI | ?
wxFONTENCODING_MACGURMUKHI | ?wxFONTENCODING_MACGUJARATI | ?
wxFONTENCODING_MACORIYA | ?wxFONTENCODING_MACBENGALI | ?
wxFONTENCODING_MACTAMIL | ?wxFONTENCODING_MACTELUGU | ?
wxFONTENCODING_MACKANNADA | ?wxFONTENCODING_MACMALAJALAM | ?
wxFONTENCODING_MACSINHALESE | ?wxFONTENCODING_MACBURMESE | ?
wxFONTENCODING_MACKHMER | ?wxFONTENCODING_MACTHAI | ?
wxFONTENCODING_MACLAOTIAN | ?wxFONTENCODING_MACGEORGIAN | ?
wxFONTENCODING_MACARMENIAN | ?wxFONTENCODING_MACCHINESESIMP | ?
wxFONTENCODING_MACTIBETAN | ?wxFONTENCODING_MACMONGOLIAN | ?
wxFONTENCODING_MACETHIOPIA | ?wxFONTENCODING_MACCENTRALEUR | ?
wxFONTENCODING_MACVIETNAMESE | ?wxFONTENCODING_MACARABICEXT | ?
wxFONTENCODING_MACSYMBOL | ?wxFONTENCODING_MACDINGBATS | ?
wxFONTENCODING_MACTURKISH | ?wxFONTENCODING_MACCROATIAN | ?
wxFONTENCODING_MACICELANDIC | ?wxFONTENCODING_MACROMANIAN | ?
wxFONTENCODING_MACCELTIC | ?wxFONTENCODING_MACGAELIC | ?
wxFONTENCODING_MACKEYBOARD | ?wxFONTENCODING_MAX | ?wxFONTENCODING_MACMIN
| ?wxFONTENCODING_MACMAX | ?wxFONTENCODING_UTF16 | ?wxFONTENCODING_UTF32 | ?
wxFONTENCODING_UNICODE | ?wxFONTENCODING_GB2312 | ?wxFONTENCODING_BIG5 | ?
wxFONTENCODING_SHIFT_JIS

```

isFixedWidth(This::wxFont()) -> bool()

See [external documentation](#).

getDefaultEncoding() -> WxFontEncoding

Types:

WxFontEncoding = integer()

See [external documentation](#).

```

WxFontEncoding is one of ?wxFONTENCODING_SYSTEM | ?wxFONTENCODING_DEFAULT | ?
wxFONTENCODING_ISO8859_1 | ?wxFONTENCODING_ISO8859_2 | ?wxFONTENCODING_ISO8859_3 | ?
wxFONTENCODING_ISO8859_4 | ?wxFONTENCODING_ISO8859_5 | ?wxFONTENCODING_ISO8859_6 | ?
wxFONTENCODING_ISO8859_7 | ?wxFONTENCODING_ISO8859_8 | ?wxFONTENCODING_ISO8859_9 | ?
wxFONTENCODING_ISO8859_10 | ?wxFONTENCODING_ISO8859_11 | ?wxFONTENCODING_ISO8859_12
| ?wxFONTENCODING_ISO8859_13 | ?wxFONTENCODING_ISO8859_14 | ?wxFONTENCODING_ISO8859_15
| ?wxFONTENCODING_ISO8859_MAX | ?wxFONTENCODING_KOI8 | ?wxFONTENCODING_KOI8_U
| ?wxFONTENCODING_ALTERNATIVE | ?wxFONTENCODING_BULGARIAN | ?
wxFONTENCODING_CP437 | ?wxFONTENCODING_CP850 | ?wxFONTENCODING_CP852 | ?
wxFONTENCODING_CP855 | ?wxFONTENCODING_CP866 | ?wxFONTENCODING_CP874 | ?
wxFONTENCODING_CP932 | ?wxFONTENCODING_CP936 | ?wxFONTENCODING_CP949 | ?

```

wxFONTENCODING_CP950		?wxFONTENCODING_CP1250		?wxFONTENCODING_CP1251		?	
wxFONTENCODING_CP1252		?wxFONTENCODING_CP1253		?wxFONTENCODING_CP1254		?	
wxFONTENCODING_CP1255		?wxFONTENCODING_CP1256		?wxFONTENCODING_CP1257		?	
wxFONTENCODING_CP12_MAX		?wxFONTENCODING_UTF7		?wxFONTENCODING_UTF8		?	
wxFONTENCODING_EUC_JP		?wxFONTENCODING_UTF16BE		?wxFONTENCODING_UTF16LE		?	
wxFONTENCODING_UTF32BE		?wxFONTENCODING_UTF32LE		?wxFONTENCODING_MACROMAN		?	
	?wxFONTENCODING_MACJAPANESE		?wxFONTENCODING_MACCHINESETRAD		?		
wxFONTENCODING_MACKOREAN		?wxFONTENCODING_MACARABIC		?			
wxFONTENCODING_MACHEBREW		?wxFONTENCODING_MACGREEK		?			
wxFONTENCODING_MACCYRILLIC		?wxFONTENCODING_MACDEVANAGARI		?			
wxFONTENCODING_MACGURMUKHI		?wxFONTENCODING_MACGUJARATI		?			
wxFONTENCODING_MACORIYA		?wxFONTENCODING_MACBENGALI		?			
wxFONTENCODING_MACTAMIL		?wxFONTENCODING_MACTELUGU		?			
wxFONTENCODING_MACKANNADA		?wxFONTENCODING_MACMALAJALAM		?			
wxFONTENCODING_MACSINHALESE		?wxFONTENCODING_MACBURMESE		?			
wxFONTENCODING_MACKHMER		?wxFONTENCODING_MACTHAI		?			
wxFONTENCODING_MACLAOTIAN		?wxFONTENCODING_MACGEORGIAN		?			
wxFONTENCODING_MACARMENIAN		?wxFONTENCODING_MACCHINESESIMP		?			
wxFONTENCODING_MACTIBETAN		?wxFONTENCODING_MACMONGOLIAN		?			
wxFONTENCODING_MACETHIOPIC		?wxFONTENCODING_MACCENTRALEUR		?			
wxFONTENCODING_MACVIATNAMESE		?wxFONTENCODING_MACARABICEXT		?			
wxFONTENCODING_MACSYMBOL		?wxFONTENCODING_MACDINGBATS		?			
wxFONTENCODING_MACTURKISH		?wxFONTENCODING_MACCROATIAN		?			
wxFONTENCODING_MACICELANDIC		?wxFONTENCODING_MACROMANIAN		?			
wxFONTENCODING_MACCEL TIC		?wxFONTENCODING_MACGAELIC		?			
wxFONTENCODING_MACKEYBOARD		?wxFONTENCODING_MAX		?wxFONTENCODING_MACMIN		?	
	?wxFONTENCODING_MACMAX		?wxFONTENCODING_UTF16		?wxFONTENCODING_UTF32		?
wxFONTENCODING_UNICODE		?wxFONTENCODING_GB2312		?wxFONTENCODING_BIG5		?	
wxFONTENCODING_SHIFT_JIS							

getFaceName(This::wxFont()) -> string()

See [external documentation](#).

getFamily(This::wxFont()) -> WxFontFamily

Types:

WxFontFamily = integer()

See [external documentation](#).

WxFontFamily	is	one	of	?wxFONTFAMILY_DEFAULT		?wxFONTFAMILY_DECORATIVE	
	?wxFONTFAMILY_ROMAN		?wxFONTFAMILY_SCRIPT		?wxFONTFAMILY_SWISS		?
wxFONTFAMILY_MODERN		?wxFONTFAMILY_TELETYPE		?wxFONTFAMILY_MAX		?	
wxFONTFAMILY_UNKNOWN							

getNativeFontInfoDesc(This::wxFont()) -> string()

See [external documentation](#).

getNativeFontInfoUserDesc(This::wxFont()) -> string()

See [external documentation](#).

getPointSize(This::wxFont()) -> integer()

See external documentation.

getStyle(This::wxFont()) -> WxFontStyle

Types:

WxFontStyle = integer()

See external documentation.

WxFontStyle is one of ?wxFONTSTYLE_NORMAL | ?wxFONTSTYLE_ITALIC | ?wxFONTSTYLE_SLANT | ?wxFONTSTYLE_MAX

getUnderlined(This::wxFont()) -> bool()

See external documentation.

getWeight(This::wxFont()) -> integer()

See external documentation.

ok(This::wxFont()) -> bool()

See external documentation.

setDefaultEncoding(Encoding::WxFontEncoding) -> ok

Types:

WxFontEncoding = integer()

See external documentation.

WxFontEncoding is one of ?wxFONTENCODING_SYSTEM | ?wxFONTENCODING_DEFAULT | ?wxFONTENCODING_ISO8859_1 | ?wxFONTENCODING_ISO8859_2 | ?wxFONTENCODING_ISO8859_3 | ?wxFONTENCODING_ISO8859_4 | ?wxFONTENCODING_ISO8859_5 | ?wxFONTENCODING_ISO8859_6 | ?wxFONTENCODING_ISO8859_7 | ?wxFONTENCODING_ISO8859_8 | ?wxFONTENCODING_ISO8859_9 | ?wxFONTENCODING_ISO8859_10 | ?wxFONTENCODING_ISO8859_11 | ?wxFONTENCODING_ISO8859_12 | ?wxFONTENCODING_ISO8859_13 | ?wxFONTENCODING_ISO8859_14 | ?wxFONTENCODING_ISO8859_15 | ?wxFONTENCODING_ISO8859_MAX | ?wxFONTENCODING_KOI8 | ?wxFONTENCODING_KOI8_U | ?wxFONTENCODING_ALTERNATIVE | ?wxFONTENCODING_BULGARIAN | ?wxFONTENCODING_CP437 | ?wxFONTENCODING_CP850 | ?wxFONTENCODING_CP852 | ?wxFONTENCODING_CP855 | ?wxFONTENCODING_CP866 | ?wxFONTENCODING_CP874 | ?wxFONTENCODING_CP932 | ?wxFONTENCODING_CP936 | ?wxFONTENCODING_CP949 | ?wxFONTENCODING_CP950 | ?wxFONTENCODING_CP1250 | ?wxFONTENCODING_CP1251 | ?wxFONTENCODING_CP1252 | ?wxFONTENCODING_CP1253 | ?wxFONTENCODING_CP1254 | ?wxFONTENCODING_CP1255 | ?wxFONTENCODING_CP1256 | ?wxFONTENCODING_CP1257 | ?wxFONTENCODING_CP12_MAX | ?wxFONTENCODING_UTF7 | ?wxFONTENCODING_UTF8 | ?wxFONTENCODING_EUC_JP | ?wxFONTENCODING_UTF16BE | ?wxFONTENCODING_UTF16LE | ?wxFONTENCODING_UTF32BE | ?wxFONTENCODING_UTF32LE | ?wxFONTENCODING_MACROMAN | ?wxFONTENCODING_MACJAPANESE | ?wxFONTENCODING_MACCHINESETRAD | ?wxFONTENCODING_MACKOREAN | ?wxFONTENCODING_MACARABIC | ?wxFONTENCODING_MACHEBREW | ?wxFONTENCODING_MACGREEK | ?wxFONTENCODING_MACCYRILLIC | ?wxFONTENCODING_MACDEVANAGARI | ?wxFONTENCODING_MACGURMUKHI | ?wxFONTENCODING_MACGUJARATI | ?wxFONTENCODING_MACORIYA | ?wxFONTENCODING_MACBENGALI | ?wxFONTENCODING_MACTAMIL | ?wxFONTENCODING_MACTELUGU

wxFONTENCODING_MACKANNADA		?wxFONTENCODING_MACMALAJALAM		?
wxFONTENCODING_MACSINHALESE		?wxFONTENCODING_MACBURMESE		?
wxFONTENCODING_MACKHMER		?wxFONTENCODING_MACTHAI		?
wxFONTENCODING_MACLAOTIAN		?wxFONTENCODING_MACGEORGIAN		?
wxFONTENCODING_MACARMENIAN		?wxFONTENCODING_MACCHINESESIMP		?
wxFONTENCODING_MACTIBETAN		?wxFONTENCODING_MACMONGOLIAN		?
wxFONTENCODING_MACETHIOPIA		?wxFONTENCODING_MACCENTRALEUR		?
wxFONTENCODING_MACVIATNAMESE		?wxFONTENCODING_MACARABICEXT		?
wxFONTENCODING_MACSYMBOL		?wxFONTENCODING_MACDINGBATS		?
wxFONTENCODING_MACTURKISH		?wxFONTENCODING_MACCROATIAN		?
wxFONTENCODING_MACICELANDIC		?wxFONTENCODING_MACROMANIAN		?
wxFONTENCODING_MACCELTIC		?wxFONTENCODING_MACGAELIC		?
wxFONTENCODING_MACKEYBOARD		?wxFONTENCODING_MAX		?wxFONTENCODING_MACMIN
?wxFONTENCODING_MACMAX		?wxFONTENCODING_UTF16		?wxFONTENCODING_UTF32
?wxFONTENCODING_UNICODE		?wxFONTENCODING_GB2312		?wxFONTENCODING_BIG5
?wxFONTENCODING_SHIFT_JIS				

setFaceName(This::wxFont(), FaceName::string()) -> bool()

See [external documentation](#).

setFamily(This::wxFont(), Family::WxFontFamily) -> ok

Types:

WxFontFamily = integer()

See [external documentation](#).

WxFontFamily is one of ?wxFONTFAMILY_DEFAULT | ?wxFONTFAMILY_DECORATIVE
| ?wxFONTFAMILY_ROMAN | ?wxFONTFAMILY_SCRIPT | ?wxFONTFAMILY_SWISS | ?
wxFONTFAMILY_MODERN | ?wxFONTFAMILY_TELETYPE | ?wxFONTFAMILY_MAX | ?
wxFONTFAMILY_UNKNOWN

setPointSize(This::wxFont(), PointSize::integer()) -> ok

See [external documentation](#).

setStyle(This::wxFont(), Style::WxFontStyle) -> ok

Types:

WxFontStyle = integer()

See [external documentation](#).

WxFontStyle is one of ?wxFONTSTYLE_NORMAL | ?wxFONTSTYLE_ITALIC | ?wxFONTSTYLE_SLANT | ?
wxFONTSTYLE_MAX

setUnderlined(This::wxFont(), Underlined::bool()) -> ok

See [external documentation](#).

setWeight(This::wxFont(), Weight::integer()) -> ok

See [external documentation](#).

```
destroy(This::wxFont()) -> ok
```

Destroys this object, do not use object again

wxFonPickerCtrl

Erlang module

See external documentation: **wxFonPickerCtrl**.

This class is derived (and can use functions) from:

wxPickerBase

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxFonPickerCtrl()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxFonPickerCtrl()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Id::integer()) -> wxFonPickerCtrl()`

Equivalent to `new(Parent, Id, [])`.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Options::[Option]) -> wxFonPickerCtrl()`

Types:

Option = {initial, wxFont() (see module wxFont)} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()} | {validator, wx() (see module wx)}

See external documentation.

`create(This::wxFonPickerCtrl(), Parent::wxWindow() (see module wxWindow), Id::integer()) -> bool()`

Equivalent to `create(This, Parent, Id, [])`.

`create(This::wxFonPickerCtrl(), Parent::wxWindow() (see module wxWindow), Id::integer(), Options::[Option]) -> bool()`

Types:

Option = {initial, wxFont() (see module wxFont)} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()} | {validator, wx() (see module wx)}

See external documentation.

getSelectedFont(This::wxFontPickerCtrl()) -> wxFont() (see module wxFont)

See external documentation.

setSelectedFont(This::wxFontPickerCtrl(), F::wxFont() (see module wxFont)) -> ok

See external documentation.

getMaxPointSize(This::wxFontPickerCtrl()) -> integer()

See external documentation.

setMaxPointSize(This::wxFontPickerCtrl(), Max::integer()) -> ok

See external documentation.

destroy(This::wxFontPickerCtrl()) -> ok

Destroys this object, do not use object again

wxFontPickerEvent

Erlang module

See external documentation: **wxFontPickerEvent**.

Use *wxEvtHandler:connect/3* with EventType:

command_fontpicker_changed

See also the message variant *#wxFontPicker{}* event record type.

This class is derived (and can use functions) from:

wxCommandEvent

wxEvent

DATA TYPES

wxFontPickerEvent()

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

getFont(This::wxFontPickerEvent()) -> wxFont() (see module **wxFont**)

See external documentation.

wxFrame

Erlang module

See external documentation: **wxFrame**.

This class is derived (and can use functions) from:

wxTopLevelWindow

wxWindow

wxEvtHandler

DATA TYPES

`wxFrame()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxFrame()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Title::string()) -> wxFrame()`

Equivalent to `new(Parent, Id, Title, [])`.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Title::string(), Options::[Option]) -> wxFrame()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`create(This::wxFrame(), Parent::wxWindow() (see module wxWindow), Id::integer(), Title::string()) -> bool()`

Equivalent to `create(This, Parent, Id, Title, [])`.

`create(This::wxFrame(), Parent::wxWindow() (see module wxWindow), Id::integer(), Title::string(), Options::[Option]) -> bool()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`createStatusBar(This::wxFrame()) -> wxStatusBar() (see module wxStatusBar)`

Equivalent to `createStatusBar(This, [])`.

`createStatusBar(This::wxFrame(), Options::[Option]) -> wxStatusBar()` (see module `wxStatusBar`)

Types:

`Option = {number, integer()} | {style, integer()} | {id, integer()}`

See external documentation.

`createToolBar(This::wxFrame()) -> wxToolBar()` (see module `wxToolBar`)

Equivalent to `createToolBar(This, [])`.

`createToolBar(This::wxFrame(), Options::[Option]) -> wxToolBar()` (see module `wxToolBar`)

Types:

`Option = {style, integer()} | {id, integer()}`

See external documentation.

`getClientAreaOrigin(This::wxFrame()) -> {X::integer(), Y::integer()}`

See external documentation.

`getMenuBar(This::wxFrame()) -> wxMenuBar()` (see module `wxMenuBar`)

See external documentation.

`getStatusBar(This::wxFrame()) -> wxStatusBar()` (see module `wxStatusBar`)

See external documentation.

`getStatusBarPane(This::wxFrame()) -> integer()`

See external documentation.

`getToolBar(This::wxFrame()) -> wxToolBar()` (see module `wxToolBar`)

See external documentation.

`processCommand(This::wxFrame(), Winid::integer()) -> bool()`

See external documentation.

`sendSizeEvent(This::wxFrame()) -> ok`

See external documentation.

`setMenuBar(This::wxFrame(), Menubar::wxMenuBar())` (see module `wxMenuBar`) -> `ok`

See external documentation.

`setStatusBar(This::wxFrame(), Statbar::wxStatusBar())` (see module `wxStatusBar`) -> `ok`

See external documentation.

setStatusBarPane(This::wxFrame(), N::integer()) -> ok

See external documentation.

setStatusText(This::wxFrame(), Text::string()) -> ok

Equivalent to *setStatusText(This, Text, [])*.

setStatusText(This::wxFrame(), Text::string(), Options::[Option]) -> ok

Types:

Option = {number, integer()}

See external documentation.

setStatusWidths(This::wxFrame(), Widths_field::[integer()]) -> ok

See external documentation.

setToolBar(This::wxFrame(), Toolbar::wxToolBar() (see module wxToolBar)) -> ok

See external documentation.

destroy(This::wxFrame()) -> ok

Destroys this object, do not use object again

wxGauge

Erlang module

See external documentation: **wxGauge**.

This class is derived (and can use functions) from:

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxGauge()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxGauge()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Range::integer()) -> wxGauge()`

Equivalent to `new(Parent, Id, Range, [])`.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Range::integer(), Options::[Option]) -> wxGauge()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()} | {validator, wx() (see module wx)}

See external documentation.

`create(This::wxGauge(), Parent::wxWindow() (see module wxWindow), Id::integer(), Range::integer()) -> bool()`

Equivalent to `create(This, Parent, Id, Range, [])`.

`create(This::wxGauge(), Parent::wxWindow() (see module wxWindow), Id::integer(), Range::integer(), Options::[Option]) -> bool()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()} | {validator, wx() (see module wx)}

See external documentation.

`getBezelFace(This::wxGauge()) -> integer()`

See external documentation.

getRange(This::wxGauge()) -> integer()

See external documentation.

getShadowWidth(This::wxGauge()) -> integer()

See external documentation.

getValue(This::wxGauge()) -> integer()

See external documentation.

isVertical(This::wxGauge()) -> bool()

See external documentation.

setBezelFace(This::wxGauge(), W::integer()) -> ok

See external documentation.

setRange(This::wxGauge(), R::integer()) -> ok

See external documentation.

setShadowWidth(This::wxGauge(), W::integer()) -> ok

See external documentation.

setValue(This::wxGauge(), Pos::integer()) -> ok

See external documentation.

pulse(This::wxGauge()) -> ok

See external documentation.

destroy(This::wxGauge()) -> ok

Destroys this object, do not use object again

wxGBSizerItem

Erlang module

See external documentation: **wxGBSizerItem**.

This class is derived (and can use functions) from:

wxSizerItem

DATA TYPES

`wxGBSizerItem()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

wxGenericDirCtrl

Erlang module

See external documentation: **wxGenericDirCtrl**.

This class is derived (and can use functions) from:

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxGenericDirCtrl()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxGenericDirCtrl()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow)) -> wxGenericDirCtrl()`

Equivalent to `new(Parent, [])`.

`new(Parent::wxWindow() (see module wxWindow), Options::[Option]) -> wxGenericDirCtrl()`

Types:

Option = {id, integer()} | {dir, string()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()} | {filter, string()} | {defaultFilter, integer()}

See external documentation.

`create(This::wxGenericDirCtrl(), Parent::wxWindow() (see module wxWindow)) -> bool()`

Equivalent to `create(This, Parent, [])`.

`create(This::wxGenericDirCtrl(), Parent::wxWindow() (see module wxWindow), Options::[Option]) -> bool()`

Types:

Option = {id, integer()} | {dir, string()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()} | {filter, string()} | {defaultFilter, integer()}

See external documentation.

`init(This::wxGenericDirCtrl()) -> ok`

See external documentation.

`collapseTree(This::wxGenericDirCtrl()) -> ok`

See external documentation.

`expandPath(This::wxGenericDirCtrl(), Path::string()) -> bool()`

See external documentation.

`getDefaultPath(This::wxGenericDirCtrl()) -> string()`

See external documentation.

`getPath(This::wxGenericDirCtrl()) -> string()`

See external documentation.

`getFilePath(This::wxGenericDirCtrl()) -> string()`

See external documentation.

`getFilter(This::wxGenericDirCtrl()) -> string()`

See external documentation.

`getFilterIndex(This::wxGenericDirCtrl()) -> integer()`

See external documentation.

`getRootId(This::wxGenericDirCtrl()) -> integer()`

See external documentation.

`getTreeCtrl(This::wxGenericDirCtrl()) -> wxTreeCtrl() (see module wxTreeCtrl)`

See external documentation.

`reCreateTree(This::wxGenericDirCtrl()) -> ok`

See external documentation.

`setDefaultPath(This::wxGenericDirCtrl(), Path::string()) -> ok`

See external documentation.

`setFilter(This::wxGenericDirCtrl(), Filter::string()) -> ok`

See external documentation.

`setFilterIndex(This::wxGenericDirCtrl(), N::integer()) -> ok`

See external documentation.

`setPath(This::wxGenericDirCtrl(), Path::string()) -> ok`

See external documentation.


```
destroy(This::wxGenericDirCtrl()) -> ok
```

Destroys this object, do not use object again

wxGLCanvas

Erlang module

See external documentation: **wxGLCanvas**.

This class is derived (and can use functions) from:

wxWindow

wxEvtHandler

DATA TYPES

`wxGLCanvas()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new(Parent::wxWindow() (see module wxWindow)) -> wxGLCanvas()`

Equivalent to `new(Parent, [])`.

`new(Parent::wxWindow() (see module wxWindow), X::term()) -> wxGLCanvas()`

See **external documentation**.

Alternatives:

```
new(Parent::wxWindow:wxWindow(), Shared::wxGLContext:wxGLContext() |  
wxGLCanvas()) -> new(Parent, Shared, [])
```

```
new(Parent::wxWindow:wxWindow(), [Option]) -> wxGLCanvas()  
Option = {id, integer()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()} |  
{name, string()} | {attribList, [integer()]} | {palette, wxPalette:wxPalette() }
```

`new(Parent::wxWindow() (see module wxWindow), Shared::wxGLContext() (see module wxGLContext) | wxGLCanvas(), Options::[Option]) -> wxGLCanvas()`

Types:

Option = {id, integer()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()} | {name, string()} | {attribList, [integer()]} | {palette, wxPalette() (see module wxPalette)}

See **external documentation**.

`getContext(This::wxGLCanvas()) -> wxGLContext() (see module wxGLContext)`

See **external documentation**.

`setCurrent(This::wxGLCanvas()) -> ok`

See **external documentation**.

`swapBuffers(This::wxGLCanvas()) -> ok`

See **external documentation**.

destroy(This::wxGLCanvas()) -> ok

Destroys this object, do not use object again

wxGraphicsBrush

Erlang module

See external documentation: **wxGraphicsBrush**.

This class is derived (and can use functions) from:
wxGraphicsObject

DATA TYPES

`wxGraphicsBrush()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

wxGraphicsContext

Erlang module

See external documentation: **wxGraphicsContext**.

This class is derived (and can use functions) from:
wxGraphicsObject

DATA TYPES

`wxGraphicsContext()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`create() -> wxGraphicsContext()`

See external documentation.

`create(Dc::wxWindowDC() (see module wxWindowDC) | wxWindow() (see module wxWindow)) -> wxGraphicsContext()`

See external documentation.

`createPen(This::wxGraphicsContext(), Pen::wxPen() (see module wxPen)) -> wxGraphicsPen() (see module wxGraphicsPen)`

See external documentation.

`createBrush(This::wxGraphicsContext(), Brush::wxBrush() (see module wxBrush)) -> wxGraphicsBrush() (see module wxGraphicsBrush)`

See external documentation.

`createRadialGradientBrush(This::wxGraphicsContext(), Xo::float(), Yo::float(), Xc::float(), Yc::float(), Radius::float(), OColor::colour() (see module wx), CColor::colour() (see module wx)) -> wxGraphicsBrush() (see module wxGraphicsBrush)`

See external documentation.

`createLinearGradientBrush(This::wxGraphicsContext(), X1::float(), Y1::float(), X2::float(), Y2::float(), C1::colour() (see module wx), C2::colour() (see module wx)) -> wxGraphicsBrush() (see module wxGraphicsBrush)`

See external documentation.

`createFont(This::wxGraphicsContext(), Font::wxFont() (see module wxFont)) -> wxGraphicsFont() (see module wxGraphicsFont)`

Equivalent to `createFont(This, Font, [])`.

`createFont(This::wxGraphicsContext(), Font::wxFont() (see module wxFont), Options::[Option]) -> wxGraphicsFont() (see module wxGraphicsFont)`

Types:

`Option = {col, colour() (see module wx)}`

See external documentation.

`createMatrix(This::wxGraphicsContext()) -> wxGraphicsMatrix() (see module wxGraphicsMatrix)`

Equivalent to `createMatrix(This, [])`.

`createMatrix(This::wxGraphicsContext(), Options::[Option]) -> wxGraphicsMatrix() (see module wxGraphicsMatrix)`

Types:

`Option = {a, float()} | {b, float()} | {c, float()} | {d, float()} | {tx, float()} | {ty, float()}`

See external documentation.

`createPath(This::wxGraphicsContext()) -> wxGraphicsPath() (see module wxGraphicsPath)`

See external documentation.

`clip(This::wxGraphicsContext(), Region::wxRegion() (see module wxRegion)) -> ok`

See external documentation.

`clip(This::wxGraphicsContext(), X::float(), Y::float(), W::float(), H::float()) -> ok`

See external documentation.

`resetClip(This::wxGraphicsContext()) -> ok`

See external documentation.

`drawBitmap(This::wxGraphicsContext(), Bmp::wxBitmap() (see module wxBitmap), X::float(), Y::float(), W::float(), H::float()) -> ok`

See external documentation.

`drawEllipse(This::wxGraphicsContext(), X::float(), Y::float(), W::float(), H::float()) -> ok`

See external documentation.

`drawIcon(This::wxGraphicsContext(), Icon::wxIcon() (see module wxIcon), X::float(), Y::float(), W::float(), H::float()) -> ok`

See external documentation.

```
drawLines(This::wxGraphicsContext(), N::integer(), Points::{X::float(),  
Y::float()}) -> ok
```

Equivalent to *drawLines(This, N, Points, [])*.

```
drawLines(This::wxGraphicsContext(), N::integer(), Points::{X::float(),  
Y::float()}, Options::[Option]) -> ok
```

Types:

Option = {fillStyle, integer()}

See external documentation.

```
drawPath(This::wxGraphicsContext(), Path::wxGraphicsPath() (see module  
wxGraphicsPath)) -> ok
```

Equivalent to *drawPath(This, Path, [])*.

```
drawPath(This::wxGraphicsContext(), Path::wxGraphicsPath() (see module  
wxGraphicsPath), Options::[Option]) -> ok
```

Types:

Option = {fillStyle, integer()}

See external documentation.

```
drawRectangle(This::wxGraphicsContext(), X::float(), Y::float(), W::float(),  
H::float()) -> ok
```

See external documentation.

```
drawRoundedRectangle(This::wxGraphicsContext(), X::float(), Y::float(),  
W::float(), H::float(), Radius::float()) -> ok
```

See external documentation.

```
drawText(This::wxGraphicsContext(), Str::string(), X::float(), Y::float()) ->  
ok
```

See external documentation.

```
drawText(This::wxGraphicsContext(), Str::string(), X::float(), Y::float(),  
X::float() | term()) -> ok
```

See external documentation.

Alternatives:

```
drawText(This::wxGraphicsContext(), Str::string(), X::float(), Y::float(),  
Angle::float()) -> ok
```

```
drawText(This::wxGraphicsContext(), Str::string(), X::float(), Y::float(),  
BackgroundBrush::wxGraphicsBrush:wxGraphicsBrush()) -> ok
```

`drawText(This::wxGraphicsContext(), Str::string(), X::float(), Y::float(), Angle::float(), BackgroundBrush::wxGraphicsBrush() (see module wxGraphicsBrush)) -> ok`

See external documentation.

`fillPath(This::wxGraphicsContext(), Path::wxGraphicsPath() (see module wxGraphicsPath)) -> ok`

Equivalent to `fillPath(This, Path, [])`.

`fillPath(This::wxGraphicsContext(), Path::wxGraphicsPath() (see module wxGraphicsPath), Options::[Option]) -> ok`

Types:

`Option = {fillStyle, integer()}`

See external documentation.

`strokePath(This::wxGraphicsContext(), Path::wxGraphicsPath() (see module wxGraphicsPath)) -> ok`

See external documentation.

`getNativeContext(This::wxGraphicsContext()) -> ok`

See external documentation.

`getPartialTextExtents(This::wxGraphicsContext(), Text::string(), Widths::[float()]) -> ok`

See external documentation.

`getTextExtent(This::wxGraphicsContext(), Text::string()) -> {Width::float(), Height::float(), Descent::float(), ExternalLeading::float()}`

See external documentation.

`rotate(This::wxGraphicsContext(), Angle::float()) -> ok`

See external documentation.

`scale(This::wxGraphicsContext(), XScale::float(), YScale::float()) -> ok`

See external documentation.

`translate(This::wxGraphicsContext(), Dx::float(), Dy::float()) -> ok`

See external documentation.

`getTransform(This::wxGraphicsContext()) -> wxGraphicsMatrix() (see module wxGraphicsMatrix)`

See external documentation.

`setTransform(This::wxGraphicsContext(), Matrix::wxGraphicsMatrix() (see module wxGraphicsMatrix)) -> ok`

See external documentation.

`concatTransform(This::wxGraphicsContext(), Matrix::wxGraphicsMatrix() (see module wxGraphicsMatrix)) -> ok`

See external documentation.

`setBrush(This::wxGraphicsContext(), Brush::wxGraphicsBrush() (see module wxGraphicsBrush) | wxBrush() (see module wxBrush)) -> ok`

See external documentation.

`setFont(This::wxGraphicsContext(), Font::wxGraphicsFont() (see module wxGraphicsFont)) -> ok`

See external documentation.

`setFont(This::wxGraphicsContext(), Font::wxFont() (see module wxFont), Colour::colour() (see module wx)) -> ok`

See external documentation.

`setPen(This::wxGraphicsContext(), Pen::wxPen() (see module wxPen) | wxGraphicsPen() (see module wxGraphicsPen)) -> ok`

See external documentation.

`strokeLine(This::wxGraphicsContext(), X1::float(), Y1::float(), X2::float(), Y2::float()) -> ok`

See external documentation.

`strokeLines(This::wxGraphicsContext(), N::integer(), Points::{X::float(), Y::float()}) -> ok`

See external documentation.

`strokeLines(This::wxGraphicsContext(), N::integer(), BeginPoints::{X::float(), Y::float()}, EndPoints::{X::float(), Y::float()}) -> ok`

See external documentation.

wxGraphicsFont

Erlang module

See external documentation: **wxGraphicsFont**.

This class is derived (and can use functions) from:
wxGraphicsObject

DATA TYPES

`wxGraphicsFont()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

wxGraphicsMatrix

Erlang module

See external documentation: **wxGraphicsMatrix**.

This class is derived (and can use functions) from:
wxGraphicsObject

DATA TYPES

`wxGraphicsMatrix()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`concat(This::wxGraphicsMatrix(), T::wxGraphicsMatrix()) -> ok`

See external documentation.

`get(This::wxGraphicsMatrix()) -> {A::float(), B::float(), C::float(),
D::float(), Tx::float(), Ty::float()}`

See external documentation.

`getNativeMatrix(This::wxGraphicsMatrix()) -> ok`

See external documentation.

`invert(This::wxGraphicsMatrix()) -> ok`

See external documentation.

`isEqual(This::wxGraphicsMatrix(), T::wxGraphicsMatrix()) -> bool()`

See external documentation.

`isIdentity(This::wxGraphicsMatrix()) -> bool()`

See external documentation.

`rotate(This::wxGraphicsMatrix(), Angle::float()) -> ok`

See external documentation.

`scale(This::wxGraphicsMatrix(), XScale::float(), YScale::float()) -> ok`

See external documentation.

`translate(This::wxGraphicsMatrix(), Dx::float(), Dy::float()) -> ok`

See external documentation.

set(This::wxGraphicsMatrix()) -> ok

Equivalent to *set(This, [])*.

set(This::wxGraphicsMatrix(), Options::[Option]) -> ok

Types:

Option = {a, float()} | {b, float()} | {c, float()} | {d, float()} | {tx, float()} | {ty, float()}

See **external documentation**.

transformPoint(This::wxGraphicsMatrix()) -> {X::float(), Y::float()}

See **external documentation**.

transformDistance(This::wxGraphicsMatrix()) -> {Dx::float(), Dy::float()}

See **external documentation**.

wxGraphicsObject

Erlang module

See external documentation: **wxGraphicsObject**.

DATA TYPES

`wxGraphicsObject()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`getRenderer(This::wxGraphicsObject()) -> wxGraphicsRenderer()` (see module `wxGraphicsRenderer`)

See external documentation.

`isNull(This::wxGraphicsObject()) -> bool()`

See external documentation.

wxGraphicsPath

Erlang module

See external documentation: **wxGraphicsPath**.

This class is derived (and can use functions) from:
wxGraphicsObject

DATA TYPES

`wxGraphicsPath()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`moveToPoint(This::wxGraphicsPath(), P::{X::float(), Y::float()}) -> ok`

See external documentation.

`moveToPoint(This::wxGraphicsPath(), X::float(), Y::float()) -> ok`

See external documentation.

`addArc(This::wxGraphicsPath(), C::{X::float(), Y::float()}, R::float(),
StartAngle::float(), EndAngle::float(), Clockwise::bool()) -> ok`

See external documentation.

`addArc(This::wxGraphicsPath(), X::float(), Y::float(), R::float(),
StartAngle::float(), EndAngle::float(), Clockwise::bool()) -> ok`

See external documentation.

`addArcToPoint(This::wxGraphicsPath(), X1::float(), Y1::float(), X2::float(),
Y2::float(), R::float()) -> ok`

See external documentation.

`addCircle(This::wxGraphicsPath(), X::float(), Y::float(), R::float()) -> ok`

See external documentation.

`addCurveToPoint(This::wxGraphicsPath(), C1::{X::float(), Y::float()}, C2::
{X::float(), Y::float()}, E::{X::float(), Y::float()}) -> ok`

See external documentation.

`addCurveToPoint(This::wxGraphicsPath(), Cx1::float(), Cy1::float(),
Cx2::float(), Cy2::float(), X::float(), Y::float()) -> ok`

See external documentation.

```
addEllipse(This::wxGraphicsPath(), X::float(), Y::float(), W::float(),  
H::float()) -> ok
```

See external documentation.

```
addLineToPoint(This::wxGraphicsPath(), P::{X::float(), Y::float()}) -> ok
```

See external documentation.

```
addLineToPoint(This::wxGraphicsPath(), X::float(), Y::float()) -> ok
```

See external documentation.

```
addPath(This::wxGraphicsPath(), Path::wxGraphicsPath()) -> ok
```

See external documentation.

```
addQuadCurveToPoint(This::wxGraphicsPath(), Cx::float(), Cy::float(),  
X::float(), Y::float()) -> ok
```

See external documentation.

```
addRectangle(This::wxGraphicsPath(), X::float(), Y::float(), W::float(),  
H::float()) -> ok
```

See external documentation.

```
addRoundedRectangle(This::wxGraphicsPath(), X::float(), Y::float(),  
W::float(), H::float(), Radius::float()) -> ok
```

See external documentation.

```
closeSubpath(This::wxGraphicsPath()) -> ok
```

See external documentation.

```
contains(This::wxGraphicsPath(), C::{X::float(), Y::float()}) -> bool()
```

Equivalent to *contains(This, C, [])*.

```
contains(This::wxGraphicsPath(), X::float() | term(), X::float() | term()) ->  
bool()
```

See external documentation.

Alternatives:

```
contains(This::wxGraphicsPath(), X::float(), Y::float()) -> contains(This,X,Y,  
[])
```

```
contains(This::wxGraphicsPath(), C::{X::float(),Y::float()}, [Option]) ->  
bool()
```

Option = {fillStyle, integer()}

```
contains(This::wxGraphicsPath(), X::float(), Y::float(), Options::[Option]) -  
> bool()
```

Types:

Option = {fillStyle, integer()}

See external documentation.

```
getBox(This::wxGraphicsPath()) -> {X::float(), Y::float(), W::float(),  
H::float()}
```

See external documentation.

```
getCurrentPoint(This::wxGraphicsPath()) -> {X::float(), Y::float()}
```

See external documentation.

```
transform(This::wxGraphicsPath(), Matrix::wxGraphicsMatrix() (see module  
wxGraphicsMatrix)) -> ok
```

See external documentation.

wxGraphicsPen

Erlang module

See external documentation: **wxGraphicsPen**.

This class is derived (and can use functions) from:
wxGraphicsObject

DATA TYPES

`wxGraphicsPen()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

wxGraphicsRenderer

Erlang module

See external documentation: **wxGraphicsRenderer**.

DATA TYPES

`wxGraphicsRenderer()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`getDefaultRenderer() -> wxGraphicsRenderer()`

See external documentation.

`createContext(This::wxGraphicsRenderer(), Dc::wxWindowDC() (see module wxWindowDC) | wxWindow() (see module wxWindow)) -> wxGraphicsContext() (see module wxGraphicsContext)`

See external documentation.

`createPen(This::wxGraphicsRenderer(), Pen::wxPen() (see module wxPen)) -> wxGraphicsPen() (see module wxGraphicsPen)`

See external documentation.

`createBrush(This::wxGraphicsRenderer(), Brush::wxBrush() (see module wxBrush)) -> wxGraphicsBrush() (see module wxGraphicsBrush)`

See external documentation.

`createLinearGradientBrush(This::wxGraphicsRenderer(), X1::float(), Y1::float(), X2::float(), Y2::float(), C1::colour() (see module wx), C2::colour() (see module wx)) -> wxGraphicsBrush() (see module wxGraphicsBrush)`

See external documentation.

`createRadialGradientBrush(This::wxGraphicsRenderer(), Xo::float(), Yo::float(), Xc::float(), Yc::float(), Radius::float(), OColor::colour() (see module wx), CColor::colour() (see module wx)) -> wxGraphicsBrush() (see module wxGraphicsBrush)`

See external documentation.

`createFont(This::wxGraphicsRenderer(), Font::wxFont() (see module wxFont)) -> wxGraphicsFont() (see module wxGraphicsFont)`

Equivalent to `createFont(This, Font, [])`.

```
createFont(This::wxGraphicsRenderer(), Font::wxFont() (see module wxFont),  
Options::[Option]) -> wxGraphicsFont() (see module wxGraphicsFont)
```

Types:

Option = {col, colour() (see module wx)}

See external documentation.

```
createMatrix(This::wxGraphicsRenderer()) -> wxGraphicsMatrix() (see module  
wxGraphicsMatrix)
```

Equivalent to *createMatrix(This, [])*.

```
createMatrix(This::wxGraphicsRenderer(), Options::[Option]) ->  
wxGraphicsMatrix() (see module wxGraphicsMatrix)
```

Types:

Option = {a, float()} | {b, float()} | {c, float()} | {d, float()} | {tx, float()} | {ty, float()}

See external documentation.

```
createPath(This::wxGraphicsRenderer()) -> wxGraphicsPath() (see module  
wxGraphicsPath)
```

See external documentation.

wxGridBagSizer

Erlang module

See external documentation: **wxGridBagSizer**.

This class is derived (and can use functions) from:

wxFlexGridSizer

wxGridSizer

wxSizer

DATA TYPES

`wxGridBagSizer()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxGridBagSizer()`

Equivalent to `new([])`.

`new(Options::[Option]) -> wxGridBagSizer()`

Types:

Option = {`vgap, integer()`} | {`hgap, integer()`}

See external documentation.

`add(This::wxGridBagSizer(), Item::wxSizerItem() (see module wxSizerItem) | wxGBSizerItem() (see module wxGBSizerItem)) -> wxSizerItem() (see module wxSizerItem)`

See external documentation.

`add(This::wxGridBagSizer(), X::integer() | term(), X::integer() | term()) -> wxSizerItem() (see module wxSizerItem)`

See external documentation.

Alternatives:

`add(This::wxGridBagSizer(), Width::integer(), Height::integer()) -> add(This,Width,Height, [])`

`add(This::wxGridBagSizer(), Window::wxWindow:wxWindow() | wxSizer:wxSizer(), Pos::{R::integer(),C::integer()}) -> add(This,Window,Pos, [])`

`add(This::wxGridBagSizer(), Window::wxWindow:wxWindow() | wxSizer:wxSizer(), [Option]) -> wxSizerItem:wxSizerItem()`

Option = {`proportion, integer()`} | {`flag, integer()`} | {`border, integer()`} | {`userData, wx:wx()`}

```
add(This::wxGridBagSizer(), X::integer() | term(), X::integer() | term(),  
X::term()) -> wxSizerItem() (see module wxSizerItem)
```

See external documentation.

Alternatives:

```
add(This::wxGridBagSizer(), Width::integer(), Height::integer(), Pos::  
{R::integer(),C::integer()}) -> add(This,Width,Height,Pos, [])
```

```
add(This::wxGridBagSizer(), Width::integer(), Height::integer(), [Option]) ->  
wxSizerItem:wxSizerItem()
```

Option = {proportion, integer()} | {flag, integer()} | {border, integer()} | {userData, wx:wx()}

```
add(This::wxGridBagSizer(), Window::wxWindow:wxWindow() | wxSizer:wxSizer(),  
Pos::{R::integer(),C::integer()}, [Option]) -> wxSizerItem:wxSizerItem()
```

Option = {span, {RS::integer(),CS::integer()}} | {flag, integer()} | {border, integer()} | {userData, wx:wx()}

```
add(This::wxGridBagSizer(), Width::integer(), Height::integer(), Pos::  
{R::integer(), C::integer()}, Options::[Option]) -> wxSizerItem() (see module  
wxSizerItem)
```

Types:

**Option = {span, {RS::integer(), CS::integer()}} | {flag, integer()} | {border, integer()} | {userData, wx()
(see module wx)}**

See external documentation.

```
calcMin(This::wxGridBagSizer()) -> {W::integer(), H::integer()}
```

See external documentation.

```
checkForIntersection(This::wxGridBagSizer(), Item::wxGBSizerItem() (see  
module wxGBSizerItem)) -> bool()
```

Equivalent to *checkForIntersection(This, Item, [])*.

```
checkForIntersection(This::wxGridBagSizer(), X::term(), X::term()) -> bool()
```

See external documentation.

Alternatives:

```
checkForIntersection(This::wxGridBagSizer(), Pos::{R::integer(),C::integer()},  
Span::{RS::integer(),CS::integer()}) -> checkForIntersection(This,Pos,Span,  
[])
```

```
checkForIntersection(This::wxGridBagSizer(),  
Item::wxGBSizerItem:wxGBSizerItem(), [Option]) -> bool()
```

Option = {excludeItem, wxGBSizerItem:wxGBSizerItem()}

```
checkForIntersection(This::wxGridBagSizer(), Pos::{R::integer(),  
C::integer()}, Span::{RS::integer(), CS::integer()}, Options::[Option]) ->  
bool()
```

Types:

Option = {excludeItem, wxGBSizerItem() (see module wxGBSizerItem)}

See external documentation.

```
findItem(This::wxGridBagSizer(), Window::wxWindow() (see module wxWindow) |  
wxSizer() (see module wxSizer)) -> wxGBSizerItem() (see module wxGBSizerItem)
```

See external documentation.

```
findItemAtPoint(This::wxGridBagSizer(), Pt::{X::integer(), Y::integer()}) ->  
wxGBSizerItem() (see module wxGBSizerItem)
```

See external documentation.

```
findItemAtPosition(This::wxGridBagSizer(), Pos::{R::integer(), C::integer()})  
-> wxGBSizerItem() (see module wxGBSizerItem)
```

See external documentation.

```
findItemWithData(This::wxGridBagSizer(), UserData::wx() (see module wx)) ->  
wxGBSizerItem() (see module wxGBSizerItem)
```

See external documentation.

```
getCellSize(This::wxGridBagSizer(), Row::integer(), Col::integer()) ->  
{W::integer(), H::integer()}
```

See external documentation.

```
getEmptyCellSize(This::wxGridBagSizer()) -> {W::integer(), H::integer()}
```

See external documentation.

```
getItemPosition(This::wxGridBagSizer(), X::integer() | term()) ->  
{R::integer(), C::integer()}
```

See external documentation.

Alternatives:

```
getItemPosition(This::wxGridBagSizer(), Index::integer()) ->  
{R::integer(), C::integer()}
```

```
getItemPosition(This::wxGridBagSizer(), Window::wxWindow:wxWindow() |  
wxSizer:wxSizer()) -> {R::integer(), C::integer()}
```

```
getItemSpan(This::wxGridBagSizer(), X::integer() | term()) -> {RS::integer(),  
CS::integer()}
```

See external documentation.

Alternatives:

```
getItemSpan(This::wxGridBagSizer(), Index::integer()) ->  
{RS::integer(), CS::integer()}
```

```
getItemSpan(This::wxGridBagSizer(), Window::wxWindow:wxWindow() |  
wxSizer:wxSizer()) -> {RS::integer(), CS::integer()}
```

```
setEmptyCellSize(This::wxGridBagSizer(), Sz::{W::integer(), H::integer()}) ->  
ok
```

See external documentation.

```
setItemPosition(This::wxGridBagSizer(), X::integer() | term(), Pos::  
{R::integer(), C::integer()}) -> bool()
```

See [external documentation](#).

Alternatives:

```
setItemPosition(This::wxGridBagSizer(), Index::integer(), Pos::  
{R::integer(), C::integer()}) -> bool()
```

```
setItemPosition(This::wxGridBagSizer(), Window::wxWindow:wxWindow() |  
wxSizer:wxSizer(), Pos::{R::integer(), C::integer()}) -> bool()
```

```
setItemSpan(This::wxGridBagSizer(), X::integer() | term(), Span::  
{RS::integer(), CS::integer()}) -> bool()
```

See [external documentation](#).

Alternatives:

```
setItemSpan(This::wxGridBagSizer(), Index::integer(), Span::  
{RS::integer(), CS::integer()}) -> bool()
```

```
setItemSpan(This::wxGridBagSizer(), Window::wxWindow:wxWindow() |  
wxSizer:wxSizer(), Span::{RS::integer(), CS::integer()}) -> bool()
```

```
destroy(This::wxGridBagSizer()) -> ok
```

Destroys this object, do not use object again

wxGridCellAttr

Erlang module

See external documentation: **wxGridCellAttr**.

DATA TYPES

`wxGridCellAttr()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparsion stored on disc or distributed for use on other nodes.

Exports

`setTextColour(This::wxGridCellAttr(), ColText::colour() (see module wx)) -> ok`

See external documentation.

`setBackgroundColour(This::wxGridCellAttr(), ColBack::colour() (see module wx)) -> ok`

See external documentation.

`setFont(This::wxGridCellAttr(), Font::wxFont() (see module wxFont)) -> ok`

See external documentation.

`setAlignment(This::wxGridCellAttr(), HAlign::integer(), VAlign::integer()) -> ok`

See external documentation.

`setReadOnly(This::wxGridCellAttr()) -> ok`

Equivalent to `setReadOnly(This, [])`.

`setReadOnly(This::wxGridCellAttr(), Options::[Option]) -> ok`

Types:

`Option = {isReadOnly, bool()}`

See external documentation.

`setRenderer(This::wxGridCellAttr(), Renderer::wxGridCellRenderer() (see module wxGridCellRenderer)) -> ok`

See external documentation.

`setEditor(This::wxGridCellAttr(), Editor::wxGridCellEditor() (see module wxGridCellEditor)) -> ok`

See external documentation.

`hasTextColour(This::wxGridCellAttr()) -> bool()`

See external documentation.

`hasBackgroundColour(This::wxGridCellAttr()) -> bool()`

See external documentation.

`hasFont(This::wxGridCellAttr()) -> bool()`

See external documentation.

`hasAlignment(This::wxGridCellAttr()) -> bool()`

See external documentation.

`hasRenderer(This::wxGridCellAttr()) -> bool()`

See external documentation.

`hasEditor(This::wxGridCellAttr()) -> bool()`

See external documentation.

`getTextColour(This::wxGridCellAttr()) -> colour() (see module wx)`

See external documentation.

`getBackgroundColour(This::wxGridCellAttr()) -> colour() (see module wx)`

See external documentation.

`getFont(This::wxGridCellAttr()) -> wxFont() (see module wxFont)`

See external documentation.

`getAlignment(This::wxGridCellAttr()) -> {HAlign::integer(),
VAlign::integer()}`

See external documentation.

`getRenderer(This::wxGridCellAttr(), Grid::wxGrid() (see module wxGrid),
Row::integer(), Col::integer()) -> wxGridCellRenderer() (see module
wxGridCellRenderer)`

See external documentation.

`getEditor(This::wxGridCellAttr(), Grid::wxGrid() (see module wxGrid),
Row::integer(), Col::integer()) -> wxGridCellEditor() (see module
wxGridCellEditor)`

See external documentation.

`isReadOnly(This::wxGridCellAttr()) -> bool()`

See external documentation.

```
setDefAttr(This::wxGridCellAttr(), DefAttr::wxGridCellAttr()) -> ok
```

See [external documentation](#).

wxGridCellBoolEditor

Erlang module

See external documentation: **wxGridCellBoolEditor**.

This class is derived (and can use functions) from:
wxGridCellEditor

DATA TYPES

`wxGridCellBoolEditor()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxGridCellBoolEditor()`

See external documentation.

`isTrueValue(Value::string()) -> bool()`

See external documentation.

`useStringValues() -> ok`

Equivalent to `useStringValues([])`.

`useStringValues(Options::[Option]) -> ok`

Types:

Option = {valueTrue, string()} | {valueFalse, string() }

See external documentation.

`destroy(This::wxGridCellBoolEditor()) -> ok`

Destroys this object, do not use object again

wxGridCellBoolRenderer

Erlang module

See external documentation: **wxGridCellBoolRenderer**.

This class is derived (and can use functions) from:
wxGridCellRenderer

DATA TYPES

`wxGridCellBoolRenderer()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new()` -> **`wxGridCellBoolRenderer()`**

See **external documentation**.

`destroy(This::wxGridCellBoolRenderer())` -> **`ok`**

Destroys this object, do not use object again

wxGridCellChoiceEditor

Erlang module

See external documentation: **wxGridCellChoiceEditor**.

This class is derived (and can use functions) from:
wxGridCellEditor

DATA TYPES

`wxGridCellChoiceEditor()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new(Choices::[[string()]]) -> wxGridCellChoiceEditor()`

Equivalent to `new(Choices, [])`.

`new(Choices::[[string()]], Options::[Option]) -> wxGridCellChoiceEditor()`

Types:

Option = {allowOthers, bool()}

See external documentation.

`setParameters(This::wxGridCellChoiceEditor(), Params::string()) -> ok`

See external documentation.

`destroy(This::wxGridCellChoiceEditor()) -> ok`

Destroys this object, do not use object again

wxGridCellEditor

Erlang module

See external documentation: **wxGridCellEditor**.

DATA TYPES

`wxGridCellEditor()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`create(This::wxGridCellEditor(), Parent::wxWindow() (see module wxWindow), Id::integer(), EvtHandler::wxEvtHandler() (see module wxEvtHandler)) -> ok`

See external documentation.

`isCreated(This::wxGridCellEditor()) -> bool()`

See external documentation.

`setSize(This::wxGridCellEditor(), Rect::{X::integer(), Y::integer(), W::integer(), H::integer()}) -> ok`

See external documentation.

`show(This::wxGridCellEditor(), Show::bool()) -> ok`

Equivalent to `show(This, Show, [])`.

`show(This::wxGridCellEditor(), Show::bool(), Options::[Option]) -> ok`

Types:

`Option = {attr, wxGridCellAttr() (see module wxGridCellAttr)}`

See external documentation.

`paintBackground(This::wxGridCellEditor(), RectCell::{X::integer(), Y::integer(), W::integer(), H::integer()}, Attr::wxGridCellAttr() (see module wxGridCellAttr)) -> ok`

See external documentation.

`beginEdit(This::wxGridCellEditor(), Row::integer(), Col::integer(), Grid::wxGrid() (see module wxGrid)) -> ok`

See external documentation.

`endEdit(This::wxGridCellEditor(), Row::integer(), Col::integer(), Grid::wxGrid() (see module wxGrid)) -> bool()`

See external documentation.

`reset(This::wxGridCellEditor()) -> ok`

See external documentation.

`startingKey(This::wxGridCellEditor(), Event::wxKeyEvent() (see module wxKeyEvent)) -> ok`

See external documentation.

`startingClick(This::wxGridCellEditor()) -> ok`

See external documentation.

`handleReturn(This::wxGridCellEditor(), Event::wxKeyEvent() (see module wxKeyEvent)) -> ok`

See external documentation.

wxGridCellFloatEditor

Erlang module

See external documentation: **wxGridCellFloatEditor**.

This class is derived (and can use functions) from:
wxGridCellEditor

DATA TYPES

`wxGridCellFloatEditor()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxGridCellFloatEditor()`

Equivalent to `new([])`.

`new(Options::[Option]) -> wxGridCellFloatEditor()`

Types:

Option = {width, integer()} | {precision, integer()}

See external documentation.

`setParameters(This::wxGridCellFloatEditor(), Params::string()) -> ok`

See external documentation.

`destroy(This::wxGridCellFloatEditor()) -> ok`

Destroys this object, do not use object again

wxGridCellFloatRenderer

Erlang module

See external documentation: **wxGridCellFloatRenderer**.

This class is derived (and can use functions) from:

wxGridCellStringRenderer

wxGridCellRenderer

DATA TYPES

`wxGridCellFloatRenderer()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxGridCellFloatRenderer()`

Equivalent to `new([])`.

`new(Options::[Option]) -> wxGridCellFloatRenderer()`

Types:

`Option = {width, integer()} | {precision, integer()}`

See external documentation.

`getPrecision(This::wxGridCellFloatRenderer()) -> integer()`

See external documentation.

`getWidth(This::wxGridCellFloatRenderer()) -> integer()`

See external documentation.

`setParameters(This::wxGridCellFloatRenderer(), Params::string()) -> ok`

See external documentation.

`setPrecision(This::wxGridCellFloatRenderer(), Precision::integer()) -> ok`

See external documentation.

`setWidth(This::wxGridCellFloatRenderer(), Width::integer()) -> ok`

See external documentation.

`destroy(This::wxGridCellFloatRenderer()) -> ok`

Destroys this object, do not use object again

wxGridCellNumberEditor

Erlang module

See external documentation: **wxGridCellNumberEditor**.

This class is derived (and can use functions) from:

wxGridCellTextEditor

wxGridCellEditor

DATA TYPES

`wxGridCellNumberEditor()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxGridCellNumberEditor()`

Equivalent to `new([])`.

`new(Options::[Option]) -> wxGridCellNumberEditor()`

Types:

Option = {min, integer()} | {max, integer()}

See external documentation.

`getValue(This::wxGridCellNumberEditor()) -> string()`

See external documentation.

`setParameters(This::wxGridCellNumberEditor(), Params::string()) -> ok`

See external documentation.

`destroy(This::wxGridCellNumberEditor()) -> ok`

Destroys this object, do not use object again

wxGridCellNumberRenderer

Erlang module

See external documentation: **wxGridCellNumberRenderer**.

This class is derived (and can use functions) from:

wxGridCellStringRenderer

wxGridCellRenderer

DATA TYPES

`wxGridCellNumberRenderer()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new()` -> **`wxGridCellNumberRenderer()`**

See external documentation.

`destroy(This::wxGridCellNumberRenderer())` -> **`ok`**

Destroys this object, do not use object again

wxGridCellRenderer

Erlang module

See external documentation: **wxGridCellRenderer**.

DATA TYPES

`wxGridCellRenderer()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparsion stored on disc or distributed for use on other nodes.

Exports

```
draw(This::wxGridCellRenderer(), Grid::wxGrid() (see module wxGrid),  
Attr::wxGridCellAttr() (see module wxGridCellAttr), Dc::wxDC() (see module  
wxDC), Rect::{X::integer(), Y::integer(), W::integer(), H::integer()},  
Row::integer(), Col::integer(), IsSelected::bool()) -> ok
```

See external documentation.

```
getBestSize(This::wxGridCellRenderer(), Grid::wxGrid() (see module wxGrid),  
Attr::wxGridCellAttr() (see module wxGridCellAttr), Dc::wxDC() (see module  
wxDC), Row::integer(), Col::integer()) -> {W::integer(), H::integer()}
```

See external documentation.

wxGridCellStringRenderer

Erlang module

See external documentation: **wxGridCellStringRenderer**.

This class is derived (and can use functions) from:
wxGridCellRenderer

DATA TYPES

`wxGridCellStringRenderer()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new()` -> **`wxGridCellStringRenderer()`**

See external documentation.

`destroy(This::wxGridCellStringRenderer())` -> **`ok`**

Destroys this object, do not use object again

wxGridCellTextEditor

Erlang module

See external documentation: **wxGridCellTextEditor**.

This class is derived (and can use functions) from:
wxGridCellEditor

DATA TYPES

`wxGridCellTextEditor()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new()` -> **`wxGridCellTextEditor()`**

See **external documentation**.

`setParameters(This::wxGridCellTextEditor(), Params::string())` -> **`ok`**

See **external documentation**.

`destroy(This::wxGridCellTextEditor())` -> **`ok`**

Destroys this object, do not use object again

wxGrid

Erlang module

See external documentation: **wxGrid**.

This class is derived (and can use functions) from:

wxScrolledWindow

wxPanel

wxWindow

wxEvtHandler

DATA TYPES

`wxGrid()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxGrid()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Id::integer()) -> wxGrid()`

Equivalent to `new(Parent, Id, [])`.

`new(Parent::wxWindow() (see module wxWindow), X::integer(), Y::integer() | term()) -> wxGrid()`

See external documentation.

Alternatives:

`new(Parent::wxWindow:wxWindow(), X::integer(), Y::integer()) -> new(Parent,X,Y, [])`

`new(Parent::wxWindow:wxWindow(), Id::integer(), [Option]) -> wxGrid()`

Option = {pos, {X::integer(),Y::integer()}} | {size, {W::integer(),H::integer()}} | {style, integer()}

`new(Parent::wxWindow() (see module wxWindow), X::integer(), Y::integer(), Options::[Option]) -> wxGrid()`

Types:

Option = {w, integer()} | {h, integer()} | {style, integer()}

See external documentation.

`appendCols(This::wxGrid()) -> bool()`

Equivalent to `appendCols(This, [])`.

`appendCols(This::wxGrid(), Options::[Option]) -> bool()`

Types:

Option = {numCols, integer()} | {updateLabels, bool()}

See [external documentation](#).

appendRows(This::wxGrid()) -> bool()

Equivalent to *appendRows(This, [])*.

appendRows(This::wxGrid(), Options::[Option]) -> bool()

Types:

Option = {numRows, integer()} | {updateLabels, bool()}

See [external documentation](#).

autoSize(This::wxGrid()) -> ok

See [external documentation](#).

autoSizeColumn(This::wxGrid(), Col::integer()) -> ok

Equivalent to *autoSizeColumn(This, Col, [])*.

autoSizeColumn(This::wxGrid(), Col::integer(), Options::[Option]) -> ok

Types:

Option = {setAsMin, bool()}

See [external documentation](#).

autoSizeColumns(This::wxGrid()) -> ok

Equivalent to *autoSizeColumns(This, [])*.

autoSizeColumns(This::wxGrid(), Options::[Option]) -> ok

Types:

Option = {setAsMin, bool()}

See [external documentation](#).

autoSizeRow(This::wxGrid(), Row::integer()) -> ok

Equivalent to *autoSizeRow(This, Row, [])*.

autoSizeRow(This::wxGrid(), Row::integer(), Options::[Option]) -> ok

Types:

Option = {setAsMin, bool()}

See [external documentation](#).

autoSizeRows(This::wxGrid()) -> ok

Equivalent to *autoSizeRows(This, [])*.

autoSizeRows(This::wxGrid(), Options::[Option]) -> ok

Types:

Option = {setAsMin, bool()}

See external documentation.

beginBatch(This::wxGrid()) -> ok

See external documentation.

blockToDeviceRect(This::wxGrid(), TopLeft::{R::integer(), C::integer()}, BottomRight::{R::integer(), C::integer()}) -> {X::integer(), Y::integer(), W::integer(), H::integer()}

See external documentation.

canDragColSize(This::wxGrid()) -> bool()

See external documentation.

canDragRowSize(This::wxGrid()) -> bool()

See external documentation.

canDragGridSize(This::wxGrid()) -> bool()

See external documentation.

canEnableCellControl(This::wxGrid()) -> bool()

See external documentation.

cellToRect(This::wxGrid(), Coords::{R::integer(), C::integer()}) -> {X::integer(), Y::integer(), W::integer(), H::integer()}

See external documentation.

cellToRect(This::wxGrid(), Row::integer(), Col::integer()) -> {X::integer(), Y::integer(), W::integer(), H::integer()}

See external documentation.

clearGrid(This::wxGrid()) -> ok

See external documentation.

clearSelection(This::wxGrid()) -> ok

See external documentation.

createGrid(This::wxGrid(), NumRows::integer(), NumCols::integer()) -> bool()

Equivalent to *createGrid(This, NumRows, NumCols, [])*.

createGrid(This::wxGrid(), NumRows::integer(), NumCols::integer(), Options::[Option]) -> bool()

Types:

Option = {selmode, WxGridSelectionModes}

WxGridSelectionModes = integer()

See **external documentation**.

WxGridSelectionModes is one of ?wxGrid_wxGridSelectCells | ?wxGrid_wxGridSelectRows | ?wxGrid_wxGridSelectColumns

deleteCols(This::wxGrid()) -> bool()

Equivalent to *deleteCols(This, [])*.

deleteCols(This::wxGrid(), Options::[Option]) -> bool()

Types:

Option = {pos, integer()} | {numCols, integer()} | {updateLabels, bool()}

See **external documentation**.

deleteRows(This::wxGrid()) -> bool()

Equivalent to *deleteRows(This, [])*.

deleteRows(This::wxGrid(), Options::[Option]) -> bool()

Types:

Option = {pos, integer()} | {numRows, integer()} | {updateLabels, bool()}

See **external documentation**.

disableCellEditControl(This::wxGrid()) -> ok

See **external documentation**.

disableDragColSize(This::wxGrid()) -> ok

See **external documentation**.

disableDragGridSize(This::wxGrid()) -> ok

See **external documentation**.

disableDragRowSize(This::wxGrid()) -> ok

See **external documentation**.

enableCellEditControl(This::wxGrid()) -> ok

Equivalent to *enableCellEditControl(This, [])*.

enableCellEditControl(This::wxGrid(), Options::[Option]) -> ok

Types:

Option = {enable, bool()}

See **external documentation**.

enableDragColSize(This::wxGrid()) -> ok

Equivalent to *enableDragColSize(This, [])*.

enableDragColSize(This::wxGrid(), Options::[Option]) -> ok

Types:

Option = {enable, bool()}

See **external documentation**.

enableDragGridSize(This::wxGrid()) -> ok

Equivalent to *enableDragGridSize(This, [])*.

enableDragGridSize(This::wxGrid(), Options::[Option]) -> ok

Types:

Option = {enable, bool()}

See **external documentation**.

enableDragRowSize(This::wxGrid()) -> ok

Equivalent to *enableDragRowSize(This, [])*.

enableDragRowSize(This::wxGrid(), Options::[Option]) -> ok

Types:

Option = {enable, bool()}

See **external documentation**.

enableEditing(This::wxGrid(), Edit::bool()) -> ok

See **external documentation**.

enableGridLines(This::wxGrid()) -> ok

Equivalent to *enableGridLines(This, [])*.

enableGridLines(This::wxGrid(), Options::[Option]) -> ok

Types:

Option = {enable, bool()}

See **external documentation**.

endBatch(This::wxGrid()) -> ok

See **external documentation**.

fit(This::wxGrid()) -> ok

See **external documentation**.

`forceRefresh(This::wxGrid()) -> ok`

See external documentation.

`getBatchCount(This::wxGrid()) -> integer()`

See external documentation.

`getCellAlignment(This::wxGrid(), Row::integer(), Col::integer()) -> {Horiz::integer(), Vert::integer()}`

See external documentation.

`getCellBackgroundColour(This::wxGrid(), Row::integer(), Col::integer()) -> colour() (see module wx)`

See external documentation.

`getCellEditor(This::wxGrid(), Row::integer(), Col::integer()) -> wxGridCellEditor() (see module wxGridCellEditor)`

See external documentation.

`getCellFont(This::wxGrid(), Row::integer(), Col::integer()) -> wxFont() (see module wxFont)`

See external documentation.

`getCellRenderer(This::wxGrid(), Row::integer(), Col::integer()) -> wxGridCellRenderer() (see module wxGridCellRenderer)`

See external documentation.

`getCellTextColour(This::wxGrid(), Row::integer(), Col::integer()) -> colour() (see module wx)`

See external documentation.

`getCellValue(This::wxGrid(), Coords::{R::integer(), C::integer()}) -> string()`

See external documentation.

`getCellValue(This::wxGrid(), Row::integer(), Col::integer()) -> string()`

See external documentation.

`getColLabelAlignment(This::wxGrid()) -> {Horiz::integer(), Vert::integer()}`

See external documentation.

`getColLabelSize(This::wxGrid()) -> integer()`

See external documentation.

`getColLabelValue(This::wxGrid(), Col::integer()) -> string()`

See external documentation.

`getColMinimalAcceptableWidth(This::wxGrid()) -> integer()`

See external documentation.

`getDefaultCellAlignment(This::wxGrid()) -> {Horiz::integer(),
Vert::integer()}`

See external documentation.

`getDefaultCellBackgroundColour(This::wxGrid()) -> colour() (see module wx)`

See external documentation.

`getDefaultCellFont(This::wxGrid()) -> wxFont() (see module wxFont)`

See external documentation.

`getDefaultCellTextColour(This::wxGrid()) -> colour() (see module wx)`

See external documentation.

`getDefaultColLabelSize(This::wxGrid()) -> integer()`

See external documentation.

`getDefaultColSize(This::wxGrid()) -> integer()`

See external documentation.

`getDefaultEditor(This::wxGrid()) -> wxGridCellEditor() (see module
wxGridCellEditor)`

See external documentation.

`getDefaultEditorForCell(This::wxGrid(), C::{R::integer(), C::integer()}) ->
wxGridCellEditor() (see module wxGridCellEditor)`

See external documentation.

`getDefaultEditorForCell(This::wxGrid(), Row::integer(), Col::integer()) ->
wxGridCellEditor() (see module wxGridCellEditor)`

See external documentation.

`getDefaultEditorForType(This::wxGrid(), TypeName::string()) ->
wxGridCellEditor() (see module wxGridCellEditor)`

See external documentation.

`getDefaultRenderer(This::wxGrid()) -> wxGridCellRenderer() (see module
wxGridCellRenderer)`

See external documentation.

`getDefaultRendererForCell(This::wxGrid(), Row::integer(), Col::integer()) -> wxGridCellRenderer()` (see module `wxGridCellRenderer`)

See external documentation.

`getDefaultRendererForType(This::wxGrid(), TypeName::string()) -> wxGridCellRenderer()` (see module `wxGridCellRenderer`)

See external documentation.

`getDefaultRowLabelSize(This::wxGrid()) -> integer()`

See external documentation.

`getDefaultRowSize(This::wxGrid()) -> integer()`

See external documentation.

`getGridCursorCol(This::wxGrid()) -> integer()`

See external documentation.

`getGridCursorRow(This::wxGrid()) -> integer()`

See external documentation.

`getGridLineColour(This::wxGrid()) -> colour()` (see module `wx`)

See external documentation.

`gridLinesEnabled(This::wxGrid()) -> bool()`

See external documentation.

`getLabelBackgroundColour(This::wxGrid()) -> colour()` (see module `wx`)

See external documentation.

`getLabelFont(This::wxGrid()) -> wxFont()` (see module `wxFont`)

See external documentation.

`getLabelTextColour(This::wxGrid()) -> colour()` (see module `wx`)

See external documentation.

`getNumberCols(This::wxGrid()) -> integer()`

See external documentation.

`getNumberRows(This::wxGrid()) -> integer()`

See external documentation.

`getOrCreateCellAttr(This::wxGrid(), Row::integer(), Col::integer()) -> wxGridCellAttr()` (see module `wxGridCellAttr`)

See external documentation.

`getRowMinimalAcceptableHeight(This::wxGrid()) -> integer()`

See external documentation.

`getRowLabelAlignment(This::wxGrid()) -> {Horiz::integer(), Vert::integer()}`

See external documentation.

`getRowLabelSize(This::wxGrid()) -> integer()`

See external documentation.

`getRowLabelValue(This::wxGrid(), Row::integer()) -> string()`

See external documentation.

`getRowSize(This::wxGrid(), Row::integer()) -> integer()`

See external documentation.

`getScrollLineX(This::wxGrid()) -> integer()`

See external documentation.

`getScrollLineY(This::wxGrid()) -> integer()`

See external documentation.

`getSelectedCells(This::wxGrid()) -> [{R::integer(), C::integer()}]`

See external documentation.

`getSelectedCols(This::wxGrid()) -> [integer()]`

See external documentation.

`getSelectedRows(This::wxGrid()) -> [integer()]`

See external documentation.

`getSelectionBackground(This::wxGrid()) -> colour()` (see module `wx`)

See external documentation.

`getSelectionBlockTopLeft(This::wxGrid()) -> [{R::integer(), C::integer()}]`

See external documentation.

`getSelectionBlockBottomRight(This::wxGrid()) -> [{R::integer(), C::integer()}]`

See external documentation.

`getSelectionForeground(This::wxGrid()) -> colour()` (see module `wx`)

See external documentation.

`getViewWidth(This::wxGrid()) -> integer()`

See external documentation.

`getGridWindow(This::wxGrid()) -> wxWindow()` (see module `wxWindow`)

See external documentation.

`getGridRowLabelWindow(This::wxGrid()) -> wxWindow()` (see module `wxWindow`)

See external documentation.

`getGridColLabelWindow(This::wxGrid()) -> wxWindow()` (see module `wxWindow`)

See external documentation.

`getGridCornerLabelWindow(This::wxGrid()) -> wxWindow()` (see module `wxWindow`)

See external documentation.

`hideCellEditControl(This::wxGrid()) -> ok`

See external documentation.

`insertCols(This::wxGrid()) -> bool()`

Equivalent to `insertCols(This, [])`.

`insertCols(This::wxGrid(), Options::[Option]) -> bool()`

Types:

Option = {pos, integer()} | {numCols, integer()} | {updateLabels, bool()}

See external documentation.

`insertRows(This::wxGrid()) -> bool()`

Equivalent to `insertRows(This, [])`.

`insertRows(This::wxGrid(), Options::[Option]) -> bool()`

Types:

Option = {pos, integer()} | {numRows, integer()} | {updateLabels, bool()}

See external documentation.

`isCellEditControlEnabled(This::wxGrid()) -> bool()`

See external documentation.

`isCurrentCellReadOnly(This::wxGrid()) -> bool()`

See external documentation.

isEditable(This::wxGrid()) -> bool()

See external documentation.

isSelected(This::wxGrid(), Coords::{R::integer(), C::integer()}) -> bool()

See external documentation.

isSelected(This::wxGrid(), Row::integer(), Col::integer()) -> bool()

See external documentation.

isReadOnly(This::wxGrid(), Row::integer(), Col::integer()) -> bool()

See external documentation.

isSelected(This::wxGrid()) -> bool()

See external documentation.

isVisible(This::wxGrid(), Coords::{R::integer(), C::integer()}) -> bool()

Equivalent to *isVisible(This, Coords, [])*.

isVisible(This::wxGrid(), X::integer() | term(), X::integer() | term()) -> bool()

See external documentation.

Alternatives:

isVisible(This::wxGrid(), Row::integer(), Col::integer()) -> bool()
isVisible(This, Row, Col, [])

isVisible(This::wxGrid(), Coords::{R::integer(), C::integer()}, [Option]) -> bool()
Option = {wholeCellVisible, bool()}

isVisible(This::wxGrid(), Row::integer(), Col::integer(), Options::[Option]) -> bool()

Types:

Option = {wholeCellVisible, bool()}

See external documentation.

makeCellVisible(This::wxGrid(), Coords::{R::integer(), C::integer()}) -> ok

See external documentation.

makeCellVisible(This::wxGrid(), Row::integer(), Col::integer()) -> ok

See external documentation.

moveCursorDown(This::wxGrid(), ExpandSelection::bool()) -> bool()

See external documentation.

`moveCursorLeft(This::wxGrid(), ExpandSelection::bool()) -> bool()`

See external documentation.

`moveCursorRight(This::wxGrid(), ExpandSelection::bool()) -> bool()`

See external documentation.

`moveCursorUp(This::wxGrid(), ExpandSelection::bool()) -> bool()`

See external documentation.

`moveCursorDownBlock(This::wxGrid(), ExpandSelection::bool()) -> bool()`

See external documentation.

`moveCursorLeftBlock(This::wxGrid(), ExpandSelection::bool()) -> bool()`

See external documentation.

`moveCursorRightBlock(This::wxGrid(), ExpandSelection::bool()) -> bool()`

See external documentation.

`moveCursorUpBlock(This::wxGrid(), ExpandSelection::bool()) -> bool()`

See external documentation.

`movePageDown(This::wxGrid()) -> bool()`

See external documentation.

`movePageUp(This::wxGrid()) -> bool()`

See external documentation.

`registerDataType(This::wxGrid(), TypeName::string(),
Renderer::wxGridCellRenderer() (see module wxGridCellRenderer),
Editor::wxGridCellEditor() (see module wxGridCellEditor)) -> ok`

See external documentation.

`saveEditControlValue(This::wxGrid()) -> ok`

See external documentation.

`selectAll(This::wxGrid()) -> ok`

See external documentation.

`selectBlock(This::wxGrid(), TopLeft::{R::integer(), C::integer()},
BottomRight::{R::integer(), C::integer()}) -> ok`

Equivalent to `selectBlock(This, TopLeft, BottomRight, [])`.

```
selectBlock(This::wxGrid(), TopLeft::{R::integer(), C::integer()},  
BottomRight::{R::integer(), C::integer()}, Options::[Option]) -> ok
```

Types:

Option = {addToSelected, bool()}

See external documentation.

```
selectBlock(This::wxGrid(), TopRow::integer(), LeftCol::integer(),  
BottomRow::integer(), RightCol::integer()) -> ok
```

Equivalent to *selectBlock(This, TopRow, LeftCol, BottomRow, RightCol, [])*.

```
selectBlock(This::wxGrid(), TopRow::integer(), LeftCol::integer(),  
BottomRow::integer(), RightCol::integer(), Options::[Option]) -> ok
```

Types:

Option = {addToSelected, bool()}

See external documentation.

```
selectCol(This::wxGrid(), Col::integer()) -> ok
```

Equivalent to *selectCol(This, Col, [])*.

```
selectCol(This::wxGrid(), Col::integer(), Options::[Option]) -> ok
```

Types:

Option = {addToSelected, bool()}

See external documentation.

```
selectRow(This::wxGrid(), Row::integer()) -> ok
```

Equivalent to *selectRow(This, Row, [])*.

```
selectRow(This::wxGrid(), Row::integer(), Options::[Option]) -> ok
```

Types:

Option = {addToSelected, bool()}

See external documentation.

```
setCellAlignment(This::wxGrid(), Align::integer()) -> ok
```

See external documentation.

```
setCellAlignment(This::wxGrid(), Align::integer(), Row::integer(),  
Col::integer()) -> ok
```

See external documentation.

```
setCellAlignment(This::wxGrid(), Row::integer(), Col::integer(),  
Horiz::integer(), Vert::integer()) -> ok
```

See external documentation.

setCellBackgroundColour(This::wxGrid(), Col::colour() (see module wx)) -> ok

See [external documentation](#).

**setCellBackgroundColour(This::wxGrid(), X::integer() | term(), X::integer(),
X::term() | integer()) -> ok**

See [external documentation](#).

Alternatives:

**setCellBackgroundColour(This::wxGrid(), Row::integer(), Col::integer(),
Val::wx:colour()) -> ok**

**setCellBackgroundColour(This::wxGrid(), Colour::wx:colour(), Row::integer(),
Col::integer()) -> ok**

**setCellEditor(This::wxGrid(), Row::integer(), Col::integer(),
Editor::wxGridCellEditor() (see module wxGridCellEditor)) -> ok**

See [external documentation](#).

**setCellFont(This::wxGrid(), Row::integer(), Col::integer(), Val::wxFont()
(see module wxFont)) -> ok**

See [external documentation](#).

**setCellRenderer(This::wxGrid(), Row::integer(), Col::integer(),
Renderer::wxGridCellRenderer() (see module wxGridCellRenderer)) -> ok**

See [external documentation](#).

setCellTextColour(This::wxGrid(), Col::colour() (see module wx)) -> ok

See [external documentation](#).

**setCellTextColour(This::wxGrid(), X::integer() | term(), X::integer(),
X::term() | integer()) -> ok**

See [external documentation](#).

Alternatives:

**setCellTextColour(This::wxGrid(), Row::integer(), Col::integer(),
Val::wx:colour()) -> ok**

**setCellTextColour(This::wxGrid(), Val::wx:colour(), Row::integer(),
Col::integer()) -> ok**

**setCellValue(This::wxGrid(), Coords::{R::integer(), C::integer()},
S::string()) -> ok**

See [external documentation](#).

**setCellValue(This::wxGrid(), X::integer() | string(), X::integer(),
X::string() | integer()) -> ok**

See [external documentation](#).

Alternatives:

```
setCellValue(This::wxGrid(), Row::integer(), Col::integer(), S::string()) -> ok  
setCellValue(This::wxGrid(), Val::string(), Row::integer(), Col::integer()) -  
> ok
```

```
setColAttr(This::wxGrid(), Col::integer(), Attr::wxGridCellAttr() (see module  
wxGridCellAttr)) -> ok
```

See [external documentation](#).

```
setColFormatBool(This::wxGrid(), Col::integer()) -> ok
```

See [external documentation](#).

```
setColFormatNumber(This::wxGrid(), Col::integer()) -> ok
```

See [external documentation](#).

```
setColFormatFloat(This::wxGrid(), Col::integer()) -> ok
```

Equivalent to `setColFormatFloat(This, Col, [])`.

```
setColFormatFloat(This::wxGrid(), Col::integer(), Options::[Option]) -> ok
```

Types:

Option = {width, integer()} | {precision, integer()}

See [external documentation](#).

```
setColFormatCustom(This::wxGrid(), Col::integer(), TypeName::string()) -> ok
```

See [external documentation](#).

```
setColLabelAlignment(This::wxGrid(), Horiz::integer(), Vert::integer()) -> ok
```

See [external documentation](#).

```
setColLabelSize(This::wxGrid(), Height::integer()) -> ok
```

See [external documentation](#).

```
setColLabelValue(This::wxGrid(), Col::integer(), Val::string()) -> ok
```

See [external documentation](#).

```
setColMinimalWidth(This::wxGrid(), Col::integer(), Width::integer()) -> ok
```

See [external documentation](#).

```
setColMinimalAcceptableWidth(This::wxGrid(), Width::integer()) -> ok
```

See [external documentation](#).

```
setColSize(This::wxGrid(), Col::integer(), Width::integer()) -> ok
```

See [external documentation](#).

`setDefaultCellAlignment(This::wxGrid(), Horiz::integer(), Vert::integer()) -> ok`

See external documentation.

`setDefaultCellBackgroundColour(This::wxGrid(), Val::colour() (see module wx)) -> ok`

See external documentation.

`setDefaultCellFont(This::wxGrid(), Val::wxFont() (see module wxFont)) -> ok`

See external documentation.

`setDefaultCellTextColour(This::wxGrid(), Val::colour() (see module wx)) -> ok`

See external documentation.

`setDefaultEditor(This::wxGrid(), Editor::wxGridCellEditor() (see module wxGridCellEditor)) -> ok`

See external documentation.

`setDefaultRenderer(This::wxGrid(), Renderer::wxGridCellRenderer() (see module wxGridCellRenderer)) -> ok`

See external documentation.

`setDefaultColSize(This::wxGrid(), Width::integer()) -> ok`

Equivalent to `setDefaultColSize(This, Width, [])`.

`setDefaultColSize(This::wxGrid(), Width::integer(), Options::[Option]) -> ok`

Types:

Option = {resizeExistingCols, bool()}

See external documentation.

`setDefaultRowSize(This::wxGrid(), Height::integer()) -> ok`

Equivalent to `setDefaultRowSize(This, Height, [])`.

`setDefaultRowSize(This::wxGrid(), Height::integer(), Options::[Option]) -> ok`

Types:

Option = {resizeExistingRows, bool()}

See external documentation.

`setGridCursor(This::wxGrid(), Row::integer(), Col::integer()) -> ok`

See external documentation.

`setGridLineColour(This::wxGrid(), Val::colour() (see module wx)) -> ok`

See external documentation.

`setLabelBackgroundColour(This::wxGrid(), Val::colour() (see module wx)) -> ok`
See external documentation.

`setLabelFont(This::wxGrid(), Val::wxFont() (see module wxFont)) -> ok`
See external documentation.

`setLabelTextColour(This::wxGrid(), Val::colour() (see module wx)) -> ok`
See external documentation.

`setMargins(This::wxGrid(), ExtraWidth::integer(), ExtraHeight::integer()) -> ok`
See external documentation.

`setReadOnly(This::wxGrid(), Row::integer(), Col::integer()) -> ok`
Equivalent to `setReadOnly(This, Row, Col, [])`.

`setReadOnly(This::wxGrid(), Row::integer(), Col::integer(), Options::[Option]) -> ok`
Types:

Option = {isReadOnly, bool()}

See external documentation.

`setRowAttr(This::wxGrid(), Row::integer(), Attr::wxGridCellAttr() (see module wxGridCellAttr)) -> ok`
See external documentation.

`setRowLabelAlignment(This::wxGrid(), Horiz::integer(), Vert::integer()) -> ok`
See external documentation.

`setRowLabelSize(This::wxGrid(), Width::integer()) -> ok`
See external documentation.

`setRowLabelValue(This::wxGrid(), Row::integer(), Val::string()) -> ok`
See external documentation.

`setRowMinimalHeight(This::wxGrid(), Row::integer(), Width::integer()) -> ok`
See external documentation.

`setRowMinimalAcceptableHeight(This::wxGrid(), Width::integer()) -> ok`
See external documentation.

`setRowSize(This::wxGrid(), Row::integer(), Height::integer()) -> ok`
See external documentation.

setScrollLineX(This::wxGrid(), X::integer()) -> ok

See external documentation.

setScrollLineY(This::wxGrid(), Y::integer()) -> ok

See external documentation.

setSelectionBackground(This::wxGrid(), C::colour() (see module wx)) -> ok

See external documentation.

setSelectionForeground(This::wxGrid(), C::colour() (see module wx)) -> ok

See external documentation.

setSelectionMode(This::wxGrid(), Selmode::WxGridSelectionMode) -> ok

Types:

WxGridSelectionMode = integer()

See external documentation.

WxGridSelectionMode is one of ?wxGrid_wxGridSelectCells | ?wxGrid_wxGridSelectRows | ?wxGrid_wxGridSelectColumns

showCellEditControl(This::wxGrid()) -> ok

See external documentation.

xToCol(This::wxGrid(), X::integer()) -> integer()

Equivalent to *xToCol(This, X, [])*.

xToCol(This::wxGrid(), X::integer(), Options::[Option]) -> integer()

Types:

Option = {clipToMinMax, bool() }

See external documentation.

xToEdgeOfCol(This::wxGrid(), X::integer()) -> integer()

See external documentation.

yToEdgeOfRow(This::wxGrid(), Y::integer()) -> integer()

See external documentation.

yToRow(This::wxGrid(), Y::integer()) -> integer()

See external documentation.

destroy(This::wxGrid()) -> ok

Destroys this object, do not use object again

wxGridEvent

Erlang module

See external documentation: **wxGridEvent**.

Use *wxEvtHandler:connect/3* with EventType:

grid_cell_left_click, grid_cell_right_click, grid_cell_left_dclick, grid_cell_right_dclick, grid_label_left_click, grid_label_right_click, grid_label_left_dclick, grid_label_right_dclick, grid_row_size, grid_col_size, grid_range_select, grid_cell_change, grid_select_cell, grid_editor_shown, grid_editor_hidden, grid_editor_created, grid_cell_begin_drag

See also the message variant *#wxGrid{}* event record type.

This class is derived (and can use functions) from:

wxNotifyEvent

wxCommandEvent

wxEvent

DATA TYPES

wxGridEvent()

An object reference, The representation is internal and can be changed without notice. It can't be used for comparsion stored on disc or distributed for use on other nodes.

Exports

altDown(*This::wxGridEvent()*) -> *bool()*

See external documentation.

controlDown(*This::wxGridEvent()*) -> *bool()*

See external documentation.

getCol(*This::wxGridEvent()*) -> *integer()*

See external documentation.

getPosition(*This::wxGridEvent()*) -> *{X::integer(), Y::integer()}*

See external documentation.

getRow(*This::wxGridEvent()*) -> *integer()*

See external documentation.

metaDown(*This::wxGridEvent()*) -> *bool()*

See external documentation.

selecting(*This::wxGridEvent()*) -> *bool()*

See external documentation.

wxGridEvent

shiftDown(This::wxGridEvent()) -> bool()

See **external documentation**.

wxGridSizer

Erlang module

See external documentation: **wxGridSizer**.

This class is derived (and can use functions) from:
wxSizer

DATA TYPES

`wxGridSizer()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new(Cols::integer()) -> wxGridSizer()`

Equivalent to `new(Cols, [])`.

`new(Cols::integer(), Options::[Option]) -> wxGridSizer()`

Types:

`Option = {vgap, integer()} | {hgap, integer()}`

See external documentation.

`new(Rows::integer(), Cols::integer(), Vgap::integer(), Hgap::integer()) -> wxGridSizer()`

See external documentation.

`getCols(This::wxGridSizer()) -> integer()`

See external documentation.

`getHGap(This::wxGridSizer()) -> integer()`

See external documentation.

`getRows(This::wxGridSizer()) -> integer()`

See external documentation.

`getVGap(This::wxGridSizer()) -> integer()`

See external documentation.

`setCols(This::wxGridSizer(), Cols::integer()) -> ok`

See external documentation.

setHGap(This::wxGridSizer(), Gap::integer()) -> ok

See external documentation.

setRows(This::wxGridSizer(), Rows::integer()) -> ok

See external documentation.

setVGap(This::wxGridSizer(), Gap::integer()) -> ok

See external documentation.

destroy(This::wxGridSizer()) -> ok

Destroys this object, do not use object again

wxHelpEvent

Erlang module

See external documentation: **wxHelpEvent**.

Use *wxEvtHandler:connect/3* with EventType:

help, detailed_help

See also the message variant *#wxHelp{}* event record type.

This class is derived (and can use functions) from:
wxEvent

DATA TYPES

`wxHelpEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`getOrigin(This::wxHelpEvent()) -> Origin`

Types:

Origin = integer()

See external documentation.

Origin is one of ?wxHelpEvent_Origin_Unknown | ?wxHelpEvent_Origin_Keyboard | ?wxHelpEvent_Origin_HelpButton

`getPosition(This::wxHelpEvent()) -> {X::integer(), Y::integer()}`

See external documentation.

`setOrigin(This::wxHelpEvent(), Origin) -> ok`

Types:

Origin = integer()

See external documentation.

Origin is one of ?wxHelpEvent_Origin_Unknown | ?wxHelpEvent_Origin_Keyboard | ?wxHelpEvent_Origin_HelpButton

`setPosition(This::wxHelpEvent(), Pos::{X::integer(), Y::integer()}) -> ok`

See external documentation.

wxHtmlEasyPrinting

Erlang module

See external documentation: **wxHtmlEasyPrinting**.

DATA TYPES

`wxHtmlEasyPrinting()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparsion stored on disc or distributed for use on other nodes.

Exports

`new() -> wxHtmlEasyPrinting()`

Equivalent to `new([])`.

`new(Options::[Option]) -> wxHtmlEasyPrinting()`

Types:

Option = {name, string()} | {parentWindow, wxWindow()} (see module **wxWindow**)

See external documentation.

`getPrintData(This::wxHtmlEasyPrinting()) -> wxPrintData()` (see module **wxPrintData**)

See external documentation.

`getPageSetupData(This::wxHtmlEasyPrinting()) -> wxPageSetupDialogData()` (see module **wxPageSetupDialogData**)

See external documentation.

`previewFile(This::wxHtmlEasyPrinting(), Htmlfile::string()) -> bool()`

See external documentation.

`previewText(This::wxHtmlEasyPrinting(), Htmltext::string()) -> bool()`

Equivalent to `previewText(This, Htmltext, [])`.

`previewText(This::wxHtmlEasyPrinting(), Htmltext::string(), Options::[Option]) -> bool()`

Types:

Option = {basepath, string() }

See external documentation.

`printFile(This::wxHtmlEasyPrinting(), Htmlfile::string()) -> bool()`

See external documentation.

```
printText(This::wxHtmlEasyPrinting(), Htmltext::string()) -> bool()
```

Equivalent to *printText(This, Htmltext, [])*.

```
printText(This::wxHtmlEasyPrinting(), Htmltext::string(), Options::[Option])  
-> bool()
```

Types:

Option = {basepath, string()}

See [external documentation](#).

```
pageSetup(This::wxHtmlEasyPrinting()) -> ok
```

See [external documentation](#).

```
setFonts(This::wxHtmlEasyPrinting(), Normal_face::string(),  
Fixed_face::string()) -> ok
```

Equivalent to *setFonts(This, Normal_face, Fixed_face, [])*.

```
setFonts(This::wxHtmlEasyPrinting(), Normal_face::string(),  
Fixed_face::string(), Options::[Option]) -> ok
```

Types:

Option = {sizes, [integer()]}

See [external documentation](#).

```
setHeader(This::wxHtmlEasyPrinting(), Header::string()) -> ok
```

Equivalent to *setHeader(This, Header, [])*.

```
setHeader(This::wxHtmlEasyPrinting(), Header::string(), Options::[Option]) ->  
ok
```

Types:

Option = {pg, integer()}

See [external documentation](#).

```
setFooter(This::wxHtmlEasyPrinting(), Footer::string()) -> ok
```

Equivalent to *setFooter(This, Footer, [])*.

```
setFooter(This::wxHtmlEasyPrinting(), Footer::string(), Options::[Option]) ->  
ok
```

Types:

Option = {pg, integer()}

See [external documentation](#).

```
destroy(This::wxHtmlEasyPrinting()) -> ok
```

Destroys this object, do not use object again

wxHtmlLinkEvent

Erlang module

See external documentation: **wxHtmlLinkEvent**.

Use *wxEvtHandler:connect/3* with EventType:

command_html_link_clicked

See also the message variant *#wxHtmlLink{}* event record type.

This class is derived (and can use functions) from:

wxCommandEvent

wxEvent

DATA TYPES

wxHtmlLinkEvent()

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

getLinkInfo(This::wxHtmlLinkEvent()) -> wxHtmlLinkInfo() (see module **wx**)

See **external documentation**.

wxHtmlWindow

Erlang module

See external documentation: **wxHtmlWindow**.

This class is derived (and can use functions) from:

wxScrolledWindow

wxPanel

wxWindow

wxEvtHandler

DATA TYPES

`wxHtmlWindow()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxHtmlWindow()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow)) -> wxHtmlWindow()`

Equivalent to `new(Parent, [])`.

`new(Parent::wxWindow() (see module wxWindow), Options::[Option]) -> wxHtmlWindow()`

Types:

Option = {id, integer()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`appendToPage(This::wxHtmlWindow(), Source::string()) -> bool()`

See external documentation.

`getOpenedAnchor(This::wxHtmlWindow()) -> string()`

See external documentation.

`getOpenedPage(This::wxHtmlWindow()) -> string()`

See external documentation.

`getOpenedPageTitle(This::wxHtmlWindow()) -> string()`

See external documentation.

`getRelatedFrame(This::wxHtmlWindow()) -> wxFrame()` (see module `wxFrame`)

See external documentation.

`historyBack(This::wxHtmlWindow()) -> bool()`

See external documentation.

`historyCanBack(This::wxHtmlWindow()) -> bool()`

See external documentation.

`historyCanForward(This::wxHtmlWindow()) -> bool()`

See external documentation.

`historyClear(This::wxHtmlWindow()) -> ok`

See external documentation.

`historyForward(This::wxHtmlWindow()) -> bool()`

See external documentation.

`loadFile(This::wxHtmlWindow(), Filename::string()) -> bool()`

See external documentation.

`loadPage(This::wxHtmlWindow(), Location::string()) -> bool()`

See external documentation.

`selectAll(This::wxHtmlWindow()) -> ok`

See external documentation.

`selectionToText(This::wxHtmlWindow()) -> string()`

See external documentation.

`selectLine(This::wxHtmlWindow(), Pos::{X::integer(), Y::integer()}) -> ok`

See external documentation.

`selectWord(This::wxHtmlWindow(), Pos::{X::integer(), Y::integer()}) -> ok`

See external documentation.

`setBorders(This::wxHtmlWindow(), B::integer()) -> ok`

See external documentation.

`setFonts(This::wxHtmlWindow(), Normal_face::string(), Fixed_face::string()) -> ok`

Equivalent to `setFonts(This, Normal_face, Fixed_face, [])`.

```
setFont(This::wxHtmlWindow(), Normal_face::string(), Fixed_face::string(),  
Options::[Option]) -> ok
```

Types:

Option = {**sizes**, **integer()**}

See external documentation.

```
setPage(This::wxHtmlWindow(), Source::string()) -> bool()
```

See external documentation.

```
setRelatedFrame(This::wxHtmlWindow(), Frame::wxFrame() (see module wxFrame),  
Format::string()) -> ok
```

See external documentation.

```
setRelatedStatusBar(This::wxHtmlWindow(), Bar::integer()) -> ok
```

See external documentation.

```
toText(This::wxHtmlWindow()) -> string()
```

See external documentation.

```
destroy(This::wxHtmlWindow()) -> ok
```

Destroys this object, do not use object again

wxIconBundle

Erlang module

See external documentation: **wxIconBundle**.

DATA TYPES

`wxIconBundle()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxIconBundle()`

See external documentation.

`new(Ic::wxIconBundle() | wxIcon() (see module wxIcon)) -> wxIconBundle()`

See external documentation.

`new(File::string(), Type::integer()) -> wxIconBundle()`

See external documentation.

`addIcon(This::wxIconBundle(), Icon::wxIcon() (see module wxIcon)) -> ok`

See external documentation.

`addIcon(This::wxIconBundle(), File::string(), Type::integer()) -> ok`

See external documentation.

`getIcon(This::wxIconBundle()) -> wxIcon() (see module wxIcon)`

Equivalent to `getIcon(This, [])`.

`getIcon(This::wxIconBundle(), X::term()) -> wxIcon() (see module wxIcon)`

See external documentation.

Alternatives:

`getIcon(This::wxIconBundle(), [Option]) -> wxIcon:wxIcon()`

Option = {size, integer()}

`getIcon(This::wxIconBundle(), Size::{W::integer(),H::integer()}) -> wxIcon:wxIcon()`

`destroy(This::wxIconBundle()) -> ok`

Destroys this object, do not use object again

wxIcon

Erlang module

See external documentation: **wxIcon**.

This class is derived (and can use functions) from:

wxBitmap

DATA TYPES

`wxIcon()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxIcon()`

See external documentation.

`new(X::string() | term()) -> wxIcon()`

See external documentation.

Alternatives:

`new(Filename::string()) -> new(Filename, [])`

`new(Loc::wx:wx()) -> wxIcon()`

`new(Filename::string(), Options::[Option]) -> wxIcon()`

Types:

Option = {type, WxBitmapType} | {desiredWidth, integer()} | {desiredHeight, integer()}

WxBitmapType = integer()

See external documentation.

WxBitmapType is one of ?wxBITMAP_TYPE_INVALID | ?wxBITMAP_TYPE_BMP | ?wxBITMAP_TYPE_BMP_RESOURCE | ?wxBITMAP_TYPE_RESOURCE | ?wxBITMAP_TYPE_ICO | ?wxBITMAP_TYPE_ICO_RESOURCE | ?wxBITMAP_TYPE_CUR | ?wxBITMAP_TYPE_CUR_RESOURCE | ?wxBITMAP_TYPE_XBM | ?wxBITMAP_TYPE_XBM_DATA | ?wxBITMAP_TYPE_XPM | ?wxBITMAP_TYPE_XPM_DATA | ?wxBITMAP_TYPE_TIF | ?wxBITMAP_TYPE_TIF_RESOURCE | ?wxBITMAP_TYPE_GIF | ?wxBITMAP_TYPE_GIF_RESOURCE | ?wxBITMAP_TYPE_PNG | ?wxBITMAP_TYPE_PNG_RESOURCE | ?wxBITMAP_TYPE_JPEG | ?wxBITMAP_TYPE_JPEG_RESOURCE | ?wxBITMAP_TYPE_PNM | ?wxBITMAP_TYPE_PNM_RESOURCE | ?wxBITMAP_TYPE_PCX | ?wxBITMAP_TYPE_PCX_RESOURCE | ?wxBITMAP_TYPE_PICT | ?wxBITMAP_TYPE_PICT_RESOURCE | ?wxBITMAP_TYPE_ICON | ?wxBITMAP_TYPE_ICON_RESOURCE | ?wxBITMAP_TYPE_ANI | ?wxBITMAP_TYPE_IFF | ?wxBITMAP_TYPE_TGA | ?wxBITMAP_TYPE_MACCURSOR | ?wxBITMAP_TYPE_MACCURSOR_RESOURCE | ?wxBITMAP_TYPE_ANY

`copyFromBitmap(This::wxIcon(), Bmp::wxBitmap() (see module wxBitmap)) -> ok`

See external documentation.

wxIcon

`destroy(This::wxIcon()) -> ok`

Destroys this object, do not use object again

wxIconizeEvent

Erlang module

See external documentation: **wxIconizeEvent**.

Use *wxEvtHandler:connect/3* with EventType:

iconize

See also the message variant *#wxIconize{}* event record type.

This class is derived (and can use functions) from:

wxEvent

DATA TYPES

`wxIconizeEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`iconized(This::wxIconizeEvent()) -> bool()`

See **external documentation**.

wxIdleEvent

Erlang module

See external documentation: **wxIdleEvent**.

Use *wxEvtHandler:connect/3* with EventType:

idle

See also the message variant *#wxIdle{}* event record type.

This class is derived (and can use functions) from:

wxEvent

DATA TYPES

`wxIdleEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparsion stored on disc or distributed for use on other nodes.

Exports

`canSend(Win::wxWindow() (see module wxWindow)) -> bool()`

See external documentation.

`getMode() -> WxIdleMode`

Types:

WxIdleMode = integer()

See external documentation.

WxIdleMode is one of ?wxIDLE_PROCESS_ALL | ?wxIDLE_PROCESS_SPECIFIED

`requestMore(This::wxIdleEvent()) -> ok`

Equivalent to *requestMore(This, [])*.

`requestMore(This::wxIdleEvent(), Options::[Option]) -> ok`

Types:

Option = {needMore, bool()}

See external documentation.

`moreRequested(This::wxIdleEvent()) -> bool()`

See external documentation.

`setMode(Mode::WxIdleMode) -> ok`

Types:

WxIdleMode = integer()

See external documentation.

WxIdleMode is one of ?wxIDLE_PROCESS_ALL | ?wxIDLE_PROCESS_SPECIFIED

wxImage

Erlang module

See external documentation: **wxImage**.

All (default) image handlers are initialized.

DATA TYPES

`wxImage()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxImage()`

See external documentation.

`new(Name::string()) -> wxImage()`

Equivalent to `new(Name, [])`.

`new(X::integer() | string(), X::integer() | term()) -> wxImage()`

See external documentation.

Alternatives:

`new(Width::integer(), Height::integer()) -> new(Width, Height, [])`

`new(Name::string(), [Option]) -> wxImage()`

Option = {type, integer()} | {index, integer()}

`new(X::integer() | string(), X::integer() | string(), X::binary() | term()) -> wxImage()`

See external documentation.

Alternatives:

`new(Width::integer(), Height::integer(), Data::binary()) -> new(Width, Height, Data, [])`

`new(Width::integer(), Height::integer(), [Option]) -> wxImage()`

Option = {clear, bool()}

`new(Name::string(), Mimetype::string(), [Option]) -> wxImage()`

Option = {index, integer()}

`new(Width::integer(), Height::integer(), Data::binary(), X::binary() | term()) -> wxImage()`

See external documentation.

Alternatives:

wxImage

```
new(Width::integer(), Height::integer(), Data::binary(), Alpha::binary()) ->
new(Width,Height,Data,Alpha, [])
```

```
new(Width::integer(), Height::integer(), Data::binary(), [Option]) -> wxImage()
Option = {static_data, bool()}
```

```
new(Width::integer(), Height::integer(), Data::binary(), Alpha::binary(),
Options::[Option]) -> wxImage()
```

Types:

Option = {static_data, bool()}

See [external documentation](#).

```
blur(This::wxImage(), Radius::integer()) -> wxImage()
```

See [external documentation](#).

```
blurHorizontal(This::wxImage(), Radius::integer()) -> wxImage()
```

See [external documentation](#).

```
blurVertical(This::wxImage(), Radius::integer()) -> wxImage()
```

See [external documentation](#).

```
convertAlphaToMask(This::wxImage()) -> bool()
```

Equivalent to *convertAlphaToMask(This, [])*.

```
convertAlphaToMask(This::wxImage(), Options::[Option]) -> bool()
```

Types:

Option = {threshold, integer()}

See [external documentation](#).

```
convertToGreyscale(This::wxImage()) -> wxImage()
```

Equivalent to *convertToGreyscale(This, [])*.

```
convertToGreyscale(This::wxImage(), Options::[Option]) -> wxImage()
```

Types:

Option = {lr, float()} | {lg, float()} | {lb, float()}

See [external documentation](#).

```
convertToMono(This::wxImage(), R::integer(), G::integer(), B::integer()) ->
wxImage()
```

See [external documentation](#).

```
copy(This::wxImage()) -> wxImage()
```

See [external documentation](#).

```
create(This::wxImage(), Width::integer(), Height::integer()) -> bool()
```

Equivalent to *create(This, Width, Height, [])*.

```
create(This::wxImage(), Width::integer(), Height::integer(), X::binary() |  
term()) -> bool()
```

See **external documentation**.

Alternatives:

```
create(This::wxImage(), Width::integer(), Height::integer(), Data::binary()) -  
> create(This, Width, Height, Data, [])
```

```
create(This::wxImage(), Width::integer(), Height::integer(), [Option]) ->  
bool()
```

Option = {clear, bool()}

```
create(This::wxImage(), Width::integer(), Height::integer(), Data::binary(),  
X::binary() | term()) -> bool()
```

See **external documentation**.

Alternatives:

```
create(This::wxImage(), Width::integer(), Height::integer(), Data::binary(),  
Alpha::binary()) -> create(This, Width, Height, Data, Alpha, [])
```

```
create(This::wxImage(), Width::integer(), Height::integer(), Data::binary(),  
[Option]) -> bool()
```

Option = {static_data, bool()}

```
create(This::wxImage(), Width::integer(), Height::integer(), Data::binary(),  
Alpha::binary(), Options::[Option]) -> bool()
```

Types:

Option = {static_data, bool()}

See **external documentation**.

```
Destroy(This::wxImage()) -> ok
```

See **external documentation**.

```
findFirstUnusedColour(This::wxImage()) -> {bool(), R::integer(),  
G::integer(), B::integer()}
```

Equivalent to *findFirstUnusedColour(This, [])*.

```
findFirstUnusedColour(This::wxImage(), Options::[Option]) -> {bool(),  
R::integer(), G::integer(), B::integer()}
```

Types:

Option = {startR, integer()} | {startG, integer()} | {startB, integer()}

See **external documentation**.

```
getImageExtWildcard() -> string()
```

See **external documentation**.

`getAlpha(This::wxImage()) -> binary()`

See external documentation.

`getAlpha(This::wxImage(), X::integer(), Y::integer()) -> integer()`

See external documentation.

`getBlue(This::wxImage(), X::integer(), Y::integer()) -> integer()`

See external documentation.

`getData(This::wxImage()) -> binary()`

See external documentation.

`getGreen(This::wxImage(), X::integer(), Y::integer()) -> integer()`

See external documentation.

`getImageCount(Name::string()) -> integer()`

Equivalent to `getImageCount(Name, [])`.

`getImageCount(Name::string(), Options::[Option]) -> integer()`

Types:

Option = {type, integer()}

See external documentation.

`getHeight(This::wxImage()) -> integer()`

See external documentation.

`getMaskBlue(This::wxImage()) -> integer()`

See external documentation.

`getMaskGreen(This::wxImage()) -> integer()`

See external documentation.

`getMaskRed(This::wxImage()) -> integer()`

See external documentation.

`getOrFindMaskColour(This::wxImage()) -> {bool(), R::integer(), G::integer(), B::integer()}`

See external documentation.

`getPalette(This::wxImage()) -> wxPalette()` (see module `wxPalette`)

See external documentation.

`getRed(This::wxImage(), X::integer(), Y::integer()) -> integer()`

See external documentation.

`getSubImage(This::wxImage(), Rect::{X::integer(), Y::integer(), W::integer(), H::integer()}) -> wxImage()`

See external documentation.

`getWidth(This::wxImage()) -> integer()`

See external documentation.

`hasAlpha(This::wxImage()) -> bool()`

See external documentation.

`hasMask(This::wxImage()) -> bool()`

See external documentation.

`getOption(This::wxImage(), Name::string()) -> string()`

See external documentation.

`getOptionInt(This::wxImage(), Name::string()) -> integer()`

See external documentation.

`hasOption(This::wxImage(), Name::string()) -> bool()`

See external documentation.

`initAlpha(This::wxImage()) -> ok`

See external documentation.

`initStandardHandlers() -> ok`

See external documentation.

`isTransparent(This::wxImage(), X::integer(), Y::integer()) -> bool()`

Equivalent to *isTransparent(This, X, Y, [])*.

`isTransparent(This::wxImage(), X::integer(), Y::integer(), Options::[Option])
-> bool()`

Types:

Option = {threshold, integer()}

See external documentation.

`loadFile(This::wxImage(), Name::string()) -> bool()`

Equivalent to *loadFile(This, Name, [])*.

```
loadFile(This::wxImage(), Name::string(), Options::[Option]) -> bool()
```

Types:

Option = {type, integer()} | {index, integer()}

See external documentation.

```
loadFile(This::wxImage(), Name::string(), Mimetype::string(), Options::  
[Option]) -> bool()
```

Types:

Option = {index, integer()}

See external documentation.

```
ok(This::wxImage()) -> bool()
```

See external documentation.

```
removeHandler(Name::string()) -> bool()
```

See external documentation.

```
mirror(This::wxImage()) -> wxImage()
```

Equivalent to *mirror(This, [])*.

```
mirror(This::wxImage(), Options::[Option]) -> wxImage()
```

Types:

Option = {horizontally, bool()}

See external documentation.

```
replace(This::wxImage(), R1::integer(), G1::integer(), B1::integer(),  
R2::integer(), G2::integer(), B2::integer()) -> ok
```

See external documentation.

```
rescale(This::wxImage(), Width::integer(), Height::integer()) -> wxImage()
```

Equivalent to *rescale(This, Width, Height, [])*.

```
rescale(This::wxImage(), Width::integer(), Height::integer(), Options::  
[Option]) -> wxImage()
```

Types:

Option = {quality, integer()}

See external documentation.

```
resize(This::wxImage(), Size::{W::integer(), H::integer()}, Pos::  
{X::integer(), Y::integer()}) -> wxImage()
```

Equivalent to *resize(This, Size, Pos, [])*.

```
resize(This::wxImage(), Size::{W::integer(), H::integer()}, Pos::{X::integer(), Y::integer()}, Options::[Option]) -> wxImage()
```

Types:

Option = {r, integer()} | {g, integer()} | {b, integer()}

See external documentation.

```
rotate(This::wxImage(), Angle::float(), Centre_of_rotation::{X::integer(), Y::integer()}) -> wxImage()
```

Equivalent to *rotate(This, Angle, Centre_of_rotation, [])*.

```
rotate(This::wxImage(), Angle::float(), Centre_of_rotation::{X::integer(), Y::integer()}, Options::[Option]) -> wxImage()
```

Types:

Option = {interpolating, bool()} | {offset_after_rotation, {X::integer(), Y::integer()}}

See external documentation.

```
rotateHue(This::wxImage(), Angle::float()) -> ok
```

See external documentation.

```
rotate90(This::wxImage()) -> wxImage()
```

Equivalent to *rotate90(This, [])*.

```
rotate90(This::wxImage(), Options::[Option]) -> wxImage()
```

Types:

Option = {clockwise, bool()}

See external documentation.

```
saveFile(This::wxImage(), Name::string()) -> bool()
```

See external documentation.

```
saveFile(This::wxImage(), Name::string(), X::integer() | string()) -> bool()
```

See external documentation.

Alternatives:

```
saveFile(This::wxImage(), Name::string(), Type::integer()) -> bool()
```

```
saveFile(This::wxImage(), Name::string(), Mimetype::string()) -> bool()
```

```
scale(This::wxImage(), Width::integer(), Height::integer()) -> wxImage()
```

Equivalent to *scale(This, Width, Height, [])*.

```
scale(This::wxImage(), Width::integer(), Height::integer(), Options::[Option]) -> wxImage()
```

Types:

Option = {quality, integer()}

See [external documentation](#).

```
size(This::wxImage(), Size::{W::integer(), H::integer()}, Pos::{X::integer(), Y::integer()}) -> wxImage()
```

Equivalent to *size(This, Size, Pos, [])*.

```
size(This::wxImage(), Size::{W::integer(), H::integer()}, Pos::{X::integer(), Y::integer()}, Options::[Option]) -> wxImage()
```

Types:

Option = {r, integer()} | {g, integer()} | {b, integer()}

See [external documentation](#).

```
setAlpha(This::wxImage(), Alpha::binary()) -> ok
```

Equivalent to *setAlpha(This, Alpha, [])*.

```
setAlpha(This::wxImage(), Alpha::binary(), Options::[Option]) -> ok
```

Types:

Option = {static_data, bool()}

See [external documentation](#).

```
setAlpha(This::wxImage(), X::integer(), Y::integer(), Alpha::integer()) -> ok
```

See [external documentation](#).

```
setData(This::wxImage(), Data::binary()) -> ok
```

Equivalent to *setData(This, Data, [])*.

```
setData(This::wxImage(), Data::binary(), Options::[Option]) -> ok
```

Types:

Option = {static_data, bool()}

See [external documentation](#).

```
setData(This::wxImage(), Data::binary(), New_width::integer(), New_height::integer()) -> ok
```

Equivalent to *setData(This, Data, New_width, New_height, [])*.

```
setData(This::wxImage(), Data::binary(), New_width::integer(), New_height::integer(), Options::[Option]) -> ok
```

Types:

Option = {static_data, bool()}

See [external documentation](#).

```
setMask(This::wxImage()) -> ok
```

Equivalent to *setMask(This, [])*.

setMask(This::wxImage(), Options::[Option]) -> ok

Types:

Option = {mask, bool()}

See external documentation.

setMaskColour(This::wxImage(), R::integer(), G::integer(), B::integer()) -> ok

See external documentation.

setMaskFromImage(This::wxImage(), Mask::wxImage(), Mr::integer(), Mg::integer(), Mb::integer()) -> bool()

See external documentation.

setOption(This::wxImage(), Name::string(), X::integer() | string()) -> ok

See external documentation.

Alternatives:

setOption(This::wxImage(), Name::string(), Value::integer()) -> ok

setOption(This::wxImage(), Name::string(), Value::string()) -> ok

setPalette(This::wxImage(), Palette::wxPalette() (see module wxPalette)) -> ok

See external documentation.

setRGB(This::wxImage(), Rect::{X::integer(), Y::integer(), W::integer(), H::integer()}, R::integer(), G::integer(), B::integer()) -> ok

See external documentation.

setRGB(This::wxImage(), X::integer(), Y::integer(), R::integer(), G::integer(), B::integer()) -> ok

See external documentation.

destroy(This::wxImage()) -> ok

Destroys this object, do not use object again

wxImageList

Erlang module

See external documentation: **wxImageList**.

DATA TYPES

`wxImageList()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxImageList()`

See external documentation.

`new(Width::integer(), Height::integer()) -> wxImageList()`

Equivalent to `new(Width, Height, [])`.

`new(Width::integer(), Height::integer(), Options::[Option]) -> wxImageList()`

Types:

Option = {mask, bool()} | {initialCount, integer()}

See external documentation.

`add(This::wxImageList(), Bitmap::wxBitmap() (see module wxBitmap)) -> integer()`

See external documentation.

`add(This::wxImageList(), Bitmap::wxBitmap() (see module wxBitmap), X::term()) -> integer()`

See external documentation.

Alternatives:

`add(This::wxImageList(), Bitmap::wxBitmap:wxBitmap(), Mask::wxBitmap:wxBitmap()) -> integer()`

`add(This::wxImageList(), Bitmap::wxBitmap:wxBitmap(), MaskColour::wx:colour()) -> integer()`

`create(This::wxImageList(), Width::integer(), Height::integer()) -> bool()`

Equivalent to `create(This, Width, Height, [])`.

`create(This::wxImageList(), Width::integer(), Height::integer(), Options::[Option]) -> bool()`

Types:

Option = {mask, bool()} | {initialCount, integer()}

See [external documentation](#).

```
draw(This::wxImageList(), Index::integer(), Dc::wxDC() (see module wxDC),  
X::integer(), Y::integer()) -> bool()
```

Equivalent to *draw(This, Index, Dc, X, Y, [])*.

```
draw(This::wxImageList(), Index::integer(), Dc::wxDC() (see module wxDC),  
X::integer(), Y::integer(), Options::[Option]) -> bool()
```

Types:

Option = {flags, integer()} | {solidBackground, bool()}

See [external documentation](#).

```
getBitmap(This::wxImageList(), Index::integer()) -> wxBitmap() (see module  
wxBitmap)
```

See [external documentation](#).

```
getIcon(This::wxImageList(), Index::integer()) -> wxIcon() (see module  
wxIcon)
```

See [external documentation](#).

```
getImageCount(This::wxImageList()) -> integer()
```

See [external documentation](#).

```
getSize(This::wxImageList(), Index::integer()) -> {bool(), Width::integer(),  
Height::integer()}
```

See [external documentation](#).

```
remove(This::wxImageList(), Index::integer()) -> bool()
```

See [external documentation](#).

```
removeAll(This::wxImageList()) -> bool()
```

See [external documentation](#).

```
replace(This::wxImageList(), Index::integer(), Bitmap::wxBitmap() (see module  
wxBitmap)) -> bool()
```

See [external documentation](#).

```
replace(This::wxImageList(), Index::integer(), Bitmap::wxBitmap() (see module  
wxBitmap), Mask::wxBitmap() (see module wxBitmap)) -> bool()
```

See [external documentation](#).

```
destroy(This::wxImageList()) -> ok
```

Destroys this object, do not use object again

wxJoystickEvent

Erlang module

See external documentation: **wxJoystickEvent**.

Use *wxEvtHandler:connect/3* with EventType:

joy_button_down, joy_button_up, joy_move, joy_zmove

See also the message variant *#wxJoystick{}* event record type.

This class is derived (and can use functions) from:

wxEvent

DATA TYPES

`wxJoystickEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparsion stored on disc or distributed for use on other nodes.

Exports

`buttonDown(This::wxJoystickEvent()) -> bool()`

Equivalent to *buttonDown(This, [])*.

`buttonDown(This::wxJoystickEvent(), Options::[Option]) -> bool()`

Types:

Option = {but, integer()}

See external documentation.

`buttonIsDown(This::wxJoystickEvent()) -> bool()`

Equivalent to *buttonIsDown(This, [])*.

`buttonIsDown(This::wxJoystickEvent(), Options::[Option]) -> bool()`

Types:

Option = {but, integer()}

See external documentation.

`buttonUp(This::wxJoystickEvent()) -> bool()`

Equivalent to *buttonUp(This, [])*.

`buttonUp(This::wxJoystickEvent(), Options::[Option]) -> bool()`

Types:

Option = {but, integer()}

See external documentation.

`getButtonChange(This::wxJoystickEvent()) -> integer()`

See external documentation.

`getButtonState(This::wxJoystickEvent()) -> integer()`

See external documentation.

`getJoystick(This::wxJoystickEvent()) -> integer()`

See external documentation.

`getPosition(This::wxJoystickEvent()) -> {X::integer(), Y::integer()}`

See external documentation.

`getZPosition(This::wxJoystickEvent()) -> integer()`

See external documentation.

`isButton(This::wxJoystickEvent()) -> bool()`

See external documentation.

`isMove(This::wxJoystickEvent()) -> bool()`

See external documentation.

`isZMove(This::wxJoystickEvent()) -> bool()`

See external documentation.

wxKeyEvent

Erlang module

See external documentation: **wxKeyEvent**.

Use *wxEvtHandler:connect/3* with EventType:

char, char_hook, key_down, key_up

See also the message variant *#wxKey{}* event record type.

This class is derived (and can use functions) from:

wxEvent

DATA TYPES

`wxKeyEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparsion stored on disc or distributed for use on other nodes.

Exports

`altDown(This::wxKeyEvent()) -> bool()`

See external documentation.

`cmdDown(This::wxKeyEvent()) -> bool()`

See external documentation.

`controlDown(This::wxKeyEvent()) -> bool()`

See external documentation.

`getKeyCode(This::wxKeyEvent()) -> integer()`

See external documentation.

`getModifiers(This::wxKeyEvent()) -> integer()`

See external documentation.

`getPosition(This::wxKeyEvent()) -> {X::integer(), Y::integer()}`

See external documentation.

`getRawKeyCode(This::wxKeyEvent()) -> integer()`

See external documentation.

`getRawKeyFlags(This::wxKeyEvent()) -> integer()`

See external documentation.

getUnicodeKey(This::wxKeyEvent()) -> integer()

See external documentation.

getX(This::wxKeyEvent()) -> integer()

See external documentation.

getY(This::wxKeyEvent()) -> integer()

See external documentation.

hasModifiers(This::wxKeyEvent()) -> bool()

See external documentation.

metaDown(This::wxKeyEvent()) -> bool()

See external documentation.

shiftDown(This::wxKeyEvent()) -> bool()

See external documentation.

wxLayoutAlgorithm

Erlang module

See external documentation: **wxLayoutAlgorithm**.

DATA TYPES

`wxLayoutAlgorithm()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxLayoutAlgorithm()`

See external documentation.

`layoutFrame(This::wxLayoutAlgorithm(), Frame::wxFrame() (see module wxFrame)) -> bool()`

Equivalent to `layoutFrame(This, Frame, [])`.

`layoutFrame(This::wxLayoutAlgorithm(), Frame::wxFrame() (see module wxFrame), Options::[Option]) -> bool()`

Types:

Option = {mainWindow, wxWindow() (see module wxWindow)}

See external documentation.

`layoutMDIFrame(This::wxLayoutAlgorithm(), Frame::wxMDIParentFrame() (see module wxMDIParentFrame)) -> bool()`

Equivalent to `layoutMDIFrame(This, Frame, [])`.

`layoutMDIFrame(This::wxLayoutAlgorithm(), Frame::wxMDIParentFrame() (see module wxMDIParentFrame), Options::[Option]) -> bool()`

Types:

Option = {rect, {X::integer(), Y::integer(), W::integer(), H::integer()}}

See external documentation.

`layoutWindow(This::wxLayoutAlgorithm(), Frame::wxWindow() (see module wxWindow)) -> bool()`

Equivalent to `layoutWindow(This, Frame, [])`.

`layoutWindow(This::wxLayoutAlgorithm(), Frame::wxWindow() (see module wxWindow), Options::[Option]) -> bool()`

Types:

Option = {mainWindow, wxWindow() (see module wxWindow)}

See **external documentation**.

destroy(This::wxLayoutAlgorithm()) -> ok

Destroys this object, do not use object again

wxListbook

Erlang module

See external documentation: **wxListbook**.

This class is derived (and can use functions) from:

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxListbook()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxListbook()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Id::integer()) -> wxListbook()`

Equivalent to `new(Parent, Id, [])`.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Options::[Option]) -> wxListbook()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`addPage(This::wxListbook(), Page::wxWindow() (see module wxWindow), Text::string()) -> bool()`

Equivalent to `addPage(This, Page, Text, [])`.

`addPage(This::wxListbook(), Page::wxWindow() (see module wxWindow), Text::string(), Options::[Option]) -> bool()`

Types:

Option = {bSelect, bool()} | {imageId, integer()}

See external documentation.

`advanceSelection(This::wxListbook()) -> ok`

Equivalent to `advanceSelection(This, [])`.

`advanceSelection(This::wxListbook(), Options::[Option]) -> ok`

Types:

Option = {forward, bool()}

See external documentation.

assignImageList(This::wxListbook(), ImageList::wxImageList() (see module wxImageList)) -> ok

See external documentation.

create(This::wxListbook(), Parent::wxWindow() (see module wxWindow), Id::integer()) -> bool()

Equivalent to *create(This, Parent, Id, [])*.

create(This::wxListbook(), Parent::wxWindow() (see module wxWindow), Id::integer(), Options::[Option]) -> bool()

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

deleteAllPages(This::wxListbook()) -> bool()

See external documentation.

deletePage(This::wxListbook(), N::integer()) -> bool()

See external documentation.

removePage(This::wxListbook(), N::integer()) -> bool()

See external documentation.

getCurrentPage(This::wxListbook()) -> wxWindow() (see module wxWindow)

See external documentation.

getImageList(This::wxListbook()) -> wxImageList() (see module wxImageList)

See external documentation.

getPage(This::wxListbook(), N::integer()) -> wxWindow() (see module wxWindow)

See external documentation.

getPageCount(This::wxListbook()) -> integer()

See external documentation.

getPageImage(This::wxListbook(), N::integer()) -> integer()

See external documentation.

getPageText(This::wxListbook(), N::integer()) -> string()

See external documentation.

`getSelection(This::wxListbook()) -> integer()`

See external documentation.

`hitTest(This::wxListbook(), Pt::{X::integer(), Y::integer()}) -> {integer(),
Flags::integer()}`

See external documentation.

`insertPage(This::wxListbook(), N::integer(), Page::wxWindow() (see module
wxWindow), Text::string()) -> bool()`

Equivalent to *insertPage(This, N, Page, Text, [])*.

`insertPage(This::wxListbook(), N::integer(), Page::wxWindow() (see module
wxWindow), Text::string(), Options::[Option]) -> bool()`

Types:

`Option = {bSelect, bool()} | {imageId, integer()}`

See external documentation.

`setImageList(This::wxListbook(), ImageList::wxImageList() (see module
wxImageList)) -> ok`

See external documentation.

`setPageSize(This::wxListbook(), Size::{W::integer(), H::integer()}) -> ok`

See external documentation.

`setPageImage(This::wxListbook(), N::integer(), ImageId::integer()) -> bool()`

See external documentation.

`setPageText(This::wxListbook(), N::integer(), StrText::string()) -> bool()`

See external documentation.

`setSelection(This::wxListbook(), N::integer()) -> integer()`

See external documentation.

`changeSelection(This::wxListbook(), N::integer()) -> integer()`

See external documentation.

`destroy(This::wxListbook()) -> ok`

Destroys this object, do not use object again

wxListBox

Erlang module

See external documentation: **wxListBox**.

This class is derived (and can use functions) from:

wxControlWithItems

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxListBox()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxListBox()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Id::integer()) -> wxListBox()`

Equivalent to `new(Parent, Id, [])`.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Options::[Option]) -> wxListBox()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {choices, [[string()]]} | {style, integer()} | {validator, wx() (see module wx)}

See external documentation.

`create(This::wxListBox(), Parent::wxWindow() (see module wxWindow), Id::integer(), Pos::{X::integer(), Y::integer()}, Size::{W::integer(), H::integer()}, Choices::[[string()]]) -> bool()`

Equivalent to `create(This, Parent, Id, Pos, Size, Choices, [])`.

`create(This::wxListBox(), Parent::wxWindow() (see module wxWindow), Id::integer(), Pos::{X::integer(), Y::integer()}, Size::{W::integer(), H::integer()}, Choices::[[string()]], Options::[Option]) -> bool()`

Types:

Option = {style, integer()} | {validator, wx() (see module wx)}

See external documentation.

deselect(This::wxListBox(), N::integer()) -> ok

See external documentation.

getSelections(This::wxListBox()) -> {integer(), ASelections::[integer()]}

See external documentation.

insertItems(This::wxListBox(), Items::[[string()]], Pos::integer()) -> ok

See external documentation.

isSelected(This::wxListBox(), N::integer()) -> bool()

See external documentation.

set(This::wxListBox(), Items::[[string()]]) -> ok

See external documentation.

hitTest(This::wxListBox(), Point::{X::integer(), Y::integer()}) -> integer()

See external documentation.

setFirstItem(This::wxListBox(), X::integer() | string()) -> ok

See external documentation.

Alternatives:

setFirstItem(This::wxListBox(), N::integer()) -> ok

setFirstItem(This::wxListBox(), S::string()) -> ok

destroy(This::wxListBox()) -> ok

Destroys this object, do not use object again

wxListCtrl

Erlang module

See external documentation: **wxListCtrl**.

This class is derived (and can use functions) from:

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxListCtrl()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxListCtrl()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow)) -> wxListCtrl()`

Equivalent to `new(Parent, [])`.

`new(Parent::wxWindow() (see module wxWindow), Options::[Option]) -> wxListCtrl()`

Types:

Option = {winid, integer()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()} | {validator, wx() (see module wx)}

See external documentation.

`arrange(This::wxListCtrl()) -> bool()`

Equivalent to `arrange(This, [])`.

`arrange(This::wxListCtrl(), Options::[Option]) -> bool()`

Types:

Option = {flag, integer()}

See external documentation.

`assignImageList(This::wxListCtrl(), ImageList::wxImageList() (see module wxImageList), Which::integer()) -> ok`

See external documentation.

`clearAll(This::wxListCtrl()) -> ok`

See external documentation.

```
create(This::wxListCtrl(), Parent::wxWindow() (see module wxWindow)) ->
bool()
```

Equivalent to *create(This, Parent, [])*.

```
create(This::wxListCtrl(), Parent::wxWindow() (see module wxWindow),
Options::[Option]) -> bool()
```

Types:

```
Option = {winid, integer()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style,
integer()} | {validator, wx() (see module wx)}
```

See external documentation.

```
deleteAllItems(This::wxListCtrl()) -> bool()
```

See external documentation.

```
deleteColumn(This::wxListCtrl(), Col::integer()) -> bool()
```

See external documentation.

```
deleteItem(This::wxListCtrl(), Item::integer()) -> bool()
```

See external documentation.

```
editLabel(This::wxListCtrl(), Item::integer()) -> wxTextCtrl() (see module
wxTextCtrl)
```

See external documentation.

```
ensureVisible(This::wxListCtrl(), Item::integer()) -> bool()
```

See external documentation.

```
findItem(This::wxListCtrl(), Start::integer(), Str::string()) -> integer()
```

Equivalent to *findItem(This, Start, Str, [])*.

```
findItem(This::wxListCtrl(), Start::integer(), X::string() | term(),
X::term() | integer()) -> integer()
```

See external documentation.

Alternatives:

```
findItem(This::wxListCtrl(), Start::integer(), Str::string(), [Option]) ->
integer()
```

Option = {partial, bool()}

```
findItem(This::wxListCtrl(), Start::integer(), Pt::
{X::integer(), Y::integer()}, Direction::integer()) -> integer()
```

```
getColumn(This::wxListCtrl(), Col::integer(), Item::wxListItem() (see module
wxListItem)) -> bool()
```

See external documentation.

`getColumnCount(This::wxListCtrl()) -> integer()`

See external documentation.

`getColumnWidth(This::wxListCtrl(), Col::integer()) -> integer()`

See external documentation.

`getCountPerPage(This::wxListCtrl()) -> integer()`

See external documentation.

`getEditControl(This::wxListCtrl()) -> wxTextCtrl() (see module wxTextCtrl)`

See external documentation.

`getImageList(This::wxListCtrl(), Which::integer()) -> wxImageList() (see module wxImageList)`

See external documentation.

`getItem(This::wxListCtrl(), Info::wxListItem() (see module wxListItem)) -> bool()`

See external documentation.

`getItemBackgroundColour(This::wxListCtrl(), Item::integer()) -> colour() (see module wx)`

See external documentation.

`getItemCount(This::wxListCtrl()) -> integer()`

See external documentation.

`getItemData(This::wxListCtrl(), Item::integer()) -> integer()`

See external documentation.

`getItemFont(This::wxListCtrl(), Item::integer()) -> wxFont() (see module wxFont)`

See external documentation.

`getItemPosition(This::wxListCtrl(), Item::integer(), Pos::{X::integer(), Y::integer()}) -> bool()`

See external documentation.

`getItemRect(This::wxListCtrl(), Item::integer(), Rect::{X::integer(), Y::integer(), W::integer(), H::integer()}) -> bool()`

Equivalent to `getItemRect(This, Item, Rect, [])`.

```
getItemRect(This::wxListCtrl(), Item::integer(), Rect::{X::integer(),  
Y::integer(), W::integer(), H::integer()}, Options::[Option]) -> bool()
```

Types:

Option = {code, integer()}

See external documentation.

```
getItemSpacing(This::wxListCtrl()) -> {W::integer(), H::integer()}
```

See external documentation.

```
getItemState(This::wxListCtrl(), Item::integer(), StateMask::integer()) ->  
integer()
```

See external documentation.

```
getItemText(This::wxListCtrl(), Item::integer()) -> string()
```

See external documentation.

```
getItemTextColour(This::wxListCtrl(), Item::integer()) -> colour() (see  
module wx)
```

See external documentation.

```
getNextItem(This::wxListCtrl(), Item::integer()) -> integer()
```

Equivalent to *getNextItem(This, Item, [])*.

```
getNextItem(This::wxListCtrl(), Item::integer(), Options::[Option]) ->  
integer()
```

Types:

Option = {geometry, integer()} | {state, integer()}

See external documentation.

```
getSelectedItemCount(This::wxListCtrl()) -> integer()
```

See external documentation.

```
getTextColour(This::wxListCtrl()) -> colour() (see module wx)
```

See external documentation.

```
getTopItem(This::wxListCtrl()) -> integer()
```

See external documentation.

```
getViewRect(This::wxListCtrl()) -> {X::integer(), Y::integer(), W::integer(),  
H::integer()}
```

See external documentation.

```
hitTest(This::wxListCtrl(), Point::{X::integer(), Y::integer()}) ->
{integer(), Flags::integer()}
```

See external documentation.

```
insertColumn(This::wxListCtrl(), Col::integer(), X::string() | term()) ->
integer()
```

See external documentation.

Alternatives:

```
insertColumn(This::wxListCtrl(), Col::integer(), Heading::string()) ->
insertColumn(This, Col, Heading, [])
```

```
insertColumn(This::wxListCtrl(), Col::integer(),
Info::wxListItem:wxListItem()) -> integer()
```

```
insertColumn(This::wxListCtrl(), Col::integer(), Heading::string(), Options::
[Option]) -> integer()
```

Types:

Option = {format, integer()} | {width, integer()}

See external documentation.

```
insertItem(This::wxListCtrl(), Info::wxListItem() (see module wxListItem)) ->
integer()
```

See external documentation.

```
insertItem(This::wxListCtrl(), Index::integer(), X::integer() | string()) ->
integer()
```

See external documentation.

Alternatives:

```
insertItem(This::wxListCtrl(), Index::integer(), ImageIndex::integer()) ->
integer()
```

```
insertItem(This::wxListCtrl(), Index::integer(), Label::string()) -> integer()
```

```
insertItem(This::wxListCtrl(), Index::integer(), Label::string(),
ImageIndex::integer()) -> integer()
```

See external documentation.

```
refreshItem(This::wxListCtrl(), Item::integer()) -> ok
```

See external documentation.

```
refreshItems(This::wxListCtrl(), ItemFrom::integer(), ItemTo::integer()) ->
ok
```

See external documentation.

```
scrollList(This::wxListCtrl(), Dx::integer(), Dy::integer()) -> bool()
```

See external documentation.

```
setBackgroundColour(This::wxListCtrl(), Colour::colour() (see module wx)) ->
bool()
```

See external documentation.

```
setColumn(This::wxListCtrl(), Col::integer(), Item::wxListItem() (see module
wxListItem)) -> bool()
```

See external documentation.

```
setColumnWidth(This::wxListCtrl(), Col::integer(), Width::integer()) ->
bool()
```

See external documentation.

```
setImageList(This::wxListCtrl(), ImageList::wxImageList() (see module
wxImageList), Which::integer()) -> ok
```

See external documentation.

```
setItem(This::wxListCtrl(), Info::wxListItem() (see module wxListItem)) ->
bool()
```

See external documentation.

```
setItem(This::wxListCtrl(), Index::integer(), Col::integer(),
Label::string()) -> integer()
```

Equivalent to *setItem(This, Index, Col, Label, [])*.

```
setItem(This::wxListCtrl(), Index::integer(), Col::integer(),
Label::string(), Options::[Option]) -> integer()
```

Types:

Option = {imageId, integer()}

See external documentation.

```
setItemBackgroundColour(This::wxListCtrl(), Item::integer(), Col::colour()
(see module wx)) -> ok
```

See external documentation.

```
setItemCount(This::wxListCtrl(), Count::integer()) -> ok
```

See external documentation.

```
setItemData(This::wxListCtrl(), Item::integer(), Data::integer()) -> bool()
```

See external documentation.

```
setItemFont(This::wxListCtrl(), Item::integer(), F::wxFont() (see module
wxFont)) -> ok
```

See external documentation.

`setItemImage(This::wxListCtrl(), Item::integer(), Image::integer()) -> bool()`

Equivalent to *setItemImage(This, Item, Image, [])*.

`setItemImage(This::wxListCtrl(), Item::integer(), Image::integer(), Options::[Option]) -> bool()`

Types:

Option = {sellImage, integer()}

See external documentation.

`setItemColumnImage(This::wxListCtrl(), Item::integer(), Column::integer(), Image::integer()) -> bool()`

See external documentation.

`setItemPosition(This::wxListCtrl(), Item::integer(), Pos::{X::integer(), Y::integer()}) -> bool()`

See external documentation.

`setItemState(This::wxListCtrl(), Item::integer(), State::integer(), StateMask::integer()) -> bool()`

See external documentation.

`setItemText(This::wxListCtrl(), Item::integer(), Str::string()) -> ok`

See external documentation.

`setItemTextColour(This::wxListCtrl(), Item::integer(), Col::colour() (see module wx)) -> ok`

See external documentation.

`setSingleStyle(This::wxListCtrl(), Style::integer()) -> ok`

Equivalent to *setSingleStyle(This, Style, [])*.

`setSingleStyle(This::wxListCtrl(), Style::integer(), Options::[Option]) -> ok`

Types:

Option = {add, bool()}

See external documentation.

`setTextColour(This::wxListCtrl(), Col::colour() (see module wx)) -> ok`

See external documentation.

`setWindowStyleFlag(This::wxListCtrl(), Style::integer()) -> ok`

See external documentation.

wxListCtrl

sortItems(This::wxListCtrl(), SortCallBack::function()) -> boolean()

Sort the items in the list control

```
SortCalBack(Item1,Item2) -> integer()
```

SortCallBack receives the client data associated with two items to compare, and should return 0 if the items are equal, a negative value if the first item is less than the second one and a positive value if the first item is greater than the second one.

NOTE: The callback may not call other processes.

destroy(This::wxListCtrl()) -> ok

Destroys this object, do not use object again

wxListEvent

Erlang module

See external documentation: **wxListEvent**.

Use `wxEvtHandler:connect/3` with `EventType`:

<code>command_list_begin_drag,</code>	<code>command_list_begin_rdrag,</code>	<code>command_list_begin_label_edit,</code>
<code>command_list_end_label_edit,</code>	<code>command_list_delete_item,</code>	<code>command_list_delete_all_items,</code>
<code>command_list_key_down,</code>	<code>command_list_insert_item,</code>	<code>command_list_col_click,</code>
<code>command_list_col_right_click,</code>		
<code>command_list_col_begin_drag,</code>	<code>command_list_col_dragging,</code>	<code>command_list_col_end_drag,</code>
<code>command_list_item_selected,</code>	<code>command_list_item_deselected,</code>	<code>command_list_item_right_click,</code>
<code>command_list_item_middle_click,</code>	<code>command_list_item_activated,</code>	<code>command_list_item_focused,</code>
<code>command_list_cache_hint</code>		

See also the message variant `#wxList{}` event record type.

This class is derived (and can use functions) from:

`wxNotifyEvent`

`wxCommandEvent`

`wxEvent`

DATA TYPES

`wxListEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`getCacheFrom(This::wxListEvent()) -> integer()`

See external documentation.

`getCacheTo(This::wxListEvent()) -> integer()`

See external documentation.

`getKeyCode(This::wxListEvent()) -> integer()`

See external documentation.

`getIndex(This::wxListEvent()) -> integer()`

See external documentation.

`getColumn(This::wxListEvent()) -> integer()`

See external documentation.

`getPoint(This::wxListEvent()) -> {X::integer(), Y::integer()}`

See external documentation.

`getLabel(This::wxListEvent()) -> string()`

See external documentation.

`getText(This::wxListEvent()) -> string()`

See external documentation.

`getImage(This::wxListEvent()) -> integer()`

See external documentation.

`getData(This::wxListEvent()) -> integer()`

See external documentation.

`getMask(This::wxListEvent()) -> integer()`

See external documentation.

`getItem(This::wxListEvent()) -> wxListItem() (see module wxListItem)`

See external documentation.

`isEditCancelled(This::wxListEvent()) -> bool()`

See external documentation.

wxListItem

Erlang module

See external documentation: **wxListItem**.

DATA TYPES

`wxListItem()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxListItem()`

See external documentation.

`new(Item::wxListItem()) -> wxListItem()`

See external documentation.

`clear(This::wxListItem()) -> ok`

See external documentation.

`getAlign(This::wxListItem()) -> WxListColumnFormat`

Types:

`WxListColumnFormat = integer()`

See external documentation.

`WxListColumnFormat` is one of `?wxLIST_FORMAT_LEFT` | `?wxLIST_FORMAT_RIGHT` | `?wxLIST_FORMAT_CENTRE` | `?wxLIST_FORMAT_CENTER`

`getBackgroundColour(This::wxListItem()) -> colour() (see module wx)`

See external documentation.

`getColumn(This::wxListItem()) -> integer()`

See external documentation.

`getFont(This::wxListItem()) -> wxFont() (see module wxFont)`

See external documentation.

`getId(This::wxListItem()) -> integer()`

See external documentation.

`getImage(This::wxListItem()) -> integer()`

See external documentation.

`getMask(This::wxListItem()) -> integer()`

See external documentation.

`getState(This::wxListItem()) -> integer()`

See external documentation.

`getText(This::wxListItem()) -> string()`

See external documentation.

`getTextColour(This::wxListItem()) -> colour() (see module wx)`

See external documentation.

`getWidth(This::wxListItem()) -> integer()`

See external documentation.

`setAlign(This::wxListItem(), Align::WxListColumnFormat) -> ok`

Types:

`WxListColumnFormat = integer()`

See external documentation.

WxListColumnFormat is one of ?wxLIST_FORMAT_LEFT | ?wxLIST_FORMAT_RIGHT | ?wxLIST_FORMAT_CENTRE | ?wxLIST_FORMAT_CENTER

`setBackgroundColour(This::wxListItem(), ColBack::colour() (see module wx)) -> ok`

See external documentation.

`setColumn(This::wxListItem(), Col::integer()) -> ok`

See external documentation.

`setFont(This::wxListItem(), Font::wxFont() (see module wxFont)) -> ok`

See external documentation.

`setId(This::wxListItem(), Id::integer()) -> ok`

See external documentation.

`setImage(This::wxListItem(), Image::integer()) -> ok`

See external documentation.

`setMask(This::wxListItem(), Mask::integer()) -> ok`

See external documentation.

`setState(This::wxListItem(), State::integer()) -> ok`

See external documentation.

setStateMask(This::wxListItem(), StateMask::integer()) -> ok

See external documentation.

setText(This::wxListItem(), Text::string()) -> ok

See external documentation.

setTextColour(This::wxListItem(), ColText::colour() (see module wx)) -> ok

See external documentation.

setWidth(This::wxListItem(), Width::integer()) -> ok

See external documentation.

destroy(This::wxListItem()) -> ok

Destroys this object, do not use object again

wxListView

Erlang module

See external documentation: **wxListView**.

This class is derived (and can use functions) from:

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxListView()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`clearColumnImage(This::wxListView(), Col::integer()) -> ok`

See external documentation.

`focus(This::wxListView(), Index::integer()) -> ok`

See external documentation.

`getFirstSelected(This::wxListView()) -> integer()`

See external documentation.

`getFocusedItem(This::wxListView()) -> integer()`

See external documentation.

`getNextSelected(This::wxListView(), Item::integer()) -> integer()`

See external documentation.

`isSelected(This::wxListView(), Index::integer()) -> bool()`

See external documentation.

`select(This::wxListView(), N::integer()) -> ok`

Equivalent to *select(This, N, [])*.

`select(This::wxListView(), N::integer(), Options::[Option]) -> ok`

Types:

Option = {on, bool()}

See external documentation.

```
setColumnImage(This::wxListView(), Col::integer(), Image::integer()) -> ok
```

See external documentation.

wxLogNull

Erlang module

See external documentation: **wxLogNull**.

DATA TYPES

`wxLogNull()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparsion stored on disc or distributed for use on other nodes.

Exports

`new() -> wxLogNull()`

See **external documentation**.

`destroy(This::wxLogNull()) -> ok`

Destroys this object, do not use object again

wxMask

Erlang module

See external documentation: **wxMask**.

DATA TYPES

`wxMask()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxMask()`

See external documentation.

`new(Bitmap::wxBitmap() (see module wxBitmap)) -> wxMask()`

See external documentation.

`new(Bitmap::wxBitmap() (see module wxBitmap), X::integer() | term()) -> wxMask()`

See external documentation.

Alternatives:

`new(Bitmap::wxBitmap:wxBitmap(), PaletteIndex::integer()) -> wxMask()`

`new(Bitmap::wxBitmap:wxBitmap(), Colour::wx:colour()) -> wxMask()`

`create(This::wxMask(), Bitmap::wxBitmap() (see module wxBitmap)) -> bool()`

See external documentation.

`create(This::wxMask(), Bitmap::wxBitmap() (see module wxBitmap), X::integer() | term()) -> bool()`

See external documentation.

Alternatives:

`create(This::wxMask(), Bitmap::wxBitmap:wxBitmap(), PaletteIndex::integer()) -> bool()`

`create(This::wxMask(), Bitmap::wxBitmap:wxBitmap(), Colour::wx:colour()) -> bool()`

`destroy(This::wxMask()) -> ok`

Destroys this object, do not use object again

wxMaximizeEvent

Erlang module

See external documentation: **wxMaximizeEvent**.

Use *wxEvtHandler:connect/3* with EventType:

maximize

See also the message variant *#wxMaximize{}* event record type.

This class is derived (and can use functions) from:

wxEvent

DATA TYPES

`wxMaximizeEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

wxMDIChildFrame

Erlang module

See external documentation: **wxMDIChildFrame**.

This class is derived (and can use functions) from:

wxFrame

wxTopLevelWindow

wxWindow

wxEvtHandler

DATA TYPES

`wxMDIChildFrame()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxMDIChildFrame()`

See external documentation.

`new(Parent::wxMDIParentFrame() (see module wxMDIParentFrame), Id::integer(), Title::string()) -> wxMDIChildFrame()`

Equivalent to `new(Parent, Id, Title, [])`.

`new(Parent::wxMDIParentFrame() (see module wxMDIParentFrame), Id::integer(), Title::string(), Options::[Option]) -> wxMDIChildFrame()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`activate(This::wxMDIChildFrame()) -> ok`

See external documentation.

`create(This::wxMDIChildFrame(), Parent::wxMDIParentFrame() (see module wxMDIParentFrame), Id::integer(), Title::string()) -> bool()`

Equivalent to `create(This, Parent, Id, Title, [])`.

`create(This::wxMDIChildFrame(), Parent::wxMDIParentFrame() (see module wxMDIParentFrame), Id::integer(), Title::string(), Options::[Option]) -> bool()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

maximize(This::wxMDIChildFrame()) -> ok

Equivalent to *maximize(This, [])*.

maximize(This::wxMDIChildFrame(), Options::[Option]) -> ok

Types:

Option = {maximize, bool()}

See **external documentation**.

restore(This::wxMDIChildFrame()) -> ok

See **external documentation**.

destroy(This::wxMDIChildFrame()) -> ok

Destroys this object, do not use object again

wxMDIClientWindow

Erlang module

See external documentation: **wxMDIClientWindow**.

This class is derived (and can use functions) from:

wxWindow

wxEvtHandler

DATA TYPES

`wxMDIClientWindow()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxMDIClientWindow()`

See external documentation.

`new(Parent::wxMDIParentFrame() (see module wxMDIParentFrame)) -> wxMDIClientWindow()`

Equivalent to `new(Parent, [])`.

`new(Parent::wxMDIParentFrame() (see module wxMDIParentFrame), Options::[Option]) -> wxMDIClientWindow()`

Types:

Option = {style, integer()}

See external documentation.

`createClient(This::wxMDIClientWindow(), Parent::wxMDIParentFrame() (see module wxMDIParentFrame)) -> bool()`

Equivalent to `createClient(This, Parent, [])`.

`createClient(This::wxMDIClientWindow(), Parent::wxMDIParentFrame() (see module wxMDIParentFrame), Options::[Option]) -> bool()`

Types:

Option = {style, integer()}

See external documentation.

`destroy(This::wxMDIClientWindow()) -> ok`

Destroys this object, do not use object again

wxMDIParentFrame

Erlang module

See external documentation: **wxMDIParentFrame**.

This class is derived (and can use functions) from:

wxFrame

wxTopLevelWindow

wxWindow

wxEvtHandler

DATA TYPES

`wxMDIParentFrame()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxMDIParentFrame()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Title::string())
-> wxMDIParentFrame()`

Equivalent to `new(Parent, Id, Title, [])`.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Title::string(),
Options::[Option]) -> wxMDIParentFrame()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`activateNext(This::wxMDIParentFrame()) -> ok`

See external documentation.

`activatePrevious(This::wxMDIParentFrame()) -> ok`

See external documentation.

`arrangeIcons(This::wxMDIParentFrame()) -> ok`

See external documentation.

`cascade(This::wxMDIParentFrame()) -> ok`

See external documentation.

```
create(This::wxMDIParentFrame(), Parent::wxWindow() (see module wxWindow),
Id::integer(), Title::string()) -> bool()
```

Equivalent to *create(This, Parent, Id, Title, [])*.

```
create(This::wxMDIParentFrame(), Parent::wxWindow() (see module wxWindow),
Id::integer(), Title::string(), Options::[Option]) -> bool()
```

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

```
getActiveChild(This::wxMDIParentFrame()) -> wxMDIChildFrame() (see module
wxMDIChildFrame)
```

See external documentation.

```
getClientWindow(This::wxMDIParentFrame()) -> wxMDIClientWindow() (see module
wxMDIClientWindow)
```

See external documentation.

```
tile(This::wxMDIParentFrame()) -> ok
```

Equivalent to *tile(This, [])*.

```
tile(This::wxMDIParentFrame(), Options::[Option]) -> ok
```

Types:

Option = {orient, WxOrientation}

WxOrientation = integer()

See external documentation.

WxOrientation is one of ?wxHORIZONTAL | ?wxVERTICAL | ?wxBOTH

```
destroy(This::wxMDIParentFrame()) -> ok
```

Destroys this object, do not use object again

wxMemoryDC

Erlang module

See external documentation: **wxMemoryDC**.

This class is derived (and can use functions) from:
wxDC

DATA TYPES

`wxMemoryDC()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new()` -> `wxMemoryDC()`

See external documentation.

`new(Dc::wxDC() (see module wxDC) | wxBitmap() (see module wxBitmap))` ->
`wxMemoryDC()`

See external documentation.

`selectObject(This::wxMemoryDC(), Bmp::wxBitmap() (see module wxBitmap))` -> ok

See external documentation.

`selectObjectAsSource(This::wxMemoryDC(), Bmp::wxBitmap() (see module wxBitmap))` -> ok

See external documentation.

`destroy(This::wxMemoryDC())` -> ok

Destroys this object, do not use object again

wxMenuBar

Erlang module

See external documentation: **wxMenuBar**.

This class is derived (and can use functions) from:

wxWindow

wxEvtHandler

DATA TYPES

`wxMenuBar()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxMenuBar()`

See external documentation.

`new(Style::integer()) -> wxMenuBar()`

See external documentation.

`append(This::wxMenuBar(), Menu::wxMenu() (see module wxMenu), Title::string()) -> bool()`

See external documentation.

`check(This::wxMenuBar(), Itemid::integer(), Check::bool()) -> ok`

See external documentation.

`enable(This::wxMenuBar()) -> bool()`

Equivalent to `enable(This, [])`.

`enable(This::wxMenuBar(), Options::[Option]) -> bool()`

Types:

Option = {enable, bool()}

See external documentation.

`enable(This::wxMenuBar(), Itemid::integer(), Enable::bool()) -> ok`

See external documentation.

`enableTop(This::wxMenuBar(), Pos::integer(), Flag::bool()) -> ok`

See external documentation.

`findMenu(This::wxMenuBar(), Title::string()) -> integer()`

See external documentation.

`findMenuItem(This::wxMenuBar(), MenuString::string(), ItemString::string()) -> integer()`

See external documentation.

`findItem(This::wxMenuBar(), Id::integer()) -> wxMenuItem()` (see module `wxMenuItem`)

See external documentation.

`getHelpString(This::wxMenuBar(), Itemid::integer()) -> string()`

See external documentation.

`getLabel(This::wxMenuBar()) -> string()`

See external documentation.

`getLabel(This::wxMenuBar(), Itemid::integer()) -> string()`

See external documentation.

`getLabelTop(This::wxMenuBar(), Pos::integer()) -> string()`

See external documentation.

`getMenu(This::wxMenuBar(), Pos::integer()) -> wxMenu()` (see module `wxMenu`)

See external documentation.

`getMenuCount(This::wxMenuBar()) -> integer()`

See external documentation.

`insert(This::wxMenuBar(), Pos::integer(), Menu::wxMenu() (see module wxMenu), Title::string()) -> bool()`

See external documentation.

`isChecked(This::wxMenuBar(), Itemid::integer()) -> bool()`

See external documentation.

`isEnabled(This::wxMenuBar()) -> bool()`

See external documentation.

`isEnabled(This::wxMenuBar(), Itemid::integer()) -> bool()`

See external documentation.

`remove(This::wxMenuBar(), Pos::integer()) -> wxMenu()` (see module `wxMenu`)

See external documentation.

`replace(This::wxMenuBar(), Pos::integer(), Menu::wxMenu()` (see module `wxMenu`), `Title::string()`) -> `wxMenu()` (see module `wxMenu`)

See external documentation.

`setHelpString(This::wxMenuBar(), Itemid::integer(), HelpString::string()) -> ok`

See external documentation.

`setLabel(This::wxMenuBar(), S::string()) -> ok`

See external documentation.

`setLabel(This::wxMenuBar(), Itemid::integer(), Label::string()) -> ok`

See external documentation.

`setLabelTop(This::wxMenuBar(), Pos::integer(), Label::string()) -> ok`

See external documentation.

`destroy(This::wxMenuBar()) -> ok`

Destroys this object, do not use object again

wxMenu

Erlang module

See external documentation: **wxMenu**.

This class is derived (and can use functions) from:
wxEvtHandler

DATA TYPES

`wxMenu()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxMenu()`

Equivalent to `new([])`.

`new(Options::[Option]) -> wxMenu()`

Types:

Option = {style, integer()}

See external documentation.

`new>Title::string(), Options::[Option]) -> wxMenu()`

Types:

Option = {style, integer()}

See external documentation.

`append(This::wxMenu(), Item::wxMenuItem() (see module wxMenuItem)) -> wxMenuItem() (see module wxMenuItem)`

See external documentation.

`append(This::wxMenu(), Itemid::integer(), Text::string()) -> wxMenuItem() (see module wxMenuItem)`

Equivalent to `append(This, Itemid, Text, [])`.

`append(This::wxMenu(), Itemid::integer(), Text::string(), X::wxMenu() | term()) -> wxMenuItem() (see module wxMenuItem)`

See external documentation.

Alternatives:

`append(This::wxMenu(), Itemid::integer(), Text::string(), Submenu::wxMenu()) -> append(This, Itemid, Text, Submenu, [])`

`append(This::wxMenu(), Itemid::integer(), Text::string(), [Option]) -> wxMenuItem:wxMenuItem()`

Option = {help, string()} | {kind, WxItemKind}

WxItemKind = integer()

WxItemKind is one of ?wxITEM_SEPARATOR | ?wxITEM_NORMAL | ?wxITEM_CHECK | ?wxITEM_RADIO
| ?wxITEM_MAX

**append(This::wxMenu(), Itemid::integer(), Text::string(), X::string() |
wxMenu(), X::bool() | term()) -> ok | wxMenuItem() (see module wxMenuItem)**

See **external documentation**.

Alternatives:

**append(This::wxMenu(), Itemid::integer(), Text::string(), Help::string(),
IsCheckable::bool()) -> ok**

**append(This::wxMenu(), Itemid::integer(), Text::string(), Submenu::wxMenu(),
[Option]) -> wxMenuItem:wxMenuItem()**

Option = {help, string() }

**appendCheckItem(This::wxMenu(), Itemid::integer(), Text::string()) ->
wxMenuItem() (see module wxMenuItem)**

Equivalent to *appendCheckItem(This, Itemid, Text, [])*.

**appendCheckItem(This::wxMenu(), Itemid::integer(), Text::string(), Options::
[Option]) -> wxMenuItem() (see module wxMenuItem)**

Types:

Option = {help, string() }

See **external documentation**.

**appendRadioItem(This::wxMenu(), Itemid::integer(), Text::string()) ->
wxMenuItem() (see module wxMenuItem)**

Equivalent to *appendRadioItem(This, Itemid, Text, [])*.

**appendRadioItem(This::wxMenu(), Itemid::integer(), Text::string(), Options::
[Option]) -> wxMenuItem() (see module wxMenuItem)**

Types:

Option = {help, string() }

See **external documentation**.

appendSeparator(This::wxMenu()) -> wxMenuItem() (see module wxMenuItem)

See **external documentation**.

break(This::wxMenu()) -> ok

See **external documentation**.

check(This::wxMenu(), Itemid::integer(), Check::bool()) -> ok

See **external documentation**.

delete(This::wxMenu(), X::integer() | term()) -> bool()

See [external documentation](#).

Alternatives:

delete(This::wxMenu(), Itemid::integer()) -> bool()

delete(This::wxMenu(), Item::wxMenuItem:wxMenuItem()) -> bool()

Destroy(This::wxMenu(), X::integer() | term()) -> bool()

See [external documentation](#).

Alternatives:

'Destroy'(This::wxMenu(), Itemid::integer()) -> bool()

'Destroy'(This::wxMenu(), Item::wxMenuItem:wxMenuItem()) -> bool()

enable(This::wxMenu(), Itemid::integer(), Enable::bool()) -> ok

See [external documentation](#).

findItem(This::wxMenu(), X::integer() | string()) -> wxMenuItem() (see module wxMenuItem) | integer()

See [external documentation](#).

Alternatives:

findItem(This::wxMenu(), Itemid::integer()) -> wxMenuItem:wxMenuItem()

findItem(This::wxMenu(), Item::string()) -> integer()

findItemByPosition(This::wxMenu(), Position::integer()) -> wxMenuItem() (see module wxMenuItem)

See [external documentation](#).

getHelpString(This::wxMenu(), Itemid::integer()) -> string()

See [external documentation](#).

getLabel(This::wxMenu(), Itemid::integer()) -> string()

See [external documentation](#).

getMenuItemCount(This::wxMenu()) -> integer()

See [external documentation](#).

getMenuItems(This::wxMenu()) -> [wxMenuItem() (see module wxMenuItem)]

See [external documentation](#).

getTitle(This::wxMenu()) -> string()

See [external documentation](#).

```
insert(This::wxMenu(), Pos::integer(), X::integer() | term()) -> wxMenuItem()
(see module wxMenuItem)
```

See external documentation.

Alternatives:

```
insert(This::wxMenu(),          Pos::integer(),          Itemid::integer())          ->
insert(This, Pos, Itemid, [])

insert(This::wxMenu(),  Pos::integer(),  Item::wxMenuItem:wxMenuItem())  ->
wxMenuItem:wxMenuItem()
```

```
insert(This::wxMenu(), Pos::integer(), Itemid::integer(), Options::[Option])
-> wxMenuItem() (see module wxMenuItem)
```

Types:

Option = {text, string()} | {help, string()} | {kind, WxItemKind}

WxItemKind = integer()

See external documentation.

WxItemKind is one of ?wxITEM_SEPARATOR | ?wxITEM_NORMAL | ?wxITEM_CHECK | ?wxITEM_RADIO
| ?wxITEM_MAX

```
insert(This::wxMenu(), Pos::integer(), Itemid::integer(), Text::string(),
Submenu::wxMenu()) -> wxMenuItem() (see module wxMenuItem)
```

Equivalent to *insert(This, Pos, Itemid, Text, Submenu, [])*.

```
insert(This::wxMenu(), Pos::integer(), Itemid::integer(), Text::string(),
X::string() | wxMenu(), X::bool() | term()) -> ok | wxMenuItem() (see module
wxMenuItem)
```

See external documentation.

Alternatives:

```
insert(This::wxMenu(),  Pos::integer(),  Itemid::integer(),  Text::string(),
Help::string(), IsCheckable::bool()) -> ok

insert(This::wxMenu(),  Pos::integer(),  Itemid::integer(),  Text::string(),
Submenu::wxMenu(), [Option]) -> wxMenuItem:wxMenuItem()
Option = {help, string()}
```

```
insertCheckItem(This::wxMenu(), Pos::integer(), Itemid::integer(),
Text::string()) -> wxMenuItem() (see module wxMenuItem)
```

Equivalent to *insertCheckItem(This, Pos, Itemid, Text, [])*.

```
insertCheckItem(This::wxMenu(), Pos::integer(), Itemid::integer(),
Text::string(), Options::[Option]) -> wxMenuItem() (see module wxMenuItem)
```

Types:

Option = {help, string()}

See external documentation.

```
insertRadioItem(This::wxMenu(), Pos::integer(), Itemid::integer(),
Text::string()) -> wxMenuItem() (see module wxMenuItem)
```

Equivalent to *insertRadioItem(This, Pos, Itemid, Text, [])*.

```
insertRadioItem(This::wxMenu(), Pos::integer(), Itemid::integer(),
Text::string(), Options::[Option]) -> wxMenuItem() (see module wxMenuItem)
```

Types:

Option = {help, string() }

See external documentation.

```
insertSeparator(This::wxMenu(), Pos::integer()) -> wxMenuItem() (see module
wxMenuItem)
```

See external documentation.

```
isChecked(This::wxMenu(), Itemid::integer()) -> bool()
```

See external documentation.

```
isEnabled(This::wxMenu(), Itemid::integer()) -> bool()
```

See external documentation.

```
prepend(This::wxMenu(), X::integer() | term()) -> wxMenuItem() (see module
wxMenuItem)
```

See external documentation.

Alternatives:

```
prepend(This::wxMenu(), Itemid::integer()) -> prepend(This, Itemid, [])
```

```
prepend(This::wxMenu(), Item::wxMenuItem:wxMenuItem()) ->
wxMenuItem:wxMenuItem()
```

```
prepend(This::wxMenu(), Itemid::integer(), Options::[Option]) -> wxMenuItem()
(see module wxMenuItem)
```

Types:

Option = {text, string() } | {help, string() } | {kind, WxItemKind}

WxItemKind = integer()

See external documentation.

WxItemKind is one of ?wxITEM_SEPARATOR | ?wxITEM_NORMAL | ?wxITEM_CHECK | ?wxITEM_RADIO
| ?wxITEM_MAX

```
prepend(This::wxMenu(), Itemid::integer(), Text::string(), Submenu::wxMenu())
-> wxMenuItem() (see module wxMenuItem)
```

Equivalent to *prepend(This, Itemid, Text, Submenu, [])*.

```
prepend(This::wxMenu(), Itemid::integer(), Text::string(), X::string() |
wxMenu(), X::bool() | term()) -> ok | wxMenuItem() (see module wxMenuItem)
```

See external documentation.

Alternatives:

```
prepend(This::wxMenu(), Itemid::integer(), Text::string(), Help::string(),
IsCheckable::bool()) -> ok
```

```
prepend(This::wxMenu(), Itemid::integer(), Text::string(), Submenu::wxMenu(),
[Option]) -> wxMenuItem:wxMenuItem()
```

Option = {help, string() }

```
prependCheckItem(This::wxMenu(), Itemid::integer(), Text::string()) ->
wxMenuItem() (see module wxMenuItem)
```

Equivalent to *prependCheckItem(This, Itemid, Text, [])*.

```
prependCheckItem(This::wxMenu(), Itemid::integer(), Text::string(), Options::
[Option]) -> wxMenuItem() (see module wxMenuItem)
```

Types:

Option = {help, string() }

See external documentation.

```
prependRadioItem(This::wxMenu(), Itemid::integer(), Text::string()) ->
wxMenuItem() (see module wxMenuItem)
```

Equivalent to *prependRadioItem(This, Itemid, Text, [])*.

```
prependRadioItem(This::wxMenu(), Itemid::integer(), Text::string(), Options::
[Option]) -> wxMenuItem() (see module wxMenuItem)
```

Types:

Option = {help, string() }

See external documentation.

```
prependSeparator(This::wxMenu()) -> wxMenuItem() (see module wxMenuItem)
```

See external documentation.

```
remove(This::wxMenu(), X::integer() | term()) -> wxMenuItem() (see module
wxMenuItem)
```

See external documentation.

Alternatives:

```
remove(This::wxMenu(), Itemid::integer()) -> wxMenuItem:wxMenuItem()
```

```
remove(This::wxMenu(), Item:wxMenuItem:wxMenuItem()) ->
wxMenuItem:wxMenuItem()
```

```
setHelpString(This::wxMenu(), Itemid::integer(), HelpString::string()) -> ok
```

See external documentation.

```
setLabel(This::wxMenu(), Itemid::integer(), Label::string()) -> ok
```

See external documentation.

wxMenu

setTitle(This::wxMenu(), Title::string()) -> ok

See **external documentation**.

destroy(This::wxMenu()) -> ok

Destroys this object, do not use object again

wxMenuEvent

Erlang module

See external documentation: **wxMenuEvent**.

Use *wxEvtHandler:connect/3* with EventType:

menu_open, menu_close, menu_highlight

See also the message variant *#wxMenu{}* event record type.

This class is derived (and can use functions) from:

wxEvt

DATA TYPES

`wxMenuEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`getMenu(This::wxMenuEvent()) -> wxMenu()` (see module `wxMenu`)

See external documentation.

`getMenuId(This::wxMenuEvent()) -> integer()`

See external documentation.

`isPopup(This::wxMenuEvent()) -> bool()`

See external documentation.

wxMenuItem

Erlang module

See external documentation: **wxMenuItem**.

DATA TYPES

`wxMenuItem()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxMenuItem()`

Equivalent to `new([])`.

`new(Options::[Option]) -> wxMenuItem()`

Types:

Option = {parentMenu, wxMenu() (see module wxMenu)} | {id, integer()} | {text, string()} | {help, string()} | {kind, WxItemKind} | {subMenu, wxMenu() (see module wxMenu)}

WxItemKind = integer()

See **external documentation**.

WxItemKind is one of ?wxITEM_SEPARATOR | ?wxITEM_NORMAL | ?wxITEM_CHECK | ?wxITEM_RADIO | ?wxITEM_MAX

`check(This::wxMenuItem()) -> ok`

Equivalent to `check(This, [])`.

`check(This::wxMenuItem(), Options::[Option]) -> ok`

Types:

Option = {check, bool()}

See **external documentation**.

`enable(This::wxMenuItem()) -> ok`

Equivalent to `enable(This, [])`.

`enable(This::wxMenuItem(), Options::[Option]) -> ok`

Types:

Option = {enable, bool()}

See **external documentation**.

`getBitmap(This::wxMenuItem()) -> wxBitmap() (see module wxBitmap)`

See **external documentation**.

`getHelp(This::wxMenuItem()) -> string()`

See external documentation.

`getId(This::wxMenuItem()) -> integer()`

See external documentation.

`getKind(This::wxMenuItem()) -> WxItemKind`

Types:

`WxItemKind = integer()`

See external documentation.

WxItemKind is one of ?wxITEM_SEPARATOR | ?wxITEM_NORMAL | ?wxITEM_CHECK | ?wxITEM_RADIO
| ?wxITEM_MAX

`getLabel(This::wxMenuItem()) -> string()`

See external documentation.

`getLabelFromText(Text::string()) -> string()`

See external documentation.

`getMenu(This::wxMenuItem()) -> wxMenu() (see module wxMenu)`

See external documentation.

`getText(This::wxMenuItem()) -> string()`

See external documentation.

`getSubMenu(This::wxMenuItem()) -> wxMenu() (see module wxMenu)`

See external documentation.

`isCheckable(This::wxMenuItem()) -> bool()`

See external documentation.

`isChecked(This::wxMenuItem()) -> bool()`

See external documentation.

`isEnabled(This::wxMenuItem()) -> bool()`

See external documentation.

`isSeparator(This::wxMenuItem()) -> bool()`

See external documentation.

`isSubMenu(This::wxMenuItem()) -> bool()`

See external documentation.

`setBitmap(This::wxMenuItem(), Bitmap::wxBitmap() (see module wxBitmap)) -> ok`

See external documentation.

`setHelp(This::wxMenuItem(), Str::string()) -> ok`

See external documentation.

`setMenu(This::wxMenuItem(), Menu::wxMenu() (see module wxMenu)) -> ok`

See external documentation.

`setSubMenu(This::wxMenuItem(), Menu::wxMenu() (see module wxMenu)) -> ok`

See external documentation.

`setText(This::wxMenuItem(), Str::string()) -> ok`

See external documentation.

`destroy(This::wxMenuItem()) -> ok`

Destroys this object, do not use object again

wxMessageDialog

Erlang module

See external documentation: **wxMessageDialog**.

This class is derived (and can use functions) from:

wxDialog

wxTopLevelWindow

wxWindow

wxEvtHandler

DATA TYPES

`wxMessageDialog()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

```
new(Parent::wxWindow() (see module wxWindow), Message::string()) ->  
wxMessageDialog()
```

Equivalent to `new(Parent, Message, [])`.

```
new(Parent::wxWindow() (see module wxWindow), Message::string(), Options:::  
[Option]) -> wxMessageDialog()
```

Types:

Option = {caption, string()} | {style, integer()} | {pos, {X::integer(), Y::integer()}}

See external documentation.

```
destroy(This::wxMessageDialog()) -> ok
```

Destroys this object, do not use object again

wxMiniFrame

Erlang module

See external documentation: **wxMiniFrame**.

This class is derived (and can use functions) from:

wxFrame

wxTopLevelWindow

wxWindow

wxEvtHandler

DATA TYPES

`wxMiniFrame()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxMiniFrame()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Title::string())
-> wxMiniFrame()`

Equivalent to `new(Parent, Id, Title, [])`.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Title::string(),
Options::[Option]) -> wxMiniFrame()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`create(This::wxMiniFrame(), Parent::wxWindow() (see module wxWindow),
Id::integer(), Title::string()) -> bool()`

Equivalent to `create(This, Parent, Id, Title, [])`.

`create(This::wxMiniFrame(), Parent::wxWindow() (see module wxWindow),
Id::integer(), Title::string(), Options::[Option]) -> bool()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`destroy(This::wxMiniFrame()) -> ok`

Destroys this object, do not use object again

wxMirrorDC

Erlang module

See external documentation: **wxMirrorDC**.

This class is derived (and can use functions) from:
wxDC

DATA TYPES

`wxMirrorDC()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new(Dc::wxDC() (see module wxDC), Mirror::bool()) -> wxMirrorDC()`

See external documentation.

`destroy(This::wxMirrorDC()) -> ok`

Destroys this object, do not use object again

wxMouseCaptureChangedEvent

Erlang module

See external documentation: **wxMouseCaptureChangedEvent**.

Use *wxEvtHandler:connect/3* with EventType:

mouse_capture_changed

See also the message variant *#wxMouseCaptureChanged{}* event record type.

This class is derived (and can use functions) from:

wxEvent

DATA TYPES

`wxMouseCaptureChangedEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparsion stored on disc or distributed for use on other nodes.

Exports

`getCapturedWindow(This::wxMouseCaptureChangedEvent()) -> wxWindow()` (see module `wxWindow`)

See external documentation.

wxMouseEvent

Erlang module

See external documentation: **wxMouseEvent**.

Use *wxEvtHandler:connect/3* with EventType:

left_down, left_up, middle_down, middle_up, right_down, right_up, motion, enter_window, leave_window, left_dclick, middle_dclick, right_dclick, mousewheel, nc_left_down, nc_left_up, nc_middle_down, nc_middle_up, nc_right_down, nc_right_up, nc_motion, nc_enter_window, nc_leave_window, nc_left_dclick, nc_middle_dclick, nc_right_dclick

See also the message variant *#wxMouse{}* event record type.

This class is derived (and can use functions) from:

wxEvent

DATA TYPES

`wxMouseEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparsion stored on disc or distributed for use on other nodes.

Exports

`altDown(This::wxMouseEvent()) -> bool()`

See external documentation.

`button(This::wxMouseEvent(), But::integer()) -> bool()`

See external documentation.

`buttonDClick(This::wxMouseEvent()) -> bool()`

Equivalent to *buttonDClick(This, [])*.

`buttonDClick(This::wxMouseEvent(), Options::[Option]) -> bool()`

Types:

Option = {but, integer()}

See external documentation.

`buttonDown(This::wxMouseEvent()) -> bool()`

Equivalent to *buttonDown(This, [])*.

`buttonDown(This::wxMouseEvent(), Options::[Option]) -> bool()`

Types:

Option = {but, integer()}

See external documentation.

`buttonUp(This::wxMouseEvent()) -> bool()`

Equivalent to `buttonUp(This, [])`.

`buttonUp(This::wxMouseEvent(), Options::[Option]) -> bool()`

Types:

`Option = {but, integer()}`

See external documentation.

`cmdDown(This::wxMouseEvent()) -> bool()`

See external documentation.

`controlDown(This::wxMouseEvent()) -> bool()`

See external documentation.

`dragging(This::wxMouseEvent()) -> bool()`

See external documentation.

`entering(This::wxMouseEvent()) -> bool()`

See external documentation.

`getButton(This::wxMouseEvent()) -> integer()`

See external documentation.

`getPosition(This::wxMouseEvent()) -> {X::integer(), Y::integer()}`

See external documentation.

`getLogicalPosition(This::wxMouseEvent(), Dc::wxDC() (see module wxDC)) -> {X::integer(), Y::integer()}`

See external documentation.

`getLinesPerAction(This::wxMouseEvent()) -> integer()`

See external documentation.

`getWheelRotation(This::wxMouseEvent()) -> integer()`

See external documentation.

`getWheelDelta(This::wxMouseEvent()) -> integer()`

See external documentation.

`getX(This::wxMouseEvent()) -> integer()`

See external documentation.

`getY(This::wxMouseEvent()) -> integer()`

See external documentation.

`isButton(This::wxMouseEvent()) -> bool()`

See external documentation.

`isPageScroll(This::wxMouseEvent()) -> bool()`

See external documentation.

`leaving(This::wxMouseEvent()) -> bool()`

See external documentation.

`leftDClick(This::wxMouseEvent()) -> bool()`

See external documentation.

`leftDown(This::wxMouseEvent()) -> bool()`

See external documentation.

`leftIsDown(This::wxMouseEvent()) -> bool()`

See external documentation.

`leftUp(This::wxMouseEvent()) -> bool()`

See external documentation.

`metaDown(This::wxMouseEvent()) -> bool()`

See external documentation.

`middleDClick(This::wxMouseEvent()) -> bool()`

See external documentation.

`middleDown(This::wxMouseEvent()) -> bool()`

See external documentation.

`middleIsDown(This::wxMouseEvent()) -> bool()`

See external documentation.

`middleUp(This::wxMouseEvent()) -> bool()`

See external documentation.

`moving(This::wxMouseEvent()) -> bool()`

See external documentation.

rightDClick(This::wxMouseEvent()) -> bool()

See [external documentation](#).

rightDown(This::wxMouseEvent()) -> bool()

See [external documentation](#).

rightIsDown(This::wxMouseEvent()) -> bool()

See [external documentation](#).

rightUp(This::wxMouseEvent()) -> bool()

See [external documentation](#).

shiftDown(This::wxMouseEvent()) -> bool()

See [external documentation](#).

wxMoveEvent

Erlang module

See external documentation: **wxMoveEvent**.

Use *wxEvtHandler:connect/3* with EventType:

move

See also the message variant *#wxMove{}* event record type.

This class is derived (and can use functions) from:

wxEvent

DATA TYPES

`wxMoveEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`getPosition(This::wxMoveEvent()) -> {X::integer(), Y::integer()}`

See **external documentation**.

wxMultiChoiceDialog

Erlang module

See external documentation: **wxMultiChoiceDialog**.

This class is derived (and can use functions) from:

wxDialog

wxTopLevelWindow

wxWindow

wxEvtHandler

DATA TYPES

`wxMultiChoiceDialog()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxMultiChoiceDialog()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Message::string(),
Caption::string(), Choices::[[string()]]) -> wxMultiChoiceDialog()`

Equivalent to `new(Parent, Message, Caption, Choices, [])`.

`new(Parent::wxWindow() (see module wxWindow), Message::string(),
Caption::string(), Choices::[[string()]], Options::[Option]) ->
wxMultiChoiceDialog()`

Types:

Option = {style, integer()} | {pos, {X::integer(), Y::integer()}}

See external documentation.

`getSelections(This::wxMultiChoiceDialog()) -> [integer()]`

See external documentation.

`setSelections(This::wxMultiChoiceDialog(), Selections::[integer()]) -> ok`

See external documentation.

`destroy(This::wxMultiChoiceDialog()) -> ok`

Destroys this object, do not use object again

wxNavigationKeyEvent

Erlang module

See external documentation: **wxNavigationKeyEvent**.

Use *wxEvtHandler:connect/3* with EventType:

navigation_key

See also the message variant *#wxNavigationKey{}* event record type.

This class is derived (and can use functions) from:

wxEvent

DATA TYPES

`wxNavigationKeyEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`getDirection(This::wxNavigationKeyEvent()) -> bool()`

See external documentation.

`setDirection(This::wxNavigationKeyEvent(), BForward::bool()) -> ok`

See external documentation.

`isWindowChange(This::wxNavigationKeyEvent()) -> bool()`

See external documentation.

`setWindowChange(This::wxNavigationKeyEvent(), BIs::bool()) -> ok`

See external documentation.

`isFromTab(This::wxNavigationKeyEvent()) -> bool()`

See external documentation.

`setFromTab(This::wxNavigationKeyEvent(), BIs::bool()) -> ok`

See external documentation.

`getCurrentFocus(This::wxNavigationKeyEvent()) -> wxWindow() (see module wxWindow)`

See external documentation.

`setCurrentFocus(This::wxNavigationKeyEvent(), Win::wxWindow() (see module wxWindow)) -> ok`

See external documentation.

wxNcPaintEvent

Erlang module

See external documentation: **wxNcPaintEvent**.

Use *wxEvtHandler:connect/3* with EventType:

nc_paint

See also the message variant *#wxNcPaint{}* event record type.

This class is derived (and can use functions) from:

wxEvent

DATA TYPES

`wxNcPaintEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparsion stored on disc or distributed for use on other nodes.

wxNotebook

Erlang module

See external documentation: **wxNotebook**.

This class is derived (and can use functions) from:

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxNotebook()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxNotebook()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Winid::integer()) -> wxNotebook()`

Equivalent to `new(Parent, Winid, [])`.

`new(Parent::wxWindow() (see module wxWindow), Winid::integer(), Options::[Option]) -> wxNotebook()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`addPage(This::wxNotebook(), Page::wxWindow() (see module wxWindow), Text::string()) -> bool()`

Equivalent to `addPage(This, Page, Text, [])`.

`addPage(This::wxNotebook(), Page::wxWindow() (see module wxWindow), Text::string(), Options::[Option]) -> bool()`

Types:

Option = {bSelect, bool()} | {imageId, integer()}

See external documentation.

`advanceSelection(This::wxNotebook()) -> ok`

Equivalent to `advanceSelection(This, [])`.

`advanceSelection(This::wxNotebook(), Options::[Option]) -> ok`

Types:

`Option = {forward, bool()}`

See external documentation.

`assignImageList(This::wxNotebook(), ImageList::wxImageList() (see module wxImageList)) -> ok`

See external documentation.

`create(This::wxNotebook(), Parent::wxWindow() (see module wxWindow), Id::integer()) -> bool()`

Equivalent to `create(This, Parent, Id, [])`.

`create(This::wxNotebook(), Parent::wxWindow() (see module wxWindow), Id::integer(), Options::[Option]) -> bool()`

Types:

`Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}`

See external documentation.

`deleteAllPages(This::wxNotebook()) -> bool()`

See external documentation.

`deletePage(This::wxNotebook(), NPage::integer()) -> bool()`

See external documentation.

`removePage(This::wxNotebook(), NPage::integer()) -> bool()`

See external documentation.

`getCurrentPage(This::wxNotebook()) -> wxWindow() (see module wxWindow)`

See external documentation.

`getImageList(This::wxNotebook()) -> wxImageList() (see module wxImageList)`

See external documentation.

`getPage(This::wxNotebook(), N::integer()) -> wxWindow() (see module wxWindow)`

See external documentation.

`getPageCount(This::wxNotebook()) -> integer()`

See external documentation.

`getPageImage(This::wxNotebook(), NPage::integer()) -> integer()`

See external documentation.

`getPageText(This::wxNotebook(), NPage::integer()) -> string()`

See external documentation.

`getRowCount(This::wxNotebook()) -> integer()`

See external documentation.

`getSelection(This::wxNotebook()) -> integer()`

See external documentation.

`getThemeBackgroundColour(This::wxNotebook()) -> colour() (see module wx)`

See external documentation.

`hitTest(This::wxNotebook(), Pt::{X::integer(), Y::integer()}) -> {integer(),
Flags::integer()}`

See external documentation.

`insertPage(This::wxNotebook(), Position::integer(), Win::wxWindow() (see
module wxWindow), StrText::string()) -> bool()`

Equivalent to *insertPage(This, Position, Win, StrText, [])*.

`insertPage(This::wxNotebook(), Position::integer(), Win::wxWindow() (see
module wxWindow), StrText::string(), Options::[Option]) -> bool()`

Types:

`Option = {bSelect, bool()} | {imageId, integer()}`

See external documentation.

`setImageList(This::wxNotebook(), ImageList::wxImageList() (see module
wxImageList)) -> ok`

See external documentation.

`setPadding(This::wxNotebook(), Padding::{W::integer(), H::integer()}) -> ok`

See external documentation.

`setPageSize(This::wxNotebook(), Size::{W::integer(), H::integer()}) -> ok`

See external documentation.

`setPageImage(This::wxNotebook(), NPage::integer(), NImage::integer()) ->
bool()`

See external documentation.

`setPageText(This::wxNotebook(), NPage::integer(), StrText::string()) ->
bool()`

See external documentation.

wxNotebook

setSelection(This::wxNotebook(), NPage::integer()) -> integer()

See **external documentation**.

changeSelection(This::wxNotebook(), NPage::integer()) -> integer()

See **external documentation**.

destroy(This::wxNotebook()) -> ok

Destroys this object, do not use object again

wxNotebookEvent

Erlang module

See external documentation: **wxNotebookEvent**.

Use *wxEvtHandler:connect/3* with EventType:

command_notebook_page_changed, command_notebook_page_changing

See also the message variant *#wxNotebook{}* event record type.

This class is derived (and can use functions) from:

wxNotifyEvent

wxCommandEvent

wxEvent

DATA TYPES

`wxNotebookEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparsion stored on disc or distributed for use on other nodes.

Exports

`getOldSelection(This::wxNotebookEvent()) -> integer()`

See external documentation.

`getSelection(This::wxNotebookEvent()) -> integer()`

See external documentation.

`setOldSelection(This::wxNotebookEvent(), NOldSel::integer()) -> ok`

See external documentation.

`setSelection(This::wxNotebookEvent(), NSel::integer()) -> ok`

See external documentation.

wxNotifyEvent

Erlang module

See external documentation: **wxNotifyEvent**.

This class is derived (and can use functions) from:

wxCommandEvent

wxEvent

DATA TYPES

`wxNotifyEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`allow(This::wxNotifyEvent()) -> ok`

See **external documentation**.

`isAllowed(This::wxNotifyEvent()) -> bool()`

See **external documentation**.

`veto(This::wxNotifyEvent()) -> ok`

See **external documentation**.

wxPageSetupDialogData

Erlang module

See external documentation: **wxPageSetupDialogData**.

DATA TYPES

`wxPageSetupDialogData()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxPageSetupDialogData()`

See external documentation.

`new(PrintData::wxPrintData() (see module wxPrintData) |
wxPageSetupDialogData()) -> wxPageSetupDialogData()`

See external documentation.

`enableHelp(This::wxPageSetupDialogData(), Flag::bool()) -> ok`

See external documentation.

`enableMargins(This::wxPageSetupDialogData(), Flag::bool()) -> ok`

See external documentation.

`enableOrientation(This::wxPageSetupDialogData(), Flag::bool()) -> ok`

See external documentation.

`enablePaper(This::wxPageSetupDialogData(), Flag::bool()) -> ok`

See external documentation.

`enablePrinter(This::wxPageSetupDialogData(), Flag::bool()) -> ok`

See external documentation.

`getDefaultMinMargins(This::wxPageSetupDialogData()) -> bool()`

See external documentation.

`getEnableMargins(This::wxPageSetupDialogData()) -> bool()`

See external documentation.

`getEnableOrientation(This::wxPageSetupDialogData()) -> bool()`

See external documentation.

`getEnablePaper(This::wxPageSetupDialogData()) -> bool()`

See external documentation.

`getEnablePrinter(This::wxPageSetupDialogData()) -> bool()`

See external documentation.

`getEnableHelp(This::wxPageSetupDialogData()) -> bool()`

See external documentation.

`getDefaultInfo(This::wxPageSetupDialogData()) -> bool()`

See external documentation.

`getMarginTopLeft(This::wxPageSetupDialogData()) -> {X::integer(),
Y::integer()}`

See external documentation.

`getMarginBottomRight(This::wxPageSetupDialogData()) -> {X::integer(),
Y::integer()}`

See external documentation.

`getMinMarginTopLeft(This::wxPageSetupDialogData()) -> {X::integer(),
Y::integer()}`

See external documentation.

`getMinMarginBottomRight(This::wxPageSetupDialogData()) -> {X::integer(),
Y::integer()}`

See external documentation.

`getPaperId(This::wxPageSetupDialogData()) -> integer()`

See external documentation.

`getPaperSize(This::wxPageSetupDialogData()) -> {W::integer(), H::integer()}`

See external documentation.

`getPrintData(This::wxPageSetupDialogData()) -> wxPrintData() (see module
wxPrintData)`

See external documentation.

`isOk(This::wxPageSetupDialogData()) -> bool()`

See external documentation.

`setDefaultInfo(This::wxPageSetupDialogData(), Flag::bool()) -> ok`

See external documentation.

setDefaultMinMargins(This::wxPageSetupDialogData(), Flag::bool()) -> ok

See external documentation.

setMarginTopLeft(This::wxPageSetupDialogData(), Pt::{X::integer(), Y::integer()}) -> ok

See external documentation.

setMarginBottomRight(This::wxPageSetupDialogData(), Pt::{X::integer(), Y::integer()}) -> ok

See external documentation.

setMinMarginTopLeft(This::wxPageSetupDialogData(), Pt::{X::integer(), Y::integer()}) -> ok

See external documentation.

setMinMarginBottomRight(This::wxPageSetupDialogData(), Pt::{X::integer(), Y::integer()}) -> ok

See external documentation.

setPaperId(This::wxPageSetupDialogData(), Id::integer()) -> ok

See external documentation.

setPaperSize(This::wxPageSetupDialogData(), X::integer() | term()) -> ok

See external documentation.

Alternatives:

setPaperSize(This::wxPageSetupDialogData(), Id::integer()) -> ok

setPaperSize(This::wxPageSetupDialogData(), Sz::{W::integer(), H::integer()}) -> ok

setPrintData(This::wxPageSetupDialogData(), PrintData::wxPrintData() (see module wxPrintData)) -> ok

See external documentation.

destroy(This::wxPageSetupDialogData()) -> ok

Destroys this object, do not use object again

wxPageSetupDialog

Erlang module

See external documentation: **wxPageSetupDialog**.

DATA TYPES

`wxPageSetupDialog()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new(Parent::wxWindow() (see module wxWindow)) -> wxPageSetupDialog()`

Equivalent to `new(Parent, [])`.

`new(Parent::wxWindow() (see module wxWindow), Options::[Option]) -> wxPageSetupDialog()`

Types:

`Option = {data, wxPageSetupDialogData() (see module wxPageSetupDialogData)}`

See external documentation.

`getPageSetupData(This::wxPageSetupDialog()) -> wxPageSetupDialogData() (see module wxPageSetupDialogData)`

See external documentation.

`showModal(This::wxPageSetupDialog()) -> integer()`

See external documentation.

`destroy(This::wxPageSetupDialog()) -> ok`

Destroys this object, do not use object again

wxPaintDC

Erlang module

See external documentation: **wxPaintDC**.

This class is derived (and can use functions) from:

wxWindowDC

wxDC

DATA TYPES

`wxPaintDC()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new()` -> **`wxPaintDC()`**

See external documentation.

`new(Win::wxWindow())` (see module **`wxWindow`**) -> **`wxPaintDC()`**

See external documentation.

`destroy(This::wxPaintDC())` -> **`ok`**

Destroys this object, do not use object again

wxPaintEvent

Erlang module

See external documentation: **wxPaintEvent**.

Use *wxEvtHandler:connect/3* with EventType:

paint, paint_icon

See also the message variant *#wxPaint{}* event record type.

This class is derived (and can use functions) from:

wxEvent

DATA TYPES

wxPaintEvent()

An object reference, The representation is internal and can be changed without notice. It can't be used for comparsion stored on disc or distributed for use on other nodes.

wxPaletteChangedEvent

Erlang module

See external documentation: **wxPaletteChangedEvent**.

Use *wxEvtHandler:connect/3* with EventType:

palette_changed

See also the message variant *#wxPaletteChanged{}* event record type.

This class is derived (and can use functions) from:

wxEvent

DATA TYPES

`wxPaletteChangedEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`setChangedWindow(This::wxPaletteChangedEvent(), Win:wxWindow()) (see module wxWindow) -> ok`

See external documentation.

`getChangedWindow(This::wxPaletteChangedEvent()) -> wxWindow() (see module wxWindow)`

See external documentation.

wxPalette

Erlang module

See external documentation: **wxPalette**.

DATA TYPES

`wxPalette()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxPalette()`

See external documentation.

`new(Red::binary(), Green::binary(), Blue::binary()) -> wxPalette()`

See external documentation.

`create(This::wxPalette(), Red::binary(), Green::binary(), Blue::binary()) -> bool()`

See external documentation.

`getColoursCount(This::wxPalette()) -> integer()`

See external documentation.

`getPixel(This::wxPalette(), Red::integer(), Green::integer(), Blue::integer()) -> integer()`

See external documentation.

`getRGB(This::wxPalette(), Pixel::integer()) -> {bool(), Red::integer(), Green::integer(), Blue::integer()}`

See external documentation.

`isOk(This::wxPalette()) -> bool()`

See external documentation.

`destroy(This::wxPalette()) -> ok`

Destroys this object, do not use object again

wxPanel

Erlang module

See external documentation: **wxPanel**.

This class is derived (and can use functions) from:

wxWindow

wxEvtHandler

DATA TYPES

`wxPanel()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxPanel()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow)) -> wxPanel()`

Equivalent to `new(Parent, [])`.

`new(Parent::wxWindow() (see module wxWindow), Options::[Option]) -> wxPanel()`

Types:

Option = {winid, integer()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), X::integer(), Y::integer(), Width::integer(), Height::integer()) -> wxPanel()`

Equivalent to `new(Parent, X, Y, Width, Height, [])`.

`new(Parent::wxWindow() (see module wxWindow), X::integer(), Y::integer(), Width::integer(), Height::integer(), Options::[Option]) -> wxPanel()`

Types:

Option = {style, integer()}

See external documentation.

`initDialog(This::wxPanel()) -> ok`

See external documentation.

`destroy(This::wxPanel()) -> ok`

Destroys this object, do not use object again

wxPasswordEntryDialog

Erlang module

See external documentation: **wxPasswordEntryDialog**.

This class is derived (and can use functions) from:

wxTextEntryDialog

wxDialog

wxTopLevelWindow

wxWindow

wxEvtHandler

DATA TYPES

`wxPasswordEntryDialog()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new(Parent::wxWindow() (see module wxWindow), Message::string()) -> wxPasswordEntryDialog()`

Equivalent to `new(Parent, Message, [])`.

`new(Parent::wxWindow() (see module wxWindow), Message::string(), Options::[Option]) -> wxPasswordEntryDialog()`

Types:

Option = {caption, string()} | {value, string()} | {style, integer()} | {pos, {X::integer(), Y::integer()}}

See external documentation.

`destroy(This::wxPasswordEntryDialog()) -> ok`

Destroys this object, do not use object again

wxPen

Erlang module

See external documentation: **wxPen**.

DATA TYPES

`wxPen()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxPen()`

See external documentation.

`new(Colour::colour() (see module wx)) -> wxPen()`

Equivalent to `new(Colour, [])`.

`new(Colour::colour() (see module wx), Options::[Option]) -> wxPen()`

Types:

`Option = {width, integer()} | {style, integer()}`

See external documentation.

`getCap(This::wxPen()) -> integer()`

See external documentation.

`getColour(This::wxPen()) -> colour() (see module wx)`

See external documentation.

`getJoin(This::wxPen()) -> integer()`

See external documentation.

`getStyle(This::wxPen()) -> integer()`

See external documentation.

`getWidth(This::wxPen()) -> integer()`

See external documentation.

`isOk(This::wxPen()) -> bool()`

See external documentation.

`setCap(This::wxPen(), CapStyle::integer()) -> ok`

See external documentation.

`setColour(This::wxPen(), Colour::colour() (see module wx)) -> ok`

See external documentation.

`setColour(This::wxPen(), Red::integer(), Green::integer(), Blue::integer()) -> ok`

See external documentation.

`setJoin(This::wxPen(), JoinStyle::integer()) -> ok`

See external documentation.

`setStyle(This::wxPen(), Style::integer()) -> ok`

See external documentation.

`setWidth(This::wxPen(), Width::integer()) -> ok`

See external documentation.

`destroy(This::wxPen()) -> ok`

Destroys this object, do not use object again

wxPickerBase

Erlang module

See external documentation: **wxPickerBase**.

This class is derived (and can use functions) from:

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxPickerBase()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`setInternalMargin(This::wxPickerBase(), Newmargin::integer()) -> ok`

See external documentation.

`getInternalMargin(This::wxPickerBase()) -> integer()`

See external documentation.

`setTextCtrlProportion(This::wxPickerBase(), Prop::integer()) -> ok`

See external documentation.

`setPickerCtrlProportion(This::wxPickerBase(), Prop::integer()) -> ok`

See external documentation.

`getTextCtrlProportion(This::wxPickerBase()) -> integer()`

See external documentation.

`getPickerCtrlProportion(This::wxPickerBase()) -> integer()`

See external documentation.

`hasTextCtrl(This::wxPickerBase()) -> bool()`

See external documentation.

`getTextCtrl(This::wxPickerBase()) -> wxTextCtrl() (see module wxTextCtrl)`

See external documentation.

`isTextCtrlGrowable(This::wxPickerBase()) -> bool()`

See external documentation.

setPickerCtrlGrowable(This::wxPickerBase()) -> ok

Equivalent to *setPickerCtrlGrowable(This, [])*.

setPickerCtrlGrowable(This::wxPickerBase(), Options::[Option]) -> ok

Types:

Option = {grow, bool()}

See **external documentation**.

setTextCtrlGrowable(This::wxPickerBase()) -> ok

Equivalent to *setTextCtrlGrowable(This, [])*.

setTextCtrlGrowable(This::wxPickerBase(), Options::[Option]) -> ok

Types:

Option = {grow, bool()}

See **external documentation**.

isPickerCtrlGrowable(This::wxPickerBase()) -> bool()

See **external documentation**.

wxPostScriptDC

Erlang module

See external documentation: **wxPostScriptDC**.

This class is derived (and can use functions) from:
wxDC

DATA TYPES

`wxPostScriptDC()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new()` -> **`wxPostScriptDC()`**

See external documentation.

`new(PrintData::wxPrintData())` (see module `wxPrintData`) -> **`wxPostScriptDC()`**

See external documentation.

`setResolution(Ppi::integer())` -> **`ok`**

See external documentation.

`getResolution()` -> **`integer()`**

See external documentation.

`destroy(This::wxPostScriptDC())` -> **`ok`**

Destroys this object, do not use object again

wxPreviewCanvas

Erlang module

See external documentation: **wxPreviewCanvas**.

This class is derived (and can use functions) from:

wxScrolledWindow

wxPanel

wxWindow

wxEvtHandler

DATA TYPES

`wxPreviewCanvas()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

wxPreviewControlBar

Erlang module

See external documentation: **wxPreviewControlBar**.

This class is derived (and can use functions) from:

wxPanel

wxWindow

wxEvtHandler

DATA TYPES

`wxPreviewControlBar()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

```
new(Preview::wxPrintPreview() (see module wxPrintPreview),
Buttons::integer(), Parent::wxWindow() (see module wxWindow)) ->
wxPreviewControlBar()
```

Equivalent to `new(Preview, Buttons, Parent, [])`.

```
new(Preview::wxPrintPreview() (see module wxPrintPreview),
Buttons::integer(), Parent::wxWindow() (see module wxWindow), Options::
[Option]) -> wxPreviewControlBar()
```

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

```
createButtons(This::wxPreviewControlBar()) -> ok
```

See external documentation.

```
getPrintPreview(This::wxPreviewControlBar()) -> wxPrintPreview() (see module
wxPrintPreview)
```

See external documentation.

```
getZoomControl(This::wxPreviewControlBar()) -> integer()
```

See external documentation.

```
setZoomControl(This::wxPreviewControlBar(), Zoom::integer()) -> ok
```

See external documentation.

```
destroy(This::wxPreviewControlBar()) -> ok
```

Destroys this object, do not use object again

wxPreviewFrame

Erlang module

See external documentation: **wxPreviewFrame**.

This class is derived (and can use functions) from:

wxFrame

wxTopLevelWindow

wxWindow

wxEvtHandler

DATA TYPES

`wxPreviewFrame()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new(Preview::wxPrintPreview() (see module wxPrintPreview), Parent::wxWindow() (see module wxWindow)) -> wxPreviewFrame()`

Equivalent to `new(Preview, Parent, [])`.

`new(Preview::wxPrintPreview() (see module wxPrintPreview), Parent::wxWindow() (see module wxWindow), Options::[Option]) -> wxPreviewFrame()`

Types:

Option = {title, string()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`createControlBar(This::wxPreviewFrame()) -> ok`

See external documentation.

`createCanvas(This::wxPreviewFrame()) -> ok`

See external documentation.

`initialize(This::wxPreviewFrame()) -> ok`

See external documentation.

`onCloseWindow(This::wxPreviewFrame(), Event::wxCloseEvent() (see module wxCloseEvent)) -> ok`

See external documentation.

`destroy(This::wxPreviewFrame()) -> ok`

Destroys this object, do not use object again

wxPrintData

Erlang module

See external documentation: **wxPrintData**.

DATA TYPES

`wxPrintData()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxPrintData()`

See external documentation.

`new(PrintData::wxPrintData()) -> wxPrintData()`

See external documentation.

`getCollate(This::wxPrintData()) -> bool()`

See external documentation.

`getBin(This::wxPrintData()) -> WxPrintBin`

Types:

WxPrintBin = integer()

See external documentation.

WxPrintBin is one of ?wxPRINTBIN_DEFAULT | ?wxPRINTBIN_ONLYONE | ?wxPRINTBIN_LOWER | ?wxPRINTBIN_MIDDLE | ?wxPRINTBIN_MANUAL | ?wxPRINTBIN_ENVELOPE | ?wxPRINTBIN_ENVMANUAL | ?wxPRINTBIN_AUTO | ?wxPRINTBIN_TRACTOR | ?wxPRINTBIN_SMALLFMT | ?wxPRINTBIN_LARGEFORMAT | ?wxPRINTBIN_LARGECAPACITY | ?wxPRINTBIN_CASSETTE | ?wxPRINTBIN_FORMSOURCE | ?wxPRINTBIN_USER

`getColour(This::wxPrintData()) -> bool()`

See external documentation.

`getDuplex(This::wxPrintData()) -> WxDuplexMode`

Types:

WxDuplexMode = integer()

See external documentation.

WxDuplexMode is one of ?wxDUPLEX_SIMPLEX | ?wxDUPLEX_HORIZONTAL | ?wxDUPLEX_VERTICAL

`getNoCopies(This::wxPrintData()) -> integer()`

See external documentation.

getOrientation(This::wxPrintData()) -> integer()

See external documentation.

getPaperId(This::wxPrintData()) -> integer()

See external documentation.

getPrinterName(This::wxPrintData()) -> string()

See external documentation.

getQuality(This::wxPrintData()) -> integer()

See external documentation.

isOk(This::wxPrintData()) -> bool()

See external documentation.

setBin(This::wxPrintData(), Bin::WxPrintBin) -> ok

Types:

WxPrintBin = integer()

See external documentation.

WxPrintBin is one of ?wxPRINTBIN_DEFAULT | ?wxPRINTBIN_ONLYONE | ?wxPRINTBIN_LOWER | ?wxPRINTBIN_MIDDLE | ?wxPRINTBIN_MANUAL | ?wxPRINTBIN_ENVELOPE | ?wxPRINTBIN_ENVMANUAL | ?wxPRINTBIN_AUTO | ?wxPRINTBIN_TRACTOR | ?wxPRINTBIN_SMALLFMT | ?wxPRINTBIN_LARGEFORMAT | ?wxPRINTBIN_LARGECAPACITY | ?wxPRINTBIN_CASSETTE | ?wxPRINTBIN_FORMSOURCE | ?wxPRINTBIN_USER

setCollate(This::wxPrintData(), Flag::bool()) -> ok

See external documentation.

setColour(This::wxPrintData(), Colour::bool()) -> ok

See external documentation.

setDuplex(This::wxPrintData(), Duplex::WxDuplexMode) -> ok

Types:

WxDuplexMode = integer()

See external documentation.

WxDuplexMode is one of ?wxDUPLEX_SIMPLEX | ?wxDUPLEX_HORIZONTAL | ?wxDUPLEX_VERTICAL

setNoCopies(This::wxPrintData(), V::integer()) -> ok

See external documentation.

setOrientation(This::wxPrintData(), Orient::integer()) -> ok

See external documentation.

setPaperId(This::wxPrintData(), SizeId::integer()) -> ok

See external documentation.

setPrinterName(This::wxPrintData(), Name::string()) -> ok

See external documentation.

setQuality(This::wxPrintData(), Quality::integer()) -> ok

See external documentation.

destroy(This::wxPrintData()) -> ok

Destroys this object, do not use object again

wxPrintDialogData

Erlang module

See external documentation: **wxPrintDialogData**.

DATA TYPES

`wxPrintDialogData()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxPrintDialogData()`

See external documentation.

`new(DialogData::wxPrintDialogData() | wxPrintData() (see module wxPrintData))
-> wxPrintDialogData()`

See external documentation.

`enableHelp(This::wxPrintDialogData(), Flag::bool()) -> ok`

See external documentation.

`enablePageNumbers(This::wxPrintDialogData(), Flag::bool()) -> ok`

See external documentation.

`enablePrintToFile(This::wxPrintDialogData(), Flag::bool()) -> ok`

See external documentation.

`enableSelection(This::wxPrintDialogData(), Flag::bool()) -> ok`

See external documentation.

`getAllPages(This::wxPrintDialogData()) -> bool()`

See external documentation.

`getCollate(This::wxPrintDialogData()) -> bool()`

See external documentation.

`getFromPage(This::wxPrintDialogData()) -> integer()`

See external documentation.

`getMaxPage(This::wxPrintDialogData()) -> integer()`

See external documentation.

`getMinPage(This::wxPrintDialogData()) -> integer()`

See external documentation.

`getNoCopies(This::wxPrintDialogData()) -> integer()`

See external documentation.

`getPrintData(This::wxPrintDialogData()) -> wxPrintData()` (see module `wxPrintData`)

See external documentation.

`getPrintToFile(This::wxPrintDialogData()) -> bool()`

See external documentation.

`getSelection(This::wxPrintDialogData()) -> bool()`

See external documentation.

`getToPage(This::wxPrintDialogData()) -> integer()`

See external documentation.

`isOk(This::wxPrintDialogData()) -> bool()`

See external documentation.

`setCollate(This::wxPrintDialogData(), Flag::bool()) -> ok`

See external documentation.

`setFromPage(This::wxPrintDialogData(), V::integer()) -> ok`

See external documentation.

`setMaxPage(This::wxPrintDialogData(), V::integer()) -> ok`

See external documentation.

`setMinPage(This::wxPrintDialogData(), V::integer()) -> ok`

See external documentation.

`setNoCopies(This::wxPrintDialogData(), V::integer()) -> ok`

See external documentation.

`setPrintData(This::wxPrintDialogData(), PrintData::wxPrintData())` (see module `wxPrintData`) -> ok

See external documentation.

`setPrintToFile(This::wxPrintDialogData(), Flag::bool()) -> ok`

See external documentation.

wxPrintDialogData

setSelection(This::wxPrintDialogData(), Flag::bool()) -> ok

See **external documentation**.

setToPage(This::wxPrintDialogData(), V::integer()) -> ok

See **external documentation**.

destroy(This::wxPrintDialogData()) -> ok

Destroys this object, do not use object again

wxPrintDialog

Erlang module

See external documentation: **wxPrintDialog**.

This class is derived (and can use functions) from:

wxDialog

wxTopLevelWindow

wxWindow

wxEvtHandler

DATA TYPES

`wxPrintDialog()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new(Parent::wxWindow() (see module wxWindow)) -> wxPrintDialog()`

Equivalent to `new(Parent, [])`.

`new(Parent::wxWindow() (see module wxWindow), X::term()) -> wxPrintDialog()`

See external documentation.

Alternatives:

`new(Parent::wxWindow:wxWindow(), [Option]) -> wxPrintDialog()`

Option = {data, wxPrintDialogData:wxPrintDialogData()}

`new(Parent::wxWindow:wxWindow(), Data::wxPrintData:wxPrintData()) -> wxPrintDialog()`

`getPrintDialogData(This::wxPrintDialog()) -> wxPrintDialogData() (see module wxPrintDialogData)`

See external documentation.

`getPrintDC(This::wxPrintDialog()) -> wxDC() (see module wxDC)`

See external documentation.

`destroy(This::wxPrintDialog()) -> ok`

Destroys this object, do not use object again

wxPrinter

Erlang module

See external documentation: **wxPrinter**.

DATA TYPES

`wxPrinter()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxPrinter()`

Equivalent to `new([])`.

`new(Options::[Option]) -> wxPrinter()`

Types:

Option = {data, wxPrintDialogData() (see module wxPrintDialogData)}

See external documentation.

`createAbortWindow(This::wxPrinter(), Parent::wxWindow() (see module wxWindow), Printout::wxPrintout() (see module wxPrintout)) -> wxWindow() (see module wxWindow)`

See external documentation.

`getAbort(This::wxPrinter()) -> bool()`

See external documentation.

`getLastError() -> WxPrinterError`

Types:

WxPrinterError = integer()

See external documentation.

WxPrinterError is one of ?wxPRINTER_NO_ERROR | ?wxPRINTER_CANCELLED | ?wxPRINTER_ERROR

`getPrintDialogData(This::wxPrinter()) -> wxPrintDialogData() (see module wxPrintDialogData)`

See external documentation.

`print(This::wxPrinter(), Parent::wxWindow() (see module wxWindow), Printout::wxPrintout() (see module wxPrintout)) -> bool()`

Equivalent to `print(This, Parent, Printout, [])`.


```
print(This::wxPrinter(), Parent::wxWindow() (see module wxWindow),  
Printout::wxPrintout() (see module wxPrintout), Options::[Option]) -> bool()
```

Types:

Option = {prompt, bool()}

See external documentation.

```
printDialog(This::wxPrinter(), Parent::wxWindow() (see module wxWindow)) ->  
wxDC() (see module wxDC)
```

See external documentation.

```
reportError(This::wxPrinter(), Parent::wxWindow() (see module wxWindow),  
Printout::wxPrintout() (see module wxPrintout), Message::string()) -> ok
```

See external documentation.

```
setup(This::wxPrinter(), Parent::wxWindow() (see module wxWindow)) -> bool()
```

See external documentation.

```
destroy(This::wxPrinter()) -> ok
```

Destroys this object, do not use object again

wxPrintout

Erlang module

See external documentation: **wxPrintout**.

DATA TYPES

`wxPrintout()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new(Title::string(), OnPrintPage::function()) -> wxPrintout()` (see module `wxPrintout`)

@equiv `new(Title, OnPrintPage, [])`

`new(Title::string(), OnPrintPage::function(), Opts::[Option]) -> wxPrintout()` (see module `wxPrintout`)

Types:

Option = {`onPreparePrinting`, `OnPreparePrinting::function()`} | {`onBeginPrinting`, `OnBeginPrinting::function()`} | {`onEndPrinting`, `OnEndPrinting::function()`} | {`onBeginDocument`, `OnBeginDocument::function()`} | {`onEndDocument`, `OnEndDocument::function()`} | {`hasPage`, `HasPage::function()`} | {`getPageInfo`, `GetPageInfo::function()`}

Creates a `wxPrintout` object with a callback fun and optionally other callback funs.

```
OnPrintPage(This,Page) -> boolean()
```

```
OnPreparePrinting(This) -> term()
```

```
OnBeginPrinting(This) -> term()
```

```
OnEndPrinting(This) -> term()
```

```
OnBeginDocument(This,StartPage,EndPage) -> boolean()
```

```
OnEndDocument(This) -> term()
```

```
HasPage(This,Page) -> boolean()
```

```
GetPageInfo(This) -> {MinPage::integer(), MaxPage::integer(), PageFrom::integer(), PageTo::integer() }
```

The *This* argument is the wxPrintout object reference to this object

NOTE: The callbacks may not call other processes.

`getDC(This::wxPrintout()) -> wxDC() (see module wxDC)`

See external documentation.

`getPageSizeMM(This::wxPrintout()) -> {W::integer(), H::integer()}`

See external documentation.

`getPageSizePixels(This::wxPrintout()) -> {W::integer(), H::integer()}`

See external documentation.

`getPaperRectPixels(This::wxPrintout()) -> {X::integer(), Y::integer(),
W::integer(), H::integer()}`

See external documentation.

`getPPIPrinter(This::wxPrintout()) -> {X::integer(), Y::integer()}`

See external documentation.

`getPPIScreen(This::wxPrintout()) -> {X::integer(), Y::integer()}`

See external documentation.

`getTitle(This::wxPrintout()) -> string()`

See external documentation.

`isPreview(This::wxPrintout()) -> bool()`

See external documentation.

`fitThisSizeToPaper(This::wxPrintout(), ImageSize::{W::integer(),
H::integer()}) -> ok`

See external documentation.

`fitThisSizeToPage(This::wxPrintout(), ImageSize::{W::integer(),
H::integer()}) -> ok`

See external documentation.

`fitThisSizeToPageMargins(This::wxPrintout(), ImageSize::{W::integer(),
H::integer()}, PageSetupData::wxPageSetupDialogData() (see module
wxPageSetupDialogData)) -> ok`

See external documentation.

`mapScreenSizeToPaper(This::wxPrintout()) -> ok`

See external documentation.

`mapScreenSizeToPage(This::wxPrintout()) -> ok`

See external documentation.

`mapScreenSizeToPageMargins(This::wxPrintout(),
PageSetupData::wxPageSetupDialogData() (see module wxPageSetupDialogData)) ->
ok`

See external documentation.

`mapScreenSizeToDevice(This::wxPrintout()) -> ok`

See external documentation.

`getLogicalPaperRect(This::wxPrintout()) -> {X::integer(), Y::integer(),
W::integer(), H::integer()}`

See external documentation.

`getLogicalPageRect(This::wxPrintout()) -> {X::integer(), Y::integer(),
W::integer(), H::integer()}`

See external documentation.

`getLogicalPageMarginsRect(This::wxPrintout(),
PageSetupData::wxPageSetupDialogData() (see module wxPageSetupDialogData)) ->
{X::integer(), Y::integer(), W::integer(), H::integer()}`

See external documentation.

`setLogicalOrigin(This::wxPrintout(), X::integer(), Y::integer()) -> ok`

See external documentation.

`offsetLogicalOrigin(This::wxPrintout(), Xoff::integer(), Yoff::integer()) ->
ok`

See external documentation.

`destroy(This::wxPrintout()) -> ok`

Destroys this object, do not use object again

wxPrintPreview

Erlang module

See external documentation: **wxPrintPreview**.

DATA TYPES

`wxPrintPreview()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new(Printout::wxPrintout() (see module wxPrintout)) -> wxPrintPreview()`

Equivalent to `new(Printout, [])`.

`new(Printout::wxPrintout() (see module wxPrintout), Options::[Option]) -> wxPrintPreview()`

Types:

`Option = {printoutForPrinting, wxPrintout() (see module wxPrintout)} | {data, wxPrintDialogData() (see module wxPrintDialogData)}`

See external documentation.

`new(Printout::wxPrintout() (see module wxPrintout),
PrintoutForPrinting::wxPrintout() (see module wxPrintout),
Data::wxPrintData() (see module wxPrintData)) -> wxPrintPreview()`

See external documentation.

`getCanvas(This::wxPrintPreview()) -> wxPreviewCanvas() (see module wxPreviewCanvas)`

See external documentation.

`getCurrentPage(This::wxPrintPreview()) -> integer()`

See external documentation.

`getFrame(This::wxPrintPreview()) -> wxFrame() (see module wxFrame)`

See external documentation.

`getMaxPage(This::wxPrintPreview()) -> integer()`

See external documentation.

`getMinPage(This::wxPrintPreview()) -> integer()`

See external documentation.

`getPrintout(This::wxPrintPreview()) -> wxPrintout()` (see module `wxPrintout`)

See external documentation.

`getPrintoutForPrinting(This::wxPrintPreview()) -> wxPrintout()` (see module `wxPrintout`)

See external documentation.

`isOk(This::wxPrintPreview()) -> bool()`

See external documentation.

`paintPage(This::wxPrintPreview(), Canvas::wxPreviewCanvas() (see module wxPreviewCanvas), Dc::wxDC() (see module wxDC)) -> bool()`

See external documentation.

`print(This::wxPrintPreview(), Interactive::bool()) -> bool()`

See external documentation.

`renderPage(This::wxPrintPreview(), PageNum::integer()) -> bool()`

See external documentation.

`setCanvas(This::wxPrintPreview(), Canvas::wxPreviewCanvas() (see module wxPreviewCanvas)) -> ok`

See external documentation.

`setCurrentPage(This::wxPrintPreview(), PageNum::integer()) -> bool()`

See external documentation.

`setFrame(This::wxPrintPreview(), Frame::wxFrame() (see module wxFrame)) -> ok`

See external documentation.

`setPrintout(This::wxPrintPreview(), Printout::wxPrintout() (see module wxPrintout)) -> ok`

See external documentation.

`setZoom(This::wxPrintPreview(), Percent::integer()) -> ok`

See external documentation.

`destroy(This::wxPrintPreview()) -> ok`

Destroys this object, do not use object again

wxProgressDialog

Erlang module

See external documentation: **wxProgressDialog**.

This class is derived (and can use functions) from:

wxDialog

wxTopLevelWindow

wxWindow

wxEvtHandler

DATA TYPES

`wxProgressDialog()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new(Title::string(), Message::string()) -> wxProgressDialog()`

Equivalent to `new(Title, Message, [])`.

`new(Title::string(), Message::string(), Options::[Option]) -> wxProgressDialog()`

Types:

Option = {maximum, integer()} | {parent, wxWindow() (see module wxWindow)} | {style, integer()}

See external documentation.

`resume(This::wxProgressDialog()) -> ok`

See external documentation.

`update(This::wxProgressDialog()) -> ok`

See external documentation.

`update(This::wxProgressDialog(), Value::integer()) -> bool()`

Equivalent to `update(This, Value, [])`.

`update(This::wxProgressDialog(), Value::integer(), Options::[Option]) -> bool()`

Types:

Option = {newmsg, string()}

See external documentation.

`destroy(This::wxProgressDialog()) -> ok`

Destroys this object, do not use object again

wxQueryNewPaletteEvent

Erlang module

See external documentation: **wxQueryNewPaletteEvent**.

Use *wxEvtHandler:connect/3* with EventType:

query_new_palette

See also the message variant *#wxQueryNewPalette{}* event record type.

This class is derived (and can use functions) from:

wxEvent

DATA TYPES

`wxQueryNewPaletteEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparsion stored on disc or distributed for use on other nodes.

Exports

`setPaletteRealized(This::wxQueryNewPaletteEvent(), Realized::bool()) -> ok`

See external documentation.

`getPaletteRealized(This::wxQueryNewPaletteEvent()) -> bool()`

See external documentation.

wxRadioBox

Erlang module

See external documentation: **wxRadioBox**.

This class is derived (and can use functions) from:

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxRadioBox()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

```
new(Parent::wxWindow() (see module wxWindow), Id::integer(), Title::string(),
Pos::{X::integer(), Y::integer()}, Size::{W::integer(), H::integer()},
Choices:[[string()]]) -> wxRadioBox()
```

Equivalent to `new(Parent, Id, Title, Pos, Size, Choices, [])`.

```
new(Parent::wxWindow() (see module wxWindow), Id::integer(), Title::string(),
Pos::{X::integer(), Y::integer()}, Size::{W::integer(), H::integer()},
Choices:[[string()]], Options:[Option]) -> wxRadioBox()
```

Types:

Option = {majorDim, integer()} | {style, integer()} | {val, wx() (see module wx)}

See external documentation.

```
create(This::wxRadioBox(), Parent::wxWindow() (see module wxWindow),
Id::integer(), Title::string(), Pos::{X::integer(), Y::integer()}, Size::
{W::integer(), H::integer()}, Choices:[[string()]]) -> bool()
```

Equivalent to `create(This, Parent, Id, Title, Pos, Size, Choices, [])`.

```
create(This::wxRadioBox(), Parent::wxWindow() (see module wxWindow),
Id::integer(), Title::string(), Pos::{X::integer(), Y::integer()}, Size::
{W::integer(), H::integer()}, Choices:[[string()]], Options:[Option]) ->
bool()
```

Types:

Option = {majorDim, integer()} | {style, integer()} | {val, wx() (see module wx)}

See external documentation.

```
enable(This::wxRadioBox()) -> bool()
```

Equivalent to `enable(This, [])`.

enable(This::wxRadioBox(), X::integer() | term()) -> bool()

See [external documentation](#).

Alternatives:

enable(This::wxRadioBox(), N::integer()) -> enable(This,N, [])

enable(This::wxRadioBox(), [Option]) -> bool()

Option = {enable, bool()}

enable(This::wxRadioBox(), N::integer(), Options::[Option]) -> bool()

Types:

Option = {enable, bool()}

See [external documentation](#).

getSelection(This::wxRadioBox()) -> integer()

See [external documentation](#).

getString(This::wxRadioBox(), N::integer()) -> string()

See [external documentation](#).

setSelection(This::wxRadioBox(), N::integer()) -> ok

See [external documentation](#).

show(This::wxRadioBox()) -> bool()

Equivalent to *show(This, [])*.

show(This::wxRadioBox(), X::integer() | term()) -> bool()

See [external documentation](#).

Alternatives:

show(This::wxRadioBox(), N::integer()) -> show(This,N, [])

show(This::wxRadioBox(), [Option]) -> bool()

Option = {show, bool()}

show(This::wxRadioBox(), N::integer(), Options::[Option]) -> bool()

Types:

Option = {show, bool()}

See [external documentation](#).

getColumnCount(This::wxRadioBox()) -> integer()

See [external documentation](#).

getItemHelpText(This::wxRadioBox(), N::integer()) -> string()

See [external documentation](#).

`getItemToolTip(This::wxRadioBox(), Item::integer()) -> wxToolTip()` (see module `wxToolTip`)

See external documentation.

`getItemFromPoint(This::wxRadioBox(), Pt::{X::integer(), Y::integer()}) -> integer()`

See external documentation.

`getRowCount(This::wxRadioBox()) -> integer()`

See external documentation.

`isItemEnabled(This::wxRadioBox(), N::integer()) -> bool()`

See external documentation.

`isItemShown(This::wxRadioBox(), N::integer()) -> bool()`

See external documentation.

`setItemHelpText(This::wxRadioBox(), N::integer(), HelpText::string()) -> ok`

See external documentation.

`setItemToolTip(This::wxRadioBox(), Item::integer(), Text::string()) -> ok`

See external documentation.

`destroy(This::wxRadioBox()) -> ok`

Destroys this object, do not use object again

wxRadioButton

Erlang module

See external documentation: **wxRadioButton**.

This class is derived (and can use functions) from:

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxRadioButton()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxRadioButton()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Label::string())
-> wxRadioButton()`

Equivalent to `new(Parent, Id, Label, [])`.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Label::string(),
Options::[Option]) -> wxRadioButton()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()} |
{validator, wx()} (see module wx)

See external documentation.

`create(This::wxRadioButton(), Parent::wxWindow() (see module wxWindow),
Id::integer(), Label::string()) -> bool()`

Equivalent to `create(This, Parent, Id, Label, [])`.

`create(This::wxRadioButton(), Parent::wxWindow() (see module wxWindow),
Id::integer(), Label::string(), Options::[Option]) -> bool()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()} |
{validator, wx()} (see module wx)

See external documentation.

`getValue(This::wxRadioButton()) -> bool()`

See external documentation.

setValue(This::wxRadioButton(), Val::bool()) -> ok

See external documentation.

destroy(This::wxRadioButton()) -> ok

Destroys this object, do not use object again

wxRegion

Erlang module

See external documentation: **wxRegion**.

DATA TYPES

`wxRegion()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new()` -> `wxRegion()`

See external documentation.

`new(X::term())` -> `wxRegion()`

See external documentation.

Alternatives:

`new(Bmp::wxBitmap:wxBitmap()) -> wxRegion()`

`new(Rect::{X::integer(),Y::integer(),W::integer(),H::integer()}) -> wxRegion()`

`new(TopLeft::{X::integer(), Y::integer()}, BottomRight::{X::integer(), Y::integer()})` -> `wxRegion()`

See external documentation.

`new(X::integer(), Y::integer(), W::integer(), H::integer())` -> `wxRegion()`

See external documentation.

`clear(This::wxRegion())` -> `ok`

See external documentation.

`contains(This::wxRegion(), X::term())` -> `WxRegionContain`

See external documentation.

Alternatives:

`contains(This::wxRegion(), Pt::{X::integer(),Y::integer()}) -> WxRegionContain`
`WxRegionContain = integer()`

`WxRegionContain` is one of `?wxOutRegion` | `?wxPartRegion` | `?wxInRegion`

`contains(This::wxRegion(), Rect::{X::integer(),Y::integer(),W::integer(),H::integer()}) -> WxRegionContain`
`WxRegionContain = integer()`

`WxRegionContain` is one of `?wxOutRegion` | `?wxPartRegion` | `?wxInRegion`

contains(This::wxRegion(), X::integer(), Y::integer()) -> WxRegionContain

Types:

WxRegionContain = integer()

See [external documentation](#).

WxRegionContain is one of ?wxOutRegion | ?wxPartRegion | ?wxInRegion

**contains(This::wxRegion(), X::integer(), Y::integer(), W::integer(),
H::integer()) -> WxRegionContain**

Types:

WxRegionContain = integer()

See [external documentation](#).

WxRegionContain is one of ?wxOutRegion | ?wxPartRegion | ?wxInRegion

convertToBitmap(This::wxRegion()) -> wxBitmap() (see module wxBitmap)

See [external documentation](#).

**getBox(This::wxRegion()) -> {X::integer(), Y::integer(), W::integer(),
H::integer() }**

See [external documentation](#).

intersect(This::wxRegion(), X::wxRegion() | term()) -> bool()

See [external documentation](#).

Alternatives:

intersect(This::wxRegion(), Region::wxRegion()) -> bool()

**intersect(This::wxRegion(),
{X::integer(),Y::integer(),W::integer(),H::integer()}) -> bool()** Rect::

**intersect(This::wxRegion(), X::integer(), Y::integer(), W::integer(),
H::integer()) -> bool()**

See [external documentation](#).

isEmpty(This::wxRegion()) -> bool()

See [external documentation](#).

subtract(This::wxRegion(), X::wxRegion() | term()) -> bool()

See [external documentation](#).

Alternatives:

subtract(This::wxRegion(), Region::wxRegion()) -> bool()

**subtract(This::wxRegion(),
{X::integer(),Y::integer(),W::integer(),H::integer()}) -> bool()** Rect::

**subtract(This::wxRegion(), X::integer(), Y::integer(), W::integer(),
H::integer()) -> bool()**

See [external documentation](#).

offset(This::wxRegion(), Pt::{X::integer(), Y::integer()}) -> bool()

See external documentation.

offset(This::wxRegion(), X::integer(), Y::integer()) -> bool()

See external documentation.

union(This::wxRegion(), X::term()) -> bool()

See external documentation.

Alternatives:

union(This::wxRegion(), Region::wxRegion() | wxBitmap:wxBitmap()) -> bool()

union(This::wxRegion(),
{X::integer(),Y::integer(),W::integer(),H::integer()}) -> bool() Rect::

union(This::wxRegion(), Bmp::wxBitmap() (see module wxBitmap),
Transp::colour() (see module wx)) -> bool()

Equivalent to *union(This, Bmp, Transp, [])*.

union(This::wxRegion(), Bmp::wxBitmap() (see module wxBitmap),
Transp::colour() (see module wx), Options::[Option]) -> bool()

Types:

Option = {tolerance, integer()}

See external documentation.

union(This::wxRegion(), X::integer(), Y::integer(), W::integer(),
H::integer()) -> bool()

See external documentation.

Xor(This::wxRegion(), X::wxRegion() | term()) -> bool()

See external documentation.

Alternatives:

'Xor'(This::wxRegion(), Region::wxRegion()) -> bool()

'Xor'(This::wxRegion(),
{X::integer(),Y::integer(),W::integer(),H::integer()}) -> bool() Rect::

Xor(This::wxRegion(), X::integer(), Y::integer(), W::integer(), H::integer())
-> bool()

See external documentation.

destroy(This::wxRegion()) -> ok

Destroys this object, do not use object again

wxSashEvent

Erlang module

See external documentation: **wxSashEvent**.

Use *wxEvtHandler:connect/3* with EventType:

sash_dragged

See also the message variant *#wxSash{}* event record type.

This class is derived (and can use functions) from:

wxCommandEvent

wxEvent

DATA TYPES

`wxSashEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparsion stored on disc or distributed for use on other nodes.

Exports

`getEdge(This::wxSashEvent()) -> WxSashEdgePosition`

Types:

`WxSashEdgePosition = integer()`

See **external documentation**.

WxSashEdgePosition is one of ?wxSASH_TOP | ?wxSASH_RIGHT | ?wxSASH_BOTTOM | ?wxSASH_LEFT | ?wxSASH_NONE

`getDragRect(This::wxSashEvent()) -> {X::integer(), Y::integer(), W::integer(), H::integer()}`

See **external documentation**.

`getDragStatus(This::wxSashEvent()) -> WxSashDragStatus`

Types:

`WxSashDragStatus = integer()`

See **external documentation**.

WxSashDragStatus is one of ?wxSASH_STATUS_OK | ?wxSASH_STATUS_OUT_OF_RANGE

wxSashLayoutWindow

Erlang module

See external documentation: **wxSashLayoutWindow**.

This class is derived (and can use functions) from:

wxSashWindow

wxWindow

wxEvtHandler

DATA TYPES

`wxSashLayoutWindow()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxSashLayoutWindow()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow)) -> wxSashLayoutWindow()`

Equivalent to `new(Parent, [])`.

`new(Parent::wxWindow() (see module wxWindow), Options::[Option]) -> wxSashLayoutWindow()`

Types:

Option = {id, integer()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`create(This::wxSashLayoutWindow(), Parent::wxWindow() (see module wxWindow)) -> bool()`

Equivalent to `create(This, Parent, [])`.

`create(This::wxSashLayoutWindow(), Parent::wxWindow() (see module wxWindow), Options::[Option]) -> bool()`

Types:

Option = {id, integer()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`getAlignment(This::wxSashLayoutWindow()) -> WxLayoutAlignment`

Types:

WxLayoutAlignment = integer()

See **external documentation**.

WxLayoutAlignment is one of ?wxLAYOUT_NONE | ?wxLAYOUT_TOP | ?wxLAYOUT_LEFT | ?wxLAYOUT_RIGHT | ?wxLAYOUT_BOTTOM

getOrientation(This::wxSashLayoutWindow()) -> WxLayoutOrientation

Types:

WxLayoutOrientation = integer()

See **external documentation**.

WxLayoutOrientation is one of ?wxLAYOUT_HORIZONTAL | ?wxLAYOUT_VERTICAL

setAlignment(This::wxSashLayoutWindow(), Align::WxLayoutAlignment) -> ok

Types:

WxLayoutAlignment = integer()

See **external documentation**.

WxLayoutAlignment is one of ?wxLAYOUT_NONE | ?wxLAYOUT_TOP | ?wxLAYOUT_LEFT | ?wxLAYOUT_RIGHT | ?wxLAYOUT_BOTTOM

setDefaultSize(This::wxSashLayoutWindow(), Size::{W::integer(), H::integer()}) -> ok

See **external documentation**.

setOrientation(This::wxSashLayoutWindow(), Orient::WxLayoutOrientation) -> ok

Types:

WxLayoutOrientation = integer()

See **external documentation**.

WxLayoutOrientation is one of ?wxLAYOUT_HORIZONTAL | ?wxLAYOUT_VERTICAL

destroy(This::wxSashLayoutWindow()) -> ok

Destroys this object, do not use object again

wxSashWindow

Erlang module

See external documentation: **wxSashWindow**.

This class is derived (and can use functions) from:

wxWindow

wxEvtHandler

DATA TYPES

`wxSashWindow()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxSashWindow()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow)) -> wxSashWindow()`

Equivalent to `new(Parent, [])`.

`new(Parent::wxWindow() (see module wxWindow), Options::[Option]) -> wxSashWindow()`

Types:

Option = {id, integer()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`getSashVisible(This::wxSashWindow(), Edge::WxSashEdgePosition) -> bool()`

Types:

WxSashEdgePosition = integer()

See external documentation.

WxSashEdgePosition is one of ?wxSASH_TOP | ?wxSASH_RIGHT | ?wxSASH_BOTTOM | ?wxSASH_LEFT | ?wxSASH_NONE

`getMaximumSizeX(This::wxSashWindow()) -> integer()`

See external documentation.

`getMaximumSizeY(This::wxSashWindow()) -> integer()`

See external documentation.

`getMinimumSizeX(This::wxSashWindow()) -> integer()`

See external documentation.

getMinimumSizeY(This::wxSashWindow()) -> integer()

See external documentation.

setMaximumSizeX(This::wxSashWindow(), Max::integer()) -> ok

See external documentation.

setMaximumSizeY(This::wxSashWindow(), Max::integer()) -> ok

See external documentation.

setMinimumSizeX(This::wxSashWindow(), Min::integer()) -> ok

See external documentation.

setMinimumSizeY(This::wxSashWindow(), Min::integer()) -> ok

See external documentation.

**setSashVisible(This::wxSashWindow(), Edge::WxSashEdgePosition, Sash::bool())
-> ok**

Types:

WxSashEdgePosition = integer()

See external documentation.

WxSashEdgePosition is one of ?wxSASH_TOP | ?wxSASH_RIGHT | ?wxSASH_BOTTOM | ?wxSASH_LEFT | ?wxSASH_NONE

destroy(This::wxSashWindow()) -> ok

Destroys this object, do not use object again

wxScreenDC

Erlang module

See external documentation: **wxScreenDC**.

This class is derived (and can use functions) from:
wxDC

DATA TYPES

`wxScreenDC()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new()` -> **`wxScreenDC()`**

See **external documentation**.

`destroy(This::wxScreenDC())` -> **`ok`**

Destroys this object, do not use object again

wxScrollBar

Erlang module

See external documentation: **wxScrollBar**.

This class is derived (and can use functions) from:

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxScrollBar()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxScrollBar()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Id::integer()) -> wxScrollBar()`

Equivalent to `new(Parent, Id, [])`.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Options::[Option]) -> wxScrollBar()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()} | {validator, wx() (see module wx)}

See external documentation.

`create(This::wxScrollBar(), Parent::wxWindow() (see module wxWindow), Id::integer()) -> bool()`

Equivalent to `create(This, Parent, Id, [])`.

`create(This::wxScrollBar(), Parent::wxWindow() (see module wxWindow), Id::integer(), Options::[Option]) -> bool()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()} | {validator, wx() (see module wx)}

See external documentation.

`getRange(This::wxScrollBar()) -> integer()`

See external documentation.

`getPageSize(This::wxScrollBar()) -> integer()`

See [external documentation](#).

`getThumbPosition(This::wxScrollBar()) -> integer()`

See [external documentation](#).

`getThumbSize(This::wxScrollBar()) -> integer()`

See [external documentation](#).

`setThumbPosition(This::wxScrollBar(), ViewStart::integer()) -> ok`

See [external documentation](#).

`setScrollbar(This::wxScrollBar(), Position::integer(), ThumbSize::integer(), Range::integer(), PageSize::integer()) -> ok`

Equivalent to `setScrollbar(This, Position, ThumbSize, Range, PageSize, [])`.

`setScrollbar(This::wxScrollBar(), Position::integer(), ThumbSize::integer(), Range::integer(), PageSize::integer(), Options::[Option]) -> ok`

Types:

Option = {refresh, bool()}

See [external documentation](#).

`destroy(This::wxScrollBar()) -> ok`

Destroys this object, do not use object again

wxScrolledWindow

Erlang module

See external documentation: **wxScrolledWindow**.

This class is derived (and can use functions) from:

wxPanel

wxWindow

wxEvtHandler

DATA TYPES

`wxScrolledWindow()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxScrolledWindow()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow)) -> wxScrolledWindow()`

Equivalent to `new(Parent, [])`.

`new(Parent::wxWindow() (see module wxWindow), Options::[Option]) -> wxScrolledWindow()`

Types:

Option = {winid, integer()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`calcScrolledPosition(This::wxScrolledWindow(), Pt::{X::integer(), Y::integer()}) -> {X::integer(), Y::integer()}`

See external documentation.

`calcScrolledPosition(This::wxScrolledWindow(), X::integer(), Y::integer()) -> {Xx::integer(), Yy::integer()}`

See external documentation.

`calcUnscrolledPosition(This::wxScrolledWindow(), Pt::{X::integer(), Y::integer()}) -> {X::integer(), Y::integer()}`

See external documentation.

```
calcUnscrolledPosition(This::wxScrolledWindow(), X::integer(), Y::integer())  
-> {Xx::integer(), Yy::integer()}
```

See external documentation.

```
enableScrolling(This::wxScrolledWindow(), X_scrolling::bool(),  
Y_scrolling::bool()) -> ok
```

See external documentation.

```
getScrollPixelsPerUnit(This::wxScrolledWindow()) ->  
{PixelsPerUnitX::integer(), PixelsPerUnitY::integer()}
```

See external documentation.

```
getViewStart(This::wxScrolledWindow()) -> {X::integer(), Y::integer()}
```

See external documentation.

```
doPrepareDC(This::wxScrolledWindow(), Dc::wxDC() (see module wxDC)) -> ok
```

See external documentation.

```
prepareDC(This::wxScrolledWindow(), Dc::wxDC() (see module wxDC)) -> ok
```

See external documentation.

```
scroll(This::wxScrolledWindow(), X::integer(), Y::integer()) -> ok
```

See external documentation.

```
setScrollbars(This::wxScrolledWindow(), PixelsPerUnitX::integer(),  
PixelsPerUnitY::integer(), NoUnitsX::integer(), NoUnitsY::integer()) -> ok
```

Equivalent to *setScrollbars(This, PixelsPerUnitX, PixelsPerUnitY, NoUnitsX, NoUnitsY, [])*.

```
setScrollbars(This::wxScrolledWindow(), PixelsPerUnitX::integer(),  
PixelsPerUnitY::integer(), NoUnitsX::integer(), NoUnitsY::integer(),  
Options::[Option]) -> ok
```

Types:

Option = {xPos, integer()} | {yPos, integer()} | {noRefresh, bool()}

See external documentation.

```
setScrollRate(This::wxScrolledWindow(), Xstep::integer(), Ystep::integer()) -  
> ok
```

See external documentation.

```
setTargetWindow(This::wxScrolledWindow(), Target::wxWindow() (see module  
wxWindow)) -> ok
```

See external documentation.

```
destroy(This::wxScrolledWindow()) -> ok
```

Destroys this object, do not use object again

wxScrollEvent

Erlang module

See external documentation: **wxScrollEvent**.

Use *wxEvtHandler:connect/3* with EventType:

scroll_top, scroll_bottom, scroll_lineup, scroll_linedown, scroll_pageup, scroll_pagedown, scroll_thumbtrack, scroll_thumbrelease, scroll_changed

See also the message variant *#wxScroll{}* event record type.

This class is derived (and can use functions) from:

wxCommandEvent

wxEvent

DATA TYPES

wxScrollEvent()

An object reference, The representation is internal and can be changed without notice. It can't be used for comparsion stored on disc or distributed for use on other nodes.

Exports

getOrientation(This::wxScrollEvent()) -> integer()

See **external documentation**.

getPosition(This::wxScrollEvent()) -> integer()

See **external documentation**.

wxScrollWinEvent

Erlang module

See external documentation: **wxScrollWinEvent**.

Use *wxEvtHandler:connect/3* with EventType:

scrollwin_top, *scrollwin_bottom*, *scrollwin_lineup*, *scrollwin_linedown*, *scrollwin_pageup*,
scrollwin_pagedown, *scrollwin_thumbtrack*, *scrollwin_thumbrelease*

See also the message variant *#wxScrollWin{}* event record type.

This class is derived (and can use functions) from:

wxEvent

DATA TYPES

`wxScrollWinEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`getOrientation(This::wxScrollWinEvent()) -> integer()`

See **external documentation**.

`getPosition(This::wxScrollWinEvent()) -> integer()`

See **external documentation**.

wxSetCursorEvent

Erlang module

See external documentation: **wxSetCursorEvent**.

Use *wxEvtHandler:connect/3* with EventType:

set_cursor

See also the message variant *#wxSetCursor{}* event record type.

This class is derived (and can use functions) from:

wxEvent

DATA TYPES

`wxSetCursorEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparsion stored on disc or distributed for use on other nodes.

Exports

`getCursor(This::wxSetCursorEvent()) -> wxCursor()` (see module `wxCursor`)

See external documentation.

`getX(This::wxSetCursorEvent()) -> integer()`

See external documentation.

`getY(This::wxSetCursorEvent()) -> integer()`

See external documentation.

`hasCursor(This::wxSetCursorEvent()) -> bool()`

See external documentation.

`setCursor(This::wxSetCursorEvent(), Cursor::wxCursor())` (see module `wxCursor`)
`-> ok`

See external documentation.

wxShowEvent

Erlang module

See external documentation: **wxShowEvent**.

Use *wxEvtHandler:connect/3* with EventType:

show

See also the message variant *#wxShow{}* event record type.

This class is derived (and can use functions) from:

wxEvent

DATA TYPES

`wxShowEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`setShow(This::wxShowEvent(), Show::bool()) -> ok`

See **external documentation**.

`getShow(This::wxShowEvent()) -> bool()`

See **external documentation**.

wxSingleChoiceDialog

Erlang module

See external documentation: **wxSingleChoiceDialog**.

This class is derived (and can use functions) from:

wxDialog

wxTopLevelWindow

wxWindow

wxEvtHandler

DATA TYPES

`wxSingleChoiceDialog()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxSingleChoiceDialog()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Message::string(),
Caption::string(), Choices::[[string()]]) -> wxSingleChoiceDialog()`

Equivalent to `new(Parent, Message, Caption, Choices, [])`.

`new(Parent::wxWindow() (see module wxWindow), Message::string(),
Caption::string(), Choices::[[string()]], Options::[Option]) ->
wxSingleChoiceDialog()`

Types:

Option = {style, integer()} | {pos, {X::integer(), Y::integer()}}

See external documentation.

`getSelection(This::wxSingleChoiceDialog()) -> integer()`

See external documentation.

`getStringSelection(This::wxSingleChoiceDialog()) -> string()`

See external documentation.

`setSelection(This::wxSingleChoiceDialog(), Sel::integer()) -> ok`

See external documentation.

`destroy(This::wxSingleChoiceDialog()) -> ok`

Destroys this object, do not use object again

wxSizeEvent

Erlang module

See external documentation: **wxSizeEvent**.

Use *wxEvtHandler:connect/3* with EventType:

size

See also the message variant *#wxSize{}* event record type.

This class is derived (and can use functions) from:

wxEvent

DATA TYPES

`wxSizeEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`getSize(This::wxSizeEvent()) -> {W::integer(), H::integer()}`

See **external documentation**.

wxSizer

Erlang module

See external documentation: **wxSizer**.

DATA TYPES

`wxSizer()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

```
add(This::wxSizer(), Window::wxWindow() (see module wxWindow) | wxSizer()) ->  
wxSizerItem() (see module wxSizerItem)
```

Equivalent to `add(This, Window, [])`.

```
add(This::wxSizer(), X::integer() | term(), X::integer() | term()) ->  
wxSizerItem() (see module wxSizerItem)
```

See external documentation.

Alternatives:

```
add(This::wxSizer(), Width::integer(), Height::integer()) ->  
add(This,Width,Height, [])
```

```
add(This::wxSizer(), Window::wxWindow:wxWindow() | wxSizer(), [Option]) ->  
wxSizerItem:wxSizerItem()
```

Option = {proportion, integer()} | {flag, integer()} | {border, integer()} | {userData, wx:wx() }

```
add(This::wxSizer(), Window::wxWindow:wxWindow() | wxSizer(),  
Flags::wxSizerFlags:wxSizerFlags()) -> wxSizerItem:wxSizerItem()
```

```
add(This::wxSizer(), Width::integer(), Height::integer(), Options::[Option])  
-> wxSizerItem() (see module wxSizerItem)
```

Types:

Option = {proportion, integer()} | {flag, integer()} | {border, integer()} | {userData, wx() (see module wx)}

See external documentation.

```
addSpacer(This::wxSizer(), Size::integer()) -> wxSizerItem() (see module  
wxSizerItem)
```

See external documentation.

```
addStretchSpacer(This::wxSizer()) -> wxSizerItem() (see module wxSizerItem)
```

Equivalent to `addStretchSpacer(This, [])`.

addStretchSpacer(This::wxSizer(), Options::[Option]) -> wxSizerItem() (see module **wxSizerItem**)

Types:

Option = {prop, integer()}

See external documentation.

calcMin(This::wxSizer()) -> {W::integer(), H::integer()}

See external documentation.

clear(This::wxSizer()) -> ok

Equivalent to *clear(This, [])*.

clear(This::wxSizer(), Options::[Option]) -> ok

Types:

Option = {delete_windows, bool()}

See external documentation.

detach(This::wxSizer(), X::integer() | term()) -> bool()

See external documentation.

Alternatives:

detach(This::wxSizer(), Index::integer()) -> bool()

detach(This::wxSizer(), Window::wxWindow:wxWindow() | wxSizer()) -> bool()

fit(This::wxSizer(), Window::wxWindow() (see module wxWindow)) -> {W::integer(), H::integer()}

See external documentation.

fitInside(This::wxSizer(), Window::wxWindow() (see module wxWindow)) -> ok

See external documentation.

getChildren(This::wxSizer()) -> [wxSizerItem() (see module wxSizerItem)]

See external documentation.

getItem(This::wxSizer(), X::term() | integer()) -> wxSizerItem() (see module **wxSizerItem**)

See external documentation.

Alternatives:

getItem(This::wxSizer(), Window::wxWindow:wxWindow() | wxSizer()) -> wxSizerItem()
getItem(This, Window, [])

getItem(This::wxSizer(), Index::integer()) -> wxSizerItem:wxSizerItem()

```
getItem(This::wxSizer(), Window::wxWindow() (see module wxWindow) |  
wxSizer(), Options::[Option]) -> wxSizerItem() (see module wxSizerItem)
```

Types:

Option = {recursive, bool()}

See external documentation.

```
getSize(This::wxSizer()) -> {W::integer(), H::integer()}
```

See external documentation.

```
getPosition(This::wxSizer()) -> {X::integer(), Y::integer()}
```

See external documentation.

```
getMinSize(This::wxSizer()) -> {W::integer(), H::integer()}
```

See external documentation.

```
hide(This::wxSizer(), X::term() | integer()) -> bool()
```

See external documentation.

Alternatives:

```
hide(This::wxSizer(), Window::wxWindow:wxWindow() | wxSizer()) ->  
hide(This, Window, [])
```

```
hide(This::wxSizer(), Index::integer()) -> bool()
```

```
hide(This::wxSizer(), Window::wxWindow() (see module wxWindow) | wxSizer(),  
Options::[Option]) -> bool()
```

Types:

Option = {recursive, bool()}

See external documentation.

```
insert(This::wxSizer(), Index::integer(), X::term()) -> wxSizerItem() (see  
module wxSizerItem)
```

See external documentation.

Alternatives:

```
insert(This::wxSizer(), Index::integer(), Window::wxWindow:wxWindow() |  
wxSizer()) -> insert(This, Index, Window, [])
```

```
insert(This::wxSizer(), Index::integer(), Item::wxSizerItem:wxSizerItem()) ->  
wxSizerItem:wxSizerItem()
```

```
insert(This::wxSizer(), Index::integer(), X::integer() | term(), X::integer()  
| term()) -> wxSizerItem() (see module wxSizerItem)
```

See external documentation.

Alternatives:

```
insert(This::wxSizer(), Index::integer(), Width::integer(), Height::integer())  
-> insert(This, Index, Width, Height, [])
```

```
insert(This::wxSizer(), Index::integer(), Window::wxWindow:wxWindow() |  
wxSizer(), [Option]) -> wxSizerItem:wxSizerItem()  
Option = {proportion, integer()} | {flag, integer()} | {border, integer()} | {userData, wx:wx()}  
  
insert(This::wxSizer(), Index::integer(), Window::wxWindow:wxWindow() |  
wxSizer(), Flags::wxSizerFlags:wxSizerFlags()) -> wxSizerItem:wxSizerItem()
```

```
insert(This::wxSizer(), Index::integer(), Width::integer(),  
Height::integer(), Options::[Option]) -> wxSizerItem() (see module  
wxSizerItem)
```

Types:

Option = {proportion, integer()} | {flag, integer()} | {border, integer()} | {userData, wx()} (see module wx)

See [external documentation](#).

```
insertSpacer(This::wxSizer(), Index::integer(), Size::integer()) ->  
wxSizerItem() (see module wxSizerItem)
```

See [external documentation](#).

```
insertStretchSpacer(This::wxSizer(), Index::integer()) -> wxSizerItem() (see  
module wxSizerItem)
```

Equivalent to *insertStretchSpacer(This, Index, [])*.

```
insertStretchSpacer(This::wxSizer(), Index::integer(), Options::[Option]) ->  
wxSizerItem() (see module wxSizerItem)
```

Types:

Option = {prop, integer()}

See [external documentation](#).

```
isShown(This::wxSizer(), X::integer() | term()) -> bool()
```

See [external documentation](#).

Alternatives:

```
isShown(This::wxSizer(), Index::integer()) -> bool()
```

```
isShown(This::wxSizer(), Window::wxWindow:wxWindow() | wxSizer()) -> bool()
```

```
layout(This::wxSizer()) -> ok
```

See [external documentation](#).

```
prepend(This::wxSizer(), X::term()) -> wxSizerItem() (see module wxSizerItem)
```

See [external documentation](#).

Alternatives:

```
prepend(This::wxSizer(), Window::wxWindow:wxWindow() | wxSizer()) ->  
prepend(This, Window, [])
```

```
prepend(This::wxSizer(), Item::wxSizerItem:wxSizerItem()) ->  
wxSizerItem:wxSizerItem()
```

```
prepend(This::wxSizer(), X::integer() | term(), X::integer() | term()) ->  
wxSizerItem() (see module wxSizerItem)
```

See **external documentation**.

Alternatives:

```
prepend(This::wxSizer(), Width::integer(), Height::integer()) ->  
prepend(This,Width,Height, [])
```

```
prepend(This::wxSizer(), Window::wxWindow:wxWindow() | wxSizer(), [Option]) -  
> wxSizerItem:wxSizerItem()
```

Option = {proportion, integer()} | {flag, integer()} | {border, integer()} | {userData, wx:wx() }

```
prepend(This::wxSizer(), Window::wxWindow:wxWindow() | wxSizer(),  
Flags::wxSizerFlags:wxSizerFlags()) -> wxSizerItem:wxSizerItem()
```

```
prepend(This::wxSizer(), Width::integer(), Height::integer(), Options::  
[Option]) -> wxSizerItem() (see module wxSizerItem)
```

Types:

Option = {proportion, integer()} | {flag, integer()} | {border, integer()} | {userData, wx() (see module wx)}

See **external documentation**.

```
prependSpacer(This::wxSizer(), Size::integer()) -> wxSizerItem() (see module  
wxSizerItem)
```

See **external documentation**.

```
prependStretchSpacer(This::wxSizer()) -> wxSizerItem() (see module  
wxSizerItem)
```

Equivalent to *prependStretchSpacer(This, [])*.

```
prependStretchSpacer(This::wxSizer(), Options::[Option]) -> wxSizerItem()  
(see module wxSizerItem)
```

Types:

Option = {prop, integer() }

See **external documentation**.

```
recalcSizes(This::wxSizer()) -> ok
```

See **external documentation**.

```
remove(This::wxSizer(), X::integer() | wxSizer()) -> bool()
```

See **external documentation**.

Alternatives:

```
remove(This::wxSizer(), Index::integer()) -> bool()
```

```
remove(This::wxSizer(), Sizer::wxSizer()) -> bool()
```

```
replace(This::wxSizer(), X::term() | integer(), X::term()) -> bool()
```

See **external documentation**.

Alternatives:

```
replace(This::wxSizer(), Oldwin::wxWindow:wxWindow() | wxSizer(),
Newwin::wxWindow:wxWindow() | wxSizer()) -> replace(This,Oldwin,Newwin, [])
replace(This::wxSizer(), Index::integer(), Newitem::wxSizerItem:wxSizerItem())
-> bool()
```

```
replace(This::wxSizer(), Oldwin::wxWindow() (see module wxWindow) |
wxSizer(), Newwin::wxWindow() (see module wxWindow) | wxSizer(), Options::
[Option]) -> bool()
```

Types:

Option = {recursive, bool()}

See [external documentation](#).

```
setDimension(This::wxSizer(), X::integer(), Y::integer(), Width::integer(),
Height::integer()) -> ok
```

See [external documentation](#).

```
setMinSize(This::wxSizer(), Size::{W::integer(), H::integer()}) -> ok
```

See [external documentation](#).

```
setMinSize(This::wxSizer(), Width::integer(), Height::integer()) -> ok
```

See [external documentation](#).

```
setItemMinSize(This::wxSizer(), X::integer() | term(), Size::{W::integer(),
H::integer()}) -> bool()
```

See [external documentation](#).

Alternatives:

```
setItemMinSize(This::wxSizer(), Index::integer(), Size::
{W::integer(),H::integer()}) -> bool()
```

```
setItemMinSize(This::wxSizer(), Window::wxWindow:wxWindow() | wxSizer(), Size::
{W::integer(),H::integer()}) -> bool()
```

```
setItemMinSize(This::wxSizer(), X::integer() | term(), Width::integer(),
Height::integer()) -> bool()
```

See [external documentation](#).

Alternatives:

```
setItemMinSize(This::wxSizer(), Index::integer(), Width::integer(),
Height::integer()) -> bool()
```

```
setItemMinSize(This::wxSizer(), Window::wxWindow:wxWindow() | wxSizer(),
Width::integer(), Height::integer()) -> bool()
```

```
setSizeHints(This::wxSizer(), Window::wxWindow() (see module wxWindow)) -> ok
```

See [external documentation](#).

setVirtualSizeHints(This::wxSizer(), Window::wxWindow() (see module wxWindow)) -> ok

See **external documentation**.

show(This::wxSizer(), X::integer() | term() | bool()) -> bool() | bool() | ok

See **external documentation**.

Alternatives:

show(This::wxSizer(), Index::integer()) -> show(This, Index, [])

show(This::wxSizer(), Window::wxWindow:wxWindow() | wxSizer()) -> show(This, Window, [])

show(This::wxSizer(), Show::bool()) -> ok

show(This::wxSizer(), X::integer() | term(), Options::[Option]) -> bool()

See **external documentation**.

Alternatives:

show(This::wxSizer(), Index::integer(), [Option]) -> bool()

Option = {show, bool()}

show(This::wxSizer(), Window::wxWindow:wxWindow() | wxSizer(), [Option]) -> bool()

Option = {show, bool()} | {recursive, bool()}

wxSizerFlags

Erlang module

See external documentation: **wxSizerFlags**.

DATA TYPES

`wxSizerFlags()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new()` -> **`wxSizerFlags()`**

Equivalent to `new([])`.

`new(Options::[Option])` -> **`wxSizerFlags()`**

Types:

`Option` = {proportion, integer()}

See external documentation.

`align(This::wxSizerFlags(), Alignment::integer())` -> **`wxSizerFlags()`**

See external documentation.

`border(This::wxSizerFlags())` -> **`wxSizerFlags()`**

Equivalent to `border(This, [])`.

`border(This::wxSizerFlags(), Options::[Option])` -> **`wxSizerFlags()`**

Types:

`Option` = {direction, integer()}

See external documentation.

`border(This::wxSizerFlags(), Direction::integer(), BorderInPixels::integer())`
-> **`wxSizerFlags()`**

See external documentation.

`center(This::wxSizerFlags())` -> **`wxSizerFlags()`**

See external documentation.

`centre(This::wxSizerFlags())` -> **`wxSizerFlags()`**

See external documentation.

expand(This::wxSizerFlags()) -> wxSizerFlags()

See external documentation.

left(This::wxSizerFlags()) -> wxSizerFlags()

See external documentation.

proportion(This::wxSizerFlags(), Proportion::integer()) -> wxSizerFlags()

See external documentation.

right(This::wxSizerFlags()) -> wxSizerFlags()

See external documentation.

destroy(This::wxSizerFlags()) -> ok

Destroys this object, do not use object again

wxSizerItem

Erlang module

See external documentation: **wxSizerItem**.

DATA TYPES

`wxSizerItem()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxSizerItem()`

See external documentation.

`new(Window::wxWindow() (see module wxWindow) | wxSizer() (see module wxSizer), Flags::wxSizerFlags() (see module wxSizerFlags)) -> wxSizerItem()`

See external documentation.

`new(Width::integer(), Height::integer(), Flags::wxSizerFlags() (see module wxSizerFlags)) -> wxSizerItem()`

See external documentation.

`new(Window::wxWindow() (see module wxWindow) | wxSizer() (see module wxSizer), Proportion::integer(), Flag::integer(), Border::integer(), UserData::wx() (see module wx)) -> wxSizerItem()`

See external documentation.

`new(Width::integer(), Height::integer(), Proportion::integer(), Flag::integer(), Border::integer(), UserData::wx() (see module wx)) -> wxSizerItem()`

See external documentation.

`calcMin(This::wxSizerItem()) -> {W::integer(), H::integer()}`

See external documentation.

`deleteWindows(This::wxSizerItem()) -> ok`

See external documentation.

`detachSizer(This::wxSizerItem()) -> ok`

See external documentation.

`getBorder(This::wxSizerItem()) -> integer()`

See external documentation.

`getFlag(This::wxSizerItem()) -> integer()`

See external documentation.

`getMinSize(This::wxSizerItem()) -> {W::integer(), H::integer()}`

See external documentation.

`getPosition(This::wxSizerItem()) -> {X::integer(), Y::integer()}`

See external documentation.

`getProportion(This::wxSizerItem()) -> integer()`

See external documentation.

`getRatio(This::wxSizerItem()) -> float()`

See external documentation.

`getRect(This::wxSizerItem()) -> {X::integer(), Y::integer(), W::integer(), H::integer()}`

See external documentation.

`getSize(This::wxSizerItem()) -> {W::integer(), H::integer()}`

See external documentation.

`getSizer(This::wxSizerItem()) -> wxSizer() (see module wxSizer)`

See external documentation.

`getSpacer(This::wxSizerItem()) -> {W::integer(), H::integer()}`

See external documentation.

`getUserData(This::wxSizerItem()) -> wx() (see module wx)`

See external documentation.

`getWindow(This::wxSizerItem()) -> wxWindow() (see module wxWindow)`

See external documentation.

`isSizer(This::wxSizerItem()) -> bool()`

See external documentation.

`isShown(This::wxSizerItem()) -> bool()`

See external documentation.

isSpacer(This::wxSizerItem()) -> bool()

See external documentation.

isWindow(This::wxSizerItem()) -> bool()

See external documentation.

setBorder(This::wxSizerItem(), Border::integer()) -> ok

See external documentation.

setDimension(This::wxSizerItem(), Pos::{X::integer(), Y::integer()}, Size::{W::integer(), H::integer()}) -> ok

See external documentation.

setFlag(This::wxSizerItem(), Flag::integer()) -> ok

See external documentation.

setInitSize(This::wxSizerItem(), X::integer(), Y::integer()) -> ok

See external documentation.

setMinSize(This::wxSizerItem(), Size::{W::integer(), H::integer()}) -> ok

See external documentation.

setMinSize(This::wxSizerItem(), X::integer(), Y::integer()) -> ok

See external documentation.

setProportion(This::wxSizerItem(), Proportion::integer()) -> ok

See external documentation.

setRatio(This::wxSizerItem(), X::float() | term()) -> ok

See external documentation.

Alternatives:

setRatio(This::wxSizerItem(), Ratio::float()) -> ok

setRatio(This::wxSizerItem(), Size::{W::integer(), H::integer()}) -> ok

setRatio(This::wxSizerItem(), Width::integer(), Height::integer()) -> ok

See external documentation.

setSize(This::wxSizerItem(), Sizer::wxSizer() (see module wxSizer)) -> ok

See external documentation.

setSpacer(This::wxSizerItem(), Size::{W::integer(), H::integer()}) -> ok

See external documentation.

`setSpacer(This::wxSizerItem(), Width::integer(), Height::integer()) -> ok`

See external documentation.

`setWindow(This::wxSizerItem(), Window::wxWindow() (see module wxWindow)) -> ok`

See external documentation.

`show(This::wxSizerItem(), Show::bool()) -> ok`

See external documentation.

`destroy(This::wxSizerItem()) -> ok`

Destroys this object, do not use object again

wxSlider

Erlang module

See external documentation: **wxSlider**.

This class is derived (and can use functions) from:

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxSlider()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxSlider()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Value::integer(), MinValue::integer(), MaxValue::integer()) -> wxSlider()`

Equivalent to `new(Parent, Id, Value, MinValue, MaxValue, [])`.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Value::integer(), MinValue::integer(), MaxValue::integer(), Options::[Option]) -> wxSlider()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()} | {validator, wx() (see module wx)}

See external documentation.

`create(This::wxSlider(), Parent::wxWindow() (see module wxWindow), Id::integer(), Value::integer(), MinValue::integer(), MaxValue::integer()) -> bool()`

Equivalent to `create(This, Parent, Id, Value, MinValue, MaxValue, [])`.

`create(This::wxSlider(), Parent::wxWindow() (see module wxWindow), Id::integer(), Value::integer(), MinValue::integer(), MaxValue::integer(), Options::[Option]) -> bool()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()} | {validator, wx() (see module wx)}

See external documentation.

`getLineSize(This::wxSlider()) -> integer()`

See external documentation.

`getMax(This::wxSlider()) -> integer()`

See external documentation.

`getMin(This::wxSlider()) -> integer()`

See external documentation.

`getPageSize(This::wxSlider()) -> integer()`

See external documentation.

`getThumbLength(This::wxSlider()) -> integer()`

See external documentation.

`getValue(This::wxSlider()) -> integer()`

See external documentation.

`setLineSize(This::wxSlider(), LineSize::integer()) -> ok`

See external documentation.

`setPageSize(This::wxSlider(), PageSize::integer()) -> ok`

See external documentation.

`setRange(This::wxSlider(), MinValue::integer(), MaxValue::integer()) -> ok`

See external documentation.

`setThumbLength(This::wxSlider(), LenPixels::integer()) -> ok`

See external documentation.

`setValue(This::wxSlider(), Value::integer()) -> ok`

See external documentation.

`destroy(This::wxSlider()) -> ok`

Destroys this object, do not use object again

wxSpinButton

Erlang module

See external documentation: **wxSpinButton**.

This class is derived (and can use functions) from:

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxSpinButton()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxSpinButton()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow)) -> wxSpinButton()`

Equivalent to `new(Parent, [])`.

`new(Parent::wxWindow() (see module wxWindow), Options::[Option]) -> wxSpinButton()`

Types:

Option = {id, integer()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`create(This::wxSpinButton(), Parent::wxWindow() (see module wxWindow)) -> bool()`

Equivalent to `create(This, Parent, [])`.

`create(This::wxSpinButton(), Parent::wxWindow() (see module wxWindow), Options::[Option]) -> bool()`

Types:

Option = {id, integer()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`getMax(This::wxSpinButton()) -> integer()`

See external documentation.

wxSpinButton

getMin(This::wxSpinButton()) -> integer()

See external documentation.

getValue(This::wxSpinButton()) -> integer()

See external documentation.

setRange(This::wxSpinButton(), MinVal::integer(), MaxVal::integer()) -> ok

See external documentation.

setValue(This::wxSpinButton(), Value::integer()) -> ok

See external documentation.

destroy(This::wxSpinButton()) -> ok

Destroys this object, do not use object again

wxSpinCtrl

Erlang module

See external documentation: **wxSpinCtrl**.

This class is derived (and can use functions) from:

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxSpinCtrl()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxSpinCtrl()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow)) -> wxSpinCtrl()`

Equivalent to `new(Parent, [])`.

`new(Parent::wxWindow() (see module wxWindow), Options::[Option]) -> wxSpinCtrl()`

Types:

Option = {id, integer()} | {value, string()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()} | {min, integer()} | {max, integer()} | {initial, integer()}

See external documentation.

`create(This::wxSpinCtrl(), Parent::wxWindow() (see module wxWindow)) -> bool()`

Equivalent to `create(This, Parent, [])`.

`create(This::wxSpinCtrl(), Parent::wxWindow() (see module wxWindow), Options::[Option]) -> bool()`

Types:

Option = {id, integer()} | {value, string()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()} | {min, integer()} | {max, integer()} | {initial, integer()}

See external documentation.

`setValue(This::wxSpinCtrl(), X::integer() | string()) -> ok`

See external documentation.

Alternatives:

wxSpinCtrl

setValue(This::wxSpinCtrl(), Value::integer()) -> ok

setValue(This::wxSpinCtrl(), Text::string()) -> ok

getValue(This::wxSpinCtrl()) -> integer()

See **external documentation**.

setRange(This::wxSpinCtrl(), MinVal::integer(), MaxVal::integer()) -> ok

See **external documentation**.

setSelection(This::wxSpinCtrl(), From::integer(), To::integer()) -> ok

See **external documentation**.

getMin(This::wxSpinCtrl()) -> integer()

See **external documentation**.

getMax(This::wxSpinCtrl()) -> integer()

See **external documentation**.

destroy(This::wxSpinCtrl()) -> ok

Destroys this object, do not use object again

wxSpinEvent

Erlang module

See external documentation: **wxSpinEvent**.

Use *wxEvtHandler:connect/3* with EventType:

command_spinctrl_updated, spin_up, spin_down, spin

See also the message variant *#wxSpin{}* event record type.

This class is derived (and can use functions) from:

wxNotifyEvent

wxCommandEvent

wxEvent

DATA TYPES

`wxSpinEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`getPosition(This::wxSpinEvent()) -> integer()`

See **external documentation**.

`setPosition(This::wxSpinEvent(), Pos::integer()) -> ok`

See **external documentation**.

wxSplashScreen

Erlang module

See external documentation: **wxSplashScreen**.

This class is derived (and can use functions) from:

wxFrame

wxTopLevelWindow

wxWindow

wxEvtHandler

DATA TYPES

`wxSplashScreen()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxSplashScreen()`

See external documentation.

`new(Bitmap::wxBitmap() (see module wxBitmap), SplashStyle::integer(),
Milliseconds::integer(), Parent::wxWindow() (see module wxWindow),
Id::integer()) -> wxSplashScreen()`

Equivalent to `new(Bitmap, SplashStyle, Milliseconds, Parent, Id, [])`.

`new(Bitmap::wxBitmap() (see module wxBitmap), SplashStyle::integer(),
Milliseconds::integer(), Parent::wxWindow() (see module wxWindow),
Id::integer(), Options::[Option]) -> wxSplashScreen()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`getSplashStyle(This::wxSplashScreen()) -> integer()`

See external documentation.

`getTimeout(This::wxSplashScreen()) -> integer()`

See external documentation.

`destroy(This::wxSplashScreen()) -> ok`

Destroys this object, do not use object again

wxSplitterEvent

Erlang module

See external documentation: **wxSplitterEvent**.

Use *wxEvtHandler:connect/3* with EventType:

command_splitter_sash_pos_changed, *command_splitter_sash_pos_changing,*
command_splitter_doubleclicked, *command_splitter_unsplit*

See also the message variant *#wxSplitter{}* event record type.

This class is derived (and can use functions) from:

wxNotifyEvent
wxCommandEvent
wxEvent

DATA TYPES

`wxSplitterEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparsion stored on disc or distributed for use on other nodes.

Exports

`getSashPosition(This::wxSplitterEvent()) -> integer()`

See external documentation.

`getX(This::wxSplitterEvent()) -> integer()`

See external documentation.

`getY(This::wxSplitterEvent()) -> integer()`

See external documentation.

`getWindowBeingRemoved(This::wxSplitterEvent()) -> wxWindow()` (see module `wxWindow`)

See external documentation.

`setSashPosition(This::wxSplitterEvent(), Pos::integer()) -> ok`

See external documentation.

wxSplitterWindow

Erlang module

See external documentation: **wxSplitterWindow**.

This class is derived (and can use functions) from:

wxWindow

wxEvtHandler

DATA TYPES

`wxSplitterWindow()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxSplitterWindow()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow)) -> wxSplitterWindow()`

Equivalent to `new(Parent, [])`.

`new(Parent::wxWindow() (see module wxWindow), Options::[Option]) -> wxSplitterWindow()`

Types:

Option = {id, integer()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`create(This::wxSplitterWindow(), Parent::wxWindow() (see module wxWindow)) -> bool()`

Equivalent to `create(This, Parent, [])`.

`create(This::wxSplitterWindow(), Parent::wxWindow() (see module wxWindow), Options::[Option]) -> bool()`

Types:

Option = {id, integer()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`getMinimumPaneSize(This::wxSplitterWindow()) -> integer()`

See external documentation.

`getSashGravity(This::wxSplitterWindow()) -> float()`

See external documentation.

`getSashPosition(This::wxSplitterWindow()) -> integer()`

See external documentation.

`getSplitMode(This::wxSplitterWindow()) -> WxSplitMode`

Types:

`WxSplitMode = integer()`

See external documentation.

WxSplitMode is one of ?wxSPLIT_HORIZONTAL | ?wxSPLIT_VERTICAL

`getWindow1(This::wxSplitterWindow()) -> wxWindow() (see module wxWindow)`

See external documentation.

`getWindow2(This::wxSplitterWindow()) -> wxWindow() (see module wxWindow)`

See external documentation.

`initialize(This::wxSplitterWindow(), Window::wxWindow() (see module wxWindow)) -> ok`

See external documentation.

`isSplit(This::wxSplitterWindow()) -> bool()`

See external documentation.

`replaceWindow(This::wxSplitterWindow(), WinOld::wxWindow() (see module wxWindow), WinNew::wxWindow() (see module wxWindow)) -> bool()`

See external documentation.

`setSashGravity(This::wxSplitterWindow(), Gravity::float()) -> ok`

See external documentation.

`setSashPosition(This::wxSplitterWindow(), Position::integer()) -> ok`

Equivalent to *setSashPosition(This, Position, [])*.

`setSashPosition(This::wxSplitterWindow(), Position::integer(), Options::[Option]) -> ok`

Types:

`Option = {redraw, bool()}`

See external documentation.

`setSashSize(This::wxSplitterWindow(), Width::integer()) -> ok`

See external documentation.

`setMinimumPaneSize(This::wxSplitterWindow(), Min::integer()) -> ok`

See external documentation.

`setSplitMode(This::wxSplitterWindow(), Mode::integer()) -> ok`

See external documentation.

`splitHorizontally(This::wxSplitterWindow(), Window1::wxWindow() (see module wxWindow), Window2::wxWindow() (see module wxWindow)) -> bool()`

Equivalent to `splitHorizontally(This, Window1, Window2, [])`.

`splitHorizontally(This::wxSplitterWindow(), Window1::wxWindow() (see module wxWindow), Window2::wxWindow() (see module wxWindow), Options::[Option]) -> bool()`

Types:

Option = {sashPosition, integer()}

See external documentation.

`splitVertically(This::wxSplitterWindow(), Window1::wxWindow() (see module wxWindow), Window2::wxWindow() (see module wxWindow)) -> bool()`

Equivalent to `splitVertically(This, Window1, Window2, [])`.

`splitVertically(This::wxSplitterWindow(), Window1::wxWindow() (see module wxWindow), Window2::wxWindow() (see module wxWindow), Options::[Option]) -> bool()`

Types:

Option = {sashPosition, integer()}

See external documentation.

`unsplit(This::wxSplitterWindow()) -> bool()`

Equivalent to `unsplit(This, [])`.

`unsplit(This::wxSplitterWindow(), Options::[Option]) -> bool()`

Types:

Option = {toRemove, wxWindow() (see module wxWindow)}

See external documentation.

`updateSize(This::wxSplitterWindow()) -> ok`

See external documentation.

`destroy(This::wxSplitterWindow()) -> ok`

Destroys this object, do not use object again

wxStaticBitmap

Erlang module

See external documentation: **wxStaticBitmap**.

This class is derived (and can use functions) from:

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxStaticBitmap()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxStaticBitmap()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Label::wxBitmap() (see module wxBitmap)) -> wxStaticBitmap()`

Equivalent to `new(Parent, Id, Label, [])`.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Label::wxBitmap() (see module wxBitmap), Options::[Option]) -> wxStaticBitmap()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`create(This::wxStaticBitmap(), Parent::wxWindow() (see module wxWindow), Id::integer(), Label::wxBitmap() (see module wxBitmap)) -> bool()`

Equivalent to `create(This, Parent, Id, Label, [])`.

`create(This::wxStaticBitmap(), Parent::wxWindow() (see module wxWindow), Id::integer(), Label::wxBitmap() (see module wxBitmap), Options::[Option]) -> bool()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`getBitmap(This::wxStaticBitmap()) -> wxBitmap() (see module wxBitmap)`

See external documentation.

wxStaticBitmap

```
setBitmap(This::wxStaticBitmap(), Bitmap:wxBitmap() (see module wxBitmap)) -  
> ok
```

See **external documentation**.

```
destroy(This::wxStaticBitmap()) -> ok
```

Destroys this object, do not use object again

wxStaticBox

Erlang module

See external documentation: **wxStaticBox**.

This class is derived (and can use functions) from:

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxStaticBox()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxStaticBox()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Label::string()) -> wxStaticBox()`

Equivalent to `new(Parent, Id, Label, [])`.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Label::string(), Options::[Option]) -> wxStaticBox()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`create(This::wxStaticBox(), Parent::wxWindow() (see module wxWindow), Id::integer(), Label::string()) -> bool()`

Equivalent to `create(This, Parent, Id, Label, [])`.

`create(This::wxStaticBox(), Parent::wxWindow() (see module wxWindow), Id::integer(), Label::string(), Options::[Option]) -> bool()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`destroy(This::wxStaticBox()) -> ok`

Destroys this object, do not use object again

wxStaticBoxSizer

Erlang module

See external documentation: **wxStaticBoxSizer**.

This class is derived (and can use functions) from:

wxBoxSizer

wxSizer

DATA TYPES

`wxStaticBoxSizer()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new(X::integer() | term(), X::term() | integer()) -> wxStaticBoxSizer()`

See **external documentation**.

Alternatives:

`new(Orient::integer(), Win::wxWindow:wxWindow()) -> new(Orient,Win, [])`

`new(Box::wxStaticBox:wxStaticBox(), Orient::integer()) -> wxStaticBoxSizer()`

`new(Orient::integer(), Win::wxWindow() (see module wxWindow), Options::[Option]) -> wxStaticBoxSizer()`

Types:

Option = {label, string()}

See **external documentation**.

`getStaticBox(This::wxStaticBoxSizer()) -> wxStaticBox() (see module wxStaticBox)`

See **external documentation**.

`destroy(This::wxStaticBoxSizer()) -> ok`

Destroys this object, do not use object again

wxStaticLine

Erlang module

See external documentation: **wxStaticLine**.

This class is derived (and can use functions) from:

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxStaticLine()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxStaticLine()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow)) -> wxStaticLine()`

Equivalent to `new(Parent, [])`.

`new(Parent::wxWindow() (see module wxWindow), Options::[Option]) -> wxStaticLine()`

Types:

Option = {id, integer()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`create(This::wxStaticLine(), Parent::wxWindow() (see module wxWindow)) -> bool()`

Equivalent to `create(This, Parent, [])`.

`create(This::wxStaticLine(), Parent::wxWindow() (see module wxWindow), Options::[Option]) -> bool()`

Types:

Option = {id, integer()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`isVertical(This::wxStaticLine()) -> bool()`

See external documentation.

wxStaticLine

getDefaultSize() -> integer()

See **external documentation**.

destroy(This::wxStaticLine()) -> ok

Destroys this object, do not use object again

wxStaticText

Erlang module

See external documentation: **wxStaticText**.

This class is derived (and can use functions) from:

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxStaticText()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxStaticText()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Label::string()) -> wxStaticText()`

Equivalent to `new(Parent, Id, Label, [])`.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Label::string(), Options::[Option]) -> wxStaticText()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`create(This::wxStaticText(), Parent::wxWindow() (see module wxWindow), Id::integer(), Label::string()) -> bool()`

Equivalent to `create(This, Parent, Id, Label, [])`.

`create(This::wxStaticText(), Parent::wxWindow() (see module wxWindow), Id::integer(), Label::string(), Options::[Option]) -> bool()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`getLabel(This::wxStaticText()) -> string()`

See external documentation.

wxStaticText

setLabel(This::wxStaticText(), Label::string()) -> ok

See **external documentation**.

wrap(This::wxStaticText(), Width::integer()) -> ok

See **external documentation**.

destroy(This::wxStaticText()) -> ok

Destroys this object, do not use object again

wxStatusBar

Erlang module

See external documentation: **wxStatusBar**.

This class is derived (and can use functions) from:

wxWindow

wxEvtHandler

DATA TYPES

`wxStatusBar()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxStatusBar()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow)) -> wxStatusBar()`

Equivalent to `new(Parent, [])`.

`new(Parent::wxWindow() (see module wxWindow), Options::[Option]) -> wxStatusBar()`

Types:

Option = {winid, integer()} | {style, integer()}

See external documentation.

`create(This::wxStatusBar(), Parent::wxWindow() (see module wxWindow)) -> bool()`

Equivalent to `create(This, Parent, [])`.

`create(This::wxStatusBar(), Parent::wxWindow() (see module wxWindow), Options::[Option]) -> bool()`

Types:

Option = {winid, integer()} | {style, integer()}

See external documentation.

`getFieldRect(This::wxStatusBar(), I::integer(), Rect::{X::integer(), Y::integer(), W::integer(), H::integer()}) -> bool()`

See external documentation.

`getFieldsCount(This::wxStatusBar()) -> integer()`

See external documentation.

`getStatusText(This::wxStatusBar()) -> string()`

Equivalent to `getStatusText(This, [])`.

`getStatusText(This::wxStatusBar(), Options::[Option]) -> string()`

Types:

Option = {number, integer()}

See [external documentation](#).

`popStatusText(This::wxStatusBar()) -> ok`

Equivalent to `popStatusText(This, [])`.

`popStatusText(This::wxStatusBar(), Options::[Option]) -> ok`

Types:

Option = {number, integer()}

See [external documentation](#).

`pushStatusText(This::wxStatusBar(), Text::string()) -> ok`

Equivalent to `pushStatusText(This, Text, [])`.

`pushStatusText(This::wxStatusBar(), Text::string(), Options::[Option]) -> ok`

Types:

Option = {number, integer()}

See [external documentation](#).

`setFieldsCount(This::wxStatusBar(), Number::integer()) -> ok`

Equivalent to `setFieldsCount(This, Number, [])`.

`setFieldsCount(This::wxStatusBar(), Number::integer(), Options::[Option]) -> ok`

Types:

Option = {widths, [integer()]}

See [external documentation](#).

`setMinHeight(This::wxStatusBar(), Height::integer()) -> ok`

See [external documentation](#).

`setStatusText(This::wxStatusBar(), Text::string()) -> ok`

Equivalent to `setStatusText(This, Text, [])`.

`setStatusText(This::wxStatusBar(), Text::string(), Options::[Option]) -> ok`

Types:

Option = {number, integer()}

See [external documentation](#).

setStatusWidths(This::wxStatusBar(), Widths_field::[integer()]) -> ok

See **external documentation**.

setStatusStyles(This::wxStatusBar(), Styles::[integer()]) -> ok

See **external documentation**.

destroy(This::wxStatusBar()) -> ok

Destroys this object, do not use object again

wxStdDialogButtonSizer

Erlang module

See external documentation: **wxStdDialogButtonSizer**.

This class is derived (and can use functions) from:

wxBoxSizer

wxSizer

DATA TYPES

`wxStdDialogButtonSizer()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxStdDialogButtonSizer()`

See external documentation.

`addButton(This::wxStdDialogButtonSizer(), Button::wxButton() (see module wxButton)) -> ok`

See external documentation.

`realize(This::wxStdDialogButtonSizer()) -> ok`

See external documentation.

`setAffirmativeButton(This::wxStdDialogButtonSizer(), Button::wxButton() (see module wxButton)) -> ok`

See external documentation.

`setCancelButton(This::wxStdDialogButtonSizer(), Button::wxButton() (see module wxButton)) -> ok`

See external documentation.

`setNegativeButton(This::wxStdDialogButtonSizer(), Button::wxButton() (see module wxButton)) -> ok`

See external documentation.

`destroy(This::wxStdDialogButtonSizer()) -> ok`

Destroys this object, do not use object again

wxStyledTextCtrl

Erlang module

See external documentation: **wxStyledTextCtrl**.

This class is derived (and can use functions) from:

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxStyledTextCtrl()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxStyledTextCtrl()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow)) -> wxStyledTextCtrl()`

Equivalent to `new(Parent, [])`.

`new(Parent::wxWindow() (see module wxWindow), Options::[Option]) -> wxStyledTextCtrl()`

Types:

Option = {id, integer()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`create(This::wxStyledTextCtrl(), Parent::wxWindow() (see module wxWindow)) -> bool()`

Equivalent to `create(This, Parent, [])`.

`create(This::wxStyledTextCtrl(), Parent::wxWindow() (see module wxWindow), Options::[Option]) -> bool()`

Types:

Option = {id, integer()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`addText(This::wxStyledTextCtrl(), Text::string()) -> ok`

See external documentation.

`addStyledText(This::wxStyledTextCtrl(), Data::wxMemoryBuffer() (see module wxMemoryBuffer)) -> ok`

See external documentation.

`insertText(This::wxStyledTextCtrl(), Pos::integer(), Text::string()) -> ok`

See external documentation.

`clearAll(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`clearDocumentStyle(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`getLength(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`getCharAt(This::wxStyledTextCtrl(), Pos::integer()) -> integer()`

See external documentation.

`getCurrentPos(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`getAnchor(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`getStyleAt(This::wxStyledTextCtrl(), Pos::integer()) -> integer()`

See external documentation.

`redo(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`setUndoCollection(This::wxStyledTextCtrl(), CollectUndo::bool()) -> ok`

See external documentation.

`selectAll(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`setSavePoint(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`getStyledText(This::wxStyledTextCtrl(), StartPos::integer(), EndPos::integer()) -> wxMemoryBuffer() (see module wxMemoryBuffer)`

See external documentation.

`canRedo(This::wxStyledTextCtrl()) -> bool()`

See external documentation.

`markerLineFromHandle(This::wxStyledTextCtrl(), Handle::integer()) -> integer()`

See external documentation.

`markerDeleteHandle(This::wxStyledTextCtrl(), Handle::integer()) -> ok`

See external documentation.

`getUndoCollection(This::wxStyledTextCtrl()) -> bool()`

See external documentation.

`getViewWhiteSpace(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`setViewWhiteSpace(This::wxStyledTextCtrl(), ViewWS::integer()) -> ok`

See external documentation.

`positionFromPoint(This::wxStyledTextCtrl(), Pt::{X::integer(), Y::integer()}) -> integer()`

See external documentation.

`positionFromPointClose(This::wxStyledTextCtrl(), X::integer(), Y::integer()) -> integer()`

See external documentation.

`gotoLine(This::wxStyledTextCtrl(), Line::integer()) -> ok`

See external documentation.

`gotoPos(This::wxStyledTextCtrl(), Pos::integer()) -> ok`

See external documentation.

`setAnchor(This::wxStyledTextCtrl(), PosAnchor::integer()) -> ok`

See external documentation.

`getCurLine(This::wxStyledTextCtrl()) -> {string(), LinePos::integer()}`

See external documentation.

`getEndStyled(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`convertEOls(This::wxStyledTextCtrl(), EolMode::integer()) -> ok`

See external documentation.

`getEOLMode(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`setEOLMode(This::wxStyledTextCtrl(), EolMode::integer()) -> ok`

See external documentation.

`startStyling(This::wxStyledTextCtrl(), Pos::integer(), Mask::integer()) -> ok`

See external documentation.

`setStyling(This::wxStyledTextCtrl(), Length::integer(), Style::integer()) -> ok`

See external documentation.

`getBufferedDraw(This::wxStyledTextCtrl()) -> bool()`

See external documentation.

`setBufferedDraw(This::wxStyledTextCtrl(), Buffered::bool()) -> ok`

See external documentation.

`setTabWidth(This::wxStyledTextCtrl(), TabWidth::integer()) -> ok`

See external documentation.

`getTabWidth(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`setCodePage(This::wxStyledTextCtrl(), CodePage::integer()) -> ok`

See external documentation.

`markerDefine(This::wxStyledTextCtrl(), MarkerNumber::integer(), MarkerSymbol::integer()) -> ok`

Equivalent to *markerDefine(This, MarkerNumber, MarkerSymbol, [])*.

`markerDefine(This::wxStyledTextCtrl(), MarkerNumber::integer(), MarkerSymbol::integer(), Options::[Option]) -> ok`

Types:

Option = {foreground, colour() (see module wx)} | {background, colour() (see module wx)}

See external documentation.

markerSetForeground(This::wxStyledTextCtrl(), MarkerNumber::integer(),
Fore::colour() (see module wx)) -> ok

See external documentation.

markerSetBackground(This::wxStyledTextCtrl(), MarkerNumber::integer(),
Back::colour() (see module wx)) -> ok

See external documentation.

markerAdd(This::wxStyledTextCtrl(), Line::integer(), MarkerNumber::integer())
-> integer()

See external documentation.

markerDelete(This::wxStyledTextCtrl(), Line::integer(),
MarkerNumber::integer()) -> ok

See external documentation.

markerDeleteAll(This::wxStyledTextCtrl(), MarkerNumber::integer()) -> ok

See external documentation.

markerGet(This::wxStyledTextCtrl(), Line::integer()) -> integer()

See external documentation.

markerNext(This::wxStyledTextCtrl(), LineStart::integer(),
MarkerMask::integer()) -> integer()

See external documentation.

markerPrevious(This::wxStyledTextCtrl(), LineStart::integer(),
MarkerMask::integer()) -> integer()

See external documentation.

markerDefineBitmap(This::wxStyledTextCtrl(), MarkerNumber::integer(),
Bmp::wxBitmap() (see module wxBitmap)) -> ok

See external documentation.

markerAddSet(This::wxStyledTextCtrl(), Line::integer(), Set::integer()) -> ok

See external documentation.

markerSetAlpha(This::wxStyledTextCtrl(), MarkerNumber::integer(),
Alpha::integer()) -> ok

See external documentation.

setMarginType(This::wxStyledTextCtrl(), Margin::integer(),
MarginType::integer()) -> ok

See external documentation.

`getMarginType(This::wxStyledTextCtrl(), Margin::integer()) -> integer()`

See external documentation.

`setMarginWidth(This::wxStyledTextCtrl(), Margin::integer(),
PixelWidth::integer()) -> ok`

See external documentation.

`getMarginWidth(This::wxStyledTextCtrl(), Margin::integer()) -> integer()`

See external documentation.

`setMarginMask(This::wxStyledTextCtrl(), Margin::integer(), Mask::integer()) -
> ok`

See external documentation.

`getMarginMask(This::wxStyledTextCtrl(), Margin::integer()) -> integer()`

See external documentation.

`setMarginSensitive(This::wxStyledTextCtrl(), Margin::integer(),
Sensitive::bool()) -> ok`

See external documentation.

`getMarginSensitive(This::wxStyledTextCtrl(), Margin::integer()) -> bool()`

See external documentation.

`styleClearAll(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`styleSetForeground(This::wxStyledTextCtrl(), Style::integer(), Fore::colour()
(see module wx)) -> ok`

See external documentation.

`styleSetBackground(This::wxStyledTextCtrl(), Style::integer(), Back::colour()
(see module wx)) -> ok`

See external documentation.

`styleSetBold(This::wxStyledTextCtrl(), Style::integer(), Bold::bool()) -> ok`

See external documentation.

`styleSetItalic(This::wxStyledTextCtrl(), Style::integer(), Italic::bool()) ->
ok`

See external documentation.

```
styleSetSize(This::wxStyledTextCtrl(), Style::integer(),  
SizePoints::integer()) -> ok
```

See external documentation.

```
styleSetFaceName(This::wxStyledTextCtrl(), Style::integer(),  
FontName::string()) -> ok
```

See external documentation.

```
styleSetEOLFilled(This::wxStyledTextCtrl(), Style::integer(), Filled::bool())  
-> ok
```

See external documentation.

```
styleResetDefault(This::wxStyledTextCtrl()) -> ok
```

See external documentation.

```
styleSetUnderline(This::wxStyledTextCtrl(), Style::integer(),  
Underline::bool()) -> ok
```

See external documentation.

```
styleSetCase(This::wxStyledTextCtrl(), Style::integer(),  
CaseForce::integer()) -> ok
```

See external documentation.

```
styleSetHotSpot(This::wxStyledTextCtrl(), Style::integer(), Hotspot::bool())  
-> ok
```

See external documentation.

```
setSelForeground(This::wxStyledTextCtrl(), UseSetting::bool(), Fore::colour())  
(see module wx) -> ok
```

See external documentation.

```
setSelBackground(This::wxStyledTextCtrl(), UseSetting::bool(), Back::colour())  
(see module wx) -> ok
```

See external documentation.

```
getSelAlpha(This::wxStyledTextCtrl()) -> integer()
```

See external documentation.

```
setSelAlpha(This::wxStyledTextCtrl(), Alpha::integer()) -> ok
```

See external documentation.

```
setCaretForeground(This::wxStyledTextCtrl(), Fore::colour() (see module wx))  
-> ok
```

See external documentation.

`cmdKeyAssign(This::wxStyledTextCtrl(), Key::integer(), Modifiers::integer(),
Cmd::integer()) -> ok`

See external documentation.

`cmdKeyClear(This::wxStyledTextCtrl(), Key::integer(), Modifiers::integer()) -
> ok`

See external documentation.

`cmdKeyClearAll(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`setStyleBytes(This::wxStyledTextCtrl(), Length::integer()) -> integer()`

See external documentation.

`styleSetVisible(This::wxStyledTextCtrl(), Style::integer(), Visible::bool())
-> ok`

See external documentation.

`getCaretPeriod(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`setCaretPeriod(This::wxStyledTextCtrl(), PeriodMilliseconds::integer()) -> ok`

See external documentation.

`setWordChars(This::wxStyledTextCtrl(), Characters::string()) -> ok`

See external documentation.

`beginUndoAction(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`endUndoAction(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`indicatorSetStyle(This::wxStyledTextCtrl(), Indic::integer(),
Style::integer()) -> ok`

See external documentation.

`indicatorGetStyle(This::wxStyledTextCtrl(), Indic::integer()) -> integer()`

See external documentation.

`indicatorSetForeground(This::wxStyledTextCtrl(), Indic::integer(),
Fore::colour()) (see module wx) -> ok`

See external documentation.

`indicatorGetForeground(This::wxStyledTextCtrl(), Indic::integer()) -> colour() (see module wx)`

See external documentation.

`setWhitespaceForeground(This::wxStyledTextCtrl(), UseSetting::bool(), Fore::colour() (see module wx)) -> ok`

See external documentation.

`setWhitespaceBackground(This::wxStyledTextCtrl(), UseSetting::bool(), Back::colour() (see module wx)) -> ok`

See external documentation.

`getStyleBits(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`setLineState(This::wxStyledTextCtrl(), Line::integer(), State::integer()) -> ok`

See external documentation.

`getLineState(This::wxStyledTextCtrl(), Line::integer()) -> integer()`

See external documentation.

`getMaxLineState(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`getCaretLineVisible(This::wxStyledTextCtrl()) -> bool()`

See external documentation.

`setCaretLineVisible(This::wxStyledTextCtrl(), Show::bool()) -> ok`

See external documentation.

`getCaretLineBackground(This::wxStyledTextCtrl()) -> colour() (see module wx)`

See external documentation.

`setCaretLineBackground(This::wxStyledTextCtrl(), Back::colour() (see module wx)) -> ok`

See external documentation.

`autoCompShow(This::wxStyledTextCtrl(), LenEntered::integer(), ItemList::string()) -> ok`

See external documentation.

`autoCompCancel(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`autoCompActive(This::wxStyledTextCtrl()) -> bool()`

See external documentation.

`autoCompPosStart(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`autoCompComplete(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`autoCompStops(This::wxStyledTextCtrl(), CharacterSet::string()) -> ok`

See external documentation.

`autoCompSetSeparator(This::wxStyledTextCtrl(), SeparatorCharacter::integer())
-> ok`

See external documentation.

`autoCompGetSeparator(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`autoCompSelect(This::wxStyledTextCtrl(), Text::string()) -> ok`

See external documentation.

`autoCompSetCancelAtStart(This::wxStyledTextCtrl(), Cancel::bool()) -> ok`

See external documentation.

`autoCompGetCancelAtStart(This::wxStyledTextCtrl()) -> bool()`

See external documentation.

`autoCompSetFillUps(This::wxStyledTextCtrl(), CharacterSet::string()) -> ok`

See external documentation.

`autoCompSetChooseSingle(This::wxStyledTextCtrl(), ChooseSingle::bool()) -> ok`

See external documentation.

`autoCompGetChooseSingle(This::wxStyledTextCtrl()) -> bool()`

See external documentation.

`autoCompSetIgnoreCase(This::wxStyledTextCtrl(), IgnoreCase::bool()) -> ok`

See external documentation.

`autoCompGetIgnoreCase(This::wxStyledTextCtrl()) -> bool()`

See external documentation.


```
userListShow(This::wxStyledTextCtrl(), ListType::integer(),  
ItemList::string()) -> ok
```

See external documentation.

```
autoCompSetAutoHide(This::wxStyledTextCtrl(), AutoHide::bool()) -> ok
```

See external documentation.

```
autoCompGetAutoHide(This::wxStyledTextCtrl()) -> bool()
```

See external documentation.

```
autoCompSetDropRestOfWord(This::wxStyledTextCtrl(), DropRestOfWord::bool()) -  
> ok
```

See external documentation.

```
autoCompGetDropRestOfWord(This::wxStyledTextCtrl()) -> bool()
```

See external documentation.

```
registerImage(This::wxStyledTextCtrl(), Type::integer(), Bmp::wxBitmap() (see  
module wxBitmap)) -> ok
```

See external documentation.

```
clearRegisteredImages(This::wxStyledTextCtrl()) -> ok
```

See external documentation.

```
autoCompGetTypeSeparator(This::wxStyledTextCtrl()) -> integer()
```

See external documentation.

```
autoCompSetTypeSeparator(This::wxStyledTextCtrl(),  
SeparatorCharacter::integer()) -> ok
```

See external documentation.

```
autoCompSetMaxWidth(This::wxStyledTextCtrl(), CharacterCount::integer()) ->  
ok
```

See external documentation.

```
autoCompGetMaxWidth(This::wxStyledTextCtrl()) -> integer()
```

See external documentation.

```
autoCompSetMaxHeight(This::wxStyledTextCtrl(), RowCount::integer()) -> ok
```

See external documentation.

```
autoCompGetMaxHeight(This::wxStyledTextCtrl()) -> integer()
```

See external documentation.

setIndent(This::wxStyledTextCtrl(), IndentSize::integer()) -> ok

See external documentation.

getIndent(This::wxStyledTextCtrl()) -> integer()

See external documentation.

setUseTabs(This::wxStyledTextCtrl(), UseTabs::bool()) -> ok

See external documentation.

getUseTabs(This::wxStyledTextCtrl()) -> bool()

See external documentation.

**setLineIndentation(This::wxStyledTextCtrl(), Line::integer(),
IndentSize::integer()) -> ok**

See external documentation.

getLineIndentation(This::wxStyledTextCtrl(), Line::integer()) -> integer()

See external documentation.

getLineIndentPosition(This::wxStyledTextCtrl(), Line::integer()) -> integer()

See external documentation.

getColumn(This::wxStyledTextCtrl(), Pos::integer()) -> integer()

See external documentation.

setUseHorizontalScrollBar(This::wxStyledTextCtrl(), Show::bool()) -> ok

See external documentation.

getUseHorizontalScrollBar(This::wxStyledTextCtrl()) -> bool()

See external documentation.

setIndentationGuides(This::wxStyledTextCtrl(), Show::bool()) -> ok

See external documentation.

getIndentationGuides(This::wxStyledTextCtrl()) -> bool()

See external documentation.

setHighlightGuide(This::wxStyledTextCtrl(), Column::integer()) -> ok

See external documentation.

getHighlightGuide(This::wxStyledTextCtrl()) -> integer()

See external documentation.

`getLineEndPosition(This::wxStyledTextCtrl(), Line::integer()) -> integer()`

See external documentation.

`getCodePage(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`getCaretForeground(This::wxStyledTextCtrl()) -> colour() (see module wx)`

See external documentation.

`getReadOnly(This::wxStyledTextCtrl()) -> bool()`

See external documentation.

`setCurrentPos(This::wxStyledTextCtrl(), Pos::integer()) -> ok`

See external documentation.

`setSelectionStart(This::wxStyledTextCtrl(), Pos::integer()) -> ok`

See external documentation.

`getSelectionStart(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`setSelectionEnd(This::wxStyledTextCtrl(), Pos::integer()) -> ok`

See external documentation.

`getSelectionEnd(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`setPrintMagnification(This::wxStyledTextCtrl(), Magnification::integer()) -> ok`

See external documentation.

`getPrintMagnification(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`setPrintColourMode(This::wxStyledTextCtrl(), Mode::integer()) -> ok`

See external documentation.

`getPrintColourMode(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`findText(This::wxStyledTextCtrl(), MinPos::integer(), MaxPos::integer(), Text::string()) -> integer()`

Equivalent to *findText(This, MinPos, MaxPos, Text, [])*.

```
findText(This::wxStyledTextCtrl(), MinPos::integer(), MaxPos::integer(),
Text::string(), Options::[Option]) -> integer()
```

Types:

```
Option = {flags, integer()}
```

See external documentation.

```
formatRange(This::wxStyledTextCtrl(), DoDraw::bool(), StartPos::integer(),
EndPos::integer(), Draw::wxDC() (see module wxDC), Target::wxDC() (see module
wxDC), RenderRect::{X::integer(), Y::integer(), W::integer(), H::integer()},
PageRect::{X::integer(), Y::integer(), W::integer(), H::integer()}) ->
integer()
```

See external documentation.

```
getFirstVisibleLine(This::wxStyledTextCtrl()) -> integer()
```

See external documentation.

```
getLine(This::wxStyledTextCtrl(), Line::integer()) -> string()
```

See external documentation.

```
getLineCount(This::wxStyledTextCtrl()) -> integer()
```

See external documentation.

```
setMarginLeft(This::wxStyledTextCtrl(), PixelWidth::integer()) -> ok
```

See external documentation.

```
getMarginLeft(This::wxStyledTextCtrl()) -> integer()
```

See external documentation.

```
setMarginRight(This::wxStyledTextCtrl(), PixelWidth::integer()) -> ok
```

See external documentation.

```
getMarginRight(This::wxStyledTextCtrl()) -> integer()
```

See external documentation.

```
getModify(This::wxStyledTextCtrl()) -> bool()
```

See external documentation.

```
setSelection(This::wxStyledTextCtrl(), Start::integer(), End::integer()) ->
ok
```

See external documentation.

```
getSelectedText(This::wxStyledTextCtrl()) -> string()
```

See external documentation.

`getTextRange(This::wxStyledTextCtrl(), StartPos::integer(),
EndPos::integer()) -> string()`

See external documentation.

`hideSelection(This::wxStyledTextCtrl(), Normal::bool()) -> ok`

See external documentation.

`lineFromPosition(This::wxStyledTextCtrl(), Pos::integer()) -> integer()`

See external documentation.

`positionFromLine(This::wxStyledTextCtrl(), Line::integer()) -> integer()`

See external documentation.

`lineScroll(This::wxStyledTextCtrl(), Columns::integer(), Lines::integer()) ->
ok`

See external documentation.

`ensureCaretVisible(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`replaceSelection(This::wxStyledTextCtrl(), Text::string()) -> ok`

See external documentation.

`setReadOnly(This::wxStyledTextCtrl(), ReadOnly::bool()) -> ok`

See external documentation.

`canPaste(This::wxStyledTextCtrl()) -> bool()`

See external documentation.

`canUndo(This::wxStyledTextCtrl()) -> bool()`

See external documentation.

`emptyUndoBuffer(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`undo(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`cut(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`copy(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`paste(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`clear(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`setText(This::wxStyledTextCtrl(), Text::string()) -> ok`

See external documentation.

`getText(This::wxStyledTextCtrl()) -> string()`

See external documentation.

`getLength(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`getOvertype(This::wxStyledTextCtrl()) -> bool()`

See external documentation.

`setCaretWidth(This::wxStyledTextCtrl(), PixelWidth::integer()) -> ok`

See external documentation.

`getCaretWidth(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`setTargetStart(This::wxStyledTextCtrl(), Pos::integer()) -> ok`

See external documentation.

`getTargetStart(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`setTargetEnd(This::wxStyledTextCtrl(), Pos::integer()) -> ok`

See external documentation.

`getTargetEnd(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`replaceTarget(This::wxStyledTextCtrl(), Text::string()) -> integer()`

See external documentation.

`searchInTarget(This::wxStyledTextCtrl(), Text::string()) -> integer()`

See external documentation.

`setSearchFlags(This::wxStyledTextCtrl(), Flags::integer()) -> ok`

See external documentation.

`getSearchFlags(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`callTipShow(This::wxStyledTextCtrl(), Pos::integer(), Definition::string()) -> ok`

See external documentation.

`callTipCancel(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`callTipActive(This::wxStyledTextCtrl()) -> bool()`

See external documentation.

`callTipPosAtStart(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`callTipSetHighlight(This::wxStyledTextCtrl(), Start::integer(), End::integer()) -> ok`

See external documentation.

`callTipSetBackground(This::wxStyledTextCtrl(), Back::colour() (see module wx)) -> ok`

See external documentation.

`callTipSetForeground(This::wxStyledTextCtrl(), Fore::colour() (see module wx)) -> ok`

See external documentation.

`callTipSetForegroundHighlight(This::wxStyledTextCtrl(), Fore::colour() (see module wx)) -> ok`

See external documentation.

`callTipUseStyle(This::wxStyledTextCtrl(), TabSize::integer()) -> ok`

See external documentation.

`visibleFromDocLine(This::wxStyledTextCtrl(), Line::integer()) -> integer()`

See external documentation.

`docLineFromVisible(This::wxStyledTextCtrl(), LineDisplay::integer()) -> integer()`

See external documentation.

`wrapCount(This::wxStyledTextCtrl(), Line::integer()) -> integer()`

See external documentation.

`setFoldLevel(This::wxStyledTextCtrl(), Line::integer(), Level::integer()) -> ok`

See external documentation.

`getFoldLevel(This::wxStyledTextCtrl(), Line::integer()) -> integer()`

See external documentation.

`getLastChild(This::wxStyledTextCtrl(), Line::integer(), Level::integer()) -> integer()`

See external documentation.

`getFoldParent(This::wxStyledTextCtrl(), Line::integer()) -> integer()`

See external documentation.

`showLines(This::wxStyledTextCtrl(), LineStart::integer(), LineEnd::integer()) -> ok`

See external documentation.

`hideLines(This::wxStyledTextCtrl(), LineStart::integer(), LineEnd::integer()) -> ok`

See external documentation.

`getLineVisible(This::wxStyledTextCtrl(), Line::integer()) -> bool()`

See external documentation.

`setFoldExpanded(This::wxStyledTextCtrl(), Line::integer(), Expanded::bool()) -> ok`

See external documentation.

`getFoldExpanded(This::wxStyledTextCtrl(), Line::integer()) -> bool()`

See external documentation.

`toggleFold(This::wxStyledTextCtrl(), Line::integer()) -> ok`

See external documentation.

`ensureVisible(This::wxStyledTextCtrl(), Line::integer()) -> ok`

See external documentation.

`setFoldFlags(This::wxStyledTextCtrl(), Flags::integer()) -> ok`

See external documentation.

`ensureVisibleEnforcePolicy(This::wxStyledTextCtrl(), Line::integer()) -> ok`

See external documentation.

`setTabIndents(This::wxStyledTextCtrl(), TabIndents::bool()) -> ok`

See external documentation.

`getTabIndents(This::wxStyledTextCtrl()) -> bool()`

See external documentation.

`setBackSpaceUnIndents(This::wxStyledTextCtrl(), BsUnIndents::bool()) -> ok`

See external documentation.

`getBackSpaceUnIndents(This::wxStyledTextCtrl()) -> bool()`

See external documentation.

`setMouseDwellTime(This::wxStyledTextCtrl(), PeriodMilliseconds::integer()) -> ok`

See external documentation.

`getMouseDwellTime(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`wordStartPosition(This::wxStyledTextCtrl(), Pos::integer(), OnlyWordCharacters::bool()) -> integer()`

See external documentation.

`wordEndPosition(This::wxStyledTextCtrl(), Pos::integer(), OnlyWordCharacters::bool()) -> integer()`

See external documentation.

`setWrapMode(This::wxStyledTextCtrl(), Mode::integer()) -> ok`

See external documentation.

`getWrapMode(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`setWrapVisualFlags(This::wxStyledTextCtrl(), WrapVisualFlags::integer()) -> ok`

See external documentation.

`getWrapVisualFlags(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`setWrapVisualFlagsLocation(This::wxStyledTextCtrl(),
WrapVisualFlagsLocation::integer()) -> ok`

See external documentation.

`getWrapVisualFlagsLocation(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`setWrapStartIndent(This::wxStyledTextCtrl(), Indent::integer()) -> ok`

See external documentation.

`getWrapStartIndent(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`setLayoutCache(This::wxStyledTextCtrl(), Mode::integer()) -> ok`

See external documentation.

`getLayoutCache(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`setScrollWidth(This::wxStyledTextCtrl(), PixelWidth::integer()) -> ok`

See external documentation.

`getScrollWidth(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`textWidth(This::wxStyledTextCtrl(), Style::integer(), Text::string()) ->
integer()`

See external documentation.

`getEndAtLastLine(This::wxStyledTextCtrl()) -> bool()`

See external documentation.

`textHeight(This::wxStyledTextCtrl(), Line::integer()) -> integer()`

See external documentation.

`setUseVerticalScrollBar(This::wxStyledTextCtrl(), Show::bool()) -> ok`

See external documentation.

`getUseVerticalScrollBar(This::wxStyledTextCtrl()) -> bool()`

See external documentation.

`appendText(This::wxStyledTextCtrl(), Text::string()) -> ok`

See external documentation.

`getTwoPhaseDraw(This::wxStyledTextCtrl()) -> bool()`

See external documentation.

`setTwoPhaseDraw(This::wxStyledTextCtrl(), TwoPhase::bool()) -> ok`

See external documentation.

`targetFromSelection(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`linesJoin(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`linesSplit(This::wxStyledTextCtrl(), PixelWidth::integer()) -> ok`

See external documentation.

`setFoldMarginColour(This::wxStyledTextCtrl(), UseSetting::bool(),
Back::colour() (see module wx)) -> ok`

See external documentation.

`setFoldMarginHiColour(This::wxStyledTextCtrl(), UseSetting::bool(),
Fore::colour() (see module wx)) -> ok`

See external documentation.

`lineDown(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`lineDownExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`lineUp(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`lineUpExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`charLeft(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`charLeftExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`charRight(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`charRightExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`wordLeft(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`wordLeftExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`wordRight(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`wordRightExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`home(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`homeExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`lineEnd(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`lineEndExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`documentStart(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`documentStartExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`documentEnd(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`documentEndExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`pageUp(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`pageUpExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`pageDown(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`pageDownExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`editToggleOvertyping(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`cancel(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`deleteBack(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`tab(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`backTab(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`newLine(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`formFeed(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`vCHome(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`vCHomeExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`zoomIn(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`zoomOut(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`delWordLeft(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`delWordRight(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`lineCut(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`lineDelete(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`lineTranspose(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`lineDuplicate(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`lowerCase(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`upperCase(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`lineScrollDown(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`lineScrollUp(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`deleteBackNotLine(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`homeDisplay(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`homeDisplayExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`lineEndDisplay(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`lineEndDisplayExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`homeWrapExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`lineEndWrap(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`lineEndWrapExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`vCHomeWrap(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`vCHomeWrapExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`lineCopy(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`moveCaretInsideView(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`lineLength(This::wxStyledTextCtrl(), Line::integer()) -> integer()`

See external documentation.

`braceHighlight(This::wxStyledTextCtrl(), Pos1::integer(), Pos2::integer()) -> ok`

See external documentation.

`braceBadLight(This::wxStyledTextCtrl(), Pos::integer()) -> ok`

See external documentation.

`braceMatch(This::wxStyledTextCtrl(), Pos::integer()) -> integer()`

See external documentation.

`getViewEOL(This::wxStyledTextCtrl()) -> bool()`

See external documentation.

`setViewEOL(This::wxStyledTextCtrl(), Visible::bool()) -> ok`

See external documentation.

`setModEventMask(This::wxStyledTextCtrl(), Mask::integer()) -> ok`

See external documentation.

`getEdgeColumn(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`setEdgeColumn(This::wxStyledTextCtrl(), Column::integer()) -> ok`

See external documentation.

`getEdgeMode(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`getEdgeColour(This::wxStyledTextCtrl()) -> colour() (see module wx)`

See external documentation.

`setEdgeColour(This::wxStyledTextCtrl(), EdgeColour::colour() (see module wx))
-> ok`

See external documentation.

`searchAnchor(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`searchNext(This::wxStyledTextCtrl(), Flags::integer(), Text::string()) ->
integer()`

See external documentation.

`searchPrev(This::wxStyledTextCtrl(), Flags::integer(), Text::string()) ->
integer()`

See external documentation.

`linesOnScreen(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`usePopUp(This::wxStyledTextCtrl(), AllowPopUp::bool()) -> ok`

See external documentation.

`selectionIsRectangle(This::wxStyledTextCtrl()) -> bool()`

See external documentation.

`setZoom(This::wxStyledTextCtrl(), Zoom::integer()) -> ok`

See external documentation.

`getZoom(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`getModEventMask(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`setSTCFocus(This::wxStyledTextCtrl(), Focus::bool()) -> ok`

See external documentation.

`getSTCFocus(This::wxStyledTextCtrl()) -> bool()`

See external documentation.

`setStatus(This::wxStyledTextCtrl(), StatusCode::integer()) -> ok`

See external documentation.

`getStatus(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`setMouseDownCaptures(This::wxStyledTextCtrl(), Captures::bool()) -> ok`

See external documentation.

`getMouseDownCaptures(This::wxStyledTextCtrl()) -> bool()`

See external documentation.

`setSTCCursor(This::wxStyledTextCtrl(), CursorType::integer()) -> ok`

See external documentation.

`getSTCCursor(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`setControlCharSymbol(This::wxStyledTextCtrl(), Symbol::integer()) -> ok`

See external documentation.

`getControlCharSymbol(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`wordPartLeft(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`wordPartLeftExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`wordPartRight(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`wordPartRightExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`setVisiblePolicy(This::wxStyledTextCtrl(), VisiblePolicy::integer(),
VisibleSlop::integer()) -> ok`

See external documentation.

`delLineLeft(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`delLineRight(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`getXOffset(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`chooseCaretX(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`setXCaretPolicy(This::wxStyledTextCtrl(), CaretPolicy::integer(),
CaretSlop::integer()) -> ok`

See external documentation.

`setYCaretPolicy(This::wxStyledTextCtrl(), CaretPolicy::integer(),
CaretSlop::integer()) -> ok`

See external documentation.

`getPrintWrapMode(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`setHotspotActiveForeground(This::wxStyledTextCtrl(), UseSetting::bool(),
Fore::colour() (see module wx)) -> ok`

See external documentation.

`setHotspotActiveBackground(This::wxStyledTextCtrl(), UseSetting::bool(),
Back::colour() (see module wx)) -> ok`

See external documentation.

`setHotspotActiveUnderline(This::wxStyledTextCtrl(), Underline::bool()) -> ok`

See external documentation.

`setHotspotSingleLine(This::wxStyledTextCtrl(), SingleLine::bool()) -> ok`

See external documentation.

`paraDownExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`paraUp(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`paraUpExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`positionBefore(This::wxStyledTextCtrl(), Pos::integer()) -> integer()`

See external documentation.

`positionAfter(This::wxStyledTextCtrl(), Pos::integer()) -> integer()`

See external documentation.

`copyRange(This::wxStyledTextCtrl(), Start::integer(), End::integer()) -> ok`

See external documentation.

`copyText(This::wxStyledTextCtrl(), Length::integer(), Text::string()) -> ok`

See external documentation.

`setSelectionMode(This::wxStyledTextCtrl(), Mode::integer()) -> ok`

See external documentation.

`getSelectionMode(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`lineDownRectExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`lineUpRectExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`charLeftRectExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`charRightRectExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`homeRectExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`vCHomeRectExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`lineEndRectExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`pageUpRectExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`pageDownRectExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`stutteredPageUp(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`stutteredPageUpExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`stutteredPageDown(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`stutteredPageDownExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`wordLeftEnd(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`wordLeftEndExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`wordRightEnd(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`wordRightEndExtend(This::wxStyledTextCtrl()) -> ok`

See external documentation.

`setWhitespaceChars(This::wxStyledTextCtrl(), Characters::string()) -> ok`

See external documentation.

setCharsDefault(This::wxStyledTextCtrl()) -> ok

See external documentation.

autoCompGetCurrent(This::wxStyledTextCtrl()) -> integer()

See external documentation.

allocate(This::wxStyledTextCtrl(), Bytes::integer()) -> ok

See external documentation.

findColumn(This::wxStyledTextCtrl(), Line::integer(), Column::integer()) -> integer()

See external documentation.

getCaretSticky(This::wxStyledTextCtrl()) -> bool()

See external documentation.

setCaretSticky(This::wxStyledTextCtrl(), UseCaretStickyBehaviour::bool()) -> ok

See external documentation.

toggleCaretSticky(This::wxStyledTextCtrl()) -> ok

See external documentation.

setPasteConvertEndings(This::wxStyledTextCtrl(), Convert::bool()) -> ok

See external documentation.

getPasteConvertEndings(This::wxStyledTextCtrl()) -> bool()

See external documentation.

selectionDuplicate(This::wxStyledTextCtrl()) -> ok

See external documentation.

setCaretLineBackAlpha(This::wxStyledTextCtrl(), Alpha::integer()) -> ok

See external documentation.

getCaretLineBackAlpha(This::wxStyledTextCtrl()) -> integer()

See external documentation.

startRecord(This::wxStyledTextCtrl()) -> ok

See external documentation.

stopRecord(This::wxStyledTextCtrl()) -> ok

See external documentation.

`setLexer(This::wxStyledTextCtrl(), Lexer::integer()) -> ok`

See external documentation.

`getLexer(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`colourise(This::wxStyledTextCtrl(), Start::integer(), End::integer()) -> ok`

See external documentation.

`setProperty(This::wxStyledTextCtrl(), Key::string(), Value::string()) -> ok`

See external documentation.

`setKeyWords(This::wxStyledTextCtrl(), KeywordSet::integer(),
KeyWords::string()) -> ok`

See external documentation.

`setLexerLanguage(This::wxStyledTextCtrl(), Language::string()) -> ok`

See external documentation.

`getProperty(This::wxStyledTextCtrl(), Key::string()) -> string()`

See external documentation.

`getStyleBitsNeeded(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`getCurrentLine(This::wxStyledTextCtrl()) -> integer()`

See external documentation.

`styleSetSpec(This::wxStyledTextCtrl(), StyleNum::integer(), Spec::string()) -
> ok`

See external documentation.

`styleSetFont(This::wxStyledTextCtrl(), StyleNum::integer(), Font::wxFont()
(see module wxFont)) -> ok`

See external documentation.

`styleSetFontAttr(This::wxStyledTextCtrl(), StyleNum::integer(),
Size::integer(), FaceName::string(), Bold::bool(), Italic::bool(),
Underline::bool()) -> ok`

Equivalent to `styleSetFontAttr(This, StyleNum, Size, FaceName, Bold, Italic, Underline, [])`.

```
styleSetFontAttr(This::wxStyledTextCtrl(), StyleNum::integer(),
Size::integer(), FaceName::string(), Bold::bool(), Italic::bool(),
Underline::bool(), Options::[Option]) -> ok
```

Types:

Option = {encoding, WxFontEncoding}

WxFontEncoding = integer()

See **external documentation**.

WxFontEncoding is one of ?wxFONTENCODING_SYSTEM | ?wxFONTENCODING_DEFAULT | ?wxFONTENCODING_ISO8859_1 | ?wxFONTENCODING_ISO8859_2 | ?wxFONTENCODING_ISO8859_3 | ?wxFONTENCODING_ISO8859_4 | ?wxFONTENCODING_ISO8859_5 | ?wxFONTENCODING_ISO8859_6 | ?wxFONTENCODING_ISO8859_7 | ?wxFONTENCODING_ISO8859_8 | ?wxFONTENCODING_ISO8859_9 | ?wxFONTENCODING_ISO8859_10 | ?wxFONTENCODING_ISO8859_11 | ?wxFONTENCODING_ISO8859_12 | ?wxFONTENCODING_ISO8859_13 | ?wxFONTENCODING_ISO8859_14 | ?wxFONTENCODING_ISO8859_15 | ?wxFONTENCODING_ISO8859_MAX | ?wxFONTENCODING_KOI8 | ?wxFONTENCODING_KOI8_U | ?wxFONTENCODING_ALTERNATIVE | ?wxFONTENCODING_BULGARIAN | ?wxFONTENCODING_CP437 | ?wxFONTENCODING_CP850 | ?wxFONTENCODING_CP852 | ?wxFONTENCODING_CP855 | ?wxFONTENCODING_CP866 | ?wxFONTENCODING_CP874 | ?wxFONTENCODING_CP932 | ?wxFONTENCODING_CP936 | ?wxFONTENCODING_CP949 | ?wxFONTENCODING_CP950 | ?wxFONTENCODING_CP1250 | ?wxFONTENCODING_CP1251 | ?wxFONTENCODING_CP1252 | ?wxFONTENCODING_CP1253 | ?wxFONTENCODING_CP1254 | ?wxFONTENCODING_CP1255 | ?wxFONTENCODING_CP1256 | ?wxFONTENCODING_CP1257 | ?wxFONTENCODING_CP12_MAX | ?wxFONTENCODING_UTF7 | ?wxFONTENCODING_UTF8 | ?wxFONTENCODING_EUC_JP | ?wxFONTENCODING_UTF16BE | ?wxFONTENCODING_UTF16LE | ?wxFONTENCODING_UTF32BE | ?wxFONTENCODING_UTF32LE | ?wxFONTENCODING_MACROMAN | ?wxFONTENCODING_MACJAPANESE | ?wxFONTENCODING_MACCHINESETRAD | ?wxFONTENCODING_MACKOREAN | ?wxFONTENCODING_MACARABIC | ?wxFONTENCODING_MACHEBREW | ?wxFONTENCODING_MACGREEK | ?wxFONTENCODING_MACCYRILLIC | ?wxFONTENCODING_MACDEVANAGARI | ?wxFONTENCODING_MACGURMUKHI | ?wxFONTENCODING_MACGUJARATI | ?wxFONTENCODING_MACORIYA | ?wxFONTENCODING_MACBENGALI | ?wxFONTENCODING_MACTAMIL | ?wxFONTENCODING_MACTELUGU | ?wxFONTENCODING_MACKANNADA | ?wxFONTENCODING_MACMALAJALAM | ?wxFONTENCODING_MACSINHALESE | ?wxFONTENCODING_MACBURMESE | ?wxFONTENCODING_MACKHMER | ?wxFONTENCODING_MACTHAI | ?wxFONTENCODING_MACLAOTIAN | ?wxFONTENCODING_MACGEORGIAN | ?wxFONTENCODING_MACARMENIAN | ?wxFONTENCODING_MACCHINESESIMP | ?wxFONTENCODING_MACTIBETAN | ?wxFONTENCODING_MACMONGOLIAN | ?wxFONTENCODING_MACETHIOPIA | ?wxFONTENCODING_MACCENTRALEUR | ?wxFONTENCODING_MACVIETNAMESE | ?wxFONTENCODING_MACARABICEXT | ?wxFONTENCODING_MACSYMBOL | ?wxFONTENCODING_MACDINGBATS | ?wxFONTENCODING_MACTURKISH | ?wxFONTENCODING_MACCROATIAN | ?wxFONTENCODING_MACICELANDIC | ?wxFONTENCODING_MACROMANIAN | ?wxFONTENCODING_MACCELTIC | ?wxFONTENCODING_MACGAELIC | ?wxFONTENCODING_MACKEYBOARD | ?wxFONTENCODING_MAX | ?wxFONTENCODING_MACMIN | ?wxFONTENCODING_MACMAX | ?wxFONTENCODING_UTF16 | ?wxFONTENCODING_UTF32 | ?wxFONTENCODING_UNICODE | ?wxFONTENCODING_GB2312 | ?wxFONTENCODING_BIG5 | ?wxFONTENCODING_SHIFT_JIS

```
styleSetCharacterSet(This::wxStyledTextCtrl(), Style::integer(),  
CharacterSet::integer()) -> ok
```

See [external documentation](#).

```
styleSetFontEncoding(This::wxStyledTextCtrl(), Style::integer(),  
Encoding::WxFontEncoding) -> ok
```

Types:

WxFontEncoding = integer()

See [external documentation](#).

WxFontEncoding is one of ?wxFONTENCODING_SYSTEM | ?wxFONTENCODING_DEFAULT | ?
wxFONTENCODING_ISO8859_1 | ?wxFONTENCODING_ISO8859_2 | ?wxFONTENCODING_ISO8859_3 | ?
wxFONTENCODING_ISO8859_4 | ?wxFONTENCODING_ISO8859_5 | ?wxFONTENCODING_ISO8859_6 | ?
wxFONTENCODING_ISO8859_7 | ?wxFONTENCODING_ISO8859_8 | ?wxFONTENCODING_ISO8859_9 | ?
wxFONTENCODING_ISO8859_10 | ?wxFONTENCODING_ISO8859_11 | ?wxFONTENCODING_ISO8859_12
| ?wxFONTENCODING_ISO8859_13 | ?wxFONTENCODING_ISO8859_14 | ?wxFONTENCODING_ISO8859_15
| ?wxFONTENCODING_ISO8859_MAX | ?wxFONTENCODING_KOI8 | ?wxFONTENCODING_KOI8_U
| ?wxFONTENCODING_ALTERNATIVE | ?wxFONTENCODING_BULGARIAN | ?
wxFONTENCODING_CP437 | ?wxFONTENCODING_CP850 | ?wxFONTENCODING_CP852 | ?
wxFONTENCODING_CP855 | ?wxFONTENCODING_CP866 | ?wxFONTENCODING_CP874 | ?
wxFONTENCODING_CP932 | ?wxFONTENCODING_CP936 | ?wxFONTENCODING_CP949 | ?
wxFONTENCODING_CP950 | ?wxFONTENCODING_CP1250 | ?wxFONTENCODING_CP1251 | ?
wxFONTENCODING_CP1252 | ?wxFONTENCODING_CP1253 | ?wxFONTENCODING_CP1254 | ?
wxFONTENCODING_CP1255 | ?wxFONTENCODING_CP1256 | ?wxFONTENCODING_CP1257 | ?
wxFONTENCODING_CP12_MAX | ?wxFONTENCODING_UTF7 | ?wxFONTENCODING_UTF8 | ?
wxFONTENCODING_EUC_JP | ?wxFONTENCODING_UTF16BE | ?wxFONTENCODING_UTF16LE | ?
wxFONTENCODING_UTF32BE | ?wxFONTENCODING_UTF32LE | ?wxFONTENCODING_MACROMAN
| ?wxFONTENCODING_MACJAPANESE | ?wxFONTENCODING_MACCHINESETRAD | ?
wxFONTENCODING_MACKOREAN | ?wxFONTENCODING_MACARABIC | ?
wxFONTENCODING_MACHEBREW | ?wxFONTENCODING_MACGREEK | ?
wxFONTENCODING_MACCYRILLIC | ?wxFONTENCODING_MACDEVANAGARI | ?
wxFONTENCODING_MACGURMUKHI | ?wxFONTENCODING_MACGUJARATI | ?
wxFONTENCODING_MACORIYA | ?wxFONTENCODING_MACBENGALI | ?
wxFONTENCODING_MACTAMIL | ?wxFONTENCODING_MACTELUGU | ?
wxFONTENCODING_MACKANNADA | ?wxFONTENCODING_MACMALAJALAM | ?
wxFONTENCODING_MACSINHALESE | ?wxFONTENCODING_MACBURMESE | ?
wxFONTENCODING_MACKHMER | ?wxFONTENCODING_MACTHAI | ?
wxFONTENCODING_MACLAOTIAN | ?wxFONTENCODING_MACGEORGIAN | ?
wxFONTENCODING_MACARMENIAN | ?wxFONTENCODING_MACCHINESESIMP | ?
wxFONTENCODING_MACTIBETAN | ?wxFONTENCODING_MACMONGOLIAN | ?
wxFONTENCODING_MACETHIOPIC | ?wxFONTENCODING_MACCENTRALEUR | ?
wxFONTENCODING_MACVIATNAMESE | ?wxFONTENCODING_MACARABICEXT | ?
wxFONTENCODING_MACSYMBOL | ?wxFONTENCODING_MACDINGBATS | ?
wxFONTENCODING_MACTURKISH | ?wxFONTENCODING_MACCROATIAN | ?
wxFONTENCODING_MACICELANDIC | ?wxFONTENCODING_MACROMANIAN | ?
wxFONTENCODING_MACCEL TIC | ?wxFONTENCODING_MACGAELIC | ?
wxFONTENCODING_MACKEYBOARD | ?wxFONTENCODING_MAX | ?wxFONTENCODING_MACMIN
| ?wxFONTENCODING_MACMAX | ?wxFONTENCODING_UTF16 | ?wxFONTENCODING_UTF32 | ?
wxFONTENCODING_UNICODE | ?wxFONTENCODING_GB2312 | ?wxFONTENCODING_BIG5 | ?
wxFONTENCODING_SHIFT_JIS

`cmdKeyExecute(This::wxStyledTextCtrl(), Cmd::integer()) -> ok`

See external documentation.

`setMargins(This::wxStyledTextCtrl(), Left::integer(), Right::integer()) -> ok`

See external documentation.

`getSelection(This::wxStyledTextCtrl()) -> {StartPos::integer(),
EndPos::integer()}`

See external documentation.

`pointFromPosition(This::wxStyledTextCtrl(), Pos::integer()) -> {X::integer(),
Y::integer()}`

See external documentation.

`scrollToLine(This::wxStyledTextCtrl(), Line::integer()) -> ok`

See external documentation.

`scrollToColumn(This::wxStyledTextCtrl(), Column::integer()) -> ok`

See external documentation.

`sendMsg(This::wxStyledTextCtrl(), Msg::integer()) -> integer()`

Equivalent to *sendMsg(This, Msg, [])*.

`sendMsg(This::wxStyledTextCtrl(), Msg::integer(), Options::[Option]) ->
integer()`

Types:

`Option = {wp, integer()} | {lp, integer()}`

See external documentation.

`setVScrollBar(This::wxStyledTextCtrl(), Bar::wxScrollBar() (see module
wxScrollBar)) -> ok`

See external documentation.

`setHScrollBar(This::wxStyledTextCtrl(), Bar::wxScrollBar() (see module
wxScrollBar)) -> ok`

See external documentation.

`getLastKeyDownProcessed(This::wxStyledTextCtrl()) -> bool()`

See external documentation.

`setLastKeyDownProcessed(This::wxStyledTextCtrl(), Val::bool()) -> ok`

See external documentation.

`saveFile(This::wxStyledTextCtrl(), Filename::string()) -> bool()`

See external documentation.

`loadFile(This::wxStyledTextCtrl(), Filename::string()) -> bool()`

See external documentation.

`doDragOver(This::wxStyledTextCtrl(), X::integer(), Y::integer(),
Def::WxDragResult) -> WxDragResult`

Types:

`WxDragResult = integer()`

`WxDragResult = integer()`

See external documentation.

WxDragResult is one of ?wxDragError | ?wxDragNone | ?wxDragCopy | ?wxDragMove | ?wxDragLink | ?wxDragCancel

WxDragResult is one of ?wxDragError | ?wxDragNone | ?wxDragCopy | ?wxDragMove | ?wxDragLink | ?wxDragCancel

`doDropText(This::wxStyledTextCtrl(), X::integer(), Y::integer(),
Data::string()) -> bool()`

See external documentation.

`getUseAntiAliasing(This::wxStyledTextCtrl()) -> bool()`

See external documentation.

`addTextRaw(This::wxStyledTextCtrl(), Text::binary()) -> ok`

See external documentation.

`insertTextRaw(This::wxStyledTextCtrl(), Pos::integer(), Text::binary()) -> ok`

See external documentation.

`getCurLineRaw(This::wxStyledTextCtrl()) -> {binary(), LinePos::integer()}`

See external documentation.

`getLineRaw(This::wxStyledTextCtrl(), Line::integer()) -> binary()`

See external documentation.

`getSelectedTextRaw(This::wxStyledTextCtrl()) -> binary()`

See external documentation.

`getTextRangeRaw(This::wxStyledTextCtrl(), StartPos::integer(),
EndPos::integer()) -> binary()`

See external documentation.

setTextRaw(This::wxStyledTextCtrl(), Text::binary()) -> ok

See external documentation.

getTextRaw(This::wxStyledTextCtrl()) -> binary()

See external documentation.

appendTextRaw(This::wxStyledTextCtrl(), Text::binary()) -> ok

See external documentation.

destroy(This::wxStyledTextCtrl()) -> ok

Destroys this object, do not use object again

wxStyledTextEvent

Erlang module

See external documentation: **wxStyledTextEvent**.

Use *wxEvtHandler:connect/3* with EventType:

stc_change, stc_stylenEEDED, stc_charadded, stc_savepointreached, stc_savepointleft, stc_romodifyattempt, stc_key, stc_doubleclick, stc_updateui, stc_modified, stc_macrorecord, stc_marginclick, stc_needshown, stc_painted, stc_userlistselection, stc_uridropped, stc_dwellstart, stc_dwellend, stc_start_drag, stc_drag_over, stc_do_drop, stc_zoom, stc_hotspot_click, stc_hotspot_dclick, stc_calltip_click, stc_autocomp_selection

See also the message variant *#wxStyledText{}* event record type.

This class is derived (and can use functions) from:

wxCommandEvent

wxEvent

DATA TYPES

wxStyledTextEvent()

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

getPosition(This::wxStyledTextEvent()) -> integer()

See external documentation.

getKey(This::wxStyledTextEvent()) -> integer()

See external documentation.

getModifiers(This::wxStyledTextEvent()) -> integer()

See external documentation.

getModificationType(This::wxStyledTextEvent()) -> integer()

See external documentation.

getText(This::wxStyledTextEvent()) -> string()

See external documentation.

getLength(This::wxStyledTextEvent()) -> integer()

See external documentation.

getLinesAdded(This::wxStyledTextEvent()) -> integer()

See external documentation.

`getLine(This::wxStyledTextEvent()) -> integer()`

See external documentation.

`getFoldLevelNow(This::wxStyledTextEvent()) -> integer()`

See external documentation.

`getFoldLevelPrev(This::wxStyledTextEvent()) -> integer()`

See external documentation.

`getMargin(This::wxStyledTextEvent()) -> integer()`

See external documentation.

`getMessage(This::wxStyledTextEvent()) -> integer()`

See external documentation.

`getWParam(This::wxStyledTextEvent()) -> integer()`

See external documentation.

`getLParam(This::wxStyledTextEvent()) -> integer()`

See external documentation.

`getListType(This::wxStyledTextEvent()) -> integer()`

See external documentation.

`getX(This::wxStyledTextEvent()) -> integer()`

See external documentation.

`getY(This::wxStyledTextEvent()) -> integer()`

See external documentation.

`getDragText(This::wxStyledTextEvent()) -> string()`

See external documentation.

`getDragAllowMove(This::wxStyledTextEvent()) -> bool()`

See external documentation.

`getDragResult(This::wxStyledTextEvent()) -> WxDragResult`

Types:

`WxDragResult = integer()`

See external documentation.

WxDragResult is one of ?wxDragError | ?wxDragNone | ?wxDragCopy | ?wxDragMove | ?wxDragLink | ?wxDragCancel

wxStyledTextEvent

getShift(This::wxStyledTextEvent()) -> bool()

See [external documentation](#).

getControl(This::wxStyledTextEvent()) -> bool()

See [external documentation](#).

getAlt(This::wxStyledTextEvent()) -> bool()

See [external documentation](#).

wxSysColourChangedEvent

Erlang module

See external documentation: **wxSysColourChangedEvent**.

Use *wxEvtHandler:connect/3* with EventType:

sys_colour_changed

See also the message variant *#wxSysColourChanged{}* event record type.

This class is derived (and can use functions) from:

wxEvent

DATA TYPES

`wxSysColourChangedEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

wxTextAttr

Erlang module

See external documentation: **wxTextAttr**.

DATA TYPES

`wxTextAttr()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxTextAttr()`

See external documentation.

`new(ColText::colour() (see module wx)) -> wxTextAttr()`

Equivalent to `new(ColText, [])`.

`new(ColText::colour() (see module wx), Options::[Option]) -> wxTextAttr()`

Types:

Option = {colBack, colour() (see module wx)} | {font, wxFont() (see module wxFont)} | {alignment, WxTextAttrAlignment}

WxTextAttrAlignment = integer()

See external documentation.

WxTextAttrAlignment is one of ?wxTEXT_ALIGNMENT_DEFAULT | ?wxTEXT_ALIGNMENT_LEFT | ?wxTEXT_ALIGNMENT_CENTRE | ?wxTEXT_ALIGNMENT_CENTER | ?wxTEXT_ALIGNMENT_RIGHT | ?wxTEXT_ALIGNMENT_JUSTIFIED

`getAlignment(This::wxTextAttr()) -> WxTextAttrAlignment`

Types:

WxTextAttrAlignment = integer()

See external documentation.

WxTextAttrAlignment is one of ?wxTEXT_ALIGNMENT_DEFAULT | ?wxTEXT_ALIGNMENT_LEFT | ?wxTEXT_ALIGNMENT_CENTRE | ?wxTEXT_ALIGNMENT_CENTER | ?wxTEXT_ALIGNMENT_RIGHT | ?wxTEXT_ALIGNMENT_JUSTIFIED

`getBackgroundColour(This::wxTextAttr()) -> colour() (see module wx)`

See external documentation.

`getFont(This::wxTextAttr()) -> wxFont() (see module wxFont)`

See external documentation.

getLeftIndent(This::wxTextAttr()) -> integer()

See external documentation.

getLeftSubIndent(This::wxTextAttr()) -> integer()

See external documentation.

getRightIndent(This::wxTextAttr()) -> integer()

See external documentation.

getTabs(This::wxTextAttr()) -> [integer()]

See external documentation.

getTextColour(This::wxTextAttr()) -> colour() (see module wx)

See external documentation.

hasBackgroundColour(This::wxTextAttr()) -> bool()

See external documentation.

hasFont(This::wxTextAttr()) -> bool()

See external documentation.

hasTextColour(This::wxTextAttr()) -> bool()

See external documentation.

getFlags(This::wxTextAttr()) -> integer()

See external documentation.

isDefault(This::wxTextAttr()) -> bool()

See external documentation.

setAlignment(This::wxTextAttr(), Alignment::WxTextAttrAlignment) -> ok

Types:

WxTextAttrAlignment = integer()

See external documentation.

WxTextAttrAlignment is one of ?wxTEXT_ALIGNMENT_DEFAULT | ?wxTEXT_ALIGNMENT_LEFT | ?wxTEXT_ALIGNMENT_CENTRE | ?wxTEXT_ALIGNMENT_CENTER | ?wxTEXT_ALIGNMENT_RIGHT | ?wxTEXT_ALIGNMENT_JUSTIFIED

setBackgroundColour(This::wxTextAttr(), ColBack::colour() (see module wx)) -> ok

See external documentation.

setFlags(This::wxTextAttr(), Flags::integer()) -> ok

See external documentation.

setFont(This::wxTextAttr(), Font::wxFont() (see module wxFont)) -> ok

Equivalent to *setFont(This, Font, [])*.

setFont(This::wxTextAttr(), Font::wxFont() (see module wxFont), Options::[Option]) -> ok

Types:

Option = {flags, integer()}

See external documentation.

setLeftIndent(This::wxTextAttr(), Indent::integer()) -> ok

Equivalent to *setLeftIndent(This, Indent, [])*.

setLeftIndent(This::wxTextAttr(), Indent::integer(), Options::[Option]) -> ok

Types:

Option = {subIndent, integer()}

See external documentation.

setRightIndent(This::wxTextAttr(), Indent::integer()) -> ok

See external documentation.

setTabs(This::wxTextAttr(), Tabs::[integer()]) -> ok

See external documentation.

setTextColour(This::wxTextAttr(), ColText::colour() (see module wx)) -> ok

See external documentation.

destroy(This::wxTextAttr()) -> ok

Destroys this object, do not use object again

wxTextCtrl

Erlang module

See external documentation: **wxTextCtrl**.

This class is derived (and can use functions) from:

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxTextCtrl()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxTextCtrl()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Id::integer()) -> wxTextCtrl()`

Equivalent to `new(Parent, Id, [])`.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Options::[Option]) -> wxTextCtrl()`

Types:

Option = {value, string()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()} | {validator, wx() (see module wx)}

See external documentation.

`appendText(This::wxTextCtrl(), Text::string()) -> ok`

See external documentation.

`canCopy(This::wxTextCtrl()) -> bool()`

See external documentation.

`canCut(This::wxTextCtrl()) -> bool()`

See external documentation.

`canPaste(This::wxTextCtrl()) -> bool()`

See external documentation.

`canRedo(This::wxTextCtrl()) -> bool()`

See external documentation.

`canUndo(This::wxTextCtrl()) -> bool()`

See external documentation.

`clear(This::wxTextCtrl()) -> ok`

See external documentation.

`copy(This::wxTextCtrl()) -> ok`

See external documentation.

`create(This::wxTextCtrl(), Parent::wxWindow() (see module wxWindow),
Id::integer()) -> bool()`

Equivalent to `create(This, Parent, Id, [])`.

`create(This::wxTextCtrl(), Parent::wxWindow() (see module wxWindow),
Id::integer(), Options::[Option]) -> bool()`

Types:

`Option = {value, string()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style,
integer()} | {validator, wx() (see module wx)}`

See external documentation.

`cut(This::wxTextCtrl()) -> ok`

See external documentation.

`discardEdits(This::wxTextCtrl()) -> ok`

See external documentation.

`emulateKeyPress(This::wxTextCtrl(), Event::wxKeyEvent() (see module
wxKeyEvent)) -> bool()`

See external documentation.

`getDefaultStyle(This::wxTextCtrl()) -> wxTextAttr() (see module wxTextAttr)`

See external documentation.

`getInsertionPoint(This::wxTextCtrl()) -> integer()`

See external documentation.

`getLastPosition(This::wxTextCtrl()) -> integer()`

See external documentation.

`getLineLength(This::wxTextCtrl(), LineNo::integer()) -> integer()`

See external documentation.

`getLineText(This::wxTextCtrl(), LineNo::integer()) -> string()`

See external documentation.

`getNumberOfLines(This::wxTextCtrl()) -> integer()`

See external documentation.

`getRange(This::wxTextCtrl(), From::integer(), To::integer()) -> string()`

See external documentation.

`getSelection(This::wxTextCtrl()) -> {From::integer(), To::integer()}`

See external documentation.

`getStringSelection(This::wxTextCtrl()) -> string()`

See external documentation.

`getStyle(This::wxTextCtrl(), Position::integer(), Style::wxTextAttr() (see module wxTextAttr)) -> bool()`

See external documentation.

`getValue(This::wxTextCtrl()) -> string()`

See external documentation.

`isEditable(This::wxTextCtrl()) -> bool()`

See external documentation.

`isModified(This::wxTextCtrl()) -> bool()`

See external documentation.

`isMultiLine(This::wxTextCtrl()) -> bool()`

See external documentation.

`isSingleLine(This::wxTextCtrl()) -> bool()`

See external documentation.

`loadFile(This::wxTextCtrl(), File::string()) -> bool()`

Equivalent to `loadFile(This, File, [])`.

`loadFile(This::wxTextCtrl(), File::string(), Options::[Option]) -> bool()`

Types:

`Option = {fileType, integer()}`

See external documentation.

`markDirty(This::wxTextCtrl()) -> ok`

See external documentation.

`paste(This::wxTextCtrl()) -> ok`

See external documentation.

`positionToXY(This::wxTextCtrl(), Pos::integer()) -> {bool(), X::integer(), Y::integer()}`

See external documentation.

`redo(This::wxTextCtrl()) -> ok`

See external documentation.

`remove(This::wxTextCtrl(), From::integer(), To::integer()) -> ok`

See external documentation.

`replace(This::wxTextCtrl(), From::integer(), To::integer(), Value::string()) -> ok`

See external documentation.

`saveFile(This::wxTextCtrl()) -> bool()`

Equivalent to `saveFile(This, [])`.

`saveFile(This::wxTextCtrl(), Options::[Option]) -> bool()`

Types:

`Option = {file, string()} | {fileType, integer()}`

See external documentation.

`setDefaultStyle(This::wxTextCtrl(), Style::wxTextAttr() (see module wxTextAttr)) -> bool()`

See external documentation.

`setEditable(This::wxTextCtrl(), Editable::bool()) -> ok`

See external documentation.

`setInsertionPoint(This::wxTextCtrl(), Pos::integer()) -> ok`

See external documentation.

`setInsertionPointEnd(This::wxTextCtrl()) -> ok`

See external documentation.

`setMaxLength(This::wxTextCtrl(), Len::integer()) -> ok`

See external documentation.

setSelection(This::wxTextCtrl(), From::integer(), To::integer()) -> ok

See external documentation.

setStyle(This::wxTextCtrl(), Start::integer(), End::integer(),
Style::wxTextAttr() (see module wxTextAttr)) -> bool()

See external documentation.

setValue(This::wxTextCtrl(), Value::string()) -> ok

See external documentation.

showPosition(This::wxTextCtrl(), Pos::integer()) -> ok

See external documentation.

undo(This::wxTextCtrl()) -> ok

See external documentation.

writeText(This::wxTextCtrl(), Text::string()) -> ok

See external documentation.

xYToPosition(This::wxTextCtrl(), X::integer(), Y::integer()) -> integer()

See external documentation.

destroy(This::wxTextCtrl()) -> ok

Destroys this object, do not use object again

wxTextDataObject

Erlang module

See external documentation: **wxTextDataObject**.

This class is derived (and can use functions) from:
wxDataObject

DATA TYPES

`wxTextDataObject()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxTextDataObject()`

Equivalent to `new([])`.

`new(Options::[Option]) -> wxTextDataObject()`

Types:

Option = {text, string()}

See external documentation.

`getTextLength(This::wxTextDataObject()) -> integer()`

See external documentation.

`getText(This::wxTextDataObject()) -> string()`

See external documentation.

`setText(This::wxTextDataObject(), Text::string()) -> ok`

See external documentation.

`destroy(This::wxTextDataObject()) -> ok`

Destroys this object, do not use object again

wxTextEntryDialog

Erlang module

See external documentation: **wxTextEntryDialog**.

This class is derived (and can use functions) from:

wxDialog

wxTopLevelWindow

wxWindow

wxEvtHandler

DATA TYPES

`wxTextEntryDialog()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

```
new(Parent::wxWindow() (see module wxWindow), Message::string()) ->  
wxTextEntryDialog()
```

Equivalent to *new(Parent, Message, [])*.

```
new(Parent::wxWindow() (see module wxWindow), Message::string(), Options::  
[Option]) -> wxTextEntryDialog()
```

Types:

Option = {caption, string()} | {value, string()} | {style, integer()} | {pos, {X::integer(), Y::integer()}}

See external documentation.

```
getValue(This::wxTextEntryDialog()) -> string()
```

See external documentation.

```
setValue(This::wxTextEntryDialog(), Val::string()) -> ok
```

See external documentation.

```
destroy(This::wxTextEntryDialog()) -> ok
```

Destroys this object, do not use object again

wxToggleButton

Erlang module

See external documentation: **wxToggleButton**.

This class is derived (and can use functions) from:

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxToggleButton()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxToggleButton()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Label::string())
-> wxToggleButton()`

Equivalent to `new(Parent, Id, Label, [])`.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Label::string(),
Options::[Option]) -> wxToggleButton()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()} |
{validator, wx()} (see module wx)

See external documentation.

`create(This::wxToggleButton(), Parent::wxWindow() (see module wxWindow),
Id::integer(), Label::string()) -> bool()`

Equivalent to `create(This, Parent, Id, Label, [])`.

`create(This::wxToggleButton(), Parent::wxWindow() (see module wxWindow),
Id::integer(), Label::string(), Options::[Option]) -> bool()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()} |
{validator, wx()} (see module wx)

See external documentation.

`getValue(This::wxToggleButton()) -> bool()`

See external documentation.

setValue(This::wxToggleButton(), State::bool()) -> ok

See external documentation.

destroy(This::wxToggleButton()) -> ok

Destroys this object, do not use object again

wxToolBar

Erlang module

See external documentation: **wxToolBar**.

This class is derived (and can use functions) from:

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxToolBar()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`addControl(This::wxToolBar(), Control::wxControl() (see module wxControl)) -> wx() (see module wx)`

See external documentation.

`addSeparator(This::wxToolBar()) -> wx() (see module wx)`

See external documentation.

`addTool(This::wxToolBar(), Tool::wx() (see module wx)) -> wx() (see module wx)`

See external documentation.

`addTool(This::wxToolBar(), Toolid::integer(), Bitmap::wxBitmap() (see module wxBitmap)) -> wx() (see module wx)`

Equivalent to `addTool(This, Toolid, Bitmap, [])`.

`addTool(This::wxToolBar(), Toolid::integer(), X::string() | term(), X::term()) -> wx() (see module wx)`

See external documentation.

Alternatives:

`addTool(This::wxToolBar(), Toolid::integer(), Label::string(), Bitmap::wxBitmap:wxBitmap()) -> addTool(This, Toolid, Label, Bitmap, [])`

`addTool(This::wxToolBar(), Toolid::integer(), Bitmap::wxBitmap:wxBitmap(), BmpDisabled::wxBitmap:wxBitmap()) -> addTool(This, Toolid, Bitmap, BmpDisabled, [])`

`addTool(This::wxToolBar(), Toolid::integer(), Bitmap::wxBitmap:wxBitmap(), [Option]) -> wx:wx()`

Option = {shortHelpString, string()} | {longHelpString, string() }

```
addTool(This::wxToolBar(), Toolid::integer(), X::string() | term(),  
X::term(), X::term()) -> wx() (see module wx)
```

See external documentation.

Alternatives:

```
addTool(This::wxToolBar(), Toolid::integer(), Label::string(),  
Bitmap::wxBitmap:wxBitmap(), BmpDisabled::wxBitmap:wxBitmap()) ->  
addTool(This, Toolid, Label, Bitmap, BmpDisabled, [])
```

```
addTool(This::wxToolBar(), Toolid::integer(), Label::string(),  
Bitmap::wxBitmap:wxBitmap(), [Option]) -> wx:wx()  
Option = {shortHelp, string()} | {kind, WxItemKind}  
WxItemKind = integer()  
WxItemKind is one of ?wxITEM_SEPARATOR | ?wxITEM_NORMAL | ?wxITEM_CHECK | ?wxITEM_RADIO  
| ?wxITEM_MAX
```

```
addTool(This::wxToolBar(), Toolid::integer(), Bitmap::wxBitmap:wxBitmap(),  
BmpDisabled::wxBitmap:wxBitmap(), [Option]) -> wx:wx()  
Option = {toggle, bool()} | {clientData, wx:wx()} | {shortHelpString, string()} | {longHelpString, string()}
```

```
addTool(This::wxToolBar(), Toolid::integer(), X::term() | string(),  
X::term(), X::bool() | term(), X::integer() | term()) -> wx() (see module wx)
```

See external documentation.

Alternatives:

```
addTool(This::wxToolBar(), Toolid::integer(), Bitmap::wxBitmap:wxBitmap(),  
BmpDisabled::wxBitmap:wxBitmap(), Toggle::bool(), XPos::integer()) ->  
addTool(This, Toolid, Bitmap, BmpDisabled, Toggle, XPos, [])
```

```
addTool(This::wxToolBar(), Toolid::integer(), Label::string(),  
Bitmap::wxBitmap:wxBitmap(), BmpDisabled::wxBitmap:wxBitmap(), [Option]) ->  
wx:wx()  
Option = {kind, WxItemKind} | {shortHelp, string()} | {longHelp, string()} | {data, wx:wx()}  
WxItemKind = integer()  
WxItemKind is one of ?wxITEM_SEPARATOR | ?wxITEM_NORMAL | ?wxITEM_CHECK | ?wxITEM_RADIO  
| ?wxITEM_MAX
```

```
addTool(This::wxToolBar(), Toolid::integer(), Bitmap::wxBitmap() (see module  
wxBitmap), BmpDisabled::wxBitmap() (see module wxBitmap), Toggle::bool(),  
XPos::integer(), Options::[Option]) -> wx() (see module wx)
```

Types:

Option = {yPos, integer()} | {clientData, wx() (see module wx)} | {shortHelp, string()} | {longHelp, string()}

See external documentation.

```
addCheckTool(This::wxToolBar(), Toolid::integer(), Label::string(),  
Bitmap::wxBitmap() (see module wxBitmap)) -> wx() (see module wx)
```

Equivalent to *addCheckTool(This, Toolid, Label, Bitmap, [])*.

```
addCheckTool(This::wxToolBar(), Toolid::integer(), Label::string(),  
Bitmap::wxBitmap() (see module wxBitmap), Options::[Option]) -> wx() (see  
module wx)
```

Types:

```
Option = {bmpDisabled, wxBitmap() (see module wxBitmap)} | {shortHelp, string()} | {longHelp, string()}  
| {data, wx() (see module wx)}
```

See external documentation.

```
addRadioTool(This::wxToolBar(), Toolid::integer(), Label::string(),  
Bitmap::wxBitmap() (see module wxBitmap)) -> wx() (see module wx)
```

Equivalent to `addRadioTool(This, Toolid, Label, Bitmap, [])`.

```
addRadioTool(This::wxToolBar(), Toolid::integer(), Label::string(),  
Bitmap::wxBitmap() (see module wxBitmap), Options::[Option]) -> wx() (see  
module wx)
```

Types:

```
Option = {bmpDisabled, wxBitmap() (see module wxBitmap)} | {shortHelp, string()} | {longHelp, string()}  
| {data, wx() (see module wx)}
```

See external documentation.

```
deleteTool(This::wxToolBar(), Toolid::integer()) -> bool()
```

See external documentation.

```
deleteToolByPos(This::wxToolBar(), Pos::integer()) -> bool()
```

See external documentation.

```
enableTool(This::wxToolBar(), Toolid::integer(), Enable::bool()) -> ok
```

See external documentation.

```
findById(This::wxToolBar(), Toolid::integer()) -> wx() (see module wx)
```

See external documentation.

```
findControl(This::wxToolBar(), Toolid::integer()) -> wxControl() (see module  
wxControl)
```

See external documentation.

```
findToolForPosition(This::wxToolBar(), X::integer(), Y::integer()) -> wx()  
(see module wx)
```

See external documentation.

```
getToolSize(This::wxToolBar()) -> {W::integer(), H::integer()}
```

See external documentation.

`getToolBitmapSize(This::wxToolBar()) -> {W::integer(), H::integer()}`

See external documentation.

`getMargins(This::wxToolBar()) -> {W::integer(), H::integer()}`

See external documentation.

`getToolEnabled(This::wxToolBar(), Toolid::integer()) -> bool()`

See external documentation.

`getToolLongHelp(This::wxToolBar(), Toolid::integer()) -> string()`

See external documentation.

`getToolPacking(This::wxToolBar()) -> integer()`

See external documentation.

`getToolPos(This::wxToolBar(), Id::integer()) -> integer()`

See external documentation.

`getToolSeparation(This::wxToolBar()) -> integer()`

See external documentation.

`getToolShortHelp(This::wxToolBar(), Toolid::integer()) -> string()`

See external documentation.

`getToolState(This::wxToolBar(), Toolid::integer()) -> bool()`

See external documentation.

`insertControl(This::wxToolBar(), Pos::integer(), Control::wxControl()) (see module wxControl) -> wx() (see module wx)`

See external documentation.

`insertSeparator(This::wxToolBar(), Pos::integer()) -> wx() (see module wx)`

See external documentation.

`insertTool(This::wxToolBar(), Pos::integer(), Tool::wx() (see module wx)) -> wx() (see module wx)`

See external documentation.

`insertTool(This::wxToolBar(), Pos::integer(), Toolid::integer(), Bitmap::wxBitmap() (see module wxBitmap)) -> wx() (see module wx)`

Equivalent to `insertTool(This, Pos, Toolid, Bitmap, [])`.

```
insertTool(This::wxToolBar(), Pos::integer(), Toolid::integer(), X::string()
| term(), X::term()) -> wx() (see module wx)
```

See [external documentation](#).

Alternatives:

```
insertTool(This::wxToolBar(),          Pos::integer(),          Toolid::integer(),
Label::string(),                      Bitmap::wxBitmap:wxBitmap() ->
insertTool(This,Pos,Toolid,Label,Bitmap, [])
```

```
insertTool(This::wxToolBar(),          Pos::integer(),          Toolid::integer(),
Bitmap::wxBitmap:wxBitmap(), [Option]) -> wx:wx()
Option = {bmpDisabled, wxBitmap:wxBitmap()} | {toggle, bool()} | {clientData, wx:wx()} | {shortHelp, string()} |
{longHelp, string()}
```

```
insertTool(This::wxToolBar(), Pos::integer(), Toolid::integer(),
Label::string(), Bitmap::wxBitmap() (see module wxBitmap), Options::[Option])
-> wx() (see module wx)
```

Types:

```
Option = {bmpDisabled, wxBitmap() (see module wxBitmap)} | {kind, WxItemKind} | {shortHelp,
string()} | {longHelp, string()} | {clientData, wx() (see module wx)}
WxItemKind = integer()
```

See [external documentation](#).

WxItemKind is one of ?wxITEM_SEPARATOR | ?wxITEM_NORMAL | ?wxITEM_CHECK | ?wxITEM_RADIO
| ?wxITEM_MAX

```
realize(This::wxToolBar()) -> bool()
```

See [external documentation](#).

```
removeTool(This::wxToolBar(), Toolid::integer()) -> wx() (see module wx)
```

See [external documentation](#).

```
setMargins(This::wxToolBar(), X::integer(), Y::integer()) -> ok
```

See [external documentation](#).

```
setToolBitmapSize(This::wxToolBar(), Size::{W::integer(), H::integer()}) ->
ok
```

See [external documentation](#).

```
setToolLongHelp(This::wxToolBar(), Toolid::integer(), HelpString::string()) -
> ok
```

See [external documentation](#).

```
setToolPacking(This::wxToolBar(), Packing::integer()) -> ok
```

See [external documentation](#).

`setToolShortHelp(This::wxToolBar(), Id::integer(), HelpString::string()) -> ok`

See external documentation.

`setToolSeparation(This::wxToolBar(), Separation::integer()) -> ok`

See external documentation.

`toggleTool(This::wxToolBar(), Toolid::integer(), Toggle::bool()) -> ok`

See external documentation.

wxToolbook

Erlang module

See external documentation: **wxToolbook**.

This class is derived (and can use functions) from:

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxToolbook()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxToolbook()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Id::integer()) -> wxToolbook()`

Equivalent to `new(Parent, Id, [])`.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Options::[Option]) -> wxToolbook()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`addPage(This::wxToolbook(), Page::wxWindow() (see module wxWindow), Text::string()) -> bool()`

Equivalent to `addPage(This, Page, Text, [])`.

`addPage(This::wxToolbook(), Page::wxWindow() (see module wxWindow), Text::string(), Options::[Option]) -> bool()`

Types:

Option = {bSelect, bool()} | {imageId, integer()}

See external documentation.

`advanceSelection(This::wxToolbook()) -> ok`

Equivalent to `advanceSelection(This, [])`.

`advanceSelection(This::wxToolbook(), Options::[Option]) -> ok`

Types:

Option = {forward, bool()}

See external documentation.

assignImageList(This::wxToolbook(), ImageList::wxImageList() (see module wxImageList)) -> ok

See external documentation.

create(This::wxToolbook(), Parent::wxWindow() (see module wxWindow), Id::integer()) -> bool()

Equivalent to *create(This, Parent, Id, [])*.

create(This::wxToolbook(), Parent::wxWindow() (see module wxWindow), Id::integer(), Options::[Option]) -> bool()

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

deleteAllPages(This::wxToolbook()) -> bool()

See external documentation.

deletePage(This::wxToolbook(), N::integer()) -> bool()

See external documentation.

removePage(This::wxToolbook(), N::integer()) -> bool()

See external documentation.

getCurrentPage(This::wxToolbook()) -> wxWindow() (see module wxWindow)

See external documentation.

getImageList(This::wxToolbook()) -> wxImageList() (see module wxImageList)

See external documentation.

getPage(This::wxToolbook(), N::integer()) -> wxWindow() (see module wxWindow)

See external documentation.

getPageCount(This::wxToolbook()) -> integer()

See external documentation.

getPageImage(This::wxToolbook(), N::integer()) -> integer()

See external documentation.

getPageText(This::wxToolbook(), N::integer()) -> string()

See external documentation.

`getSelection(This::wxToolbook()) -> integer()`

See external documentation.

`hitTest(This::wxToolbook(), Pt::{X::integer(), Y::integer()}) -> {integer(),
Flags::integer()}`

See external documentation.

`insertPage(This::wxToolbook(), N::integer(), Page::wxWindow() (see module
wxWindow), Text::string()) -> bool()`

Equivalent to *insertPage(This, N, Page, Text, [])*.

`insertPage(This::wxToolbook(), N::integer(), Page::wxWindow() (see module
wxWindow), Text::string(), Options::[Option]) -> bool()`

Types:

`Option = {bSelect, bool()} | {imageId, integer()}`

See external documentation.

`setImageList(This::wxToolbook(), ImageList::wxImageList() (see module
wxImageList)) -> ok`

See external documentation.

`setPageSize(This::wxToolbook(), Size::{W::integer(), H::integer()}) -> ok`

See external documentation.

`setPageImage(This::wxToolbook(), N::integer(), ImageId::integer()) -> bool()`

See external documentation.

`setPageText(This::wxToolbook(), N::integer(), StrText::string()) -> bool()`

See external documentation.

`setSelection(This::wxToolbook(), N::integer()) -> integer()`

See external documentation.

`changeSelection(This::wxToolbook(), N::integer()) -> integer()`

See external documentation.

`destroy(This::wxToolbook()) -> ok`

Destroys this object, do not use object again

wxToolTip

Erlang module

See external documentation: **wxToolTip**.

DATA TYPES

`wxToolTip()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`enable(Flag::bool()) -> ok`

See external documentation.

`setDelay(Msecs::integer()) -> ok`

See external documentation.

`new(Tip::string()) -> wxToolTip()`

See external documentation.

`setTip(This::wxToolTip(), Tip::string()) -> ok`

See external documentation.

`getTip(This::wxToolTip()) -> string()`

See external documentation.

`getWindow(This::wxToolTip()) -> wxWindow() (see module wxWindow)`

See external documentation.

`destroy(This::wxToolTip()) -> ok`

Destroys this object, do not use object again

wxTopLevelWindow

Erlang module

See external documentation: **wxTopLevelWindow**.

This class is derived (and can use functions) from:

wxWindow

wxEvtHandler

DATA TYPES

`wxTopLevelWindow()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`getIcon(This::wxTopLevelWindow()) -> wxIcon()` (see module `wxIcon`)

See external documentation.

`getIcons(This::wxTopLevelWindow()) -> wxIconBundle()` (see module `wxIconBundle`)

See external documentation.

`getTitle(This::wxTopLevelWindow()) -> string()`

See external documentation.

`isActive(This::wxTopLevelWindow()) -> bool()`

See external documentation.

`iconize(This::wxTopLevelWindow()) -> ok`

Equivalent to `iconize(This, [])`.

`iconize(This::wxTopLevelWindow(), Options::[Option]) -> ok`

Types:

Option = {iconize, bool()}

See external documentation.

`isFullScreen(This::wxTopLevelWindow()) -> bool()`

See external documentation.

`isIconized(This::wxTopLevelWindow()) -> bool()`

See external documentation.

isMaximized(This::wxTopLevelWindow()) -> bool()

See external documentation.

maximize(This::wxTopLevelWindow()) -> ok

Equivalent to *maximize(This, [])*.

maximize(This::wxTopLevelWindow(), Options::[Option]) -> ok

Types:

Option = {maximize, bool()}

See external documentation.

requestUserAttention(This::wxTopLevelWindow()) -> ok

Equivalent to *requestUserAttention(This, [])*.

requestUserAttention(This::wxTopLevelWindow(), Options::[Option]) -> ok

Types:

Option = {flags, integer()}

See external documentation.

setIcon(This::wxTopLevelWindow(), Icon::wxIcon() (see module wxIcon)) -> ok

See external documentation.

setIcons(This::wxTopLevelWindow(), Icons::wxIconBundle() (see module wxIconBundle)) -> ok

See external documentation.

centerOnScreen(This::wxTopLevelWindow()) -> ok

Equivalent to *centerOnScreen(This, [])*.

centerOnScreen(This::wxTopLevelWindow(), Options::[Option]) -> ok

Types:

Option = {dir, integer()}

See external documentation.

centreOnScreen(This::wxTopLevelWindow()) -> ok

Equivalent to *centreOnScreen(This, [])*.

centreOnScreen(This::wxTopLevelWindow(), Options::[Option]) -> ok

Types:

Option = {dir, integer()}

See external documentation.

```
setShape(This::wxTopLevelWindow(), Region::wxRegion() (see module wxRegion))  
-> bool()
```

See [external documentation](#).

```
setTitle(This::wxTopLevelWindow(), Title::string()) -> ok
```

See [external documentation](#).

```
showFullScreen(This::wxTopLevelWindow(), Show::bool()) -> bool()
```

Equivalent to *showFullScreen(This, Show, [])*.

```
showFullScreen(This::wxTopLevelWindow(), Show::bool(), Options::[Option]) ->  
bool()
```

Types:

Option = {style, integer()}

See [external documentation](#).

wxTreebook

Erlang module

See external documentation: **wxTreebook**.

This class is derived (and can use functions) from:

wxControl

wxWindow

wxEvtHandler

DATA TYPES

`wxTreebook()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxTreebook()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow), Id::integer()) -> wxTreebook()`

Equivalent to `new(Parent, Id, [])`.

`new(Parent::wxWindow() (see module wxWindow), Id::integer(), Options::[Option]) -> wxTreebook()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`addPage(This::wxTreebook(), Page::wxWindow() (see module wxWindow), Text::string()) -> bool()`

Equivalent to `addPage(This, Page, Text, [])`.

`addPage(This::wxTreebook(), Page::wxWindow() (see module wxWindow), Text::string(), Options::[Option]) -> bool()`

Types:

Option = {bSelect, bool()} | {imageId, integer()}

See external documentation.

`advanceSelection(This::wxTreebook()) -> ok`

Equivalent to `advanceSelection(This, [])`.

`advanceSelection(This::wxTreebook(), Options::[Option]) -> ok`

Types:

Option = {forward, bool()}

See external documentation.

assignImageList(This::wxTreebook(), ImageList::wxImageList() (see module wxImageList)) -> ok

See external documentation.

create(This::wxTreebook(), Parent::wxWindow() (see module wxWindow), Id::integer()) -> bool()

Equivalent to *create(This, Parent, Id, [])*.

create(This::wxTreebook(), Parent::wxWindow() (see module wxWindow), Id::integer(), Options::[Option]) -> bool()

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

deleteAllPages(This::wxTreebook()) -> bool()

See external documentation.

deletePage(This::wxTreebook(), Pos::integer()) -> bool()

See external documentation.

removePage(This::wxTreebook(), N::integer()) -> bool()

See external documentation.

getCurrentPage(This::wxTreebook()) -> wxWindow() (see module wxWindow)

See external documentation.

getImageList(This::wxTreebook()) -> wxImageList() (see module wxImageList)

See external documentation.

getPage(This::wxTreebook(), N::integer()) -> wxWindow() (see module wxWindow)

See external documentation.

getPageCount(This::wxTreebook()) -> integer()

See external documentation.

getPageImage(This::wxTreebook(), N::integer()) -> integer()

See external documentation.

getPageText(This::wxTreebook(), N::integer()) -> string()

See external documentation.

getSelection(This::wxTreebook()) -> integer()

See external documentation.

expandNode(This::wxTreebook(), Pos::integer()) -> bool()

Equivalent to *expandNode(This, Pos, [])*.

expandNode(This::wxTreebook(), Pos::integer(), Options::[Option]) -> bool()

Types:

Option = {expand, bool()}

See external documentation.

isNodeExpanded(This::wxTreebook(), Pos::integer()) -> bool()

See external documentation.

**hitTest(This::wxTreebook(), Pt::{X::integer(), Y::integer()}) -> {integer(),
Flags::integer()}**

See external documentation.

**insertPage(This::wxTreebook(), Pos::integer(), Page::wxWindow() (see module
wxWindow), Text::string()) -> bool()**

Equivalent to *insertPage(This, Pos, Page, Text, [])*.

**insertPage(This::wxTreebook(), Pos::integer(), Page::wxWindow() (see module
wxWindow), Text::string(), Options::[Option]) -> bool()**

Types:

Option = {bSelect, bool()} | {imageId, integer()}

See external documentation.

**insertSubPage(This::wxTreebook(), Pos::integer(), Page::wxWindow() (see
module wxWindow), Text::string()) -> bool()**

Equivalent to *insertSubPage(This, Pos, Page, Text, [])*.

**insertSubPage(This::wxTreebook(), Pos::integer(), Page::wxWindow() (see
module wxWindow), Text::string(), Options::[Option]) -> bool()**

Types:

Option = {bSelect, bool()} | {imageId, integer()}

See external documentation.

**setImageList(This::wxTreebook(), ImageList::wxImageList() (see module
wxImageList)) -> ok**

See external documentation.

`setPageSize(This::wxTreebook(), Size::{W::integer(), H::integer()}) -> ok`

See external documentation.

`setPageImage(This::wxTreebook(), N::integer(), ImageId::integer()) -> bool()`

See external documentation.

`setPageText(This::wxTreebook(), N::integer(), StrText::string()) -> bool()`

See external documentation.

`setSelection(This::wxTreebook(), N::integer()) -> integer()`

See external documentation.

`changeSelection(This::wxTreebook(), N::integer()) -> integer()`

See external documentation.

`destroy(This::wxTreebook()) -> ok`

Destroys this object, do not use object again

wxTreeCtrl

Erlang module

See external documentation: **wxTreeCtrl**.

Note: The representation of `treeItemId()` have changed from the original class implementation to be an semi-opaque type, Equality between `TreeItemId`'s can be tested and zero means that the `TreeItem` is invalid.

DATA TYPES

`wxTreeCtrl()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxTreeCtrl()`

See external documentation.

`new(Parent::wxWindow() (see module wxWindow)) -> wxTreeCtrl()`

Equivalent to `new(Parent, [])`.

`new(Parent::wxWindow() (see module wxWindow), Options::[Option]) -> wxTreeCtrl()`

Types:

Option = {**id**, integer()} | {**pos**, {**X**::integer(), **Y**::integer()}} | {**size**, {**W**::integer(), **H**::integer()}} | {**style**, integer()} | {**validator**, wx() (see module wx)}

See external documentation.

`addRoot(This::wxTreeCtrl(), Text::string()) -> integer()`

Equivalent to `addRoot(This, Text, [])`.

`addRoot(This::wxTreeCtrl(), Text::string(), Options::[Option]) -> integer()`

Types:

Option = {**image**, integer()} | {**selectedImage**, integer()} | {**data**, term() }

See external documentation.

`appendItem(This::wxTreeCtrl(), Parent::integer(), Text::string()) -> integer()`

Equivalent to `appendItem(This, Parent, Text, [])`.

`appendItem(This::wxTreeCtrl(), Parent::integer(), Text::string(), Options::[Option]) -> integer()`

Types:

Option = {**image**, integer()} | {**selectedImage**, integer()} | {**data**, term() }

See external documentation.

```
assignImageList(This::wxTreeCtrl(), ImageList::wxImageList() (see module wxImageList)) -> ok
```

See external documentation.

```
assignStateImageList(This::wxTreeCtrl(), ImageList::wxImageList() (see module wxImageList)) -> ok
```

See external documentation.

```
collapse(This::wxTreeCtrl(), Item::integer()) -> ok
```

See external documentation.

```
collapseAndReset(This::wxTreeCtrl(), Item::integer()) -> ok
```

See external documentation.

```
create(This::wxTreeCtrl(), Parent::wxWindow() (see module wxWindow)) -> bool()
```

Equivalent to *create(This, Parent, [])*.

```
create(This::wxTreeCtrl(), Parent::wxWindow() (see module wxWindow), Options::[Option]) -> bool()
```

Types:

Option = {id, integer()} | {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()} | {validator, wx() (see module wx)}

See external documentation.

```
delete(This::wxTreeCtrl(), Item::integer()) -> ok
```

See external documentation.

```
deleteAllItems(This::wxTreeCtrl()) -> ok
```

See external documentation.

```
deleteChildren(This::wxTreeCtrl(), Item::integer()) -> ok
```

See external documentation.

```
ensureVisible(This::wxTreeCtrl(), Item::integer()) -> ok
```

See external documentation.

```
expand(This::wxTreeCtrl(), Item::integer()) -> ok
```

See external documentation.

```
getBoundingRect(This::wxTreeCtrl(), Item::integer(), Rect::{X::integer(),  
Y::integer(), W::integer(), H::integer()}) -> bool()
```

Equivalent to *getBoundingRect(This, Item, Rect, [])*.

```
getBoundingRect(This::wxTreeCtrl(), Item::integer(), Rect::{X::integer(),  
Y::integer(), W::integer(), H::integer()}, Options::[Option]) -> bool()
```

Types:

Option = {textOnly, bool()}

See external documentation.

```
getChildrenCount(This::wxTreeCtrl(), Item::integer()) -> integer()
```

Equivalent to *getChildrenCount(This, Item, [])*.

```
getChildrenCount(This::wxTreeCtrl(), Item::integer(), Options::[Option]) ->  
integer()
```

Types:

Option = {recursively, bool()}

See external documentation.

```
getCount(This::wxTreeCtrl()) -> integer()
```

See external documentation.

```
getEditControl(This::wxTreeCtrl()) -> wxTextCtrl() (see module wxTextCtrl)
```

See external documentation.

```
getFirstChild(This::wxTreeCtrl(), Item::integer()) -> {integer(),  
Cookie::integer()}
```

See external documentation.

```
getNextChild(This::wxTreeCtrl(), Item::integer(), Cookie::integer()) ->  
{integer(), Cookie::integer()}
```

See external documentation.

```
getFirstVisibleItem(This::wxTreeCtrl()) -> integer()
```

See external documentation.

```
getImageList(This::wxTreeCtrl()) -> wxImageList() (see module wxImageList)
```

See external documentation.

```
getIndent(This::wxTreeCtrl()) -> integer()
```

See external documentation.

`getItemBackgroundColour(This::wxTreeCtrl(), Item::integer()) -> colour()` (see module `wx`)

See external documentation.

`getItemData(This::wxTreeCtrl(), Item::integer()) -> term()`

See external documentation.

`getItemFont(This::wxTreeCtrl(), Item::integer()) -> wxFont()` (see module `wxFont`)

See external documentation.

`getItemImage(This::wxTreeCtrl(), Item::integer()) -> integer()`

See external documentation.

`getItemImage(This::wxTreeCtrl(), Item::integer(), Options::[Option]) -> integer()`

Types:

Option = {which, WxTreeItemIcon}

WxTreeItemIcon = integer()

See external documentation.

WxTreeItemIcon is one of ?wxTreeItemIcon_Normal | ?wxTreeItemIcon_Selected | ?wxTreeItemIcon_Expanded | ?wxTreeItemIcon_SelectedExpanded | ?wxTreeItemIcon_Max

`getItemText(This::wxTreeCtrl(), Item::integer()) -> string()`

See external documentation.

`getItemTextColour(This::wxTreeCtrl(), Item::integer()) -> colour()` (see module `wx`)

See external documentation.

`getLastChild(This::wxTreeCtrl(), Item::integer()) -> integer()`

See external documentation.

`getNextSibling(This::wxTreeCtrl(), Item::integer()) -> integer()`

See external documentation.

`getNextVisible(This::wxTreeCtrl(), Item::integer()) -> integer()`

See external documentation.

`getItemParent(This::wxTreeCtrl(), Item::integer()) -> integer()`

See external documentation.

`getPrevSibling(This::wxTreeCtrl(), Item::integer()) -> integer()`

See external documentation.

`getPrevVisible(This::wxTreeCtrl(), Item::integer()) -> integer()`

See external documentation.

`getRootItem(This::wxTreeCtrl()) -> integer()`

See external documentation.

`getSelection(This::wxTreeCtrl()) -> integer()`

See external documentation.

`getSelections(This::wxTreeCtrl()) -> {integer(), Val::[integer()]}`

See external documentation.

`getStateImageList(This::wxTreeCtrl()) -> wxImageList() (see module wxImageList)`

See external documentation.

`hitTest(This::wxTreeCtrl(), Point::{X::integer(), Y::integer()}) -> integer()`

See external documentation.

`insertItem(This::wxTreeCtrl(), Parent::integer(), Pos::integer(), Text::string()) -> integer()`

Equivalent to *insertItem(This, Parent, Pos, Text, [])*.

`insertItem(This::wxTreeCtrl(), Parent::integer(), Pos::integer(), Text::string(), Options::[Option]) -> integer()`

Types:

Option = {image, integer()} | {setImage, integer()} | {data, term()}

See external documentation.

`isBold(This::wxTreeCtrl(), Item::integer()) -> bool()`

See external documentation.

`isExpanded(This::wxTreeCtrl(), Item::integer()) -> bool()`

See external documentation.

`isSelected(This::wxTreeCtrl(), Item::integer()) -> bool()`

See external documentation.

`isVisible(This::wxTreeCtrl(), Item::integer()) -> bool()`

See external documentation.

`itemHasChildren(This::wxTreeCtrl(), Item::integer()) -> bool()`

See external documentation.

```
prependItem(This::wxTreeCtrl(), Parent::integer(), Text::string()) -> integer()
```

Equivalent to *prependItem(This, Parent, Text, [])*.

```
prependItem(This::wxTreeCtrl(), Parent::integer(), Text::string(), Options::[Option]) -> integer()
```

Types:

Option = {image, integer()} | {selectedImage, integer()} | {data, term()}

See external documentation.

```
scrollTo(This::wxTreeCtrl(), Item::integer()) -> ok
```

See external documentation.

```
selectItem(This::wxTreeCtrl(), Item::integer()) -> ok
```

See external documentation.

```
selectItem(This::wxTreeCtrl(), Item::integer(), Options::[Option]) -> ok
```

Types:

Option = {select, bool()}

See external documentation.

```
setIndent(This::wxTreeCtrl(), Indent::integer()) -> ok
```

See external documentation.

```
setImageList(This::wxTreeCtrl(), ImageList::wxImageList() (see module wxImageList)) -> ok
```

See external documentation.

```
setItemBackgroundColour(This::wxTreeCtrl(), Item::integer(), Col::colour() (see module wx)) -> ok
```

See external documentation.

```
setItemBold(This::wxTreeCtrl(), Item::integer()) -> ok
```

Equivalent to *setItemBold(This, Item, [])*.

```
setItemBold(This::wxTreeCtrl(), Item::integer(), Options::[Option]) -> ok
```

Types:

Option = {bold, bool()}

See external documentation.

```
setItemData(This::wxTreeCtrl(), Item::integer(), Data::term()) -> ok
```

See external documentation.

```
setItemDropHighlight(This::wxTreeCtrl(), Item::integer()) -> ok
```

Equivalent to *setItemDropHighlight(This, Item, [])*.

```
setItemDropHighlight(This::wxTreeCtrl(), Item::integer(), Options::[Option])
-> ok
```

Types:

Option = {highlight, bool()}

See [external documentation](#).

```
setItemFont(This::wxTreeCtrl(), Item::integer(), Font::wxFont() (see module
wxFont)) -> ok
```

See [external documentation](#).

```
setItemHasChildren(This::wxTreeCtrl(), Item::integer()) -> ok
```

Equivalent to *setItemHasChildren(This, Item, [])*.

```
setItemHasChildren(This::wxTreeCtrl(), Item::integer(), Options::[Option]) ->
ok
```

Types:

Option = {has, bool()}

See [external documentation](#).

```
setItemImage(This::wxTreeCtrl(), Item::integer(), Image::integer()) -> ok
```

See [external documentation](#).

```
setItemImage(This::wxTreeCtrl(), Item::integer(), Image::integer(), Options::
[Option]) -> ok
```

Types:

Option = {which, WxTreeItemIcon}

WxTreeItemIcon = integer()

See [external documentation](#).

WxTreeItemIcon is one of ?wxTreeItemIcon_Normal | ?wxTreeItemIcon_Selected | ?wxTreeItemIcon_Expanded | ?wxTreeItemIcon_SelectedExpanded | ?wxTreeItemIcon_Max

```
setItemText(This::wxTreeCtrl(), Item::integer(), Text::string()) -> ok
```

See [external documentation](#).

```
setItemTextColour(This::wxTreeCtrl(), Item::integer(), Col::colour() (see
module wx)) -> ok
```

See [external documentation](#).

```
setStateImageList(This::wxTreeCtrl(), ImageList::wxImageList() (see module
wxImageList)) -> ok
```

See [external documentation](#).

setWindowStyle(This::wxTreeCtrl(), Styles::integer()) -> ok

See [external documentation](#).

sortChildren(This::wxTreeCtrl(), Item::integer()) -> ok

See [external documentation](#).

toggle(This::wxTreeCtrl(), Item::integer()) -> ok

See [external documentation](#).

toggleItemSelection(This::wxTreeCtrl(), Item::integer()) -> ok

See [external documentation](#).

unselect(This::wxTreeCtrl()) -> ok

See [external documentation](#).

unselectAll(This::wxTreeCtrl()) -> ok

See [external documentation](#).

unselectItem(This::wxTreeCtrl(), Item::integer()) -> ok

See [external documentation](#).

destroy(This::wxTreeCtrl()) -> ok

Destroys this object, do not use object again

wxTreeEvent

Erlang module

See external documentation: **wxTreeEvent**.

Use `wxEvtHandler:connect/3` with EventType:

```
command_tree_begin_drag,      command_tree_begin_rdrag,      command_tree_begin_label_edit,
command_tree_end_label_edit, command_tree_delete_item, command_tree_get_info, command_tree_set_info,
command_tree_item_expanded,  command_tree_item_expanding,  command_tree_item_collapsed,
command_tree_item_collapsing, command_tree_sel_changed,      command_tree_sel_changing,
command_tree_key_down,      command_tree_item_activated,  command_tree_item_right_click,
command_tree_item_middle_click, command_tree_end_drag,        command_tree_state_image_click,
command_tree_item_gettooltip, command_tree_item_menu
```

See also the message variant `#wxTree{}` event record type.

This class is derived (and can use functions) from:

```
wxNotifyEvent
wxCommandEvent
wxEvent
```

DATA TYPES

```
wxTreeEvent()
```

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

```
getKeyCode(This::wxTreeEvent()) -> integer()
```

See external documentation.

```
getItem(This::wxTreeEvent()) -> integer()
```

See external documentation.

```
getKeyEvent(This::wxTreeEvent()) -> wxKeyEvent() (see module wxKeyEvent)
```

See external documentation.

```
getLabel(This::wxTreeEvent()) -> string()
```

See external documentation.

```
getOldItem(This::wxTreeEvent()) -> integer()
```

See external documentation.

```
getPoint(This::wxTreeEvent()) -> {X::integer(), Y::integer()}
```

See external documentation.

wxTreeEvent

isEditCancelled(This::wxTreeEvent()) -> bool()

See **external documentation**.

setToolTip(This::wxTreeEvent(), ToolTip::string()) -> ok

See **external documentation**.

wxUpdateUIEvent

Erlang module

See external documentation: **wxUpdateUIEvent**.

Use *wxEvtHandler:connect/3* with EventType:

update_ui

See also the message variant *#wxUpdateUI{}* event record type.

This class is derived (and can use functions) from:

wxCommandEvent

wxEvent

DATA TYPES

`wxUpdateUIEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparsion stored on disc or distributed for use on other nodes.

Exports

`canUpdate(Win::wxWindow() (see module wxWindow)) -> bool()`

See external documentation.

`check(This::wxUpdateUIEvent(), Check::bool()) -> ok`

See external documentation.

`enable(This::wxUpdateUIEvent(), Enable::bool()) -> ok`

See external documentation.

`show(This::wxUpdateUIEvent(), Show::bool()) -> ok`

See external documentation.

`getChecked(This::wxUpdateUIEvent()) -> bool()`

See external documentation.

`getEnabled(This::wxUpdateUIEvent()) -> bool()`

See external documentation.

`getShown(This::wxUpdateUIEvent()) -> bool()`

See external documentation.

`getSetChecked(This::wxUpdateUIEvent()) -> bool()`

See external documentation.

getSetEnabled(This::wxUpdateUIEvent()) -> bool()

See external documentation.

getSetShown(This::wxUpdateUIEvent()) -> bool()

See external documentation.

getSetText(This::wxUpdateUIEvent()) -> bool()

See external documentation.

getText(This::wxUpdateUIEvent()) -> string()

See external documentation.

getMode() -> WxUpdateUIMode

Types:

WxUpdateUIMode = integer()

See external documentation.

WxUpdateUIMode is one of ?wxUPDATE_UI_PROCESS_ALL | ?wxUPDATE_UI_PROCESS_SPECIFIED

getUpdateInterval() -> integer()

See external documentation.

resetUpdateTime() -> ok

See external documentation.

setMode(Mode::WxUpdateUIMode) -> ok

Types:

WxUpdateUIMode = integer()

See external documentation.

WxUpdateUIMode is one of ?wxUPDATE_UI_PROCESS_ALL | ?wxUPDATE_UI_PROCESS_SPECIFIED

setText(This::wxUpdateUIEvent(), Text::string()) -> ok

See external documentation.

setUpdateInterval(UpdateInterval::integer()) -> ok

See external documentation.

wxWindowCreateEvent

Erlang module

See external documentation: **wxWindowCreateEvent**.

Use *wxEvtHandler:connect/3* with EventType:

create

See also the message variant *#wxWindowCreate{}* event record type.

This class is derived (and can use functions) from:

wxCommandEvent

wxEvent

DATA TYPES

`wxWindowCreateEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

wxWindowDC

Erlang module

See external documentation: **wxWindowDC**.

This class is derived (and can use functions) from:
wxDC

DATA TYPES

`wxWindowDC()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxWindowDC()`

See **external documentation**.

`new(Win::wxWindow()) (see module wxWindow) -> wxWindowDC()`

See **external documentation**.

`destroy(This::wxWindowDC()) -> ok`

Destroys this object, do not use object again

wxWindowDestroyEvent

Erlang module

See external documentation: **wxWindowDestroyEvent**.

Use *wxEvtHandler:connect/3* with EventType:

destroy

See also the message variant *#wxWindowDestroy{}* event record type.

This class is derived (and can use functions) from:

wxCommandEvent

wxEvent

DATA TYPES

`wxWindowDestroyEvent()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

wxWindow

Erlang module

See external documentation: **wxWindow**.

This class is derived (and can use functions) from:
wxEvtHandler

DATA TYPES

`wxWindow()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxWindow()`

See external documentation.

`new(Parent::wxWindow(), Id::integer()) -> wxWindow()`

Equivalent to `new(Parent, Id, [])`.

`new(Parent::wxWindow(), Id::integer(), Options::[Option]) -> wxWindow()`

Types:

Option = {pos, {X::integer(), Y::integer()}} | {size, {W::integer(), H::integer()}} | {style, integer()}

See external documentation.

`cacheBestSize(This::wxWindow(), Size::{W::integer(), H::integer()}) -> ok`

See external documentation.

`captureMouse(This::wxWindow()) -> ok`

See external documentation.

`center(This::wxWindow()) -> ok`

Equivalent to `center(This, [])`.

`center(This::wxWindow(), Options::[Option]) -> ok`

Types:

Option = {dir, integer()}

See external documentation.

`centerOnParent(This::wxWindow()) -> ok`

Equivalent to `centerOnParent(This, [])`.

`centerOnParent(This::wxWindow(), Options::[Option]) -> ok`

Types:

Option = {dir, integer()}

See external documentation.

`centre(This::wxWindow()) -> ok`

Equivalent to *centre(This, [])*.

`centre(This::wxWindow(), Options::[Option]) -> ok`

Types:

Option = {dir, integer()}

See external documentation.

`centreOnParent(This::wxWindow()) -> ok`

Equivalent to *centreOnParent(This, [])*.

`centreOnParent(This::wxWindow(), Options::[Option]) -> ok`

Types:

Option = {dir, integer()}

See external documentation.

`clearBackground(This::wxWindow()) -> ok`

See external documentation.

`clientToScreen(This::wxWindow(), Pt::{X::integer(), Y::integer()}) ->
{X::integer(), Y::integer()}`

See external documentation.

`clientToScreen(This::wxWindow(), X::integer(), Y::integer()) ->
{X::integer(), Y::integer()}`

See external documentation.

`close(This::wxWindow()) -> bool()`

Equivalent to *close(This, [])*.

`close(This::wxWindow(), Options::[Option]) -> bool()`

Types:

Option = {force, bool()}

See external documentation.

`convertDialogToPixels(This::wxWindow(), Sz::{W::integer(), H::integer()}) ->
{W::integer(), H::integer()}`

See external documentation.

`convertPixelsToDialog(This::wxWindow(), Sz::{W::integer(), H::integer()}) -> {W::integer(), H::integer()}`

See external documentation.

`Destroy(This::wxWindow()) -> bool()`

See external documentation.

`destroyChildren(This::wxWindow()) -> bool()`

See external documentation.

`disable(This::wxWindow()) -> bool()`

See external documentation.

`enable(This::wxWindow()) -> bool()`

Equivalent to `enable(This, [])`.

`enable(This::wxWindow(), Options::[Option]) -> bool()`

Types:

Option = {enable, bool()}

See external documentation.

`findFocus() -> wxWindow()`

See external documentation.

`findWindow(This::wxWindow(), X::integer() | string()) -> wxWindow()`

See external documentation.

Alternatives:

`findWindow(This::wxWindow(), Winid::integer()) -> wxWindow()`

`findWindow(This::wxWindow(), Name::string()) -> wxWindow()`

`findWindowById(Winid::integer()) -> wxWindow()`

Equivalent to `findWindowById(Winid, [])`.

`findWindowById(Winid::integer(), Options::[Option]) -> wxWindow()`

Types:

Option = {parent, wxWindow()}

See external documentation.

`findWindowByName(Name::string()) -> wxWindow()`

Equivalent to `findWindowByName(Name, [])`.

`findWindowByName(Name::string(), Options::[Option]) -> wxWindow()`

Types:

Option = {parent, wxWindow()}

See external documentation.

findWindowByLabel(Label::string()) -> wxWindow()

Equivalent to *findWindowByLabel*(Label, []).

findWindowByLabel(Label::string(), Options::[Option]) -> wxWindow()

Types:

Option = {parent, wxWindow()}

See external documentation.

fit(This::wxWindow()) -> ok

See external documentation.

fitInside(This::wxWindow()) -> ok

See external documentation.

freeze(This::wxWindow()) -> ok

See external documentation.

getAcceleratorTable(This::wxWindow()) -> wxAcceleratorTable() (see module wxAcceleratorTable)

See external documentation.

getBackgroundColour(This::wxWindow()) -> colour() (see module wx)

See external documentation.

getBackgroundStyle(This::wxWindow()) -> WxBackgroundStyle

Types:

WxBackgroundStyle = integer()

See external documentation.

WxBackgroundStyle is one of ?wxBG_STYLE_SYSTEM | ?wxBG_STYLE_COLOUR | ?wxBG_STYLE_CUSTOM

getBestSize(This::wxWindow()) -> {W::integer(), H::integer()}

See external documentation.

getCaret(This::wxWindow()) -> wxCaret() (see module wxCaret)

See external documentation.

getCapture() -> wxWindow()

See external documentation.

`getCharHeight(This::wxWindow()) -> integer()`

See external documentation.

`getCharWidth(This::wxWindow()) -> integer()`

See external documentation.

`getChildren(This::wxWindow()) -> [wxWindow()]`

See external documentation.

`getClientSize(This::wxWindow()) -> {W::integer(), H::integer()}`

See external documentation.

`getContainingSizer(This::wxWindow()) -> wxSizer() (see module wxSizer)`

See external documentation.

`getCursor(This::wxWindow()) -> wxCursor() (see module wxCursor)`

See external documentation.

`getDropTarget(This::wxWindow()) -> wxDropTarget() (see module wxDropTarget)`

See external documentation.

`getEventHandler(This::wxWindow()) -> wxEvtHandler() (see module wxEvtHandler)`

See external documentation.

`getExtraStyle(This::wxWindow()) -> integer()`

See external documentation.

`getFont(This::wxWindow()) -> wxFont() (see module wxFont)`

See external documentation.

`getForegroundColour(This::wxWindow()) -> colour() (see module wx)`

See external documentation.

`getGrandParent(This::wxWindow()) -> wxWindow()`

See external documentation.

`getHandle(This::wxWindow()) -> integer()`

See external documentation.

`getHelpText(This::wxWindow()) -> string()`

See external documentation.

`getId(This::wxWindow()) -> integer()`

See external documentation.

`getLabel(This::wxWindow()) -> string()`

See external documentation.

`getMaxSize(This::wxWindow()) -> {W::integer(), H::integer()}`

See external documentation.

`getMinSize(This::wxWindow()) -> {W::integer(), H::integer()}`

See external documentation.

`getName(This::wxWindow()) -> string()`

See external documentation.

`getParent(This::wxWindow()) -> wxWindow()`

See external documentation.

`getPosition(This::wxWindow()) -> {X::integer(), Y::integer()}`

See external documentation.

`getRect(This::wxWindow()) -> {X::integer(), Y::integer(), W::integer(),
H::integer()}`

See external documentation.

`getScreenPosition(This::wxWindow()) -> {X::integer(), Y::integer()}`

See external documentation.

`getScreenRect(This::wxWindow()) -> {X::integer(), Y::integer(), W::integer(),
H::integer()}`

See external documentation.

`getScrollPos(This::wxWindow(), Orient::integer()) -> integer()`

See external documentation.

`getScrollRange(This::wxWindow(), Orient::integer()) -> integer()`

See external documentation.

`getScrollThumb(This::wxWindow(), Orient::integer()) -> integer()`

See external documentation.

`getSize(This::wxWindow()) -> {W::integer(), H::integer()}`

See external documentation.

`getSizer(This::wxWindow()) -> wxSizer()` (see module `wxSizer`)

See external documentation.

`getTextExtent(This::wxWindow(), String::string()) -> {X::integer(),
Y::integer(), Descent::integer(), ExternalLeading::integer()}`

Equivalent to `getTextExtent(This, String, [])`.

`getTextExtent(This::wxWindow(), String::string(), Options::[Option]) ->
{X::integer(), Y::integer(), Descent::integer(), ExternalLeading::integer()}`

Types:

`Option = {theFont, wxFont() (see module wxFont)}`

See external documentation.

`getToolTip(This::wxWindow()) -> wxToolTip()` (see module `wxToolTip`)

See external documentation.

`getUpdateRegion(This::wxWindow()) -> wxRegion()` (see module `wxRegion`)

See external documentation.

`getVirtualSize(This::wxWindow()) -> {W::integer(), H::integer()}`

See external documentation.

`getWindowStyleFlag(This::wxWindow()) -> integer()`

See external documentation.

`getWindowVariant(This::wxWindow()) -> WxWindowVariant`

Types:

`WxWindowVariant = integer()`

See external documentation.

`WxWindowVariant` is one of `?wxWINDOW_VARIANT_NORMAL` | `?wxWINDOW_VARIANT_SMALL` | `?wxWINDOW_VARIANT_MINI` | `?wxWINDOW_VARIANT_LARGE` | `?wxWINDOW_VARIANT_MAX`

`hasCapture(This::wxWindow()) -> bool()`

See external documentation.

`hasScrollbar(This::wxWindow(), Orient::integer()) -> bool()`

See external documentation.

`hasTransparentBackground(This::wxWindow()) -> bool()`

See external documentation.

`hide(This::wxWindow()) -> bool()`

See external documentation.

inheritAttributes(This::wxWindow()) -> ok

See external documentation.

initDialog(This::wxWindow()) -> ok

See external documentation.

invalidateBestSize(This::wxWindow()) -> ok

See external documentation.

isEnabled(This::wxWindow()) -> bool()

See external documentation.

isExposed(This::wxWindow(), X::term()) -> bool()

See external documentation.

Alternatives:

isExposed(This::wxWindow(), Pt::{X::integer(),Y::integer()}) -> bool()

**isExposed(This::wxWindow(),
{X::integer(),Y::integer(),W::integer(),H::integer()}) -> bool()** Rect::

isExposed(This::wxWindow(), X::integer(), Y::integer()) -> bool()

See external documentation.

**isExposed(This::wxWindow(), X::integer(), Y::integer(), W::integer(),
H::integer()) -> bool()**

See external documentation.

isRetained(This::wxWindow()) -> bool()

See external documentation.

isShown(This::wxWindow()) -> bool()

See external documentation.

isTopLevel(This::wxWindow()) -> bool()

See external documentation.

layout(This::wxWindow()) -> bool()

See external documentation.

lineDown(This::wxWindow()) -> bool()

See external documentation.

lineUp(This::wxWindow()) -> bool()

See external documentation.

`lower(This::wxWindow()) -> ok`

See [external documentation](#).

`makeModal(This::wxWindow()) -> ok`

Equivalent to `makeModal(This, [])`.

`makeModal(This::wxWindow(), Options::[Option]) -> ok`

Types:

Option = {modal, bool()}

See [external documentation](#).

`move(This::wxWindow(), Pt::{X::integer(), Y::integer()}) -> ok`

Equivalent to `move(This, Pt, [])`.

`move(This::wxWindow(), X::integer() | term(), X::integer() | term()) -> ok`

See [external documentation](#).

Alternatives:

`move(This::wxWindow(), X::integer(), Y::integer()) -> move(This, X, Y, [])`

`move(This::wxWindow(), Pt::{X::integer(), Y::integer()}, [Option]) -> ok`

Option = {flags, integer()}

`move(This::wxWindow(), X::integer(), Y::integer(), Options::[Option]) -> ok`

Types:

Option = {flags, integer()}

See [external documentation](#).

`moveAfterInTabOrder(This::wxWindow(), Win::wxWindow()) -> ok`

See [external documentation](#).

`moveBeforeInTabOrder(This::wxWindow(), Win::wxWindow()) -> ok`

See [external documentation](#).

`navigate(This::wxWindow()) -> bool()`

Equivalent to `navigate(This, [])`.

`navigate(This::wxWindow(), Options::[Option]) -> bool()`

Types:

Option = {flags, integer()}

See [external documentation](#).

`pageDown(This::wxWindow()) -> bool()`

See [external documentation](#).

pageUp(This::wxWindow()) -> bool()

See external documentation.

popEventHandler(This::wxWindow()) -> wxEvtHandler() (see module wxEvtHandler)

Equivalent to *popEventHandler(This, [])*.

popEventHandler(This::wxWindow(), Options::[Option]) -> wxEvtHandler() (see module wxEvtHandler)

Types:

Option = {deleteHandler, bool()}

See external documentation.

popupMenu(This::wxWindow(), Menu::wxMenu() (see module wxMenu)) -> bool()

Equivalent to *popupMenu(This, Menu, [])*.

popupMenu(This::wxWindow(), Menu::wxMenu() (see module wxMenu), Options::[Option]) -> bool()

Types:

Option = {pos, {X::integer(), Y::integer()}}

See external documentation.

popupMenu(This::wxWindow(), Menu::wxMenu() (see module wxMenu), X::integer(), Y::integer()) -> bool()

See external documentation.

raise(This::wxWindow()) -> ok

See external documentation.

refresh(This::wxWindow()) -> ok

Equivalent to *refresh(This, [])*.

refresh(This::wxWindow(), Options::[Option]) -> ok

Types:

Option = {eraseBackground, bool()} | {rect, {X::integer(), Y::integer(), W::integer(), H::integer()}}

See external documentation.

refreshRect(This::wxWindow(), Rect::{X::integer(), Y::integer(), W::integer(), H::integer()}) -> ok

Equivalent to *refreshRect(This, Rect, [])*.

refreshRect(This::wxWindow(), Rect::{X::integer(), Y::integer(), W::integer(), H::integer()}, Options::[Option]) -> ok

Types:

Option = {eraseBackground, bool()}

See external documentation.

releaseMouse(This::wxWindow()) -> ok

See external documentation.

removeChild(This::wxWindow(), Child::wxWindow()) -> ok

See external documentation.

reparent(This::wxWindow(), NewParent::wxWindow()) -> bool()

See external documentation.

screenToClient(This::wxWindow()) -> {X::integer(), Y::integer()}

See external documentation.

screenToClient(This::wxWindow(), Pt::{X::integer(), Y::integer()}) -> {X::integer(), Y::integer()}

See external documentation.

scrollLines(This::wxWindow(), Lines::integer()) -> bool()

See external documentation.

scrollPages(This::wxWindow(), Pages::integer()) -> bool()

See external documentation.

scrollWindow(This::wxWindow(), Dx::integer(), Dy::integer()) -> ok

Equivalent to *scrollWindow(This, Dx, Dy, [])*.

scrollWindow(This::wxWindow(), Dx::integer(), Dy::integer(), Options::[Option]) -> ok

Types:

Option = {rect, {X::integer(), Y::integer(), W::integer(), H::integer()}}

See external documentation.

setAcceleratorTable(This::wxWindow(), Accel::wxAcceleratorTable() (see module wxAcceleratorTable)) -> ok

See external documentation.

setAutoLayout(This::wxWindow(), AutoLayout::bool()) -> ok

See external documentation.

```
setBackgroundColour(This::wxWindow(), Colour::colour() (see module wx)) ->
bool()
```

See external documentation.

```
setBackgroundStyle(This::wxWindow(), Style::WxBackgroundStyle) -> bool()
```

Types:

```
WxBackgroundStyle = integer()
```

See external documentation.

WxBackgroundStyle is one of ?wxBG_STYLE_SYSTEM | ?wxBG_STYLE_COLOUR | ?wxBG_STYLE_CUSTOM

```
setCaret(This::wxWindow(), Caret::wxCaret() (see module wxCaret)) -> ok
```

See external documentation.

```
setClientSize(This::wxWindow(), X::term()) -> ok
```

See external documentation.

Alternatives:

```
setClientSize(This::wxWindow(), Size::{W::integer(),H::integer()}) -> ok
```

```
setClientSize(This::wxWindow(), Rect::{X::integer(),Y::integer(),W::integer(),H::integer()}) -> ok
```

```
setClientSize(This::wxWindow(), Width::integer(), Height::integer()) -> ok
```

See external documentation.

```
setContainingSizer(This::wxWindow(), Sizer::wxSizer() (see module wxSizer)) -> ok
```

See external documentation.

```
setCursor(This::wxWindow(), Cursor::wxCursor() (see module wxCursor)) ->
bool()
```

See external documentation.

```
setMaxSize(This::wxWindow(), MaxSize::{W::integer(), H::integer()}) -> ok
```

See external documentation.

```
setMinSize(This::wxWindow(), MinSize::{W::integer(), H::integer()}) -> ok
```

See external documentation.

```
setOwnBackgroundColour(This::wxWindow(), Colour::colour() (see module wx)) ->
ok
```

See external documentation.

```
setOwnFont(This::wxWindow(), Font::wxFont() (see module wxFont)) -> ok
```

See external documentation.

`setOwnForegroundColour(This::wxWindow(), Colour::colour() (see module wx)) -> ok`

See external documentation.

`setDropTarget(This::wxWindow(), DropTarget::wxDropTarget() (see module wxDropTarget)) -> ok`

See external documentation.

`setExtraStyle(This::wxWindow(), ExStyle::integer()) -> ok`

See external documentation.

`setFocus(This::wxWindow()) -> ok`

See external documentation.

`setFocusFromKbd(This::wxWindow()) -> ok`

See external documentation.

`setFont(This::wxWindow(), Font::wxFont() (see module wxFont)) -> bool()`

See external documentation.

`setForegroundColour(This::wxWindow(), Colour::colour() (see module wx)) -> bool()`

See external documentation.

`setHelpText(This::wxWindow(), Text::string()) -> ok`

See external documentation.

`setId(This::wxWindow(), Winid::integer()) -> ok`

See external documentation.

`setLabel(This::wxWindow(), Label::string()) -> ok`

See external documentation.

`setName(This::wxWindow(), Name::string()) -> ok`

See external documentation.

`setPalette(This::wxWindow(), Pal::wxPalette() (see module wxPalette)) -> ok`

See external documentation.

`setScrollbar(This::wxWindow(), Orient::integer(), Pos::integer(), ThumbVisible::integer(), Range::integer()) -> ok`

Equivalent to `setScrollbar(This, Orient, Pos, ThumbVisible, Range, [])`.


```
setScrollbar(This::wxWindow(), Orient::integer(), Pos::integer(),
ThumbVisible::integer(), Range::integer(), Options::[Option]) -> ok
```

Types:

Option = {refresh, bool()}

See external documentation.

```
setScrollPos(This::wxWindow(), Orient::integer(), Pos::integer()) -> ok
```

Equivalent to *setScrollPos(This, Orient, Pos, [])*.

```
setScrollPos(This::wxWindow(), Orient::integer(), Pos::integer(), Options::
[Option]) -> ok
```

Types:

Option = {refresh, bool()}

See external documentation.

```
setSize(This::wxWindow(), X::term()) -> ok
```

See external documentation.

Alternatives:

```
setSize(This::wxWindow(), Rect::
{X::integer(),Y::integer(),W::integer(),H::integer()}) -> setSize(This,Rect,
[])
```

```
setSize(This::wxWindow(), Size::{W::integer(),H::integer()}) -> ok
```

```
setSize(This::wxWindow(), X::integer() | term(), X::integer() | term()) -> ok
```

See external documentation.

Alternatives:

```
setSize(This::wxWindow(), Width::integer(), Height::integer()) -> ok
```

```
setSize(This::wxWindow(), Rect::
{X::integer(),Y::integer(),W::integer(),H::integer()}, [Option]) -> ok
Option = {sizeFlags, integer()}
```

```
setSize(This::wxWindow(), X::integer(), Y::integer(), Width::integer(),
Height::integer()) -> ok
```

Equivalent to *setSize(This, X, Y, Width, Height, [])*.

```
setSize(This::wxWindow(), X::integer(), Y::integer(), Width::integer(),
Height::integer(), Options::[Option]) -> ok
```

Types:

Option = {sizeFlags, integer()}

See external documentation.

```
setSizeHints(This::wxWindow(), MinSize::{W::integer(), H::integer()}) -> ok
```

Equivalent to *setSizeHints(This, MinSize, [])*.

```
setSizeHints(This::wxWindow(), X::integer() | term(), X::integer() | term())  
-> ok
```

See [external documentation](#).

Alternatives:

```
setSizeHints(This::wxWindow(), MinW::integer(), MinH::integer()) ->  
setSizeHints(This, MinW, MinH, [])
```

```
setSizeHints(This::wxWindow(), MinSize::{W::integer(), H::integer()}, [Option])  
-> ok
```

```
Option = {maxSize, {W::integer(), H::integer()}} | {incSize, {W::integer(), H::integer()}}
```

```
setSizeHints(This::wxWindow(), MinW::integer(), MinH::integer(), Options::  
[Option]) -> ok
```

Types:

```
Option = {maxW, integer()} | {maxH, integer()} | {incW, integer()} | {incH, integer()}
```

See [external documentation](#).

```
setSize(This::wxWindow(), Sizer::wxSizer() (see module wxSizer)) -> ok
```

Equivalent to *setSize(This, Sizer, [])*.

```
setSize(This::wxWindow(), Sizer::wxSizer() (see module wxSizer), Options::  
[Option]) -> ok
```

Types:

```
Option = {deleteOld, bool()}
```

See [external documentation](#).

```
setSizeAndFit(This::wxWindow(), Sizer::wxSizer() (see module wxSizer)) -> ok
```

Equivalent to *setSizeAndFit(This, Sizer, [])*.

```
setSizeAndFit(This::wxWindow(), Sizer::wxSizer() (see module wxSizer),  
Options::[Option]) -> ok
```

Types:

```
Option = {deleteOld, bool()}
```

See [external documentation](#).

```
setThemeEnabled(This::wxWindow(), EnableTheme::bool()) -> ok
```

See [external documentation](#).

```
setToolTip(This::wxWindow(), X::string() | term()) -> ok
```

See [external documentation](#).

Alternatives:

```
setToolTip(This::wxWindow(), Tip::string()) -> ok
```

```
setToolTip(This::wxWindow(), Tip::wxToolTip:wxToolTip()) -> ok
```

```
setVirtualSize(This::wxWindow(), Size::{W::integer(), H::integer()}) -> ok
```

See external documentation.

```
setVirtualSize(This::wxWindow(), X::integer(), Y::integer()) -> ok
```

See external documentation.

```
setVirtualSizeHints(This::wxWindow(), MinSize::{W::integer(), H::integer()})  
-> ok
```

Equivalent to *setVirtualSizeHints(This, MinSize, [])*.

```
setVirtualSizeHints(This::wxWindow(), X::integer() | term(), X::integer() |  
term()) -> ok
```

See external documentation.

Alternatives:

```
setVirtualSizeHints(This::wxWindow(), MinW::integer(), MinH::integer()) ->  
setVirtualSizeHints(This, MinW, MinH, [])
```

```
setVirtualSizeHints(This::wxWindow(), MinSize::{W::integer(), H::integer()},  
[Option]) -> ok
```

```
Option = {maxSize, {W::integer(), H::integer()}}
```

```
setVirtualSizeHints(This::wxWindow(), MinW::integer(), MinH::integer(),  
Options::[Option]) -> ok
```

Types:

```
Option = {maxW, integer()} | {maxH, integer()}
```

See external documentation.

```
setWindowStyle(This::wxWindow(), Style::integer()) -> ok
```

See external documentation.

```
setWindowStyleFlag(This::wxWindow(), Style::integer()) -> ok
```

See external documentation.

```
setWindowVariant(This::wxWindow(), Variant::WxWindowVariant) -> ok
```

Types:

```
WxWindowVariant = integer()
```

See external documentation.

WxWindowVariant is one of ?wxWINDOW_VARIANT_NORMAL | ?wxWINDOW_VARIANT_SMALL | ?wxWINDOW_VARIANT_MINI | ?wxWINDOW_VARIANT_LARGE | ?wxWINDOW_VARIANT_MAX

```
shouldInheritColours(This::wxWindow()) -> bool()
```

See external documentation.

```
show(This::wxWindow()) -> bool()
```

Equivalent to *show(This, [])*.

show(This::wxWindow(), Options::[Option]) -> bool()

Types:

Option = {show, bool()}

See external documentation.

thaw(This::wxWindow()) -> ok

See external documentation.

transferDataFromWindow(This::wxWindow()) -> bool()

See external documentation.

transferDataToWindow(This::wxWindow()) -> bool()

See external documentation.

update(This::wxWindow()) -> ok

See external documentation.

updateWindowUI(This::wxWindow()) -> ok

Equivalent to *updateWindowUI(This, [])*.

updateWindowUI(This::wxWindow(), Options::[Option]) -> ok

Types:

Option = {flags, integer()}

See external documentation.

validate(This::wxWindow()) -> bool()

See external documentation.

warpPointer(This::wxWindow(), X::integer(), Y::integer()) -> ok

See external documentation.

destroy(This::wxWindow()) -> ok

Destroys this object, do not use object again

wxXmlResource

Erlang module

See external documentation: [wxXmlResource](#).

DATA TYPES

`wxXmlResource()`

An object reference, The representation is internal and can be changed without notice. It can't be used for comparison stored on disc or distributed for use on other nodes.

Exports

`new() -> wxXmlResource()`

Equivalent to `new([])`.

`new(Options::[Option]) -> wxXmlResource()`

Types:

`Option = {flags, integer()} | {domain, string()}`

See external documentation.

`new(Filemask::string(), Options::[Option]) -> wxXmlResource()`

Types:

`Option = {flags, integer()} | {domain, string()}`

See external documentation.

`attachUnknownControl(This::wxXmlResource(), Name::string(), Control::wxWindow() (see module wxWindow)) -> bool()`

Equivalent to `attachUnknownControl(This, Name, Control, [])`.

`attachUnknownControl(This::wxXmlResource(), Name::string(), Control::wxWindow() (see module wxWindow), Options::[Option]) -> bool()`

Types:

`Option = {parent, wxWindow() (see module wxWindow)}`

See external documentation.

`clearHandlers(This::wxXmlResource()) -> ok`

See external documentation.

`compareVersion(This::wxXmlResource(), Major::integer(), Minor::integer(), Release::integer(), Revision::integer()) -> integer()`

See external documentation.

`get()` -> `wxXmlResource()`

See external documentation.

`getFlags(This::wxXmlResource())` -> `integer()`

See external documentation.

`getVersion(This::wxXmlResource())` -> `integer()`

See external documentation.

`getXRCID(Str_id::[string()])` -> `integer()`

Equivalent to `getXRCID(Str_id, [])`.

`getXRCID(Str_id::[string()], Options::[Option])` -> `integer()`

Types:

`Option = {value_if_not_found, integer()}`

See external documentation.

`initAllHandlers(This::wxXmlResource())` -> `ok`

See external documentation.

`load(This::wxXmlResource(), Filemask::string())` -> `bool()`

See external documentation.

`loadBitmap(This::wxXmlResource(), Name::string())` -> `wxBitmap()` (see module `wxBitmap`)

See external documentation.

`loadDialog(This::wxXmlResource(), Parent::wxWindow() (see module wxWindow), Name::string())` -> `wxDialog()` (see module `wxDialog`)

See external documentation.

`loadDialog(This::wxXmlResource(), Dlg::wxDialog() (see module wxDialog), Parent::wxWindow() (see module wxWindow), Name::string())` -> `bool()`

See external documentation.

`loadFrame(This::wxXmlResource(), Parent::wxWindow() (see module wxWindow), Name::string())` -> `wxFrame()` (see module `wxFrame`)

See external documentation.

`loadFrame(This::wxXmlResource(), Frame::wxFrame() (see module wxFrame), Parent::wxWindow() (see module wxWindow), Name::string())` -> `bool()`

See external documentation.

`loadIcon(This::wxXmlResource(), Name::string()) -> wxIcon()` (see module `wxIcon`)

See external documentation.

`loadMenu(This::wxXmlResource(), Name::string()) -> wxMenu()` (see module `wxMenu`)

See external documentation.

`loadMenuBar(This::wxXmlResource(), Name::string()) -> wxMenuBar()` (see module `wxMenuBar`)

See external documentation.

`loadMenuBar(This::wxXmlResource(), Parent::wxWindow() (see module wxWindow), Name::string()) -> wxMenuBar()` (see module `wxMenuBar`)

See external documentation.

`loadPanel(This::wxXmlResource(), Parent::wxWindow() (see module wxWindow), Name::string()) -> wxPanel()` (see module `wxPanel`)

See external documentation.

`loadPanel(This::wxXmlResource(), Panel::wxPanel() (see module wxPanel), Parent::wxWindow() (see module wxWindow), Name::string()) -> bool()`

See external documentation.

`loadToolBar(This::wxXmlResource(), Parent::wxWindow() (see module wxWindow), Name::string()) -> wxToolBar()` (see module `wxToolBar`)

See external documentation.

`set(Res::wxXmlResource()) -> wxXmlResource()`

See external documentation.

`setFlags(This::wxXmlResource(), Flags::integer()) -> ok`

See external documentation.

`unload(This::wxXmlResource(), Filename::string()) -> bool()`

See external documentation.

`xrcctrl(Window::wxWindow() (see module wxWindow), Name::string(), Type::atom()) -> wxObject()` (see module `wx`)

Looks up a control with Name in a window created with XML resources. You can use it to set/get values from controls. The object is type casted to *Type*. Example:

```
Xrc = wxXmlResource::get(),
Dlg = wxDialog::new(),
true = wxXmlResource::loadDialog(Xrc, Dlg, Frame, "controls_dialog"),
LCtrl = xrcctrl(Dlg, "controls_listctrl", wxListCtrl),
```

wxXmlResource

`wxListCtrl::insertColumn(LCtrl, 0, "Name", [{ width, 200}]),`

`destroy(This::wxXmlResource()) -> ok`

Destroys this object, do not use object again

wx_misc

Erlang module

See external documentation: **Misc**.

Exports

getKeyState(Key::WxKeyCode) -> bool()

Types:

WxKeyCode = integer()

See external documentation.

WxKeyCode is one of ?WXXK_BACK | ?WXXK_TAB | ?WXXK_RETURN | ?WXXK_ESCAPE | ?WXXK_SPACE | ?WXXK_DELETE | ?WXXK_START | ?WXXK_LBUTTON | ?WXXK_RBUTTON | ?WXXK_CANCEL | ?WXXK_MBUTTON | ?WXXK_CLEAR | ?WXXK_SHIFT | ?WXXK_ALT | ?WXXK_CONTROL | ?WXXK_MENU | ?WXXK_PAUSE | ?WXXK_CAPITAL | ?WXXK_END | ?WXXK_HOME | ?WXXK_LEFT | ?WXXK_UP | ?WXXK_RIGHT | ?WXXK_DOWN | ?WXXK_SELECT | ?WXXK_PRINT | ?WXXK_EXECUTE | ?WXXK_SNAPSHOT | ?WXXK_INSERT | ?WXXK_HELP | ?WXXK_NUMPAD0 | ?WXXK_NUMPAD1 | ?WXXK_NUMPAD2 | ?WXXK_NUMPAD3 | ?WXXK_NUMPAD4 | ?WXXK_NUMPAD5 | ?WXXK_NUMPAD6 | ?WXXK_NUMPAD7 | ?WXXK_NUMPAD8 | ?WXXK_NUMPAD9 | ?WXXK_MULTIPLY | ?WXXK_ADD | ?WXXK_SEPARATOR | ?WXXK_SUBTRACT | ?WXXK_DECIMAL | ?WXXK_DIVIDE | ?WXXK_F1 | ?WXXK_F2 | ?WXXK_F3 | ?WXXK_F4 | ?WXXK_F5 | ?WXXK_F6 | ?WXXK_F7 | ?WXXK_F8 | ?WXXK_F9 | ?WXXK_F10 | ?WXXK_F11 | ?WXXK_F12 | ?WXXK_F13 | ?WXXK_F14 | ?WXXK_F15 | ?WXXK_F16 | ?WXXK_F17 | ?WXXK_F18 | ?WXXK_F19 | ?WXXK_F20 | ?WXXK_F21 | ?WXXK_F22 | ?WXXK_F23 | ?WXXK_F24 | ?WXXK_NUMLOCK | ?WXXK_SCROLL | ?WXXK_PAGEUP | ?WXXK_PAGEDOWN | ?WXXK_NUMPAD_SPACE | ?WXXK_NUMPAD_TAB | ?WXXK_NUMPAD_ENTER | ?WXXK_NUMPAD_F1 | ?WXXK_NUMPAD_F2 | ?WXXK_NUMPAD_F3 | ?WXXK_NUMPAD_F4 | ?WXXK_NUMPAD_HOME | ?WXXK_NUMPAD_LEFT | ?WXXK_NUMPAD_UP | ?WXXK_NUMPAD_RIGHT | ?WXXK_NUMPAD_DOWN | ?WXXK_NUMPAD_PAGEUP | ?WXXK_NUMPAD_PAGEDOWN | ?WXXK_NUMPAD_END | ?WXXK_NUMPAD_BEGIN | ?WXXK_NUMPAD_INSERT | ?WXXK_NUMPAD_DELETE | ?WXXK_NUMPAD_EQUAL | ?WXXK_NUMPAD_MULTIPLY | ?WXXK_NUMPAD_ADD | ?WXXK_NUMPAD_SEPARATOR | ?WXXK_NUMPAD_SUBTRACT | ?WXXK_NUMPAD_DECIMAL | ?WXXK_NUMPAD_DIVIDE | ?WXXK_WINDOWS_LEFT | ?WXXK_WINDOWS_RIGHT | ?WXXK_WINDOWS_MENU | ?WXXK_COMMAND | ?WXXK_SPECIAL1 | ?WXXK_SPECIAL2 | ?WXXK_SPECIAL3 | ?WXXK_SPECIAL4 | ?WXXK_SPECIAL5 | ?WXXK_SPECIAL6 | ?WXXK_SPECIAL7 | ?WXXK_SPECIAL8 | ?WXXK_SPECIAL9 | ?WXXK_SPECIAL10 | ?WXXK_SPECIAL11 | ?WXXK_SPECIAL12 | ?WXXK_SPECIAL13 | ?WXXK_SPECIAL14 | ?WXXK_SPECIAL15 | ?WXXK_SPECIAL16 | ?WXXK_SPECIAL17 | ?WXXK_SPECIAL18 | ?WXXK_SPECIAL19 | ?WXXK_SPECIAL20

getMousePosition() -> {X::integer(), Y::integer()}

See external documentation.

getMouseState() -> wxMouseState() (see module **wx**)

See external documentation.

setDetectableAutoRepeat(Flag::bool()) -> bool()

See external documentation.

bell() -> ok

See external documentation.

findMenuItemId(Frame::wxFrame() (see module wxFrame), MenuString::string(), ItemString::string()) -> integer()

See external documentation.

genericFindWindowAtPoint(Pt::{X::integer(), Y::integer()}) -> wxWindow() (see module wxWindow)

See external documentation.

findWindowAtPoint(Pt::{X::integer(), Y::integer()}) -> wxWindow() (see module wxWindow)

See external documentation.

beginBusyCursor() -> ok

Equivalent to *beginBusyCursor([])*.

beginBusyCursor(Options::[Option]) -> ok

Types:

Option = {cursor, wxCursor() (see module wxCursor)}

See external documentation.

endBusyCursor() -> ok

See external documentation.

isBusy() -> bool()

See external documentation.

shutdown(WFlags::WxShutdownFlags) -> bool()

Types:

WxShutdownFlags = integer()

See external documentation.

WxShutdownFlags is one of ?wxSHUTDOWN_POWEROFF | ?wxSHUTDOWN_REBOOT

shell() -> bool()

Equivalent to *shell([])*.

shell(Options::[Option]) -> bool()

Types:

Option = {command, string() }

See external documentation.

launchDefaultBrowser(Url::string()) -> bool()

Equivalent to *launchDefaultBrowser*(Url, []).

launchDefaultBrowser(Url::string(), Options::[Option]) -> bool()

Types:

Option = {flags, integer()}

See external documentation.

getEmailAddress() -> string()

See external documentation.

getUserId() -> string()

See external documentation.

getHomeDir() -> string()

See external documentation.

newId() -> integer()

See external documentation.

registerId(Id::integer()) -> ok

See external documentation.

getCurrentId() -> integer()

See external documentation.

getOsDescription() -> string()

See external documentation.

isPlatformLittleEndian() -> bool()

See external documentation.

isPlatform64Bit() -> bool()

See external documentation.

glu

Erlang module

A part of the standard OpenGL Utility api. See www.opengl.org

Booleans are represented by integers 0 and 1.

DATA TYPES

`clamp()`

A float clamped between 0.0 - 1.0

`enum()`

An integer defined in gl.hrl

`offset()`

An integer which is an offset in an array

`wx_mem()`

see wx.erl on memory allocation functions

Exports

`tessellate(X1::Vec3, Vs::[Vec3]) -> {Triangles, VertexPos}`

Types:

Vec3 = {float(), float(), float()}

Triangles = [VertexIndex::integer()]

VertexPos = binary()

General purpose polygon triangulation. The first argument is the normal and the second a list of vertex positions. Returned is a list of indecies of the vertices and a binary (64bit native float) containing an array of vertex positions, it starts with the vertices in Vs and may contain newly created vertices in the end.

`build1DMipmapLevels(Target::enum(), InternalFormat::integer(), Width::integer(), Format::enum(), Type::enum(), Level::integer(), Base::integer(), Max::integer(), Data::binary()) -> integer()`

See **external** documentation.

`build1DMipmaps(Target::enum(), InternalFormat::integer(), Width::integer(), Format::enum(), Type::enum(), Data::binary()) -> integer()`

See **external** documentation.

`build2DMipmapLevels(Target::enum(), InternalFormat::integer(), Width::integer(), Height::integer(), Format::enum(), Type::enum(), Level::integer(), Base::integer(), Max::integer(), Data::binary()) -> integer()`

See **external** documentation.

```
build2DMipmaps(Target::enum(), InternalFormat::integer(), Width::integer(),  
Height::integer(), Format::enum(), Type::enum(), Data::binary()) -> integer()
```

See **external** documentation.

```
build3DMipmapLevels(Target::enum(), InternalFormat::integer(),  
Width::integer(), Height::integer(), Depth::integer(), Format::enum(),  
Type::enum(), Level::integer(), Base::integer(), Max::integer(),  
Data::binary()) -> integer()
```

See **external** documentation.

```
build3DMipmaps(Target::enum(), InternalFormat::integer(), Width::integer(),  
Height::integer(), Depth::integer(), Format::enum(), Type::enum(),  
Data::binary()) -> integer()
```

See **external** documentation.

```
checkExtension(ExtName::[integer()], ExtString::[integer()]) -> 0 | 1
```

See **external** documentation.

```
cylinder(Quad::integer(), Base::float(), Top::float(), Height::float(),  
Slices::integer(), Stacks::integer()) -> ok
```

See **external** documentation.

```
deleteQuadric(Quad::integer()) -> ok
```

See **external** documentation.

```
disk(Quad::integer(), Inner::float(), Outer::float(), Slices::integer(),  
Loops::integer()) -> ok
```

See **external** documentation.

```
errorString(Error::enum()) -> string()
```

See **external** documentation.

```
getString(Name::enum()) -> string()
```

See **external** documentation.

```
lookAt(EyeX::float(), EyeY::float(), EyeZ::float(), CenterX::float(),  
CenterY::float(), CenterZ::float(), UpX::float(), UpY::float(), UpZ::float())  
-> ok
```

See **external** documentation.

```
newQuadric() -> integer()
```

See **external** documentation.

`ortho2D(Left::float(), Right::float(), Bottom::float(), Top::float()) -> ok`

See **external** documentation.

`partialDisk(Quad::integer(), Inner::float(), Outer::float(),
Slices::integer(), Loops::integer(), Start::float(), Sweep::float()) -> ok`

See **external** documentation.

`perspective(Fovy::float(), Aspect::float(), ZNear::float(), ZFar::float()) ->
ok`

See **external** documentation.

`pickMatrix(X::float(), Y::float(), DelX::float(), DelY::float(), Viewport::
{integer()}) -> ok`

See **external** documentation.

`project(ObjX::float(), ObjY::float(), ObjZ::float(), Model::{float()}, Proj::
{float()}, View::{integer()}) -> {integer(), WinX::float(), WinY::float(),
WinZ::float()}`

See **external** documentation.

`quadricDrawStyle(Quad::integer(), Draw::enum()) -> ok`

See **external** documentation.

`quadricNormals(Quad::integer(), Normal::enum()) -> ok`

See **external** documentation.

`quadricOrientation(Quad::integer(), Orientation::enum()) -> ok`

See **external** documentation.

`quadricTexture(Quad::integer(), Texture::0 | 1) -> ok`

See **external** documentation.

`scaleImage(Format::enum(), WIn::integer(), HIn::integer(), TypeIn::enum(),
DataIn::binary(), WOut::integer(), HOut::integer(), TypeOut::enum(),
DataOut::wx_mem() (see module wx)) -> integer()`

See **external** documentation.

`sphere(Quad::integer(), Radius::float(), Slices::integer(),
Stacks::integer()) -> ok`

See **external** documentation.

```
unProject(WinX::float(), WinY::float(), WinZ::float(), Model::{float()},  
Proj::{float()}, View::{integer()}) -> {integer(), ObjX::float(),  
ObjY::float(), ObjZ::float()}
```

See **external** documentation.

```
unProject4(WinX::float(), WinY::float(), WinZ::float(), ClipW::float(),  
Model::{float()}, Proj::{float()}, View::{integer()}, NearVal::float(),  
FarVal::float()) -> {integer(), ObjX::float(), ObjY::float(), ObjZ::float(),  
ObjW::float()}
```

See **external** documentation.

gl

Erlang module

Standard OpenGL api. See www.opengl.org

Booleans are represented by integers 0 and 1.

DATA TYPES

`clamp()`

A float clamped between 0.0 - 1.0

`enum()`

An integer defined in `gl.hrl`

`offset()`

An integer which is an offset in an array

`wx_mem()`

see `wx.erl` on memory allocation functions

Exports

`accum(Op::enum(), Value::float()) -> ok`

See **external** documentation.

`alphaFunc(Func::enum(), Ref::clamp()) -> ok`

See **external** documentation.

`areTexturesResident(Textures::[integer()]) -> {0 | 1, Residences::[0 | 1]}`

See **external** documentation.

`arrayElement(I::integer()) -> ok`

See **external** documentation.

`begin(Mode::enum()) -> ok`

See **external** documentation.

`bindTexture(Target::enum(), Texture::integer()) -> ok`

See **external** documentation.

`bitmap(Width::integer(), Height::integer(), Xorig::float(), Yorig::float(),
Xmove::float(), Ymove::float(), Bitmap::offset() | binary()) -> ok`

See **external** documentation.

blendFunc(Sfactor::enum(), Dfactor::enum()) -> ok

See **external** documentation.

callList(List::integer()) -> ok

See **external** documentation.

callLists(Lists::[integer()]) -> ok

See **external** documentation.

clear(Mask::integer()) -> ok

See **external** documentation.

clearAccum(Red::float(), Green::float(), Blue::float(), Alpha::float()) -> ok

See **external** documentation.

clearColor(Red::clamp(), Green::clamp(), Blue::clamp(), Alpha::clamp()) -> ok

See **external** documentation.

clearDepth(Depth::clamp()) -> ok

See **external** documentation.

clearIndex(C::float()) -> ok

See **external** documentation.

clearStencil(S::integer()) -> ok

See **external** documentation.

clipPlane(Plane::enum(), Equation::{float()}) -> ok

See **external** documentation.

color3b(Red::integer(), Green::integer(), Blue::integer()) -> ok

See **external** documentation.

color3bv(X1::{Red, Green, Blue}) -> ok

Equivalent to *color3b(Red, Green, Blue)*.

color3d(Red::float(), Green::float(), Blue::float()) -> ok

See **external** documentation.

color3dv(X1::{Red, Green, Blue}) -> ok

Equivalent to *color3d(Red, Green, Blue)*.

`color3f(Red::float(), Green::float(), Blue::float()) -> ok`

See **external** documentation.

`color3fv(X1::{Red, Green, Blue}) -> ok`

Equivalent to *color3f(Red, Green, Blue)*.

`color3i(Red::integer(), Green::integer(), Blue::integer()) -> ok`

See **external** documentation.

`color3iv(X1::{Red, Green, Blue}) -> ok`

Equivalent to *color3i(Red, Green, Blue)*.

`color3s(Red::integer(), Green::integer(), Blue::integer()) -> ok`

See **external** documentation.

`color3sv(X1::{Red, Green, Blue}) -> ok`

Equivalent to *color3s(Red, Green, Blue)*.

`color3ub(Red::integer(), Green::integer(), Blue::integer()) -> ok`

See **external** documentation.

`color3ubv(X1::{Red, Green, Blue}) -> ok`

Equivalent to *color3ub(Red, Green, Blue)*.

`color3ui(Red::integer(), Green::integer(), Blue::integer()) -> ok`

See **external** documentation.

`color3uiv(X1::{Red, Green, Blue}) -> ok`

Equivalent to *color3ui(Red, Green, Blue)*.

`color3us(Red::integer(), Green::integer(), Blue::integer()) -> ok`

See **external** documentation.

`color3usv(X1::{Red, Green, Blue}) -> ok`

Equivalent to *color3us(Red, Green, Blue)*.

`color4b(Red::integer(), Green::integer(), Blue::integer(), Alpha::integer())
-> ok`

See **external** documentation.

`color4bv(X1::{Red, Green, Blue, Alpha}) -> ok`

Equivalent to *color4b(Red, Green, Blue, Alpha)*.

```
color4d(Red::float(), Green::float(), Blue::float(), Alpha::float()) -> ok
```

See **external** documentation.

```
color4dv(X1::{Red, Green, Blue, Alpha}) -> ok
```

Equivalent to *color4d(Red, Green, Blue, Alpha)*.

```
color4f(Red::float(), Green::float(), Blue::float(), Alpha::float()) -> ok
```

See **external** documentation.

```
color4fv(X1::{Red, Green, Blue, Alpha}) -> ok
```

Equivalent to *color4f(Red, Green, Blue, Alpha)*.

```
color4i(Red::integer(), Green::integer(), Blue::integer(), Alpha::integer())  
-> ok
```

See **external** documentation.

```
color4iv(X1::{Red, Green, Blue, Alpha}) -> ok
```

Equivalent to *color4i(Red, Green, Blue, Alpha)*.

```
color4s(Red::integer(), Green::integer(), Blue::integer(), Alpha::integer())  
-> ok
```

See **external** documentation.

```
color4sv(X1::{Red, Green, Blue, Alpha}) -> ok
```

Equivalent to *color4s(Red, Green, Blue, Alpha)*.

```
color4ub(Red::integer(), Green::integer(), Blue::integer(), Alpha::integer())  
-> ok
```

See **external** documentation.

```
color4ubv(X1::{Red, Green, Blue, Alpha}) -> ok
```

Equivalent to *color4ub(Red, Green, Blue, Alpha)*.

```
color4ui(Red::integer(), Green::integer(), Blue::integer(), Alpha::integer())  
-> ok
```

See **external** documentation.

```
color4uiv(X1::{Red, Green, Blue, Alpha}) -> ok
```

Equivalent to *color4ui(Red, Green, Blue, Alpha)*.

```
color4us(Red::integer(), Green::integer(), Blue::integer(), Alpha::integer())  
-> ok
```

See **external** documentation.

`color4usv(X1::{Red, Green, Blue, Alpha}) -> ok`

Equivalent to *color4us(Red, Green, Blue, Alpha)*.

`colorMask(Red::0 | 1, Green::0 | 1, Blue::0 | 1, Alpha::0 | 1) -> ok`

See **external** documentation.

`colorMaterial(Face::enum(), Mode::enum()) -> ok`

See **external** documentation.

`colorPointer(Size::integer(), Type::enum(), Stride::integer(),
Pointer::offset() | binary()) -> ok`

See **external** documentation.

`copyPixels(X::integer(), Y::integer(), Width::integer(), Height::integer(),
Type::enum()) -> ok`

See **external** documentation.

`copyTexImage1D(Target::enum(), Level::integer(), InternalFormat::enum(),
X::integer(), Y::integer(), Width::integer(), Border::integer()) -> ok`

See **external** documentation.

`copyTexImage2D(Target::enum(), Level::integer(), InternalFormat::enum(),
X::integer(), Y::integer(), Width::integer(), Height::integer(),
Border::integer()) -> ok`

See **external** documentation.

`copyTexSubImage1D(Target::enum(), Level::integer(), Xoffset::integer(),
X::integer(), Y::integer(), Width::integer()) -> ok`

See **external** documentation.

`copyTexSubImage2D(Target::enum(), Level::integer(), Xoffset::integer(),
Yoffset::integer(), X::integer(), Y::integer(), Width::integer(),
Height::integer()) -> ok`

See **external** documentation.

`cullFace(Mode::enum()) -> ok`

See **external** documentation.

`deleteLists(List::integer(), Range::integer()) -> ok`

See **external** documentation.

`deleteTextures(Textures::[integer()]) -> ok`

See **external** documentation.

depthFunc(Func::enum()) -> ok

See **external** documentation.

depthMask(Flag::0 | 1) -> ok

See **external** documentation.

depthRange(ZNear::clamp(), ZFar::clamp()) -> ok

See **external** documentation.

disable(Cap::enum()) -> ok

See **external** documentation.

disableClientState(Array::enum()) -> ok

See **external** documentation.

drawArrays(Mode::enum(), First::integer(), Count::integer()) -> ok

See **external** documentation.

drawBuffer(Mode::enum()) -> ok

See **external** documentation.

**drawElements(Mode::enum(), Count::integer(), Type::enum(), Indices::offset()
| binary()) -> ok**

See **external** documentation.

**drawPixels(Width::integer(), Height::integer(), Format::enum(), Type::enum(),
Pixels::offset() | binary()) -> ok**

See **external** documentation.

edgeFlag(Flag::0 | 1) -> ok

See **external** documentation.

edgeFlagPointer(Stride::integer(), Pointer::offset() | binary()) -> ok

See **external** documentation.

edgeFlagv(X1::{Flag}) -> ok

Equivalent to *edgeFlag(Flag)*.

enable(Cap::enum()) -> ok

See **external** documentation.

enableClientState(Array::enum()) -> ok

See **external** documentation.

end() -> ok

See **external** documentation.

endList() -> ok

See **external** documentation.

evalCoord1d(U::float()) -> ok

See **external** documentation.

evalCoord1dv(X1::{U}) -> ok

Equivalent to *evalCoord1d(U)*.

evalCoord1f(U::float()) -> ok

See **external** documentation.

evalCoord1fv(X1::{U}) -> ok

Equivalent to *evalCoord1f(U)*.

evalCoord2d(U::float(), V::float()) -> ok

See **external** documentation.

evalCoord2dv(X1::{U, V}) -> ok

Equivalent to *evalCoord2d(U, V)*.

evalCoord2f(U::float(), V::float()) -> ok

See **external** documentation.

evalCoord2fv(X1::{U, V}) -> ok

Equivalent to *evalCoord2f(U, V)*.

evalMesh1(Mode::enum(), I1::integer(), I2::integer()) -> ok

See **external** documentation.

evalMesh2(Mode::enum(), I1::integer(), I2::integer(), J1::integer(), J2::integer()) -> ok

See **external** documentation.

evalPoint1(I::integer()) -> ok

See **external** documentation.

evalPoint2(I::integer(), J::integer()) -> ok

See **external** documentation.

feedbackBuffer(Size::integer(), Type::enum(), Buffer::wx_mem()) (see module **wx**) -> ok

See **external** documentation.

finish() -> ok

See **external** documentation.

flush() -> ok

See **external** documentation.

fogf(Pname::enum(), Param::float()) -> ok

See **external** documentation.

fogfv(Pname::enum(), Params::{float()}) -> ok

See **external** documentation.

fogi(Pname::enum(), Param::integer()) -> ok

See **external** documentation.

fogiv(Pname::enum(), Params::{integer()}) -> ok

See **external** documentation.

frontFace(Mode::enum()) -> ok

See **external** documentation.

frustum(Left::float(), Right::float(), Bottom::float(), Top::float(), ZNear::float(), ZFar::float()) -> ok

See **external** documentation.

genLists(Range::integer()) -> integer()

See **external** documentation.

genTextures(N::integer()) -> [integer()]

See **external** documentation.

getBooleanv(Pname::enum()) -> [0 | 1]

See **external** documentation.

getClipPlane(Plane::enum()) -> {float()}

See **external** documentation.

getDoublev(Pname::enum()) -> [float()]

See **external** documentation.

`getError()` -> `enum()`

See **external** documentation.

`getFloatv(Pname::enum())` -> `[float()]`

See **external** documentation.

`getIntegerv(Pname::enum())` -> `[integer()]`

See **external** documentation.

`getLightfv(Light::enum(), Pname::enum())` -> `{float()}`

See **external** documentation.

`getLightiv(Light::enum(), Pname::enum())` -> `{integer()}`

See **external** documentation.

`getMapdv(Target::enum(), Query::enum(), V::wx_mem() (see module wx))` -> `ok`

See **external** documentation.

`getMapfv(Target::enum(), Query::enum(), V::wx_mem() (see module wx))` -> `ok`

See **external** documentation.

`getMapiv(Target::enum(), Query::enum(), V::wx_mem() (see module wx))` -> `ok`

See **external** documentation.

`getMaterialfv(Face::enum(), Pname::enum())` -> `{float()}`

See **external** documentation.

`getMaterialiv(Face::enum(), Pname::enum())` -> `{integer()}`

See **external** documentation.

`getPixelMapfv(Map::enum(), Values::wx_mem() (see module wx))` -> `ok`

See **external** documentation.

`getPixelMapuiv(Map::enum(), Values::wx_mem() (see module wx))` -> `ok`

See **external** documentation.

`getPixelMapusv(Map::enum(), Values::wx_mem() (see module wx))` -> `ok`

See **external** documentation.

`getPolygonStipple()` -> `binary()`

See **external** documentation.

`getString(Name::enum()) -> string()`

See **external** documentation.

`getTexEnvfv(Target::enum(), Pname::enum()) -> {float()}`

See **external** documentation.

`getTexEnviv(Target::enum(), Pname::enum()) -> {integer()}`

See **external** documentation.

`getTexGendv(Coord::enum(), Pname::enum()) -> {float()}`

See **external** documentation.

`getTexGenfv(Coord::enum(), Pname::enum()) -> {float()}`

See **external** documentation.

`getTexGeniv(Coord::enum(), Pname::enum()) -> {integer()}`

See **external** documentation.

`getTexImage(Target::enum(), Level::integer(), Format::enum(), Type::enum(),
Pixels::wx_mem() (see module wx)) -> ok`

See **external** documentation.

`getTexLevelParameterfv(Target::enum(), Level::integer(), Pname::enum()) ->
{float()}`

See **external** documentation.

`getTexLevelParameteriv(Target::enum(), Level::integer(), Pname::enum()) ->
{integer()}`

See **external** documentation.

`getTexParameterfv(Target::enum(), Pname::enum()) -> {float()}`

See **external** documentation.

`getTexParameteriv(Target::enum(), Pname::enum()) -> {integer()}`

See **external** documentation.

`hint(Target::enum(), Mode::enum()) -> ok`

See **external** documentation.

`indexMask(Mask::integer()) -> ok`

See **external** documentation.

```
indexPointer(Type::enum(), Stride::integer(), Pointer::offset() | binary()) -> ok
```

See **external** documentation.

```
indexd(C::float()) -> ok
```

See **external** documentation.

```
indexdv(X1::{C}) -> ok
```

Equivalent to *indexd(C)*.

```
indexf(C::float()) -> ok
```

See **external** documentation.

```
indexfv(X1::{C}) -> ok
```

Equivalent to *indexf(C)*.

```
indexi(C::integer()) -> ok
```

See **external** documentation.

```
indexiv(X1::{C}) -> ok
```

Equivalent to *indexi(C)*.

```
indexs(C::integer()) -> ok
```

See **external** documentation.

```
indexsv(X1::{C}) -> ok
```

Equivalent to *indexs(C)*.

```
indexub(C::integer()) -> ok
```

See **external** documentation.

```
indexubv(X1::{C}) -> ok
```

Equivalent to *indexub(C)*.

```
initNames() -> ok
```

See **external** documentation.

```
interleavedArrays(Format::enum(), Stride::integer(), Pointer::offset() | binary()) -> ok
```

See **external** documentation.

```
isEnabled(Cap::enum()) -> 0 | 1
```

See **external** documentation.

`isList(List::integer()) -> 0 | 1`

See **external** documentation.

`isTexture(Texture::integer()) -> 0 | 1`

See **external** documentation.

`lightModelf(Pname::enum(), Param::float()) -> ok`

See **external** documentation.

`lightModelfv(Pname::enum(), Params::{float()}) -> ok`

See **external** documentation.

`lightModeli(Pname::enum(), Param::integer()) -> ok`

See **external** documentation.

`lightModeliv(Pname::enum(), Params::{integer()}) -> ok`

See **external** documentation.

`lightf(Light::enum(), Pname::enum(), Param::float()) -> ok`

See **external** documentation.

`lightfv(Light::enum(), Pname::enum(), Params::{float()}) -> ok`

See **external** documentation.

`lighti(Light::enum(), Pname::enum(), Param::integer()) -> ok`

See **external** documentation.

`lightiv(Light::enum(), Pname::enum(), Params::{integer()}) -> ok`

See **external** documentation.

`lineStipple(Factor::integer(), Pattern::integer()) -> ok`

See **external** documentation.

`lineWidth(Width::float()) -> ok`

See **external** documentation.

`listBase(Base::integer()) -> ok`

See **external** documentation.

`loadIdentity() -> ok`

See **external** documentation.

`loadMatrixd(M::{float()}) -> ok`

See **external** documentation.

`loadMatrixf(M::{float()}) -> ok`

See **external** documentation.

`loadName(Name::integer()) -> ok`

See **external** documentation.

`logicOp(Opcode::enum()) -> ok`

See **external** documentation.

`map1d(Target::enum(), U1::float(), U2::float(), Stride::integer(),
Order::integer(), Points::binary()) -> ok`

See **external** documentation.

`map1f(Target::enum(), U1::float(), U2::float(), Stride::integer(),
Order::integer(), Points::binary()) -> ok`

See **external** documentation.

`map2d(Target::enum(), U1::float(), U2::float(), Ustride::integer(),
Uorder::integer(), V1::float(), V2::float(), Vstride::integer(),
Vorder::integer(), Points::binary()) -> ok`

See **external** documentation.

`map2f(Target::enum(), U1::float(), U2::float(), Ustride::integer(),
Uorder::integer(), V1::float(), V2::float(), Vstride::integer(),
Vorder::integer(), Points::binary()) -> ok`

See **external** documentation.

`mapGrid1d(Un::integer(), U1::float(), U2::float()) -> ok`

See **external** documentation.

`mapGrid1f(Un::integer(), U1::float(), U2::float()) -> ok`

See **external** documentation.

`mapGrid2d(Un::integer(), U1::float(), U2::float(), Vn::integer(),
V1::float(), V2::float()) -> ok`

See **external** documentation.

`mapGrid2f(Un::integer(), U1::float(), U2::float(), Vn::integer(),
V1::float(), V2::float()) -> ok`

See **external** documentation.

materialf(Face::enum(), Pname::enum(), Param::float()) -> ok

See **external** documentation.

materialfv(Face::enum(), Pname::enum(), Params::{float()}) -> ok

See **external** documentation.

materiali(Face::enum(), Pname::enum(), Param::integer()) -> ok

See **external** documentation.

materialiv(Face::enum(), Pname::enum(), Params::{integer()}) -> ok

See **external** documentation.

matrixMode(Mode::enum()) -> ok

See **external** documentation.

multMatrixd(M::{float()}) -> ok

See **external** documentation.

multMatrixf(M::{float()}) -> ok

See **external** documentation.

newList(List::integer(), Mode::enum()) -> ok

See **external** documentation.

normal3b(Nx::integer(), Ny::integer(), Nz::integer()) -> ok

See **external** documentation.

normal3bv(X1::{Nx, Ny, Nz}) -> ok

Equivalent to *normal3b(Nx, Ny, Nz)*.

normal3d(Nx::float(), Ny::float(), Nz::float()) -> ok

See **external** documentation.

normal3dv(X1::{Nx, Ny, Nz}) -> ok

Equivalent to *normal3d(Nx, Ny, Nz)*.

normal3f(Nx::float(), Ny::float(), Nz::float()) -> ok

See **external** documentation.

normal3fv(X1::{Nx, Ny, Nz}) -> ok

Equivalent to *normal3f(Nx, Ny, Nz)*.

normal3i(Nx::integer(), Ny::integer(), Nz::integer()) -> ok

See **external** documentation.

normal3iv(Xl::{Nx, Ny, Nz}) -> ok

Equivalent to *normal3i*(Nx, Ny, Nz).

normal3s(Nx::integer(), Ny::integer(), Nz::integer()) -> ok

See **external** documentation.

normal3sv(Xl::{Nx, Ny, Nz}) -> ok

Equivalent to *normal3s*(Nx, Ny, Nz).

normalPointer(Type::enum(), Stride::integer(), Pointer::offset() | binary())
-> ok

See **external** documentation.

ortho(Left::float(), Right::float(), Bottom::float(), Top::float(),
ZNear::float(), ZFar::float()) -> ok

See **external** documentation.

passThrough(Token::float()) -> ok

See **external** documentation.

pixelMapfv(Map::enum(), Mapsize::integer(), Values::binary()) -> ok

See **external** documentation.

pixelMapuiv(Map::enum(), Mapsize::integer(), Values::binary()) -> ok

See **external** documentation.

pixelMapusv(Map::enum(), Mapsize::integer(), Values::binary()) -> ok

See **external** documentation.

pixelStoref(Pname::enum(), Param::float()) -> ok

See **external** documentation.

pixelStorei(Pname::enum(), Param::integer()) -> ok

See **external** documentation.

pixelTransferf(Pname::enum(), Param::float()) -> ok

See **external** documentation.

pixelTransferi(Pname::enum(), Param::integer()) -> ok

See **external** documentation.

pixelZoom(Xfactor::float(), Yfactor::float()) -> ok

See **external** documentation.

pointSize(Size::float()) -> ok

See **external** documentation.

polygonMode(Face::enum(), Mode::enum()) -> ok

See **external** documentation.

polygonOffset(Factor::float(), Units::float()) -> ok

See **external** documentation.

polygonStipple(Mask::binary()) -> ok

See **external** documentation.

popAttrib() -> ok

See **external** documentation.

popClientAttrib() -> ok

See **external** documentation.

popMatrix() -> ok

See **external** documentation.

popName() -> ok

See **external** documentation.

prioritizeTextures(Textures::[integer()], Priorities::[clamp()]) -> ok

See **external** documentation.

pushAttrib(Mask::integer()) -> ok

See **external** documentation.

pushClientAttrib(Mask::integer()) -> ok

See **external** documentation.

pushMatrix() -> ok

See **external** documentation.

pushName(Name::integer()) -> ok

See **external** documentation.

rasterPos2d(X::float(), Y::float()) -> ok

See **external** documentation.

rasterPos2dv(X1::{X, Y}) -> ok

Equivalent to *rasterPos2d*(X, Y).

rasterPos2f(X::float(), Y::float()) -> ok

See **external** documentation.

rasterPos2fv(X1::{X, Y}) -> ok

Equivalent to *rasterPos2f*(X, Y).

rasterPos2i(X::integer(), Y::integer()) -> ok

See **external** documentation.

rasterPos2iv(X1::{X, Y}) -> ok

Equivalent to *rasterPos2i*(X, Y).

rasterPos2s(X::integer(), Y::integer()) -> ok

See **external** documentation.

rasterPos2sv(X1::{X, Y}) -> ok

Equivalent to *rasterPos2s*(X, Y).

rasterPos3d(X::float(), Y::float(), Z::float()) -> ok

See **external** documentation.

rasterPos3dv(X1::{X, Y, Z}) -> ok

Equivalent to *rasterPos3d*(X, Y, Z).

rasterPos3f(X::float(), Y::float(), Z::float()) -> ok

See **external** documentation.

rasterPos3fv(X1::{X, Y, Z}) -> ok

Equivalent to *rasterPos3f*(X, Y, Z).

rasterPos3i(X::integer(), Y::integer(), Z::integer()) -> ok

See **external** documentation.

rasterPos3iv(X1::{X, Y, Z}) -> ok

Equivalent to *rasterPos3i*(X, Y, Z).

rasterPos3s(X::integer(), Y::integer(), Z::integer()) -> ok

See **external** documentation.

rasterPos3sv(X1::{X, Y, Z}) -> ok

Equivalent to *rasterPos3s*(X, Y, Z).

rasterPos4d(X::float(), Y::float(), Z::float(), W::float()) -> ok

See **external** documentation.

rasterPos4dv(X1::{X, Y, Z, W}) -> ok

Equivalent to *rasterPos4d*(X, Y, Z, W).

rasterPos4f(X::float(), Y::float(), Z::float(), W::float()) -> ok

See **external** documentation.

rasterPos4fv(X1::{X, Y, Z, W}) -> ok

Equivalent to *rasterPos4f*(X, Y, Z, W).

rasterPos4i(X::integer(), Y::integer(), Z::integer(), W::integer()) -> ok

See **external** documentation.

rasterPos4iv(X1::{X, Y, Z, W}) -> ok

Equivalent to *rasterPos4i*(X, Y, Z, W).

rasterPos4s(X::integer(), Y::integer(), Z::integer(), W::integer()) -> ok

See **external** documentation.

rasterPos4sv(X1::{X, Y, Z, W}) -> ok

Equivalent to *rasterPos4s*(X, Y, Z, W).

readBuffer(Mode::enum()) -> ok

See **external** documentation.

readPixels(X::integer(), Y::integer(), Width::integer(), Height::integer(),
Format::enum(), Type::enum(), Pixels::wx_mem() (see module wx)) -> ok

See **external** documentation.

rectd(X1::float(), Y1::float(), X2::float(), Y2::float()) -> ok

See **external** documentation.

rectdv(V1::{float()}, V2::{float()}) -> ok

See **external** documentation.

rectf(X1::float(), Y1::float(), X2::float(), Y2::float()) -> ok

See **external** documentation.

rectfv(V1::{float()}, V2::{float()}) -> ok

See **external** documentation.

recti(X1::integer(), Y1::integer(), X2::integer(), Y2::integer()) -> ok

See **external** documentation.

rectiv(V1::{integer()}, V2::{integer()}) -> ok

See **external** documentation.

rects(X1::integer(), Y1::integer(), X2::integer(), Y2::integer()) -> ok

See **external** documentation.

rectsv(V1::{integer()}, V2::{integer()}) -> ok

See **external** documentation.

renderMode(Mode::enum()) -> integer()

See **external** documentation.

rotated(Angle::float(), X::float(), Y::float(), Z::float()) -> ok

See **external** documentation.

rotatef(Angle::float(), X::float(), Y::float(), Z::float()) -> ok

See **external** documentation.

scaled(X::float(), Y::float(), Z::float()) -> ok

See **external** documentation.

scalef(X::float(), Y::float(), Z::float()) -> ok

See **external** documentation.

scissor(X::integer(), Y::integer(), Width::integer(), Height::integer()) -> ok

See **external** documentation.

selectBuffer(Size::integer(), Buffer::wx_mem() (see module wx)) -> ok

See **external** documentation.

shadeModel(Mode::enum()) -> ok

See **external** documentation.

stencilFunc(Func::enum(), Ref::integer(), Mask::integer()) -> ok

See **external** documentation.

stencilMask(Mask::integer()) -> ok

See **external** documentation.

stencilOp(Fail::enum(), Zfail::enum(), Zpass::enum()) -> ok

See **external** documentation.

texCoord1d(S::float()) -> ok

See **external** documentation.

texCoord1dv(X1::S) -> ok

Equivalent to *texCoord1d(S)*.

texCoord1f(S::float()) -> ok

See **external** documentation.

texCoord1fv(X1::S) -> ok

Equivalent to *texCoord1f(S)*.

texCoord1i(S::integer()) -> ok

See **external** documentation.

texCoord1iv(X1::S) -> ok

Equivalent to *texCoord1i(S)*.

texCoord1s(S::integer()) -> ok

See **external** documentation.

texCoord1sv(X1::S) -> ok

Equivalent to *texCoord1s(S)*.

texCoord2d(S::float(), T::float()) -> ok

See **external** documentation.

texCoord2dv(X1::S, T) -> ok

Equivalent to *texCoord2d(S, T)*.

texCoord2f(S::float(), T::float()) -> ok

See **external** documentation.

`texCoord2fv(X1::{S, T}) -> ok`

Equivalent to *texCoord2f(S, T)*.

`texCoord2i(S::integer(), T::integer()) -> ok`

See **external** documentation.

`texCoord2iv(X1::{S, T}) -> ok`

Equivalent to *texCoord2i(S, T)*.

`texCoord2s(S::integer(), T::integer()) -> ok`

See **external** documentation.

`texCoord2sv(X1::{S, T}) -> ok`

Equivalent to *texCoord2s(S, T)*.

`texCoord3d(S::float(), T::float(), R::float()) -> ok`

See **external** documentation.

`texCoord3dv(X1::{S, T, R}) -> ok`

Equivalent to *texCoord3d(S, T, R)*.

`texCoord3f(S::float(), T::float(), R::float()) -> ok`

See **external** documentation.

`texCoord3fv(X1::{S, T, R}) -> ok`

Equivalent to *texCoord3f(S, T, R)*.

`texCoord3i(S::integer(), T::integer(), R::integer()) -> ok`

See **external** documentation.

`texCoord3iv(X1::{S, T, R}) -> ok`

Equivalent to *texCoord3i(S, T, R)*.

`texCoord3s(S::integer(), T::integer(), R::integer()) -> ok`

See **external** documentation.

`texCoord3sv(X1::{S, T, R}) -> ok`

Equivalent to *texCoord3s(S, T, R)*.

`texCoord4d(S::float(), T::float(), R::float(), Q::float()) -> ok`

See **external** documentation.

```
texCoord4dv(X1::{S, T, R, Q}) -> ok
```

Equivalent to *texCoord4d(S, T, R, Q)*.

```
texCoord4f(S::float(), T::float(), R::float(), Q::float()) -> ok
```

See **external** documentation.

```
texCoord4fv(X1::{S, T, R, Q}) -> ok
```

Equivalent to *texCoord4f(S, T, R, Q)*.

```
texCoord4i(S::integer(), T::integer(), R::integer(), Q::integer()) -> ok
```

See **external** documentation.

```
texCoord4iv(X1::{S, T, R, Q}) -> ok
```

Equivalent to *texCoord4i(S, T, R, Q)*.

```
texCoord4s(S::integer(), T::integer(), R::integer(), Q::integer()) -> ok
```

See **external** documentation.

```
texCoord4sv(X1::{S, T, R, Q}) -> ok
```

Equivalent to *texCoord4s(S, T, R, Q)*.

```
texCoordPointer(Size::integer(), Type::enum(), Stride::integer(),  
Pointer::offset() | binary()) -> ok
```

See **external** documentation.

```
texEnvf(Target::enum(), Pname::enum(), Param::float()) -> ok
```

See **external** documentation.

```
texEnvfv(Target::enum(), Pname::enum(), Params::{float()}) -> ok
```

See **external** documentation.

```
texEnvi(Target::enum(), Pname::enum(), Param::integer()) -> ok
```

See **external** documentation.

```
texEnviv(Target::enum(), Pname::enum(), Params::{integer()}) -> ok
```

See **external** documentation.

```
texGend(Coord::enum(), Pname::enum(), Param::float()) -> ok
```

See **external** documentation.

```
texGendv(Coord::enum(), Pname::enum(), Params::{float()}) -> ok
```

See **external** documentation.

```
texGenf(Coord::enum(), Pname::enum(), Param::float()) -> ok
```

See **external** documentation.

```
texGenfv(Coord::enum(), Pname::enum(), Params::{float()}) -> ok
```

See **external** documentation.

```
texGeni(Coord::enum(), Pname::enum(), Param::integer()) -> ok
```

See **external** documentation.

```
texGeniv(Coord::enum(), Pname::enum(), Params::{integer()}) -> ok
```

See **external** documentation.

```
texImage1D(Target::enum(), Level::integer(), Internalformat::integer(),  
Width::integer(), Border::integer(), Format::enum(), Type::enum(),  
Pixels::offset() | binary()) -> ok
```

See **external** documentation.

```
texImage2D(Target::enum(), Level::integer(), Internalformat::integer(),  
Width::integer(), Height::integer(), Border::integer(), Format::enum(),  
Type::enum(), Pixels::offset() | binary()) -> ok
```

See **external** documentation.

```
texParameterf(Target::enum(), Pname::enum(), Param::float()) -> ok
```

See **external** documentation.

```
texParameterfv(Target::enum(), Pname::enum(), Params::{float()}) -> ok
```

See **external** documentation.

```
texParameteri(Target::enum(), Pname::enum(), Param::integer()) -> ok
```

See **external** documentation.

```
texParameteriv(Target::enum(), Pname::enum(), Params::{integer()}) -> ok
```

See **external** documentation.

```
texSubImage1D(Target::enum(), Level::integer(), Xoffset::integer(),  
Width::integer(), Format::enum(), Type::enum(), Pixels::offset() | binary())  
-> ok
```

See **external** documentation.

```
texSubImage2D(Target::enum(), Level::integer(), Xoffset::integer(),  
Yoffset::integer(), Width::integer(), Height::integer(), Format::enum(),  
Type::enum(), Pixels::offset() | binary()) -> ok
```

See **external** documentation.

translated(X::float(), Y::float(), Z::float()) -> ok

See **external** documentation.

translatef(X::float(), Y::float(), Z::float()) -> ok

See **external** documentation.

vertex2d(X::float(), Y::float()) -> ok

See **external** documentation.

vertex2dv(X1::{X, Y}) -> ok

Equivalent to *vertex2d(X, Y)*.

vertex2f(X::float(), Y::float()) -> ok

See **external** documentation.

vertex2fv(X1::{X, Y}) -> ok

Equivalent to *vertex2f(X, Y)*.

vertex2i(X::integer(), Y::integer()) -> ok

See **external** documentation.

vertex2iv(X1::{X, Y}) -> ok

Equivalent to *vertex2i(X, Y)*.

vertex2s(X::integer(), Y::integer()) -> ok

See **external** documentation.

vertex2sv(X1::{X, Y}) -> ok

Equivalent to *vertex2s(X, Y)*.

vertex3d(X::float(), Y::float(), Z::float()) -> ok

See **external** documentation.

vertex3dv(X1::{X, Y, Z}) -> ok

Equivalent to *vertex3d(X, Y, Z)*.

vertex3f(X::float(), Y::float(), Z::float()) -> ok

See **external** documentation.

vertex3fv(X1::{X, Y, Z}) -> ok

Equivalent to *vertex3f(X, Y, Z)*.

vertex3i(X::integer(), Y::integer(), Z::integer()) -> ok

See **external** documentation.

vertex3iv(X1::{X, Y, Z}) -> ok

Equivalent to *vertex3i*(X, Y, Z).

vertex3s(X::integer(), Y::integer(), Z::integer()) -> ok

See **external** documentation.

vertex3sv(X1::{X, Y, Z}) -> ok

Equivalent to *vertex3s*(X, Y, Z).

vertex4d(X::float(), Y::float(), Z::float(), W::float()) -> ok

See **external** documentation.

vertex4dv(X1::{X, Y, Z, W}) -> ok

Equivalent to *vertex4d*(X, Y, Z, W).

vertex4f(X::float(), Y::float(), Z::float(), W::float()) -> ok

See **external** documentation.

vertex4fv(X1::{X, Y, Z, W}) -> ok

Equivalent to *vertex4f*(X, Y, Z, W).

vertex4i(X::integer(), Y::integer(), Z::integer(), W::integer()) -> ok

See **external** documentation.

vertex4iv(X1::{X, Y, Z, W}) -> ok

Equivalent to *vertex4i*(X, Y, Z, W).

vertex4s(X::integer(), Y::integer(), Z::integer(), W::integer()) -> ok

See **external** documentation.

vertex4sv(X1::{X, Y, Z, W}) -> ok

Equivalent to *vertex4s*(X, Y, Z, W).

vertexPointer(Size::integer(), Type::enum(), Stride::integer(),
Pointer::offset() | binary()) -> ok

See **external** documentation.

viewport(X::integer(), Y::integer(), Width::integer(), Height::integer()) ->
ok

See **external** documentation.

```
blendColor(Red::clamp(), Green::clamp(), Blue::clamp(), Alpha::clamp()) -> ok
```

See **external** documentation.

```
blendEquation(Mode::enum()) -> ok
```

See **external** documentation.

```
drawRangeElements(Mode::enum(), Start::integer(), End::integer(),  
Count::integer(), Type::enum(), Indices::offset() | binary()) -> ok
```

See **external** documentation.

```
texImage3D(Target::enum(), Level::integer(), Internalformat::integer(),  
Width::integer(), Height::integer(), Depth::integer(), Border::integer(),  
Format::enum(), Type::enum(), Pixels::offset() | binary()) -> ok
```

See **external** documentation.

```
texSubImage3D(Target::enum(), Level::integer(), Xoffset::integer(),  
Yoffset::integer(), Zoffset::integer(), Width::integer(), Height::integer(),  
Depth::integer(), Format::enum(), Type::enum(), Pixels::offset() | binary())  
-> ok
```

See **external** documentation.

```
copyTexSubImage3D(Target::enum(), Level::integer(), Xoffset::integer(),  
Yoffset::integer(), Zoffset::integer(), X::integer(), Y::integer(),  
Width::integer(), Height::integer()) -> ok
```

See **external** documentation.

```
colorTable(Target::enum(), Internalformat::enum(), Width::integer(),  
Format::enum(), Type::enum(), Table::offset() | binary()) -> ok
```

See **external** documentation.

```
colorTableParameterfv(Target::enum(), Pname::enum(), Params::{float()}) -> ok
```

See **external** documentation.

```
colorTableParameteriv(Target::enum(), Pname::enum(), Params::{integer()}) ->  
ok
```

See **external** documentation.

```
copyColorTable(Target::enum(), Internalformat::enum(), X::integer(),  
Y::integer(), Width::integer()) -> ok
```

See **external** documentation.

```
getColorTable(Target::enum(), Format::enum(), Type::enum(), Table::wx_mem()  
(see module wx)) -> ok
```

See **external** documentation.

```
getColorTableParameterfv(Target::enum(), Pname::enum()) -> {float()}
```

See **external** documentation.

```
getColorTableParameteriv(Target::enum(), Pname::enum()) -> {integer()}
```

See **external** documentation.

```
colorSubTable(Target::enum(), Start::integer(), Count::integer(),  
Format::enum(), Type::enum(), Data::offset() | binary()) -> ok
```

See **external** documentation.

```
copyColorSubTable(Target::enum(), Start::integer(), X::integer(),  
Y::integer(), Width::integer()) -> ok
```

See **external** documentation.

```
convolutionFilter1D(Target::enum(), Internalformat::enum(), Width::integer(),  
Format::enum(), Type::enum(), Image::offset() | binary()) -> ok
```

See **external** documentation.

```
convolutionFilter2D(Target::enum(), Internalformat::enum(), Width::integer(),  
Height::integer(), Format::enum(), Type::enum(), Image::offset() | binary())  
-> ok
```

See **external** documentation.

```
convolutionParameterf(Target::enum(), Pname::enum(), Params::{float()}) -> ok
```

See **external** documentation.

```
convolutionParameterfv(Target, Pname, X3::{Params}) -> ok
```

Equivalent to *convolutionParameterf(Target, Pname, Params)*.

```
convolutionParameteri(Target::enum(), Pname::enum(), Params::{integer()}) ->  
ok
```

See **external** documentation.

```
convolutionParameteriv(Target, Pname, X3::{Params}) -> ok
```

Equivalent to *convolutionParameteri(Target, Pname, Params)*.

```
copyConvolutionFilter1D(Target::enum(), Internalformat::enum(), X::integer(),  
Y::integer(), Width::integer()) -> ok
```

See **external** documentation.

```
copyConvolutionFilter2D(Target::enum(), Internalformat::enum(), X::integer(),  
Y::integer(), Width::integer(), Height::integer()) -> ok
```

See **external** documentation.

```
getConvolutionFilter(Target::enum(), Format::enum(), Type::enum(),  
Image::wx_mem() (see module wx)) -> ok
```

See **external** documentation.

```
getConvolutionParameterfv(Target::enum(), Pname::enum()) -> {float()}
```

See **external** documentation.

```
getConvolutionParameteriv(Target::enum(), Pname::enum()) -> {integer()}
```

See **external** documentation.

```
separableFilter2D(Target::enum(), Internalformat::enum(), Width::integer(),  
Height::integer(), Format::enum(), Type::enum(), Row::offset() | binary(),  
Column::offset() | binary()) -> ok
```

See **external** documentation.

```
getHistogram(Target::enum(), Reset::0 | 1, Format::enum(), Type::enum(),  
Values::wx_mem() (see module wx)) -> ok
```

See **external** documentation.

```
getHistogramParameterfv(Target::enum(), Pname::enum()) -> {float()}
```

See **external** documentation.

```
getHistogramParameteriv(Target::enum(), Pname::enum()) -> {integer()}
```

See **external** documentation.

```
getMinmax(Target::enum(), Reset::0 | 1, Format::enum(), Type::enum(),  
Values::wx_mem() (see module wx)) -> ok
```

See **external** documentation.

```
getMinmaxParameterfv(Target::enum(), Pname::enum()) -> {float()}
```

See **external** documentation.

```
getMinmaxParameteriv(Target::enum(), Pname::enum()) -> {integer()}
```

See **external** documentation.

```
histogram(Target::enum(), Width::integer(), Internalformat::enum(), Sink::0 |  
1) -> ok
```

See **external** documentation.

```
minmax(Target::enum(), Internalformat::enum(), Sink::0 | 1) -> ok
```

See **external** documentation.

```
resetHistogram(Target::enum()) -> ok
```

See **external** documentation.

`resetMinmax(Target::enum()) -> ok`

See **external** documentation.

`activeTexture(Texture::enum()) -> ok`

See **external** documentation.

`sampleCoverage(Value::clamp(), Invert::0 | 1) -> ok`

See **external** documentation.

`compressedTexImage3D(Target::enum(), Level::integer(),
Internalformat::enum(), Width::integer(), Height::integer(),
Depth::integer(), Border::integer(), ImageSize::integer(), Data::offset() |
binary()) -> ok`

See **external** documentation.

`compressedTexImage2D(Target::enum(), Level::integer(),
Internalformat::enum(), Width::integer(), Height::integer(),
Border::integer(), ImageSize::integer(), Data::offset() | binary()) -> ok`

See **external** documentation.

`compressedTexImage1D(Target::enum(), Level::integer(),
Internalformat::enum(), Width::integer(), Border::integer(),
ImageSize::integer(), Data::offset() | binary()) -> ok`

See **external** documentation.

`compressedTexSubImage3D(Target::enum(), Level::integer(), Xoffset::integer(),
Yoffset::integer(), Zoffset::integer(), Width::integer(), Height::integer(),
Depth::integer(), Format::enum(), ImageSize::integer(), Data::offset() |
binary()) -> ok`

See **external** documentation.

`compressedTexSubImage2D(Target::enum(), Level::integer(), Xoffset::integer(),
Yoffset::integer(), Width::integer(), Height::integer(), Format::enum(),
ImageSize::integer(), Data::offset() | binary()) -> ok`

See **external** documentation.

`compressedTexSubImage1D(Target::enum(), Level::integer(), Xoffset::integer(),
Width::integer(), Format::enum(), ImageSize::integer(), Data::offset() |
binary()) -> ok`

See **external** documentation.

`getCompressedTexImage(Target::enum(), Level::integer(), Img::wx_mem() (see
module wx)) -> ok`

See **external** documentation.

```
clientActiveTexture(Texture::enum()) -> ok
```

See **external** documentation.

```
multiTexCoord1d(Target::enum(), S::float()) -> ok
```

See **external** documentation.

```
multiTexCoord1dv(Target, X2::{S}) -> ok
```

Equivalent to *multiTexCoord1d(Target, S)*.

```
multiTexCoord1f(Target::enum(), S::float()) -> ok
```

See **external** documentation.

```
multiTexCoord1fv(Target, X2::{S}) -> ok
```

Equivalent to *multiTexCoord1f(Target, S)*.

```
multiTexCoord1i(Target::enum(), S::integer()) -> ok
```

See **external** documentation.

```
multiTexCoord1iv(Target, X2::{S}) -> ok
```

Equivalent to *multiTexCoord1i(Target, S)*.

```
multiTexCoord1s(Target::enum(), S::integer()) -> ok
```

See **external** documentation.

```
multiTexCoord1sv(Target, X2::{S}) -> ok
```

Equivalent to *multiTexCoord1s(Target, S)*.

```
multiTexCoord2d(Target::enum(), S::float(), T::float()) -> ok
```

See **external** documentation.

```
multiTexCoord2dv(Target, X2::{S, T}) -> ok
```

Equivalent to *multiTexCoord2d(Target, S, T)*.

```
multiTexCoord2f(Target::enum(), S::float(), T::float()) -> ok
```

See **external** documentation.

```
multiTexCoord2fv(Target, X2::{S, T}) -> ok
```

Equivalent to *multiTexCoord2f(Target, S, T)*.

```
multiTexCoord2i(Target::enum(), S::integer(), T::integer()) -> ok
```

See **external** documentation.

```
multiTexCoord2iv(Target, X2::{S, T}) -> ok
```

Equivalent to *multiTexCoord2i(Target, S, T)*.

```
multiTexCoord2s(Target::enum(), S::integer(), T::integer()) -> ok
```

See **external** documentation.

```
multiTexCoord2sv(Target, X2::{S, T}) -> ok
```

Equivalent to *multiTexCoord2s(Target, S, T)*.

```
multiTexCoord3d(Target::enum(), S::float(), T::float(), R::float()) -> ok
```

See **external** documentation.

```
multiTexCoord3dv(Target, X2::{S, T, R}) -> ok
```

Equivalent to *multiTexCoord3d(Target, S, T, R)*.

```
multiTexCoord3f(Target::enum(), S::float(), T::float(), R::float()) -> ok
```

See **external** documentation.

```
multiTexCoord3fv(Target, X2::{S, T, R}) -> ok
```

Equivalent to *multiTexCoord3f(Target, S, T, R)*.

```
multiTexCoord3i(Target::enum(), S::integer(), T::integer(), R::integer()) -> ok
```

See **external** documentation.

```
multiTexCoord3iv(Target, X2::{S, T, R}) -> ok
```

Equivalent to *multiTexCoord3i(Target, S, T, R)*.

```
multiTexCoord3s(Target::enum(), S::integer(), T::integer(), R::integer()) -> ok
```

See **external** documentation.

```
multiTexCoord3sv(Target, X2::{S, T, R}) -> ok
```

Equivalent to *multiTexCoord3s(Target, S, T, R)*.

```
multiTexCoord4d(Target::enum(), S::float(), T::float(), R::float(),  
Q::float()) -> ok
```

See **external** documentation.

```
multiTexCoord4dv(Target, X2::{S, T, R, Q}) -> ok
```

Equivalent to *multiTexCoord4d(Target, S, T, R, Q)*.

multiTexCoord4f(Target::enum(), S::float(), T::float(), R::float(), Q::float()) -> ok

See **external** documentation.

multiTexCoord4fv(Target, X2::{S, T, R, Q}) -> ok

Equivalent to *multiTexCoord4f*(Target, S, T, R, Q).

multiTexCoord4i(Target::enum(), S::integer(), T::integer(), R::integer(), Q::integer()) -> ok

See **external** documentation.

multiTexCoord4iv(Target, X2::{S, T, R, Q}) -> ok

Equivalent to *multiTexCoord4i*(Target, S, T, R, Q).

multiTexCoord4s(Target::enum(), S::integer(), T::integer(), R::integer(), Q::integer()) -> ok

See **external** documentation.

multiTexCoord4sv(Target, X2::{S, T, R, Q}) -> ok

Equivalent to *multiTexCoord4s*(Target, S, T, R, Q).

loadTransposeMatrixf(M::{float()}) -> ok

See **external** documentation.

loadTransposeMatrixd(M::{float()}) -> ok

See **external** documentation.

multTransposeMatrixf(M::{float()}) -> ok

See **external** documentation.

multTransposeMatrixd(M::{float()}) -> ok

See **external** documentation.

blendFuncSeparate(SfactorRGB::enum(), DfactorRGB::enum(), SfactorAlpha::enum(), DfactorAlpha::enum()) -> ok

See **external** documentation.

multiDrawArrays(Mode::enum(), First:[integer()], Count:[integer()]) -> ok

See **external** documentation.

pointParameterf(Pname::enum(), Param::float()) -> ok

See **external** documentation.

pointParameterfv(Pname::enum(), Params::{float()}) -> ok

See **external** documentation.

pointParameteri(Pname::enum(), Param::integer()) -> ok

See **external** documentation.

pointParameteriv(Pname::enum(), Params::{integer()}) -> ok

See **external** documentation.

fogCoordf(Coord::float()) -> ok

See **external** documentation.

fogCoordfv(X1::{Coord}) -> ok

Equivalent to *fogCoordf(Coord)*.

fogCoordd(Coord::float()) -> ok

See **external** documentation.

fogCoorddv(X1::{Coord}) -> ok

Equivalent to *fogCoordd(Coord)*.

**fogCoordPointer(Type::enum(), Stride::integer(), Pointer::offset() |
binary()) -> ok**

See **external** documentation.

secondaryColor3b(Red::integer(), Green::integer(), Blue::integer()) -> ok

See **external** documentation.

secondaryColor3bv(X1::{Red, Green, Blue}) -> ok

Equivalent to *secondaryColor3b(Red, Green, Blue)*.

secondaryColor3d(Red::float(), Green::float(), Blue::float()) -> ok

See **external** documentation.

secondaryColor3dv(X1::{Red, Green, Blue}) -> ok

Equivalent to *secondaryColor3d(Red, Green, Blue)*.

secondaryColor3f(Red::float(), Green::float(), Blue::float()) -> ok

See **external** documentation.

secondaryColor3fv(X1::{Red, Green, Blue}) -> ok

Equivalent to *secondaryColor3f(Red, Green, Blue)*.

secondaryColor3i(Red::integer(), Green::integer(), Blue::integer()) -> ok

See **external** documentation.

secondaryColor3iv(X1::{Red, Green, Blue}) -> ok

Equivalent to *secondaryColor3i*(Red, Green, Blue).

secondaryColor3s(Red::integer(), Green::integer(), Blue::integer()) -> ok

See **external** documentation.

secondaryColor3sv(X1::{Red, Green, Blue}) -> ok

Equivalent to *secondaryColor3s*(Red, Green, Blue).

secondaryColor3ub(Red::integer(), Green::integer(), Blue::integer()) -> ok

See **external** documentation.

secondaryColor3ubv(X1::{Red, Green, Blue}) -> ok

Equivalent to *secondaryColor3ub*(Red, Green, Blue).

secondaryColor3ui(Red::integer(), Green::integer(), Blue::integer()) -> ok

See **external** documentation.

secondaryColor3uiv(X1::{Red, Green, Blue}) -> ok

Equivalent to *secondaryColor3ui*(Red, Green, Blue).

secondaryColor3us(Red::integer(), Green::integer(), Blue::integer()) -> ok

See **external** documentation.

secondaryColor3usv(X1::{Red, Green, Blue}) -> ok

Equivalent to *secondaryColor3us*(Red, Green, Blue).

secondaryColorPointer(Size::integer(), Type::enum(), Stride::integer(),
Pointer::offset() | binary()) -> ok

See **external** documentation.

windowPos2d(X::float(), Y::float()) -> ok

See **external** documentation.

windowPos2dv(X1::{X, Y}) -> ok

Equivalent to *windowPos2d*(X, Y).

windowPos2f(X::float(), Y::float()) -> ok

See **external** documentation.

windowPos2fv(X1::{X, Y}) -> ok

Equivalent to *windowPos2f(X, Y)*.

windowPos2i(X::integer(), Y::integer()) -> ok

See **external** documentation.

windowPos2iv(X1::{X, Y}) -> ok

Equivalent to *windowPos2i(X, Y)*.

windowPos2s(X::integer(), Y::integer()) -> ok

See **external** documentation.

windowPos2sv(X1::{X, Y}) -> ok

Equivalent to *windowPos2s(X, Y)*.

windowPos3d(X::float(), Y::float(), Z::float()) -> ok

See **external** documentation.

windowPos3dv(X1::{X, Y, Z}) -> ok

Equivalent to *windowPos3d(X, Y, Z)*.

windowPos3f(X::float(), Y::float(), Z::float()) -> ok

See **external** documentation.

windowPos3fv(X1::{X, Y, Z}) -> ok

Equivalent to *windowPos3f(X, Y, Z)*.

windowPos3i(X::integer(), Y::integer(), Z::integer()) -> ok

See **external** documentation.

windowPos3iv(X1::{X, Y, Z}) -> ok

Equivalent to *windowPos3i(X, Y, Z)*.

windowPos3s(X::integer(), Y::integer(), Z::integer()) -> ok

See **external** documentation.

windowPos3sv(X1::{X, Y, Z}) -> ok

Equivalent to *windowPos3s(X, Y, Z)*.

genQueries(N::integer()) -> [integer()]

See **external** documentation.

```
deleteQueries(Ids::[integer()]) -> ok
```

See **external** documentation.

```
isQuery(Id::integer()) -> 0 | 1
```

See **external** documentation.

```
beginQuery(Target::enum(), Id::integer()) -> ok
```

See **external** documentation.

```
endQuery(Target::enum()) -> ok
```

See **external** documentation.

```
getQueryiv(Target::enum(), Pname::enum()) -> integer()
```

See **external** documentation.

```
getQueryObjectiv(Id::integer(), Pname::enum()) -> integer()
```

See **external** documentation.

```
getQueryObjectuiv(Id::integer(), Pname::enum()) -> integer()
```

See **external** documentation.

```
bindBuffer(Target::enum(), Buffer::integer()) -> ok
```

See **external** documentation.

```
deleteBuffers(Buffers::[integer()]) -> ok
```

See **external** documentation.

```
genBuffers(N::integer()) -> [integer()]
```

See **external** documentation.

```
isBuffer(Buffer::integer()) -> 0 | 1
```

See **external** documentation.

```
bufferData(Target::enum(), Size::integer(), Data::offset() | binary(),  
Usage::enum()) -> ok
```

See **external** documentation.

```
bufferSubData(Target::enum(), Offset::integer(), Size::integer(),  
Data::offset() | binary()) -> ok
```

See **external** documentation.

getBufferSubData(Target::enum(), Offset::integer(), Size::integer(),
Data::wx_mem() (see module wx)) -> ok

See **external** documentation.

getBufferParameteriv(Target::enum(), Pname::enum()) -> integer()

See **external** documentation.

blendEquationSeparate(ModeRGB::enum(), ModeAlpha::enum()) -> ok

See **external** documentation.

drawBuffers(Bufs::[enum()]) -> ok

See **external** documentation.

stencilOpSeparate(Face::enum(), Sfail::enum(), Dpfail::enum(),
Dppass::enum()) -> ok

See **external** documentation.

stencilFuncSeparate(Frontfunc::enum(), Backfunc::enum(), Ref::integer(),
Mask::integer()) -> ok

See **external** documentation.

stencilMaskSeparate(Face::enum(), Mask::integer()) -> ok

See **external** documentation.

attachShader(Program::integer(), Shader::integer()) -> ok

See **external** documentation.

bindAttribLocation(Program::integer(), Index::integer(), Name::string()) ->
ok

See **external** documentation.

compileShader(Shader::integer()) -> ok

See **external** documentation.

createProgram() -> integer()

See **external** documentation.

createShader(Type::enum()) -> integer()

See **external** documentation.

deleteProgram(Program::integer()) -> ok

See **external** documentation.

deleteShader(Shader::integer()) -> ok

See **external** documentation.

detachShader(Program::integer(), Shader::integer()) -> ok

See **external** documentation.

disableVertexAttribArray(Index::integer()) -> ok

See **external** documentation.

enableVertexAttribArray(Index::integer()) -> ok

See **external** documentation.

getActiveAttrib(Program::integer(), Index::integer(), BufSize::integer()) -> {Size::integer(), Type::enum(), Name::string()}

See **external** documentation.

getActiveUniform(Program::integer(), Index::integer(), BufSize::integer()) -> {Size::integer(), Type::enum(), Name::string()}

See **external** documentation.

getAttachedShaders(Program::integer(), MaxCount::integer()) -> [integer()]

See **external** documentation.

getAttribLocation(Program::integer(), Name::string()) -> integer()

See **external** documentation.

getProgramiv(Program::integer(), Pname::enum()) -> integer()

See **external** documentation.

getProgramInfoLog(Program::integer(), BufSize::integer()) -> string()

See **external** documentation.

getShaderiv(Shader::integer(), Pname::enum()) -> integer()

See **external** documentation.

getShaderInfoLog(Shader::integer(), BufSize::integer()) -> string()

See **external** documentation.

getShaderSource(Shader::integer(), BufSize::integer()) -> string()

See **external** documentation.

getUniformLocation(Program::integer(), Name::string()) -> integer()

See **external** documentation.

`getUniformfv(Program::integer(), Location::integer()) -> {float()}`

See **external** documentation.

`getUniformiv(Program::integer(), Location::integer()) -> {integer()}`

See **external** documentation.

`getVertexAttribdv(Index::integer(), Pname::enum()) -> {float()}`

See **external** documentation.

`getVertexAttribfv(Index::integer(), Pname::enum()) -> {float()}`

See **external** documentation.

`getVertexAttribiv(Index::integer(), Pname::enum()) -> {integer()}`

See **external** documentation.

`isProgram(Program::integer()) -> 0 | 1`

See **external** documentation.

`isShader(Shader::integer()) -> 0 | 1`

See **external** documentation.

`linkProgram(Program::integer()) -> ok`

See **external** documentation.

`shaderSource(Shader::integer(), String::[string()]) -> ok`

See **external** documentation.

`useProgram(Program::integer()) -> ok`

See **external** documentation.

`uniform1f(Location::integer(), V0::float()) -> ok`

See **external** documentation.

`uniform2f(Location::integer(), V0::float(), V1::float()) -> ok`

See **external** documentation.

`uniform3f(Location::integer(), V0::float(), V1::float(), V2::float()) -> ok`

See **external** documentation.

`uniform4f(Location::integer(), V0::float(), V1::float(), V2::float(),
V3::float()) -> ok`

See **external** documentation.

`uniform1i(Location::integer(), V0::integer()) -> ok`

See **external** documentation.

`uniform2i(Location::integer(), V0::integer(), V1::integer()) -> ok`

See **external** documentation.

`uniform3i(Location::integer(), V0::integer(), V1::integer(), V2::integer()) -> ok`

See **external** documentation.

`uniform4i(Location::integer(), V0::integer(), V1::integer(), V2::integer(), V3::integer()) -> ok`

See **external** documentation.

`uniform1fv(Location::integer(), Value::[float()]) -> ok`

See **external** documentation.

`uniform2fv(Location::integer(), Value::[{float()}]) -> ok`

See **external** documentation.

`uniform3fv(Location::integer(), Value::[{float()}]) -> ok`

See **external** documentation.

`uniform4fv(Location::integer(), Value::[{float()}]) -> ok`

See **external** documentation.

`uniform1iv(Location::integer(), Value::[integer()]) -> ok`

See **external** documentation.

`uniform2iv(Location::integer(), Value::[{integer()}]) -> ok`

See **external** documentation.

`uniform3iv(Location::integer(), Value::[{integer()}]) -> ok`

See **external** documentation.

`uniform4iv(Location::integer(), Value::[{integer()}]) -> ok`

See **external** documentation.

`uniformMatrix2fv(Location::integer(), Transpose::0 | 1, Value::[{float()}]) -> ok`

See **external** documentation.

```
uniformMatrix3fv(Location::integer(), Transpose::0 | 1, Value::[{float()}]) -  
> ok
```

See **external** documentation.

```
uniformMatrix4fv(Location::integer(), Transpose::0 | 1, Value::[{float()}]) -  
> ok
```

See **external** documentation.

```
validateProgram(Program::integer()) -> ok
```

See **external** documentation.

```
vertexAttrib1d(Index::integer(), X::float()) -> ok
```

See **external** documentation.

```
vertexAttrib1dv(Index, X2::{X}) -> ok
```

Equivalent to *vertexAttrib1d(Index, X)*.

```
vertexAttrib1f(Index::integer(), X::float()) -> ok
```

See **external** documentation.

```
vertexAttrib1fv(Index, X2::{X}) -> ok
```

Equivalent to *vertexAttrib1f(Index, X)*.

```
vertexAttrib1s(Index::integer(), X::integer()) -> ok
```

See **external** documentation.

```
vertexAttrib1sv(Index, X2::{X}) -> ok
```

Equivalent to *vertexAttrib1s(Index, X)*.

```
vertexAttrib2d(Index::integer(), X::float(), Y::float()) -> ok
```

See **external** documentation.

```
vertexAttrib2dv(Index, X2::{X, Y}) -> ok
```

Equivalent to *vertexAttrib2d(Index, X, Y)*.

```
vertexAttrib2f(Index::integer(), X::float(), Y::float()) -> ok
```

See **external** documentation.

```
vertexAttrib2fv(Index, X2::{X, Y}) -> ok
```

Equivalent to *vertexAttrib2f(Index, X, Y)*.

```
vertexAttrib2s(Index::integer(), X::integer(), Y::integer()) -> ok
```

See **external** documentation.

```
vertexAttrib2sv(Index, X2::{X, Y}) -> ok
```

Equivalent to *vertexAttrib2s(Index, X, Y)*.

```
vertexAttrib3d(Index::integer(), X::float(), Y::float(), Z::float()) -> ok
```

See **external** documentation.

```
vertexAttrib3dv(Index, X2::{X, Y, Z}) -> ok
```

Equivalent to *vertexAttrib3d(Index, X, Y, Z)*.

```
vertexAttrib3f(Index::integer(), X::float(), Y::float(), Z::float()) -> ok
```

See **external** documentation.

```
vertexAttrib3fv(Index, X2::{X, Y, Z}) -> ok
```

Equivalent to *vertexAttrib3f(Index, X, Y, Z)*.

```
vertexAttrib3s(Index::integer(), X::integer(), Y::integer(), Z::integer()) -> ok
```

See **external** documentation.

```
vertexAttrib3sv(Index, X2::{X, Y, Z}) -> ok
```

Equivalent to *vertexAttrib3s(Index, X, Y, Z)*.

```
vertexAttrib4Nbv(Index::integer(), V::{integer()}) -> ok
```

See **external** documentation.

```
vertexAttrib4Niv(Index::integer(), V::{integer()}) -> ok
```

See **external** documentation.

```
vertexAttrib4Nsv(Index::integer(), V::{integer()}) -> ok
```

See **external** documentation.

```
vertexAttrib4Nub(Index::integer(), X::integer(), Y::integer(), Z::integer(),  
W::integer()) -> ok
```

See **external** documentation.

```
vertexAttrib4Nubv(Index, X2::{X, Y, Z, W}) -> ok
```

Equivalent to *vertexAttrib4Nub(Index, X, Y, Z, W)*.

```
vertexAttrib4Nuiv(Index::integer(), V::{integer()}) -> ok
```

See **external** documentation.

```
vertexAttrib4Nusv(Index::integer(), V::{integer()}) -> ok
```

See **external** documentation.

vertexAttrib4bv(Index::integer(), V::{integer()}) -> ok

See **external** documentation.

vertexAttrib4d(Index::integer(), X::float(), Y::float(), Z::float(),
W::float()) -> ok

See **external** documentation.

vertexAttrib4dv(Index, X2::{X, Y, Z, W}) -> ok

Equivalent to *vertexAttrib4d*(Index, X, Y, Z, W).

vertexAttrib4f(Index::integer(), X::float(), Y::float(), Z::float(),
W::float()) -> ok

See **external** documentation.

vertexAttrib4fv(Index, X2::{X, Y, Z, W}) -> ok

Equivalent to *vertexAttrib4f*(Index, X, Y, Z, W).

vertexAttrib4iv(Index::integer(), V::{integer()}) -> ok

See **external** documentation.

vertexAttrib4s(Index::integer(), X::integer(), Y::integer(), Z::integer(),
W::integer()) -> ok

See **external** documentation.

vertexAttrib4sv(Index, X2::{X, Y, Z, W}) -> ok

Equivalent to *vertexAttrib4s*(Index, X, Y, Z, W).

vertexAttrib4ubv(Index::integer(), V::{integer()}) -> ok

See **external** documentation.

vertexAttrib4uiv(Index::integer(), V::{integer()}) -> ok

See **external** documentation.

vertexAttrib4usv(Index::integer(), V::{integer()}) -> ok

See **external** documentation.

vertexAttribPointer(Index::integer(), Size::integer(), Type::enum(),
Normalized::0 | 1, Stride::integer(), Pointer::offset() | binary()) -> ok

See **external** documentation.

uniformMatrix2x3fv(Location::integer(), Transpose::0 | 1, Value::{float()})
-> ok

See **external** documentation.

```
uniformMatrix3x2fv(Location::integer(), Transpose::0 | 1, Value::[{float()}])  
-> ok
```

See **external** documentation.

```
uniformMatrix2x4fv(Location::integer(), Transpose::0 | 1, Value::[{float()}])  
-> ok
```

See **external** documentation.

```
uniformMatrix4x2fv(Location::integer(), Transpose::0 | 1, Value::[{float()}])  
-> ok
```

See **external** documentation.

```
uniformMatrix3x4fv(Location::integer(), Transpose::0 | 1, Value::[{float()}])  
-> ok
```

See **external** documentation.

```
uniformMatrix4x3fv(Location::integer(), Transpose::0 | 1, Value::[{float()}])  
-> ok
```

See **external** documentation.

```
colorMaski(Index::integer(), R::0 | 1, G::0 | 1, B::0 | 1, A::0 | 1) -> ok
```

See **external** documentation.

```
getBooleani_v(Target::enum(), Index::integer()) -> [0 | 1]
```

See **external** documentation.

```
getIntegeri_v(Target::enum(), Index::integer()) -> [integer()]
```

See **external** documentation.

```
enablei(Target::enum(), Index::integer()) -> ok
```

See **external** documentation.

```
disablei(Target::enum(), Index::integer()) -> ok
```

See **external** documentation.

```
isEnabledi(Target::enum(), Index::integer()) -> 0 | 1
```

See **external** documentation.

```
beginTransformFeedback(PrimitiveMode::enum()) -> ok
```

See **external** documentation.

```
endTransformFeedback() -> ok
```

See **external** documentation.

```
bindBufferRange(Target::enum(), Index::integer(), Buffer::integer(),  
Offset::integer(), Size::integer()) -> ok
```

See **external** documentation.

```
bindBufferBase(Target::enum(), Index::integer(), Buffer::integer()) -> ok
```

See **external** documentation.

```
transformFeedbackVaryings(Program::integer(), Varyings::[string()],  
BufferMode::enum()) -> ok
```

See **external** documentation.

```
getTransformFeedbackVarying(Program::integer(), Index::integer(),  
BufSize::integer()) -> {Size::integer(), Type::enum(), Name::string()}
```

See **external** documentation.

```
clampColor(Target::enum(), Clamp::enum()) -> ok
```

See **external** documentation.

```
beginConditionalRender(Id::integer(), Mode::enum()) -> ok
```

See **external** documentation.

```
endConditionalRender() -> ok
```

See **external** documentation.

```
vertexAttribIPointer(Index::integer(), Size::integer(), Type::enum(),  
Stride::integer(), Pointer::offset() | binary()) -> ok
```

See **external** documentation.

```
getVertexAttribIiv(Index::integer(), Pname::enum()) -> {integer()}
```

See **external** documentation.

```
getVertexAttribIuiv(Index::integer(), Pname::enum()) -> {integer()}
```

See **external** documentation.

```
getUniformuiv(Program::integer(), Location::integer()) -> {integer()}
```

See **external** documentation.

```
bindFragDataLocation(Program::integer(), Color::integer(), Name::string()) ->  
ok
```

See **external** documentation.

```
getFragDataLocation(Program::integer(), Name::string()) -> integer()
```

See **external** documentation.

uniform1ui(Location::integer(), V0::integer()) -> ok

See **external** documentation.

uniform2ui(Location::integer(), V0::integer(), V1::integer()) -> ok

See **external** documentation.

uniform3ui(Location::integer(), V0::integer(), V1::integer(), V2::integer())
-> ok

See **external** documentation.

uniform4ui(Location::integer(), V0::integer(), V1::integer(), V2::integer(),
V3::integer()) -> ok

See **external** documentation.

uniform1uiv(Location::integer(), Value::[integer()]) -> ok

See **external** documentation.

uniform2uiv(Location::integer(), Value::[{integer()}]) -> ok

See **external** documentation.

uniform3uiv(Location::integer(), Value::[{integer()}]) -> ok

See **external** documentation.

uniform4uiv(Location::integer(), Value::[{integer()}]) -> ok

See **external** documentation.

texParameterIiv(Target::enum(), Pname::enum(), Params::{integer()}) -> ok

See **external** documentation.

texParameterIuiv(Target::enum(), Pname::enum(), Params::{integer()}) -> ok

See **external** documentation.

getTexParameterIiv(Target::enum(), Pname::enum()) -> {integer()}

See **external** documentation.

getTexParameterIuiv(Target::enum(), Pname::enum()) -> {integer()}

See **external** documentation.

clearBufferiv(Buffer::enum(), Drawbuffer::integer(), Value::{integer()}) ->
ok

See **external** documentation.

```
clearBufferuiv(Buffer::enum(), Drawbuffer::integer(), Value::{integer()}) -> ok
```

See **external** documentation.

```
clearBufferfv(Buffer::enum(), Drawbuffer::integer(), Value::{float()}) -> ok
```

See **external** documentation.

```
clearBufferfi(Buffer::enum(), Drawbuffer::integer(), Depth::float(), Stencil::integer()) -> ok
```

See **external** documentation.

```
getStringi(Name::enum(), Index::integer()) -> string()
```

See **external** documentation.

```
vertexAttribI1i(Index::integer(), X::integer()) -> ok
```

See **external** documentation.

```
vertexAttribI2i(Index::integer(), X::integer(), Y::integer()) -> ok
```

See **external** documentation.

```
vertexAttribI3i(Index::integer(), X::integer(), Y::integer(), Z::integer()) -> ok
```

See **external** documentation.

```
vertexAttribI4i(Index::integer(), X::integer(), Y::integer(), Z::integer(), W::integer()) -> ok
```

See **external** documentation.

```
vertexAttribI1ui(Index::integer(), X::integer()) -> ok
```

See **external** documentation.

```
vertexAttribI2ui(Index::integer(), X::integer(), Y::integer()) -> ok
```

See **external** documentation.

```
vertexAttribI3ui(Index::integer(), X::integer(), Y::integer(), Z::integer()) -> ok
```

See **external** documentation.

```
vertexAttribI4ui(Index::integer(), X::integer(), Y::integer(), Z::integer(), W::integer()) -> ok
```

See **external** documentation.

```
vertexAttribI1iv(Index, X2::{X}) -> ok
```

Equivalent to *vertexAttribI1i*(Index, X).

```
vertexAttribI2iv(Index, X2::{X, Y}) -> ok
```

Equivalent to *vertexAttribI2i(Index, X, Y)*.

```
vertexAttribI3iv(Index, X2::{X, Y, Z}) -> ok
```

Equivalent to *vertexAttribI3i(Index, X, Y, Z)*.

```
vertexAttribI4iv(Index, X2::{X, Y, Z, W}) -> ok
```

Equivalent to *vertexAttribI4i(Index, X, Y, Z, W)*.

```
vertexAttribI1uiv(Index, X2::{X}) -> ok
```

Equivalent to *vertexAttribI1ui(Index, X)*.

```
vertexAttribI2uiv(Index, X2::{X, Y}) -> ok
```

Equivalent to *vertexAttribI2ui(Index, X, Y)*.

```
vertexAttribI3uiv(Index, X2::{X, Y, Z}) -> ok
```

Equivalent to *vertexAttribI3ui(Index, X, Y, Z)*.

```
vertexAttribI4uiv(Index, X2::{X, Y, Z, W}) -> ok
```

Equivalent to *vertexAttribI4ui(Index, X, Y, Z, W)*.

```
vertexAttribI4bv(Index::integer(), V::{integer()}) -> ok
```

See **external** documentation.

```
vertexAttribI4sv(Index::integer(), V::{integer()}) -> ok
```

See **external** documentation.

```
vertexAttribI4ubv(Index::integer(), V::{integer()}) -> ok
```

See **external** documentation.

```
vertexAttribI4usv(Index::integer(), V::{integer()}) -> ok
```

See **external** documentation.

```
drawArraysInstanced(Mode::enum(), First::integer(), Count::integer(),  
Primcount::integer()) -> ok
```

See **external** documentation.

```
drawElementsInstanced(Mode::enum(), Count::integer(), Type::enum(),  
Indices::offset() | binary(), Primcount::integer()) -> ok
```

See **external** documentation.

```
texBuffer(Target::enum(), Internalformat::enum(), Buffer::integer()) -> ok
```

See **external** documentation.

primitiveRestartIndex(Index::integer()) -> ok

See **external** documentation.

loadTransposeMatrixfARB(M::{float()}) -> ok

See **external** documentation.

loadTransposeMatrixdARB(M::{float()}) -> ok

See **external** documentation.

multTransposeMatrixfARB(M::{float()}) -> ok

See **external** documentation.

multTransposeMatrixdARB(M::{float()}) -> ok

See **external** documentation.

weightbvARB(Weights::[integer()]) -> ok

See **external** documentation.

weightsvARB(Weights::[integer()]) -> ok

See **external** documentation.

weightivARB(Weights::[integer()]) -> ok

See **external** documentation.

weightfvARB(Weights::[float()]) -> ok

See **external** documentation.

weightdvARB(Weights::[float()]) -> ok

See **external** documentation.

weightubvARB(Weights::[integer()]) -> ok

See **external** documentation.

weightusvARB(Weights::[integer()]) -> ok

See **external** documentation.

weightuivARB(Weights::[integer()]) -> ok

See **external** documentation.

vertexBlendARB(Count::integer()) -> ok

See **external** documentation.

currentPaletteMatrixARB(Index::integer()) -> ok

See **external** documentation.

matrixIndexubvARB(Indices::[integer()]) -> ok

See **external** documentation.

matrixIndexusvARB(Indices::[integer()]) -> ok

See **external** documentation.

matrixIndexuivARB(Indices::[integer()]) -> ok

See **external** documentation.

programStringARB(Target::enum(), Format::enum(), String::string()) -> ok

See **external** documentation.

bindProgramARB(Target::enum(), Program::integer()) -> ok

See **external** documentation.

deleteProgramsARB(Programs::[integer()]) -> ok

See **external** documentation.

genProgramsARB(N::integer()) -> [integer()]

See **external** documentation.

programEnvParameter4dARB(Target::enum(), Index::integer(), X::float(), Y::float(), Z::float(), W::float()) -> ok

See **external** documentation.

**programEnvParameter4dvARB(Target::enum(), Index::integer(), Params::
{float()}) -> ok**

See **external** documentation.

programEnvParameter4fARB(Target::enum(), Index::integer(), X::float(), Y::float(), Z::float(), W::float()) -> ok

See **external** documentation.

**programEnvParameter4fvARB(Target::enum(), Index::integer(), Params::
{float()}) -> ok**

See **external** documentation.

programLocalParameter4dARB(Target::enum(), Index::integer(), X::float(), Y::float(), Z::float(), W::float()) -> ok

See **external** documentation.

```
programLocalParameter4dvARB(Target::enum(), Index::integer(), Params::
{float()}) -> ok
```

See **external** documentation.

```
programLocalParameter4fARB(Target::enum(), Index::integer(), X::float(),
Y::float(), Z::float(), W::float()) -> ok
```

See **external** documentation.

```
programLocalParameter4fvARB(Target::enum(), Index::integer(), Params::
{float()}) -> ok
```

See **external** documentation.

```
getProgramEnvParameterdvARB(Target::enum(), Index::integer()) -> {float()}
```

See **external** documentation.

```
getProgramEnvParameterfvARB(Target::enum(), Index::integer()) -> {float()}
```

See **external** documentation.

```
getProgramLocalParameterdvARB(Target::enum(), Index::integer()) -> {float()}
```

See **external** documentation.

```
getProgramLocalParameterfvARB(Target::enum(), Index::integer()) -> {float()}
```

See **external** documentation.

```
getProgramStringARB(Target::enum(), Pname::enum(), String::wx_mem() (see
module wx)) -> ok
```

See **external** documentation.

```
deleteObjectARB(Obj::integer()) -> ok
```

See **external** documentation.

```
getHandleARB(Pname::enum()) -> integer()
```

See **external** documentation.

```
detachObjectARB(ContainerObj::integer(), AttachedObj::integer()) -> ok
```

See **external** documentation.

```
createShaderObjectARB(ShaderType::enum()) -> integer()
```

See **external** documentation.

```
shaderSourceARB(ShaderObj::integer(), String::[string()]) -> ok
```

See **external** documentation.

`compileShaderARB(ShaderObj::integer()) -> ok`

See **external** documentation.

`createProgramObjectARB() -> integer()`

See **external** documentation.

`attachObjectARB(ContainerObj::integer(), Obj::integer()) -> ok`

See **external** documentation.

`linkProgramARB(ProgramObj::integer()) -> ok`

See **external** documentation.

`useProgramObjectARB(ProgramObj::integer()) -> ok`

See **external** documentation.

`validateProgramARB(ProgramObj::integer()) -> ok`

See **external** documentation.

`getObjectParameterfvARB(Obj::integer(), Pname::enum()) -> float()`

See **external** documentation.

`getObjectParameterivARB(Obj::integer(), Pname::enum()) -> integer()`

See **external** documentation.

`getInfoLogARB(Obj::integer(), MaxLength::integer()) -> string()`

See **external** documentation.

`getAttachedObjectsARB(ContainerObj::integer(), MaxCount::integer()) -> [integer()]`

See **external** documentation.

`getUniformLocationARB(ProgramObj::integer(), Name::string()) -> integer()`

See **external** documentation.

`getActiveUniformARB(ProgramObj::integer(), Index::integer(),
MaxLength::integer()) -> {Size::integer(), Type::enum(), Name::string()}`

See **external** documentation.

`getUniformfvARB(ProgramObj::integer(), Location::integer()) -> {float()}`

See **external** documentation.

`getUniformivARB(ProgramObj::integer(), Location::integer()) -> {integer()}`

See **external** documentation.

getShaderSourceARB(Obj::integer(), MaxLength::integer()) -> string()

See **external** documentation.

bindAttribLocationARB(ProgramObj::integer(), Index::integer(),
Name::string()) -> ok

See **external** documentation.

getActiveAttribARB(ProgramObj::integer(), Index::integer(),
MaxLength::integer()) -> {Size::integer(), Type::enum(), Name::string()}

See **external** documentation.

getAttribLocationARB(ProgramObj::integer(), Name::string()) -> integer()

See **external** documentation.

isRenderbuffer(Renderbuffer::integer()) -> 0 | 1

See **external** documentation.

bindRenderbuffer(Target::enum(), Renderbuffer::integer()) -> ok

See **external** documentation.

deleteRenderbuffers(Renderbuffers::[integer()]) -> ok

See **external** documentation.

genRenderbuffers(N::integer()) -> [integer()]

See **external** documentation.

renderbufferStorage(Target::enum(), Internalformat::enum(), Width::integer(),
Height::integer()) -> ok

See **external** documentation.

getRenderbufferParameteriv(Target::enum(), Pname::enum()) -> integer()

See **external** documentation.

isFramebuffer(Framebuffer::integer()) -> 0 | 1

See **external** documentation.

bindFramebuffer(Target::enum(), Framebuffer::integer()) -> ok

See **external** documentation.

deleteFramebuffers(Framebuffers::[integer()]) -> ok

See **external** documentation.

```
genFramebuffers(N::integer()) -> [integer()]
```

See **external** documentation.

```
checkFramebufferStatus(Target::enum()) -> enum()
```

See **external** documentation.

```
framebufferTexture1D(Target::enum(), Attachment::enum(), Textarget::enum(),  
Texture::integer(), Level::integer()) -> ok
```

See **external** documentation.

```
framebufferTexture2D(Target::enum(), Attachment::enum(), Textarget::enum(),  
Texture::integer(), Level::integer()) -> ok
```

See **external** documentation.

```
framebufferTexture3D(Target::enum(), Attachment::enum(), Textarget::enum(),  
Texture::integer(), Level::integer(), Zoffset::integer()) -> ok
```

See **external** documentation.

```
framebufferRenderbuffer(Target::enum(), Attachment::enum(),  
Renderbuffertarget::enum(), Renderbuffer::integer()) -> ok
```

See **external** documentation.

```
getFramebufferAttachmentParameteriv(Target::enum(), Attachment::enum(),  
Pname::enum()) -> integer()
```

See **external** documentation.

```
generateMipmap(Target::enum()) -> ok
```

See **external** documentation.

```
blitFramebuffer(SrcX0::integer(), SrcY0::integer(), SrcX1::integer(),  
SrcY1::integer(), DstX0::integer(), DstY0::integer(), DstX1::integer(),  
DstY1::integer(), Mask::integer(), Filter::enum()) -> ok
```

See **external** documentation.

```
renderbufferStorageMultisample(Target::enum(), Samples::integer(),  
Internalformat::enum(), Width::integer(), Height::integer()) -> ok
```

See **external** documentation.

```
framebufferTextureLayer(Target::enum(), Attachment::enum(),  
Texture::integer(), Level::integer(), Layer::integer()) -> ok
```

See **external** documentation.

```
programParameteriARB(Program::integer(), Pname::enum(), Value::integer()) ->
ok
```

See **external** documentation.

```
framebufferTextureARB(Target::enum(), Attachment::enum(), Texture::integer(),
Level::integer()) -> ok
```

See **external** documentation.

```
framebufferTextureFaceARB(Target::enum(), Attachment::enum(),
Texture::integer(), Level::integer(), Face::enum()) -> ok
```

See **external** documentation.

```
vertexAttribDivisorARB(Index::integer(), Divisor::integer()) -> ok
```

See **external** documentation.

```
flushMappedBufferRange(Target::enum(), Offset::integer(), Length::integer())
-> ok
```

See **external** documentation.

```
bindVertexArray(Array::integer()) -> ok
```

See **external** documentation.

```
deleteVertexArrays(Arrays::[integer()]) -> ok
```

See **external** documentation.

```
genVertexArrays(N::integer()) -> [integer()]
```

See **external** documentation.

```
isVertexArray(Array::integer()) -> 0 | 1
```

See **external** documentation.

```
getUniformIndices(Program::integer(), UniformNames::[string()]) ->
[integer()]
```

See **external** documentation.

```
getActiveUniformsiv(Program::integer(), UniformIndices::[integer()],
Pname::enum()) -> [integer()]
```

See **external** documentation.

```
getActiveUniformName(Program::integer(), UniformIndex::integer(),
BufSize::integer()) -> string()
```

See **external** documentation.

```
getUniformBlockIndex(Program::integer(), UniformBlockName::string()) ->
integer()
```

See **external** documentation.

```
getActiveUniformBlockiv(Program::integer(), UniformBlockIndex::integer(),
Pname::enum(), Params::wx_mem() (see module wx)) -> ok
```

See **external** documentation.

```
getActiveUniformBlockName(Program::integer(), UniformBlockIndex::integer(),
BufSize::integer()) -> string()
```

See **external** documentation.

```
uniformBlockBinding(Program::integer(), UniformBlockIndex::integer(),
UniformBlockBinding::integer()) -> ok
```

See **external** documentation.

```
copyBufferSubData(ReadTarget::enum(), WriteTarget::enum(),
ReadOffset::integer(), WriteOffset::integer(), Size::integer()) -> ok
```

See **external** documentation.

```
resizeBuffersMESA() -> ok
```

See **external** documentation.

```
windowPos4dMESA(X::float(), Y::float(), Z::float(), W::float()) -> ok
```

See **external** documentation.

```
windowPos4dvMESA(X1::{X, Y, Z, W}) -> ok
```

Equivalent to *windowPos4dMESA(X, Y, Z, W)*.

```
windowPos4fMESA(X::float(), Y::float(), Z::float(), W::float()) -> ok
```

See **external** documentation.

```
windowPos4fvMESA(X1::{X, Y, Z, W}) -> ok
```

Equivalent to *windowPos4fMESA(X, Y, Z, W)*.

```
windowPos4iMESA(X::integer(), Y::integer(), Z::integer(), W::integer()) -> ok
```

See **external** documentation.

```
windowPos4ivMESA(X1::{X, Y, Z, W}) -> ok
```

Equivalent to *windowPos4iMESA(X, Y, Z, W)*.

```
windowPos4sMESA(X::integer(), Y::integer(), Z::integer(), W::integer()) -> ok
```

See **external** documentation.

`windowPos4svMESA(X1::{X, Y, Z, W}) -> ok`

Equivalent to *windowPos4sMESA(X, Y, Z, W)*.

`depthBoundsEXT(Zmin::clamp(), Zmax::clamp()) -> ok`

See **external** documentation.

`stencilClearTagEXT(StencilTagBits::integer(), StencilClearTag::integer()) -> ok`

See **external** documentation.